

1. GENERAL (CONTD)**1.6.1.2. Requirements for operation for aircraft B747-8 at stands 33 & 34 (contd)**

In case aircraft B747-8 taking off at the beginning of Rwy 07R must cancel the take-off clearance and aircraft must decelerate via Twy S5, aircraft requested to follow Tower and Ground Control Unit instructions strictly.

Aircraft shall have to control the speed and need small amount of judgemental oversteering to maintain ICAO recommended 15'(4.5m) clearances of outside main gear track and pavement edge when taxiing on the intersections of Rwys and Twys, and of Twys and apron.

1.6.1.3. Operation of aircraft A350-900, B787-9.

Use Rwy 25L/07R as main Rwy for these aircraft types to take-off and land.

Limited use of Rwy 25R/07L for these aircraft types to take-off and land.

1.6.1.4. Addition of stands 01VJ, 02VJ, 03VJ, 04VJ using for Viet Jet Aviation Joint Stock Company

Operational procedure:

- Serve for maintenance and aircraft parking overnight (without commercial purpose).
- Only used for aircraft up to A320/A321 and equivalent.
- Tow tractor is used for pushing aircraft from commercial stands to stand 01VJ, 02VJ, 03VJ, 04VJ and vice versa.

1.6.2. OPERATIONAL CAPABILITY OF NON-COMMERCIAL AIRCRAFT STANDS

Aircraft stand	Usage
1T, 2T, 3T	- Used for acft code C (wingspan from 79'(24m) up to but not including 118'(36m)). - Suspend operation of the portion of Twy V (the portion from the intermediate holding position of Twys V and S3 to the intermediate holding position of Twys V and S) when there is acft parking. The intersections of Twy V and Twys S3, S remain normal operation during suspend operation of the portion of Twy V.
4T	- Used for acft code C (wingspan from 79'(24m) up to but not including 118'(36m)). - Suspend operation of the portion of taxiway Y2 (the portion behind stands 23, 24 and stands 26, 27) when there is acft parking. The portion of taxiway Y2 (the portion from the intersection of Twy S5 to behind stands 25, 27) remains normal operation during suspend operation of the portion of taxiway Y2.
5T	- Used for acft code C (wingspan from 79'(24m) up to but not including 118'(36m)). - Suspend operation of taxiway Y2 when there is acft parking at this stand.
6T, 7T	- Used for acft code E (wingspan from 171'(52m) up to but not including 213'(65m)). - Suspend operation of taxiway Y1 (the portion behind stands from 37 to 40) when there is acft parking at these stands.
8T	- Used for acft code E (wingspan from 171'(52m) up to but not including 213'(65m)). - Suspend operation of taxiway Y1 (the portion behind stands from 35, 36) when there is acft parking at this stand.
9T	- Used for acft code C (wingspan from 79'(24m) up to but not including 118'(36m)). - Suspend operation of taxiway Y3 when there is acft parking at this stand.
10T	- Used for acft code C (wingspan from 79'(24m) up to but not including 118'(36m)). - Suspend operation of taxiway Y3 (the portion behind stands 42, 43 and 45, 46) when there is acft parking at this stand.
11T	- Used for acft code C (wingspan from 79'(24m) up to but not including 118'(36m)). - Suspend operation of taxiway Y4 (the portion behind stands from 47 to 49 and from 50 to 54) when there is acft parking at this stand.
12A, 12B	- Used for acft code C (wingspan from 79'(24m) up to but not including 118'(36m)). - Suspend operation of stand 12 when there is non-commercial acft (parking overnight).
12T	- Used for acft code E (wingspan from 171'(52m) up to but not including 213'(65m)). - Suspend operation of Twy S6 when there is acft parking at this stand. - Only applied when Rwy 25L is used for take-off/landing.
13T	- Used for acft code E (wingspan from 171'(52m) up to but not including 213'(65m)). - Suspend operation of Twy S7 when there is acft parking at this stand. - Only applied when Rwy 07R is used for take-off/landing.
14A, 14B	- Used for acft code C (wingspan from 79'(24m) up to but not including 118'(36m)). - Suspend operation of stand 14 when there is non-commercial acft (parking overnight).
16A, 16B	- Used for acft code C (wingspan from 79'(24m) up to but not including 118'(36m)). - Suspend operation of stand 16 when there is non-commercial acft (parking overnight).