SOLUTIONS OF PRACTICE PROBLEMS FOR LAB 3

A1.

Using rotate instruction sets or resets the carry flag depending on the bit rotated.

Instruction on 10E is JNC (same as JAE)





A2. Method 2

Any number greater than 32 is divisible by 32 if the 5 LSB in binary representation are all ‘0’s.

We don’t care about rest bits so mask them by using AND with 0000 0000 0001 1111 i.e. 1F (hex)

1F (hex) AND D3E0

0000 0000 0001 1111 AND 1101 0011 1110 0000

Output : AX contains 1 if number divisible by 32, 2 otherwise

```
-u 100
0859:0100 BAE0D3            MOV     DX,D3E0
0859:0103 BB1F00            MOV     BX,001F
0859:0106 21D3              AND     BX,DX
0859:0108 83FB00            CMP     BX,+00
0859:010B 7404              JZ      0111
0859:010D B002              MOV     AL,02
0859:010F EB02              JMP     0113
0859:0111 B001              MOV     AL,01
0859:0113 C3                RET
0859:0114 0000              ADD     [BX+SI],AL
0859:0116 0000              ADD     [BX+SI],AL
0859:0118 0000              ADD     [BX+SI],AL
0859:011A 0000              ADD     [BX+SI],AL
0859:011C 0000              ADD     [BX+SI],AL
0859:011E 0000              ADD     [BX+SI],AL
-g=100 113
AX=0001 BX=0000 CX=0000 DX=D3E0 SP=FFFE BP=0000 SI=0000 DI=0000
DS=0859 ES=0859 SS=0859 CS=0859 IP=0113 NV UP EI PL ZR NA PE NC
0859:0113 C3                RET
-
```

```
-a 100
0859:0100 mov dx,d3f0
0859:0103
-r ax 0
-g=100 113
AX=0002 BX=0010 CX=0000 DX=D3F0 SP=FFFE BP=0000 SI=0000 DI=0000
DS=0859 ES=0859 SS=0859 CS=0859 IP=0113 NV UP EI PL NZ NA PO NC
0859:0113 C3                RET
-
```

A3.

Loading text from .txt file to DosBox :

1. Save .txt file in the “DEBUG” folder.
2. -n filename.txt
3. -l [memory location to load]

Check each character in first string and cross it out from second string if present in both.

Output : AX contains 1 if anagrams, 2 otherwise.



```
-u 100
0859:0100 B90600          MOV     CX,0006
0859:0103 BE0000          MOV     SI,0000
0859:0106 8A9C0002        MOV     BL,[SI+0200]
0859:010A BF0000          MOV     DI,0000
0859:010D 3A9D2002        CMP     BL,[DI+0220]
0859:0111 7407            JZ      011A
0859:0113 47              INC     DI
0859:0114 39CF            CMP     DI,CX
0859:0116 75F5            JNZ     010D
0859:0118 EB0D            JMP     0127
0859:011A 888D2002        MOV     [DI+0220],CL
0859:011E 46              INC     SI
0859:011F 39CE            CMP     SI,CX
-
```



```
-
0859:0121 75E3            JNZ     0106
0859:0123 B001            MOV     AL,01
0859:0125 EB02            JMP     0129
0859:0127 B002            MOV     AL,02
0859:0129 C3              RET
0859:012A 0000            ADD     [BX+SI],AL
```



```
-n l3a.txt
-l 200
-n l3b.txt
-l 220
-d 200
0859:0200  6C 69 73 74 65 6E 00 00-00 00 00 00 00 00 00 00  listen..........
0859:0210  00 00 00 00 00 00 00 00-00 00 00 00 00 00 00 00  ................
0859:0220  73 69 6C 65 6E 74 00 00-00 00 00 00 00 00 00 00  silent..........
0859:0230  00 00 00 00 00 00 00 00-00 00 00 00 00 00 00 00  ................
0859:0240  00 00 00 00 00 00 00 00-00 00 00 00 00 00 00 00  ................
0859:0250  00 00 00 00 00 00 00 00-00 00 00 00 00 00 00 00  ................
0859:0260  00 00 00 00 00 00 00 00-00 00 00 00 00 00 00 00  ................
0859:0270  00 00 00 00 00 00 00 00-00 00 00 00 00 00 00 00  ................
-g=100 129
AX=0001 BX=006E CX=0006 DX=0000 SP=FFFE BP=0000 SI=0006 DI=0004
DS=0859 ES=0859 SS=0859 CS=0859 IP=0129 NV UP EI PL ZR NA PE NC
0859:0129 C3              RET
-
```


-n l3a.txt
-l 200
-n l3b.txt
-l 220
-d 200
0859:0200 6E 6F 69 73 65 73 00 00-00 00 00 00 00 00 00 00 noises.....
0859:0210 00 00 00 00 00 00 00 00-00 00 00 00 00 00 00 00 ....
0859:0220 73 74 6F 6E 65 73 00 00-00 00 00 00 00 00 00 00 stones.....
0859:0230 00 00 00 00 00 00 00 00-00 00 00 00 00 00 00 00 ....
0859:0240 00 00 00 00 00 00 00 00-00 00 00 00 00 00 00 00 ....
0859:0250 00 00 00 00 00 00 00 00-00 00 00 00 00 00 00 00 ....
0859:0260 00 00 00 00 00 00 00 00-00 00 00 00 00 00 00 00 ....
0859:0270 00 00 00 00 00 00 00 00-00 00 00 00 00 00 00 00 ....
-g=100 129
AX=0002 BX=0069 CX=0006 DX=0000 SP=FFFE BP=0000 SI=0002 DI=0006
DS=0859 ES=0859 SS=0859 CS=0859 IP=0129 NV UP EI PL ZR NA PE NC
0859:0129 C3 RET
-