Filter Feature Regression

Workflow Validation

2026

FILTER FEATURE REGRESSION AND WORKFLOW DEMONSTRATION

Purpose

This is a self-contained .txt fixture for the Markdown-to-PDF workflow. Compile this file by itself with compile.bat. A successful build exercises the real Windows wrapper, Pandoc, config-normalizer.lua, config-fence-runner.lua, config.tex, and XeLaTeX. The Python examples use standard library features except for the optional Matplotlib figure example, which skips cleanly when Matplotlib is not installed.

This is a broad, repeatable regression sample, not a mathematical proof that every possible input is supported. Expected-failure cases are listed near the end and are intentionally not activated as build-breaking input.

Run this exact fixture

In File Explorer, drag this file onto compile.bat, or run the following from Command Prompt after changing to the folder containing compile.bat and this fixture:

```
compile.bat "FILTER_FEATURE_REGRESSION.txt"
```

The template and filters are read from the config folder beside compile.bat. The PDF should be created beside this .txt file with the same base name. Expected console notices include summaries for intentionally cleaned citation markers / unsupported emoji and the deliberately failing Python demonstration. The build should still complete and produce a PDF.

1. Document metadata, order, and Markdown basics

The YAML title and author below exercise YAML metadata in a .txt input. The title in the produced PDF should be “Filter Feature Regression”.

The first input’s content order is preserved. This standalone file is one input; the multi-file behavior is covered in WORKFLOW_ARCHITECTURE.txt.

Markdown supports **bold**, *italic*, ~~strikeout~~, `inline code`, links, lists, headings, and ordinary paragraphs. This is a link to Pandoc.

Checklist syntax note: `[ ] item` without a list marker is ordinary paragraph text, not a list. Use `- [ ] item` for a Pandoc task-list item (or `- item` for an ordinary bullet). This fixture uses ordinary bullets in its final checklist.

Bare URLs are autolinked by the cleaned-input reader: https://pandoc.org/installing.html

The `<br>` tag outside code becomes a line break.
HTML subscript and superscript are converted: H_2O and x^2.

Code-like text is protected from prose rewriting: `<br>`, `\maketitle`, and `\usepackage{fakepackage}` remain literal here.

Raw HTML nodes represented by Pandoc as raw blocks (for example scripts) are removed rather than passed to XeLaTeX:

Pandoc represents an HTML div as a structural Div, not a raw HTML block. Its ordinary text content is retained by this filter:

HTML div content is retained as document text.

The same special-looking text is protected inside a verbatim environment:

```
<br>
\maketitle
\usepackage{fakepackage}
```

Lists and inline formatting

- Apple costs $5.
- Pear costs $7.
- A third item stays separate from the currency examples.

1. Ordered item with **bold** text.
2. Ordered item with *emphasis*.
3. Ordered item with inline math, $a^2 + b^2 = c^2$.

   Indented code remains code:

   fakepackage

Pipe table and math inside a table

Quantity	Value
Inline math	$x^2 + y^2$
Greek	$\alpha + \beta$
Pipe-like math outside the table	See the display equation below

The table exercises ordinary pipe-table parsing, alignment, inline math, and Unicode-capable LaTeX output. Table cells containing complex aligned math may need simpler formatting; see the limitations section.

2. Math and Unicode handling

Inline math: $E = mc^2$, $x_1 + x_2$, and $\alpha \leq \beta$.

Display math:

$$\int_0^1 x^2 \, dx = \frac{1}{3}.$$

An aligned raw-LaTeX math environment:

$$(a+b)^2 = a^2 + 2ab + b^2, \tag{1}$$
$$(a-b)^2 = a^2 - 2ab + b^2. \tag{2}$$

The next display contains a line that starts and ends with vertical bars. It must remain math, not be reinterpreted as a Markdown table:

$$|a+b| \leq |a| + |b|$$

Price-like list items above must not be joined into one formula. A real multi-line single-dollar formula may continue across lines when its content clearly contains math:

$x + y = z$

Unicode examples cover Greek letters, capital Greek / Latin-lookalike letters, operators, arrows, relations, and stacked superscripts/subscripts:

Greek: α β γ Δ Ω Υ. Relations: $\leq$ $\geq$ $\neq$ $\approx$ $\in$ $\emptyset$ $\forall$ $\exists$. Arrows: $\rightarrow$ $\Rightarrow$ $\leftrightarrow$. Scripts: x^2, x^{-1}, H_2O, and $_{12}$. Template symbol-font examples: ■ □ ● ○ ★. Meaning-bearing status marks: ✓ × ! (from ✓ × !).

Unicode script characters in source-code listings are kept in the code and declared for XeLaTeX when needed. Some glyphs still depend on installed fonts.

3. Real citations and AI-marker cleanup

This citation uses inline CSL reference metadata from the YAML block: (Doe 2024).

The following AI-generated citation artifacts should be removed while their removal count is reported to the console:

An old marker and an old citation are removed. The bracketed source marker is removed.

Emoji with meaning are mapped to printable check/cross/warning marks above. An unsupported emoji in ordinary prose () is removed and counted. Citation cleanup is for known AI artifacts; it is not a replacement for real citations.

4. Pasted LaTeX and template integration

Commands in ordinary pasted LaTeX are moved to the preamble when supported. Template-loaded packages such as siunitx and tcolorbox are not loaded a second time, preventing option clashes. Multiple usepackage commands may share a line:

The template's siunitx/physics quantity dispatcher supports: 1.5 m

Theorem-like environments are converted to Markdown-parsed bodies and restored to LaTeX wrappers:

Theorem 1. *For every real number x, $x^2 \geq 0$.*


Proof. The square of a real number is nonnegative. □

The custom theorem and environment recovered from the LaTeX fence are used below:

Regression Claim 1. The regression fixture exercises the configured theorem definition.

The recovered custom environment also wraps its body.

TikZ settings are hoisted before the picture that uses them. Settings declared inside a tikzpicture are intentionally not globalized:



A complete LaTeX fence keeps its document body and rescues recognized preamble definitions. The duplicate siunitx package request is filtered out.

Recovered command: $\mathbb{R}$. Recovered optional argument: x^2 and x^3. Recovered document command: x. Recovered declared command: x. Recovered math declarations: $\operatorname{rank}(A)$, $|x|$, and $\mathbb{N}$. Recovered Unicode declaration: **Unicode recovered from a LaTeX fence**.

LaTeX/TeX fences are rendered, not executed. The source of a LaTeX fence is hidden by default; add show=true when the source itself should appear in the PDF. Unrecognized or malformed preamble commands may not be rescued. The `tex` language alias is also accepted:

```
\[
\sum_{k=1}^{n} k = \frac{n(n+1)}{2}.
\]
```

$$\sum_{k=1}^{n} k = \frac{n(n+1)}{2}.$$

The fence parser also respects marker length. The shorter inner fence below must remain inside the four-backtick Markdown example rather than closing it:

````
```python
This is displayed Markdown code, not an executable Python block.
```
````

5. Python execution, presentation, and cache behavior

An omitted run attribute and run=true both mean “run normally”. A cold run executes; an unchanged later build can use the cache.

```
print(”Python runs by default.”)
print(”Standard-library arithmetic:”, sum(range(1, 6)))
```

OUTPUT:

```
Python runs by default.
Standard-library arithmetic: 15
```

The Python runner presents **file** in the input working directory and keeps that directory on sys.path:

OUTPUT:

```
Working directory: D:\latex_editor
__file__ parent is working directory: True
```

The py, python3, and py3 class aliases are recognized:

OUTPUT:

```
Python alias py works.
```

OUTPUT:

```
Python alias python3 works.
```

OUTPUT:

```
Python alias py3 works.
```

run=true does not bypass the cache. run=new forces this block to execute again for this build, then refreshes the cache entry for a later ordinary build:

OUTPUT:

```
This run=new block is deliberately fresh on every build of this fixture.
```

cache=false is the alternate cache-bypass option:

OUTPUT:

```
This cache=false block also executes on every build.
```

show=false hides source; output=false hides standard output; maxlines limits displayed standard output:

OUTPUT:

```
Visible output line 1
Visible output line 2
... (1 more lines)
```

The explicit deps attribute adds the named file’s content to the cache key:

OUTPUT:

```
Explicit input dependency bytes: 18340
```

run=false does not execute this recognized Python fence; it remains a normal code listing. The print statement is source text, not expected output:

```python
print("This must not execute because run=false is set.")
```

The next block is an intentional, controlled failure. The traceback should be reported to the console and shown as an error block; the overall document should still compile:

Python error - this block did not finish:


```
Traceback (most recent call last):
  File "<code block>", line 1, in <module>
    raise RuntimeError("Expected regression demonstration: visible Python error
↪   is non-fatal to the PDF build.")
RuntimeError: Expected regression demonstration: visible Python error is
↪   non-fatal to the PDF build.
```

error=false keeps the failure on the console but hides its error block:

Matplotlib is optional. When installed, this block saves a figure and the runner captures it for the PDF. Without Matplotlib, it reports a skip and the rest of the document continues:

OUTPUT:

```
Matplotlib figure captured.
```



The legacy img attribute embeds a Python-created image when automatic figure capture is disabled. The image is stored inside md2pdf_cache and is disposable:

OUTPUT:

```
Saved image for the img attribute.
```

Python fences may read/write ordinary local files. This pair checks cache restoration of a workspace-local side effect between dependent blocks:

OUTPUT:

```
Created a disposable cache-side-effect fixture.
```

OUTPUT:

```
Restored/read value: value
42
```

The final cleanup block runs every time, including on a later build after the first block's cache has restored the generated file:

OUTPUT:

```
Removed the disposable side-effect fixture.
```

The cache tracks many file opens and restores eligible workspace-local side effects on a valid cache hit. Use deps="relative-or-absolute-path" for dependencies that automatic tracking cannot identify reliably. The generated CSV is removed by the cleanup block; the legacy img example remains in md2pdf_cache until that regenerable cache folder is cleared.

6. Images and unsupported inputs

Remote images and unsupported extensions are dropped with a warning instead of being passed to XeLaTeX as broken image paths:

The filter supports existing local PNG, JPG/JPEG, and PDF images. Missing local images are dropped with a warning. A Python-generated figure above exercises image embedding without requiring a separate fixture asset.

Raw HTML nodes represented by Pandoc as raw blocks/inlines are removed. HTML divs may instead become structural Divs, whose text content is retained. Selected HTML leftovers in prose (br, sub, sup) are converted by text normalization. HTML inside code spans, indented code, fenced code, and supported verbatim/listing environments stays literal.

7. Expected failures and limits (not activated here)

These examples are intentionally not active build input. Copy one at a time into a disposable file only when testing its failure path:

````
Missing input file:
    compile.bat "missing.txt"
    Expected: rejected before Pandoc starts; no new PDF.

Python exception:
    ```{.python}
````
````

```
    raise ValueError("controlled failure")
    ```
    Expected: traceback reported; failure is not cached; PDF build continues.

Unclosed fence:
    Start a fence and omit its closing markers.
    Expected: [markdown-normalizer] warning; the rest of the input is treated as code.

Malformed one-line fence:
    ```inline```
    Expected: ignored-fence warning; do not rely on it as a valid code block.

Missing/unsupported image:
    ![missing](missing.png)
    Expected: image dropped with a warning; build can continue.

Unsupported raw package:
    A command that requires a package absent from the TeX distribution may
    fail with an undefined control sequence. Install the package or remove
    the command; template-managed packages are not reloaded from pasted text.

TeX syntax error:
    An unmatched brace or invalid environment may make XeLaTeX fail.
    Expected: compile.bat reports the log error and does not replace a
    previously existing destination PDF with a failed build.
```

Other known constraints: XeLaTeX is required; bibliography support is Pandoc citeproc, not raw natbib/biblatex; Python caching cannot track every network, environment, or external-state dependency; remote images are not embedded; complex Markdown or raw-LaTeX combinations may need explicit blank lines or simpler markup. See WORKFLOW_ARCHITECTURE.txt for the implementation details.

8. Validation checklist

After compiling this file:

- PDF exists beside this .txt file.
- PDF title and author match the YAML metadata.
- Both citation text and a CSL-formatted reference list appear.
- Headings, lists, table, inline/display math, theorem, proof, and TikZ render.
- Real Python output appears; run=false source appears without its output.
- run=new and cache=false blocks show output on every build.
- The dependent Python blocks can restore/read their cached CSV on a later build.
- The controlled Python failure is visible on the console but does not stop PDF creation.
- Matplotlib figure appears when the optional dependency is installed.
- Console warnings explain intentionally removed markers/emoji and dropped remote SVG.
- The input .txt file remains unchanged.

Expected output file: FILTER_FEATURE_REGRESSION.pdf

References

[] Doe, Jane. 2024. “A Small Reference for Workflow Testing.” *Regression Notes*.