calls
MilestoneFileController
-milestoneFileService: MilestoneFileService
+getMilestoneFiles(userId, roleName, contractId, milestoneId)
+uploadMilestoneFile(userId, contractId, milestoneId, file)
+deleteMilestoneFile(userId, contractId, milestoneId, fileId)
maps to
<<route>>
MilestoneFileRoutes
+GET /contracts/:contractId/milestones/:milestoneId/files (AuthGuard, PermissionGuard)
+POST /contracts/:contractId/milestones/:milestoneId/files (AuthGuard, PermissionGuard, FileInterc
+DELETE /contracts/:contractId/milestones/:milestoneId/files/:fileId (AuthGuard, PermissionGuard)
AuthGuard
-tokenService: TokenService
-prisma: PrismaService
-reflector: Reflector
+canActivate(context: ExecutionContext): Promise<boolean>
-extractTokenFromHeader(request: Request): string | undefined
PermissionGuard
-reflector: Reflector
-sharedPermissionRepository: SharedPermissionRepository
+canActivate(context: ExecutionContext): Promise<boolean>
<<dto>>
UploadMilestoneFileResponseDTO
+id: number
+milestoneId: number
+uploaderId: number
+fileUrl: string
+fileName: string | null
<<dto>>
GetMilestoneFilesResponseDTO
+files: MilestoneFileType[]
+length: number
<<dto>>
DeleteMilestoneFileResponseDTO
+id: number
+milestoneId: number
+deletedAt: Date | null
<<type>>
MilestoneFileType
+id: number
+milestoneId: number
+uploaderId: number
+fileUrl: string
+publicId: string
+fileName: string | null
+createdAt: Date
MilestoneFileService
-milestoneFileRepository: MilestoneFileRepository
-cloudinaryService: CloudinaryService
+getMilestoneFiles(userId, roleName, contractId, milestoneId)
+uploadMilestoneFile(userId, contractId, milestoneId, file)
+deleteMilestoneFile(userId, contractId, milestoneId, fileId)
calls
<<utility>>
CloudinaryService
+isConfigured(): boolean
+uploadFile(file: Express.Multer.File, folder?: string)
+deleteFile(publicId: string): Promise<any>
calls
MilestoneFileRepository
-prisma: PrismaService
+findContractById(contractId: number)
+findMilestoneById(milestoneId: number)
+findFileById(fileId: number)
+getMilestoneFiles(milestoneId: number)
+createMilestoneFile(data: { milestoneId, uploaderId, fileUrl, publicId, fileName? })
+softDeleteFile(fileId: number)
maps to
maps to
<<schema>>
MilestoneFile
+id: number [PK]
+milestoneId: number [FK]
+uploaderId: number [FK]
+fileUrl: string
+publicId: string
+fileName: string | null
+createdAt: Date
+deletedAt: Date | null
1..*
<<schema>>
Milestone
+id: number [PK]
+contractId: number [FK]
+title: string
+status: MilestoneStatus
1..*
<<schema>>
Contract
+id: number [PK]
+clientId: number [FK]
+freelancerId: number [FK]
+status: ContractStatus
1
<<schema>>
User
+id: number [PK]
+email: string
+roleId: number [FK]
+deletedAt: Date | null