FPT UNIVERSITY

# Capstone Project Report

## Report 4 – Software Design Document

– Can Tho, October 2026 –

# Table of Contents

**I. Record of Changes** **9**

**II. Software Design Document** **10**

**1. System Design** . . . . . **10**

1.1 System Architecture . . . . . 10

1.1.1 Layered Architecture . . . . . 11

1.1.2 API Module Structure . . . . . 12

1.2 Package Diagram . . . . . 13

1.3 Assumptions and Risks . . . . . 15

1.4 Design Constraints . . . . . 16

1.4.1 Platform Compatibility . . . . . 16

1.4.2 Integration Complexity . . . . . 16

1.4.3 Performance Requirements . . . . . 17

1.5 Technology Stack . . . . . 17

1.5.1 NestJS Framework . . . . . 18

1.5.2 Next.js and React 19 Frontend . . . . . 18

1.5.3 Prisma ORM and PostgreSQL . . . . . 18

1.5.4 Supporting Services . . . . . 19

**2. Database Design** . . . . . **19**

2.1 Table Relationships . . . . . 20

2.2 Module Entity–Relationship Diagrams . . . . . 29

**3. Detailed Design** . . . . . **42**

3.1 Forum Management . . . . . 42

3.1.0.1 Class Diagram . . . . . 43

3.1.0.2 UC-14.01 – View Forum Category List . . . . . 44

3.1.0.3 UC-14.02 – View Forum Category Detail . . . . . 45

3.1.0.4 UC-14.03 – View Post List . . . . . 46

3.1.0.5 UC-14.04 – View Post Detail . . . . . 47

3.1.0.6 UC-14.05 – Create Post . . . . . 48

3.1.0.7 UC-14.06 – Update Post . . . . . 49

3.1.0.8 UC-14.07 – Delete Post . . . . . 50

3.1.0.9 UC-14.08 – Like Post . . . . . 51

3.1.0.10 UC-14.09 – Unlike Post . . . . . 52

3.1.0.11 UC-14.10 – View Post Likes . . . . . 53

3.1.0.12 UC-14.11 – View Post Comments . . . . . 54

3.1.0.13 UC-14.12 – Create Comment . . . . . 55

3.1.0.14 UC-14.13 – Update Comment . . . . . 56

3.1.0.15 UC-14.14 – Delete Comment . . . 57
3.1.0.16 UC-14.15 – Like Comment . . . 58
3.1.0.17 UC-14.16 – Unlike Comment . . . 59
3.1.0.18 UC-14.17 – Report Content . . . 60
3.2 Job Browsing . . . 61
3.2.0.1 Class Diagram . . . 61
3.2.0.2 UC-10.01 – View Job List . . . 62
3.2.0.3 UC-10.02 – View Job Detail . . . 63
3.3 Job Management . . . 63
3.3.0.1 Class Diagram . . . 64
3.3.0.2 UC-11.01 – View My Jobs . . . 65
3.3.0.3 UC-11.02 – Create Job . . . 66
3.3.0.4 UC-11.03 – Publish Job . . . 67
3.3.0.5 UC-11.04 – Update Job . . . 68
3.3.0.6 UC-11.05 – Delete Job . . . 69
3.3.0.7 UC-11.06 – Change Job Status . . . 70
3.4 Bookmarked Jobs Management . . . 70
3.4.0.1 Class Diagram . . . 71
3.4.0.2 UC-12.01 – View Bookmarked Job List . . . 72
3.4.0.3 UC-12.02 – Bookmark Job . . . 73
3.4.0.4 UC-12.03 – Remove Bookmark . . . 74
3.5 Verify JWT . . . 74
3.5.0.1 Class Diagram . . . 75
3.5.0.2 UC-00 – Verify JWT . . . 76
3.6 Authentication . . . 76
3.6.0.1 Class Diagram . . . 77
3.6.0.2 UC-01 – Login with Google . . . 78
3.6.0.3 UC-02 – Login . . . 79
3.6.0.4 UC-03 – Logout . . . 80
3.6.0.5 UC-04 – Register . . . 81
3.6.0.6 UC-05 – Forgot Password . . . 82
3.7 Role Management . . . 83
3.7.0.1 Class Diagram . . . 83
3.7.0.2 UC-06.01 – View Role List . . . 84
3.7.0.3 UC-06.02 – View Role Detail . . . 85
3.7.0.4 UC-06.03 – Create Role . . . 86
3.7.0.5 UC-06.04 – Update Role . . . 87
3.7.0.6 UC-06.05 – Delete Role . . . 88
3.7.0.7 UC-06.06 – Update Role Permissions . . . 89
3.8 Manage Conversation . . . 90

3.8.0.1 Class Diagram . . . 90
3.8.0.2 UC-27.01 – View Conversation List . . . 91
3.8.0.3 UC-27.02 – Start Conversation . . . 92
3.8.0.4 UC-27.03 – View Conversation Detail . . . 93
3.8.0.5 UC-27.04 – Send Message . . . 94
3.8.0.6 UC-27.05 – Mark Message as Read . . . 95
3.8.0.7 UC-27.06 – Delete/Recall Message . . . 96
3.8.0.8 UC-27.07 – Pin/Unpin Conversation . . . 97
3.8.0.9 UC-27.08 – Send File . . . 98
3.9 Saved Search Management . . . 98
3.9.0.1 Class Diagram . . . 99
3.9.0.2 UC-22.01 – View Saved Search List . . . 100
3.9.0.3 UC-22.02 – View Saved Search Detail . . . 101
3.9.0.4 UC-22.03 – Create Saved Search . . . 102
3.9.0.5 UC-22.04 – Update Saved Search . . . 103
3.9.0.6 UC-22.05 – Delete Saved Search . . . 104
3.10 Job Alert Management . . . 104
3.10.0.1Class Diagram . . . 105
3.10.0.2UC-23.01 – View Job Alert List . . . 106
3.10.0.3UC-23.02 – View Job Alert Detail . . . 107
3.10.0.4UC-23.03 – Create Job Alert . . . 108
3.10.0.5UC-23.04 – Update Job Alert . . . 109
3.10.0.6UC-23.05 – Delete Job Alert . . . 110
3.11 Permission Management . . . 110
3.11.0.1Class Diagram . . . 111
3.11.0.2UC-15.01 – View Permission List . . . 111
3.11.0.3UC-15.02 – View Permission Detail . . . 112
3.12 Session Management . . . 112
3.12.0.1Class Diagram . . . 113
3.12.0.2UC-16.01 – View Session List . . . 113
3.12.0.3UC-16.02 – View Session Detail . . . 114
3.12.0.4UC-16.03 – Revoke Session . . . 115
3.13 Forum Category Management . . . 115
3.13.0.1Class Diagram . . . 116
3.13.0.2UC-17.01 – Create Forum Category . . . 117
3.13.0.3UC-17.02 – Update Forum Category . . . 118
3.13.0.4UC-17.03 – Delete Forum Category . . . 119
3.13.0.5UC-17.06 – Restore Forum Category . . . 120
3.14 Manage Moderation . . . 120
3.14.0.1Class Diagram . . . 121

3.14.0.2UC-34.01 – View Moderation Queue . . . 121
3.14.0.3UC-34.02 – View Moderation Item Detail . . . 122
3.14.0.4UC-34.03 – Resolve Moderation Item . . . 123
3.15 Manage ID Verification . . . 124
3.15.0.1Class Diagram . . . 124
3.15.0.2UC-35.01 – View ID Verification Request List . . . 124
3.15.0.3UC-35.02 – View ID Verification Request Detail . . . 125
3.15.0.4UC-35.03 – Approve ID Verification . . . 126
3.15.0.5UC-35.04 – Reject ID Verification . . . 127
3.16 Manage Forum Trash . . . 128
3.16.0.1Class Diagram . . . 128
3.16.0.2UC-36.01 – View Deleted Posts/Comments List . . . 129
3.16.0.3UC-36.02 – View Deleted Posts/Comments Detail . . . 130
3.16.0.4UC-36.03 – Restore Deleted Posts/Comments . . . 131
3.17 Proposal Management . . . 132
3.17.0.1Class Diagram . . . 132
3.17.0.2UC-32.01 – View My Proposal List . . . 134
3.17.0.3UC-32.02 – View My Proposal Detail . . . 135
3.17.0.4UC-32.03 – Submit Proposal . . . 136
3.17.0.5UC-32.04 – Update Proposal . . . 137
3.17.0.6UC-32.05 – Withdraw Proposal . . . 138
3.17.0.7UC-32.06 – Accept Proposal . . . 139
3.17.0.8UC-32.07 – Reject Proposal . . . 140
3.17.0.9UC-32.08 – View Job Proposal List . . . 141
3.17.0.10UC-32.09 – View Proposal Detail . . . 142
3.18 User Management . . . 142
3.18.0.1Class Diagram . . . 143
3.18.0.2UC-28.01 – View User List . . . 144
3.18.0.3UC-28.02 – View User Detail . . . 145
3.18.0.4UC-28.03 – Create User . . . 146
3.18.0.5UC-28.04 – Update User . . . 147
3.18.0.6UC-28.05 – Update Client Profile . . . 148
3.18.0.7UC-28.06 – Update Freelancer Basic Info . . . 149
3.18.0.8UC-28.07 – Update Freelancer Skills . . . 150
3.18.0.9UC-28.08 – Update Freelancer Portfolio . . . 151
3.19 Banner Management . . . 151
3.19.0.1Class Diagram . . . 152
3.19.0.2UC-37.01 – View Banner List . . . 153
3.19.0.3UC-37.02 – View Banner Detail . . . 154
3.19.0.4UC-37.03 – Create Banner . . . 155

3.19.0.5UC-37.04 – Update Banner . . . 156
3.19.0.6UC-37.05 – Delete Banner . . . 157
3.20 Skill Management . . . 157
3.20.0.1Class Diagram . . . 158
3.20.0.2UC-38.01 – View Skill List . . . 159
3.20.0.3UC-38.02 – View Skill Detail . . . 160
3.20.0.4UC-38.03 – Create Skill . . . 161
3.20.0.5UC-38.04 – Update Skill . . . 162
3.20.0.6UC-38.05 – Delete Skill . . . 163
3.20.0.7UC-38.06 – Restore Skill . . . 164
3.21 Expert Profile Management . . . 164
3.21.0.1Class Diagram . . . 165
3.21.0.2UC-28.09 – Update Expert Profile . . . 166
3.22 Job Category Management . . . 166
3.22.0.1Class Diagram . . . 167
3.22.0.2UC-46.01 – View Job Category List . . . 167
3.22.0.3UC-46.02 – View Job Category Detail . . . 168
3.22.0.4UC-46.03 – Create Job Category . . . 169
3.22.0.5UC-46.04 – Update Job Category . . . 170
3.22.0.6UC-46.05 – Delete Job Category . . . 171
**4. Class Specification . . . 171**
4.1 AuthGuard Class . . . 171
4.1.0.1 ClassMethod . . . 171
4.1.0.2 ClassAttribute . . . 172
4.2 AuthController Class . . . 172
4.2.0.1 ClassMethod . . . 172
4.2.0.2 ClassAttribute . . . 175
4.3 AuthService Class . . . 175
4.3.0.1 ClassMethod . . . 175
4.3.0.2 ClassAttribute . . . 178
4.4 AuthRepository Class . . . 179
4.4.0.1 ClassMethod . . . 179
4.4.0.2 ClassAttribute . . . 182
4.5 RolesController Class . . . 182
4.5.0.1 ClassMethod . . . 182
4.5.0.2 ClassAttribute . . . 183
4.6 RolesService Class . . . 183
4.6.0.1 ClassMethod . . . 183
4.6.0.2 ClassAttribute . . . 184

4.7 RolesRepository Class . . . 185
4.7.0.1 ClassMethod . . . 185
4.7.0.2 ClassAttribute . . . 186
4.8 PermissionsController Class . . . 186
4.8.0.1 ClassMethod . . . 186
4.8.0.2 ClassAttribute . . . 187
4.9 PermissionsService Class . . . 187
4.9.0.1 ClassMethod . . . 187
4.9.0.2 ClassAttribute . . . 187
4.10 PermissionsRepository Class . . . 188
4.10.0.1ClassMethod . . . 188
4.10.0.2ClassAttribute . . . 188
4.11 SessionsController Class . . . 188
4.11.0.1ClassMethod . . . 188
4.11.0.2ClassAttribute . . . 189
4.12 SessionsService Class . . . 189
4.12.0.1ClassMethod . . . 189
4.12.0.2ClassAttribute . . . 190
4.13 SessionsRepository Class . . . 191
4.13.0.1ClassMethod . . . 191
4.13.0.2ClassAttribute . . . 191
4.14 Forum Category Administration (Shared Classes) . . . 192
4.15 UsersController Class . . . 192
4.15.0.1ClassMethod . . . 192
4.15.0.2ClassAttribute . . . 194
4.16 UsersService Class . . . 194
4.16.0.1ClassMethod . . . 194
4.16.0.2ClassAttribute . . . 198
4.17 UsersRepository Class . . . 198
4.17.0.1ClassMethod . . . 198
4.17.0.2ClassAttribute . . . 201
4.18 BannersAdminController Class . . . 201
4.18.0.1ClassMethod . . . 201
4.18.0.2ClassAttribute . . . 202
4.19 BannersAdminService Class . . . 202
4.19.0.1ClassMethod . . . 202
4.19.0.2ClassAttribute . . . 204
4.20 BannersAdminRepository Class . . . 204
4.20.0.1ClassMethod . . . 204

4.20.0.2ClassAttribute . . . . . 205
4.21 SkillsAdminController Class . . . . . 205
4.21.0.1ClassMethod . . . . . 205
4.21.0.2ClassAttribute . . . . . 206
4.22 SkillsAdminService Class . . . . . 206
4.22.0.1ClassMethod . . . . . 206
4.22.0.2ClassAttribute . . . . . 208
4.23 SkillsAdminRepository Class . . . . . 208
4.23.0.1ClassMethod . . . . . 208
4.23.0.2ClassAttribute . . . . . 209
4.24 AdminExpertProfileController Class . . . . . 209
4.24.0.1ClassMethod . . . . . 209
4.24.0.2ClassAttribute . . . . . 210
4.25 ExpertProfileService Class . . . . . 210
4.25.0.1ClassMethod . . . . . 210
4.25.0.2ClassAttribute . . . . . 211
4.26 ExpertProfileRepository Class . . . . . 212
4.26.0.1ClassMethod . . . . . 212
4.26.0.2ClassAttribute . . . . . 213
4.27 JobCategoriesAdminController Class . . . . . 213
4.27.0.1ClassMethod . . . . . 213
4.27.0.2ClassAttribute . . . . . 214
4.28 JobCategoriesAdminService Class . . . . . 214
4.28.0.1ClassMethod . . . . . 214
4.28.0.2ClassAttribute . . . . . 216
4.29 JobCategoriesAdminRepository Class . . . . . 216
4.29.0.1ClassMethod . . . . . 216
4.29.0.2ClassAttribute . . . . . 217

# I. Record of Changes

| Date | A*<br>M, D | In charge | Change Description |
|---|---|---|---|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

**A - Added M - Modified D - Deleted*

# II. Software Design Document

## 1. System Design

### 1.1 System Architecture

Frevia follows a three-tier, deployment-separated architecture (Figure 1).




Figure 1: Overall architecture of the Frevia system

The three tiers are:

- **Presentation tier — Next.js 16 web application:** server components render public pages (job board, job detail, community forum, expert directory) and private dashboards; client components handle interactivity such as forms, likes, and chat. All server access goes through a single typed HTTP client that attaches the JWT access token and refreshes it transparently when it expires.
- **Application tier — NestJS REST API:** a modular monolith organized into 31 route modules. Every module is internally layered as Controller → Service → Repository. Controllers validate and serialize with shared Zod DTOs; services hold business rules and authorization checks; repositories encapsulate all Prisma queries.
- **Data tier — PostgreSQL via Prisma 7:** the relational store for 64 domain models. Binary files are never stored in the database but in Cloudinary; real-time transport for chat and

notifications is handled by a Socket.io gateway beside the REST API.

The two applications are deployed independently (the web app on Vercel, the API on a Node.js host) and communicate only through the documented REST contract validated by the shared Zod schemas package.

Beside the three tiers, four external systems are connected to the application tier (Figure 1): **Stripe** (Checkout, Connect and webhooks) for escrow payments and payouts, **Cloudinary** for avatar, document and portfolio binaries, **Google OAuth** for federated login, and the **AI moderation/analysis service** that scores forum content, parses CVs and checks identity documents. E-mail (OTP and notifications) is delivered through SMTP with Nodemailer, and secrets are loaded from **Infisical** at start-up. None of these systems is called from the browser: the web application only talks to the API, which owns every credential and decides when a third party is contacted. The table below (Table 1) explains the API modules, and Section 1.2 explains every package of the repository.

### 1.1.1 Layered Architecture

The internal architecture of the API follows a strict layered pattern, enforced identically in every module (Figure 2):

- **Controller layer** — thin Routing Layer. Exposes REST endpoints, applies guards (authentication, roles, permissions), binds validated request DTOs, and delegates to a service. Controllers never query the database directly.
- **Service layer** — business logic layer. Implements use cases, ownership/authorization checks, state-machine transitions (proposal, contract, dispute), and cross-aggregation logic; it throws typed HTTP exceptions (`NotFoundException 404`, `ForbiddenException 403`, `ConflictException 409`) that a global exception filter converts to a uniform error response.
- **Repository layer** — data access layer. The only component allowed to touch Prisma; complex list queries (pagination + counting) are wrapped in `$transaction` for consistency.
- **Shared kernel** — the `@shared/types` workspace package contains Zod models, constants, permission names, and error codes shared with the web app.

Security flow: every request carries a JWT access token; the auth guard validates it and resolves the active role; role and permission guards authorize module-specific operations; refresh tokens are stored server-side in a `Session` row and can be revoked from the session management feature.

AI-assisted pipeline: user-generated content (forum posts/comments, CVs, identity documents) is passed through AI moderation or AI analysis services; forum content can be auto-approved when clean, or queued in `ModerationQueue` for administrator approval when suspicious.




Figure 2: Layered system architecture with security and AI moderation flows

### 1.1.2 API Module Structure

Table 1 summarizes the 31 route modules of the API and their responsibilities.

Table 1: API route modules and responsibilities

| Module | Responsibility |
|---|---|
| auth | registration, OTP, login, refresh token, logout, forgot password, Google OAuth, current account, role switching/joining |
| sessions | device session listing, detail, revocation |
| account-profile | general account profile, avatar, identity verification upload/AI check, client profile, social links, favorite freelancers, following |
| users | administrator user management and skill catalog |
| roles, permissions | RBAC role and permission administration |
| profiles | professional profile, CV upload/AI analysis, skills |
| portfolios | portfolio item CRUD on profiles |
| expert-profile | expert profile management and public expert directory |
| profile-revisions | profile change request approval workflow |
| identity-verifications-admin | identity verification review |
| job-categories | public job category browsing |

| Module | Responsibility |
|---|---|
| job-categories-admin | job category administration (soft delete + restore) |
| skills-admin | skill catalog administration (soft delete + restore) |
| browse-job | public job listing and job detail by slug |
| manage-job | client job management, bookmarks, skill search |
| proposals | proposal lifecycle: draft, submit, withdraw, interview, reject, accept |
| contract | contract lifecycle: create, update, sign, complete, cancel |
| milestone | milestone management inside a contract |
| milestone-file, milestone-submission | milestone attachments and work submission review |
| shared-file | contract shared workspace files |
| payments | Stripe Connect onboarding, platform fee, milestone funding, release, refund, dispute fee, transactions, webhook |
| disputes | dispute lifecycle (user side and admin arbitration side) |
| reviews | contract reviews and responses |
| conversations | direct messaging with real-time delivery |
| notifications | notification feed management |
| forums | forum categories and posts (public side) |
| forums-comment, forums-like, forums-reports | comments, likes, content reports |
| forums-admin | AI moderation queue, pending posts, trash restore, forum statistics |
| saved-search | saved job search filters |
| banners, banners-admin | advertisement banner delivery and administration |

### 1.2 Package Diagram

The repository is a pnpm monorepo managed by Turborepo (Figure 3):

- `apps/web` — the Next.js application. Sub-packages group screens by actor (guest browsing, client, freelancer, admin), shared UI components (`@repo/ui`), server actions, and the i18n message catalogs used by next-intl.
- `apps/api` — the NestJS application. `src/routes/*` contains the 31 domain modules described above; `src/shared` contains cross-cutting infrastructure: authentication guards and decorators, permission constants, global HTTP exception filter, Zod serializer interceptor, Cloudinary storage service, and Prisma client setup. Each domain module folder is organized as `<module>.controller.ts`, `<module>.service.ts`, `<module>.repository.ts`, DTO classes, and module-specific error factories (e.g., `forums.error.ts`).

- `packages/shared-type` — the single source of truth for API contracts: Zod request/response models (`model/*`), enumeration/constant definitions, and permission name lists, imported by both `apps/web` and `apps/api`.

Dependencies only point downwards: `web` and `api` both depend on `shared-type`; no route module imports another route module — cross-module data needs flow through services at the Prisma schema level.




Figure 3: Package diagram of the Frevia monorepo

## Package Descriptions

Table 2 lists every workspace package of the repository and its responsibility.

Table 2: Workspace packages and their responsibility

| No | Package | Description |
|---|---|---|
| 01 | `apps/web` | Next.js 16 presentation layer (App Router, React Server Components, next-intl, TanStack Query, TailwindCSS 4 with shadcn/ui). Contains the screens per actor, the shared UI components, the server actions and the BFF route handlers that attach the access token. |
| 02 | `apps/api` | NestJS 11 application tier: 31 route modules laid out as Controller, Service, Repository and DTO files, together with the global guards, exception filter, Zod serializer interceptor and the Socket.io gateway used by messaging. |

| No | Package | Description |
|---|---|---|
| 03 | apps/api/prisma | Prisma 7 data layer: schema.prisma (64 models and their enums), migrations and seed data. The generated client is the only component allowed to query PostgreSQL. |
| 04 | packages/shared-type | Contract single source of truth (@shared/types): Zod request/response models, enumerations, permission names and error codes consumed by both applications. |
| 05 | packages/ui | Shared React component library (@repo/ui) imported by the web application so that buttons, dialogs, tables and form controls look and behave identically on every screen. |
| 06 | packages/eslint-config | Shared ESLint configuration (@repo/eslint-config) applied to every workspace so that the same rules run across the monorepo. |
| 07 | packages/typescript-config | Shared TypeScript configuration baselines (@repo/typescript-config) that the applications extend for strict compilation. |

### 1.3 Assumptions and Risks

This system is designed based on the following assumptions:

- The Node.js runtime and the frameworks chosen for the project (NestJS 11 for the back-end and Next.js 16 for the frontend) will continue to be actively supported and maintained, ensuring long-term stability and compatibility with evolving technologies.
- The RESTful API architecture will remain a scalable and efficient choice for separating the Next.js presentation layer from the NestJS business layer.
- PostgreSQL, accessed through Prisma ORM 7, will continue to provide reliable, scalable, and secure relational data storage suitable for handling user identity, jobs, contracts, escrow payments, and forum data.
- Third-party services used by the platform — Stripe (payments and escrow), Cloudinary (file storage), Google (OAuth login), the AI moderation/analysis service, and mail delivery via Nodemailer — will stay available and API-compatible during the project lifetime.
- Modern web browsers (e.g., Chrome, Edge, Firefox, Safari) will continue to support the front-end standards required by Next.js/React 19, including HTML5, CSS3 (TailwindCSS), JavaScript ESM, and responsive rendering with React Server Components.
- The application will be deployed in environments with stable internet access to support real-time messaging (Socket.io) and online payment processing.

- Users (Guests, Clients, Freelancers, Experts, and Admins) are familiar with basic web application navigation: browsing job boards, filling forms, managing profiles, and following payment flows.

This system design is also based on the following risks:

- Any breaking change in the major versions of Next.js, NestJS, or Prisma could require refactoring of the user interface components or of the data access layer.
- Cross-browser inconsistencies or outdated device software may affect rendering or the real-time messaging experience.
- Cybersecurity threats such as credential stuffing, token hijacking, or database breaches could compromise sensitive personal and financial information if not proactively managed (the design therefore includes bcrypt-hashed passwords, JWT access/refresh tokens, session revocation, and role-based access control).
- Outages or policy changes of the integrated third-party services (Stripe, Cloudinary, Google OAuth, AI moderation) could temporarily disrupt payments, file uploads, login, or content moderation.
- Network connectivity issues could disrupt access to job proposals, contract collaboration, or checkout flows that rely on server interaction.

## 1.4 Design Constraints

This system should comply with the following constraints:

### 1.4.1 Platform Compatibility

The Frevia application must be compatible with modern web browsers (e.g., Chrome, Edge, Firefox, Safari) for all user roles including Guest, Client, Freelancer, Expert, and Admin. The frontend is implemented with Next.js 16 (App Router, React Server Components) styled with TailwindCSS 4 and shadcn/ui components; the backend is a NestJS 11 REST API. Responsive web design principles must be applied so that a consistent user experience is provided across desktop, tablet, and mobile browsers. Internationalization is achieved with next-intl so the interface can be served in multiple languages from the same code base.

### 1.4.2 Integration Complexity

The Frevia platform integrates a variety of components: the Next.js web application, the NestJS REST API, the PostgreSQL database (via Prisma 7 with the pg adapter), Stripe Checkout and Stripe Connect for escrow payments and payouts, Cloudinary for image and document storage, Socket.io for real-time chat and notifications, Google OAuth for federated login, e-mail for OTP delivery, and AI services for content moderation, CV parsing, and identity document

verification. Communication between the client and the server is carried out through versioned REST endpoints secured with JWT access tokens and refresh tokens stored in dedicated session records; role-based access control restricts each operation to the allowed roles. Design decisions must keep these integrations loosely coupled behind services and repositories so that a provider can be replaced without rewriting business logic.

### 1.4.3 Performance Requirements

The application must remain responsive under concurrent usage by many freelancers and clients. Job browsing, proposal listing, forum feeds, and conversation histories must load promptly; therefore the design mandates server-side pagination for every list operation, database indexes on frequently filtered columns, optimized Prisma queries executed inside transactions for counted lists, and streaming React Server Components to reduce time-to-first-byte. Real-time features (messaging, notifications) must propagate events with minimal delay via Socket.io. Payment operations must reconcile eventual states through Stripe webhooks and explicit synchronization endpoints.

## 1.5 Technology Stack

Frevia adopts a RESTful API architecture to support secure, stateless, and scalable communication between the Next.js frontend and the NestJS backend. This approach provides:

- Modular, reusable API endpoints for account management, job posting, proposals, contracting, milestone escrow, dispute resolution, community forum, and administration.
- Easy extension for mobile applications or third-party integrations in the future.
- Secure access using JWT tokens with role-based authorization for every endpoint.
- Uniform use of standard HTTP methods (GET, POST, PATCH, PUT, DELETE), making the system intuitive to maintain.
- A clear separation between the presentation layer and the business logic layer.

All request/response payloads are validated and typed with shared Zod schemas packaged in `@shared/types`, which is consumed by both the frontend and the backend so that a single source of truth prevents contract drift between the two applications.




Figure 4: RESTful API communication between the Next.js frontend and the NestJS backend

### 1.5.1 NestJS Framework

The backend of Frevia is built with NestJS 11, a TypeScript-first, modular web framework running on Node.js. It is selected for its:

- Rich dependency-injection and module ecosystem, matching the Controller–Service–Repository layering.
- First-class decorator-based REST routing with guards and interceptors for authentication, roles, permissions, and response serialization.
- Excellent support for Zod schema validation (nestjs-zod) and typed DTOs.
- Component structure for WebSockets (Socket.io gateways) used by the messaging module.
- Straightforward integration with Prisma ORM and PostgreSQL for persistence.

### 1.5.2 Next.js and React 19 Frontend

The web client uses Next.js 16 with the App Router. React Server Components render public pages (job lists, job details, forum) directly from the server, while TanStack Query drives interactive islands (forms, likes, real-time chat). react-hook-form together with Zod resolvers validate user input with the same schemas the API uses.

### 1.5.3 Prisma ORM and PostgreSQL

Persistence relies on PostgreSQL accessed through Prisma 7. The schema defines 64 models covering identity and access, profiles, jobs, proposals, contracts and milestones, payments and disputes, reviews, messaging, the community forum, and platform configuration. Prisma's type-safe client keeps data access code verifiable at compile time.

### 1.5.4 Supporting Services

Payments and payouts use Stripe Checkout and Stripe Connect with webhook-driven reconciliation; binaries are stored in Cloudinary; emails (OTP, notifications) are sent with Nodemailer; Google login uses OAuth 2.0; environment configuration is loaded through Infisical so no secret is committed to the repository.

## 2. Database Design

Frevia persists every domain object in a single PostgreSQL database whose schema is declared with Prisma 7 in `apps/api/prisma/schema.prisma`. The schema contains 64 models together with their enumerations, every table has a surrogate integer primary key generated by the database (nine membership tables use a composite key instead), and deletion is either restricted by a foreign-key rule (identity and money-related rows are never removed) or implemented as a soft delete through a `deletedAt` column (content that an administrator must be able to restore: jobs, forum categories and posts, skills, banners, contract term templates). Binary files are not stored in the database: only their Cloudinary URL is kept in the owning row.

Figure 5 shows the entity–relationship diagram of the whole schema. Every table is drawn as a frameless box: the header carries the table name, each of the following rows is one column, and the key columns are flagged with `PK` (primary key) or `FK` (foreign key). A relationship is a line that leaves the many-side table with a crow's foot and ends on the one-side table with a single bar, so it reads from the row that holds the foreign key to the row it references.



Figure 5: Entity–relationship diagram of the Frevia database

### 2.1 Table Relationships

The 64 tables are grouped into nine families; inside a family the relationships are one-to-many, and membership tables carry the many-to-many links:

- **Identity and access** — `User` is the root of the schema. `UserRole` links an account to a `Role`, and `RolePermission` links a role to a `Permission`, which yields the RBAC model enforced by the guards. Authentication adds `Session` (one row per device), `VerificationCode` (OTP for registration and password reset), `OauthAccount` (Google login), `TwoFactorAuth` and `UserSetting`.

- **Profiles** — `Profile` is shared by every account; `FreelancerProfile` and `ClientProfile` extend it with role-specific columns, `Expert` publishes an expert entry in the public directory, and `FreelancerSkill` joins a freelancer to the `Skill` catalogue. `PortfolioItem`, `SocialLink`, `Certificate`, `IdVerificationDocument` and `ProfileRevision` hang from the profile.

- **Jobs** — `Job` belongs to a client and is classified through `JobJobCategory` (`JobCategory`) and `JobSkill` (`Skill`). `JobBookmark`, `RecentlyViewedJob`, `SavedSearch` and `JobAlert` record the browsing behaviour of a freelancer.

- **Proposals and contracts** — `Proposal` references one `Job` and one freelancer; accepting it creates exactly one `Contract`, which carries `ContractTermTemplate` snapshots and a list of

Milestone rows. ProjectProgressUpdate, SharedFile and MilestoneFile document the work in progress, while MilestoneSubmission (with MilestoneSubmissionFile) records the deliverable and its review decision.

- **Payments** — Transaction stores every Stripe movement (funding, release, refund, platform fee, dispute fee) with its payment-intent identifier, and Invoice holds the invoice issued per contract. Money is never derived: the escrow balance of a milestone is the sum of its transactions.
- **Disputes** — Dispute is opened on a contract or a milestone, DisputeEvidence collects the attachments of both parties, DisputeFee records the fee charged to open it, and DisputeDecisionReview stores the request of a party that asks for the decision to be reconsidered.
- **Reviews** — one Review per completed contract, answered by at most one ReviewResponse.
- **Messaging and notifications** — Conversation groups the DirectMessage rows exchanged by two accounts (pin and read state are kept on the message and on the conversation), and Notification feeds the in-app bell.
- **Community forum and configuration** — ForumCategory contains ForumPost, a post contains ForumComment, and ForumLike / ForumReport attach reactions and reports to posts or comments. Administrators work through ModerationQueue and BannedKeyword; platform-wide configuration lives in SystemSetting, AnnouncementBanner and AdvertisementBanner.

### Table Descriptions

Table 3 describes the purpose of every table of the schema, in the order in which the models are declared in schema.prisma, together with its primary key and its foreign keys.

Table 3: Table descriptions of the Frevia database

| No | Table | Description |
|---|---|---|
| 01 | Role | Role catalogue of the RBAC model (admin, client, freelancer, expert); carries the role code, name and description.<br>• **Primary keys:** id<br>• **Foreign keys:** — |
| 02 | UserRole | Assignment of a role to an account, so one account can hold several roles and switch between them.<br>• **Primary keys:** userId, roleId<br>• **Foreign keys:** userId → User, roleId → Role |

| No | Table | Description |
|---|---|---|
| 03 | Permission | Catalogue of route-level permissions (module.action names) used by the permission guard.<br>• **Primary keys:** id<br>• **Foreign keys:** — |
| 04 | RolePermission | Permissions granted to a role; drives the effective permission list of every signed-in account.<br>• **Primary keys:** roleId, permissionId<br>• **Foreign keys:** roleId → Role, permissionId → Permission |
| 05 | User | Account identity: e-mail, username, bcrypt password hash, status, verification and ban flags, preferred language and timestamps.<br>• **Primary keys:** id<br>• **Foreign keys:** — |
| 06 | VerificationCode | One-time code (OTP) issued for e-mail verification or password reset, with its purpose, expiry and consumed flag.<br>• **Primary keys:** id<br>• **Foreign keys:** — |
| 07 | Session | Server-side session per device: refresh-token hash, device/user-agent information, last activity and revocation time.<br>• **Primary keys:** id<br>• **Foreign keys:** userId → User |
| 08 | OauthAccount | Link between an account and an external identity provider (Google) for federated login.<br>• **Primary keys:** id<br>• **Foreign keys:** userId → User |
| 09 | TwoFactorAuth | Two-factor authentication secret and enabled flag of an account (one row per account).<br>• **Primary keys:** id<br>• **Foreign keys:** userId → User |
| 10 | UserSetting | Per-account preferences: interface theme, language and the JSON notification preferences.<br>• **Primary keys:** id<br>• **Foreign keys:** userId → User |
| 11 | Profile | Base profile shared by all accounts: display name, avatar, cover, headline and biography.<br>• **Primary keys:** id<br>• **Foreign keys:** userId → User |

| No | Table | Description |
|---|---|---|
| 12 | FreelancerProfile | Professional data of a freelancer: professional title, overview, hourly rate, availability and total earnings.<br>• **Primary keys:** id<br>• **Foreign keys:** profileId → Profile |
| 13 | FreelancerSkill | Many-to-many link between a freelancer profile and a skill, with the self-declared proficiency level.<br>• **Primary keys:** id<br>• **Foreign keys:** freelancerProfileId → FreelancerProfile, skillId → Skill |
| 14 | ClientProfile | Client-side data: company name, company size, industry and billing information.<br>• **Primary keys:** id<br>• **Foreign keys:** profileId → Profile |
| 15 | Expert | Expert entry published in the public expert directory, with specialisation and verification state.<br>• **Primary keys:** id<br>• **Foreign keys:** profileId → Profile |
| 16 | ProfileRevision | Pending change request on a profile, reviewed and approved or rejected by an administrator.<br>• **Primary keys:** id<br>• **Foreign keys:** userId → User, adminId → User, profileId → Profile |
| 17 | PortfolioItem | Portfolio entry of a profile: title, description, media URL, project link and ordering position.<br>• **Primary keys:** id<br>• **Foreign keys:** freelancerProfileId → FreelancerProfile |
| 18 | SocialLink | External link of a profile (website, LinkedIn, GitHub, Behance) shown on the public profile.<br>• **Primary keys:** id<br>• **Foreign keys:** profileId → Profile |
| 19 | IdVerificationDocument | Identity document uploaded for eKYC, with the AI check result and the administrator decision.<br>• **Primary keys:** id<br>• **Foreign keys:** userId → User, adminId → User, duplicateOfId → IdVerificationDocument |
| 20 | ProfileVisitLog | View log of a freelancer profile (viewerId, targetFreelancerId, viewedAt); source of the profile statistics.<br>• **Primary keys:** id<br>• **Foreign keys:** viewerId → User, targetFreelancerId → User |

| No | Table | Description |
|---|---|---|
| 21 | JobCategory | Hierarchical job category (parent reference, slug, name, icon) with soft-delete support.<br>• **Primary keys:** id<br>• **Foreign keys:** — |
| 22 | Job | Job posting: slug, title, description, budget range, duration, deadline, visibility, status and the owning client.<br>• **Primary keys:** id<br>• **Foreign keys:** clientId → User |
| 23 | JobJobCategory | Many-to-many link between a job and the job categories it is published in.<br>• **Primary keys:** jobId, categoryId<br>• **Foreign keys:** jobId → Job, categoryId → JobCategory |
| 24 | Skill | Skill catalogue shared by freelancer profiles and jobs, with soft-delete support.<br>• **Primary keys:** id<br>• **Foreign keys:** — |
| 25 | JobSkill | Skills required by a job, with the required proficiency level.<br>• **Primary keys:** jobId, skillId<br>• **Foreign keys:** jobId → Job, skillId → Skill |
| 26 | JobBookmark | Jobs saved by a freelancer.<br>• **Primary keys:** userId, jobId<br>• **Foreign keys:** userId → User, jobId → Job |
| 27 | RecentlyViewedJob | Recently opened job postings of an account, with the viewing timestamp.<br>• **Primary keys:** id<br>• **Foreign keys:** userId → User, jobId → Job |
| 28 | SavedSearch | Stored job filter criteria (keyword, categories, budget, skills) that the freelancer can reapply.<br>• **Primary keys:** id<br>• **Foreign keys:** userId → User |
| 29 | JobAlert | Alert configuration attached to a saved search (frequency, channel, active flag).<br>• **Primary keys:** id<br>• **Foreign keys:** userId → User |
| 30 | Proposal | Proposal submitted by a freelancer for a job: cover letter, bid amount, estimated duration and lifecycle status.<br>• **Primary keys:** id<br>• **Foreign keys:** jobId → Job, freelancerId → User |

| No | Table | Description |
|---|---|---|
| 31 | ProposalAttachment | File attached to a proposal (portfolio sample, reference document) stored in Cloudinary.<br>• **Primary keys:** id<br>• **Foreign keys:** proposalId → Proposal |
| 32 | Contract | Contract created when a proposal is accepted: client, freelancer, total amount, terms, signature state, start/end dates and status.<br>• **Primary keys:** id<br>• **Foreign keys:** jobId → Job, proposalId → Proposal, clientId → User, freelancerId → User |
| 33 | ContractTermTemplate | Reusable contract term template owned by a user, with category, content and soft-delete support.<br>• **Primary keys:** id<br>• **Foreign keys:** creatorId → User |
| 34 | Milestone | Milestone inside a contract: title, description, amount, due date, escrow status, progress percentage and approval state.<br>• **Primary keys:** id<br>• **Foreign keys:** contractId → Contract |
| 35 | MilestoneFile | Reference file attached to a milestone and shared with both parties.<br>• **Primary keys:** id<br>• **Foreign keys:** milestoneId → Milestone, uploaderId → User |
| 36 | MilestoneSubmission | Work submitted for a milestone, with the submitted note, timestamp and the client review decision.<br>• **Primary keys:** id<br>• **Foreign keys:** milestoneId → Milestone, freelancerId → User |
| 37 | MilestoneSubmissionFile | Join table linking a submission to the milestone files it delivers.<br>• **Primary keys:** submissionId, fileId<br>• **Foreign keys:** submissionId → MilestoneSubmission, fileId → MilestoneFile |
| 38 | Invoice | Invoice of a contract (one per contract): invoice number, total amount, status, issued, due and paid dates.<br>• **Primary keys:** id<br>• **Foreign keys:** contractId → Contract |

| No | Table | Description |
|---|---|---|
| 39 | Certificate | Completion certificate generated when a contract is finished: unique certificate UID, completion date and JSON metadata.<br>• **Primary keys:** id<br>• **Foreign keys:** contractId → Contract, freelancerId → User, clientId → User |
| 40 | Dispute | Dispute opened on a contract or a milestone: reason, description, opened by, status, resolution and decision timestamps.<br>• **Primary keys:** id<br>• **Foreign keys:** milestoneId → Milestone, openedById → User, respondentId → User, decisionById → User |
| 41 | DisputeFee | Fee charged to open a dispute, with its amount, payment state and the transaction that settled it.<br>• **Primary keys:** id<br>• **Foreign keys:** disputeId → Dispute, userId → User |
| 42 | DisputeEvidence | Evidence attached by either party to a dispute (file, description, uploader).<br>• **Primary keys:** id<br>• **Foreign keys:** disputeId → Dispute, submittedById → User, fileId → SharedFile |
| 43 | DisputeDecisionReview | Request of a party to reconsider a dispute decision, with the response, the reason and the timestamp.<br>• **Primary keys:** id<br>• **Foreign keys:** disputeId → Dispute, userId → User |
| 44 | Transaction | Payment movement reconciled with Stripe (funding, release, refund, platform fee, dispute fee): type, amount, status, payment-intent id and timestamps.<br>• **Primary keys:** id<br>• **Foreign keys:** userId → User, contractId → Contract |
| 45 | Review | Review written after a contract is completed: rating, comment, author, recipient and the reviewed contract.<br>• **Primary keys:** id<br>• **Foreign keys:** contractId → Contract, reviewerId → User, revieweeId → User |

| No | Table | Description |
|---|---|---|
| 46 | ReviewResponse | Reply of the reviewed party to a review (at most one per review).<br>• **Primary keys:** id<br>• **Foreign keys:** reviewId → Review, userId → User |
| 47 | ForumCategory | Forum category: slug, name, description, display order, post counter and soft-delete support.<br>• **Primary keys:** id<br>• **Foreign keys:** — |
| 48 | ForumPost | Forum post: title, content, author, category, moderation status, AI score, reviewer and soft-delete support.<br>• **Primary keys:** id<br>• **Foreign keys:** categoryId → ForumCategory, userId → User, reviewedById → User |
| 49 | ForumComment | Comment on a forum post; comments are one level deep and can be soft-deleted.<br>• **Primary keys:** id<br>• **Foreign keys:** postId → ForumPost, userId → User |
| 50 | ForumLike | Reaction of a member on a post or a comment; a member can like a target only once.<br>• **Primary keys:** id<br>• **Foreign keys:** userId → User, postId → ForumPost, commentId → ForumComment |
| 51 | ForumReport | Content report filed by a member: reason, description, status and the administrator who handled it.<br>• **Primary keys:** id<br>• **Foreign keys:** reporterId → User, postId → ForumPost, commentId → ForumComment, adminId → User |
| 52 | Notification | In-app notification of an account: type, title, body, target link and read state.<br>• **Primary keys:** id<br>• **Foreign keys:** userId → User |
| 53 | AnnouncementBanner | Platform announcement shown in the application: message, link, display window, active flag and soft delete.<br>• **Primary keys:** id<br>• **Foreign keys:** — |

| No | Table | Description |
|---|---|---|
| 54 | ModerationQueue | Queue of AI-flagged or user-reported content waiting for an administrator decision, with the item type, the score and the assignee.<br>• **Primary keys:** id<br>• **Foreign keys:** reporterId → User, adminId → User |
| 55 | SystemSetting | Platform-wide configuration values stored as key/value rows.<br>• **Primary keys:** id<br>• **Foreign keys:** — |
| 56 | BannedKeyword | Keyword list used by the moderation filter before the AI service is called.<br>• **Primary keys:** id<br>• **Foreign keys:** createdBy → User |
| 57 | AdvertisementBanner | Advertising banner with image, target URL, position, schedule and click counter.<br>• **Primary keys:** id<br>• **Foreign keys:** — |
| 58 | FavoriteFreelancer | Freelancers marked as favourite by a client account.<br>• **Primary keys:** clientId, freelancerId<br>• **Foreign keys:** clientId → User, freelancerId → User |
| 59 | FollowFreelancer | Follow relationship between two accounts, used by the activity feed.<br>• **Primary keys:** clientId, freelancerId<br>• **Foreign keys:** clientId → User, freelancerId → User |
| 60 | PortfolioLike | Like given on a portfolio item.<br>• **Primary keys:** userId, portfolioItemId<br>• **Foreign keys:** userId → User, portfolioItemId → PortfolioItem |
| 61 | ProjectProgressUpdate | Progress note posted by the freelancer on a contract, with the update timestamp.<br>• **Primary keys:** id<br>• **Foreign keys:** contractId → Contract, freelancerId → User |
| 62 | SharedFile | File shared in the workspace of a contract (both parties can upload and read).<br>• **Primary keys:** id<br>• **Foreign keys:** contractId → Contract, uploaderId → User |

| No | Table | Description |
|---|---|---|
| 63 | Conversation | Direct conversation between two accounts, with last-message cache and the pin state of each participant.<br>• **Primary keys:** id<br>• **Foreign keys:** participant1 → User, participant2 → User |
| 64 | DirectMessage | Message of a conversation: sender, content, attachments, read state, recall (soft delete) flag and timestamp.<br>• **Primary keys:** id<br>• **Foreign keys:** conversationId → Conversation, senderId → User |

## 2.2 Module Entity–Relationship Diagrams

The whole schema is easier to navigate when it is split along the functional modules used in Report 3. Each figure below shows one module together with the tables that the module references, so every foreign key of the module is visible in the same picture. The notation is the one of Figure 5: the crow's foot marks the many side of a relationship and the single bar marks the one side.




Figure 6: ERD1 — Authentication & Sessions (`User`, `Session`, `OauthAccount`, `TwoFactorAuth`, `UserSetting`, `VerificationCode`)




Figure 7: ERD2 — Role-Based Access Control (`User`, `Role`, `UserRole`, `Permission`, `RolePermission`)




Figure 8: ERD3 — Profile Core (`User`, `Profile`, `FreelancerProfile`, `ClientProfile`, `Expert`)




Figure 9: ERD4 — Profile History & Social Links (`User`, `Profile`, `ProfileRevision`, `SocialLink`)




Figure 10: ERD5 — Identity Verification & Profile Visits (`User`, `IdVerificationDocument`, `ProfileVisitLog`)




Figure 11: ERD6 — Portfolio & Skills (`User`, `FreelancerProfile`, `FreelancerSkill`, `Skill`, `PortfolioItem`, `PortfolioLike`)




Figure 12: ERD7 — Favorites & Follows (`User`, `FavoriteFreelancer`, `FollowFreelancer`)




Figure 13: ERD8 — Job Posting (`User`, `Job`, `JobCategory`, `JobJobCategory`, `JobSkill`, `Skill`)




Figure 14: ERD9 — Job Discovery & Alerts (`User`, `Job`, `JobBookmark`, `RecentlyViewedJob`, `SavedSearch`, `JobAlert`)




Figure 15: ERD10 — Proposal (`Job`, `User`, `Proposal`, `ProposalAttachment`)




Figure 16: ERD11 — Contract (`Job`, `Proposal`, `User`, `Contract`, `ContractTermTemplate`)




Figure 17: ERD12 — Milestone & Project Progress (`User`, `Contract`, `Milestone`, `MilestoneFile`, `ProjectProgressUpdate`)




Figure 18: ERD13 — Milestone Submission (`User`, `Milestone`, `MilestoneFile`, `MilestoneSubmission`, `MilestoneSubmissionFile`)




Figure 19: ERD14 — Escrow, Payments & Certificates (`User`, `Contract`, `Invoice`, `Transaction`, `Certificate`)




Figure 20: ERD15 — Dispute Core (`Contract`, `Milestone`, `User`, `SharedFile`, `Dispute`)




Figure 21: ERD16 — Dispute Resolution (`User`, `Dispute`, `DisputeFee`, `DisputeEvidence`, `SharedFile`, `DisputeDecisionReview`)




Figure 22: ERD17 — Reviews & Reputation (`Contract`, `User`, `Review`, `ReviewResponse`)




Figure 23: ERD18 — Forum Posts & Comments (`ForumCategory`, `ForumPost`, `User`, `ForumComment`)




Figure 24: ERD19 — Forum Likes (`User`, `ForumPost`, `ForumComment`, `ForumLike`)




Figure 25: ERD20 — Forum Reports & Moderation (`User`, `ForumPost`, `ForumComment`, `ForumReport`)




Figure 26: ERD21 — Messaging & Notifications (`User`, `Conversation`, `DirectMessage`, `Notification`)




Figure 27: ERD22 — Administration & System (`User`, `ModerationQueue`, `BannedKeyword`, `AnnouncementBanner`, `AdvertisementBanner`, `SystemSetting`)

# 3. Detailed Design

This chapter presents the detailed design of every feature of the system. Each section (3.x) covers one feature and contains the class diagram of the feature (3.x.1) followed by its sequence diagrams (3.x.2, 3.x.3, ...), one for each use case of the feature. Where several functions are built from the same classes and follow the same interaction pattern, the diagrams are presented once for the representative function and the other functions refer to that section.

## 3.1 Forum Management

Forum Management covers the UC-14 community forum: browsing forum categories and posts, publishing and maintaining posts and comments, toggling likes on posts and comments, and reporting content that breaks the forum rules.

### 3.1.0.1 Class Diagram



Figure 28: Class diagram of Forum Management

### 3.1.0.2 UC-14.01 – View Forum Category List




Figure 29: Sequence diagram of UC-14.01 View Forum Category List

### 3.1.0.3 UC-14.02 – View Forum Category Detail




Figure 30: Sequence diagram of UC-14.02 View Forum Category Detail

#### 3.1.0.4 UC-14.03 – View Post List




Figure 31: Sequence diagram of UC-14.03 View Post List

### 3.1.0.5 UC-14.04 – View Post Detail




Figure 32: Sequence diagram of UC-14.04 View Post Detail

### 3.1.0.6 UC-14.05 – Create Post




Figure 33: Sequence diagram of UC-14.05 Create Post

### 3.1.0.7 UC-14.06 – Update Post




Figure 34: Sequence diagram of UC-14.06 Update Post

### 3.1.0.8 UC-14.07 – Delete Post




Figure 35: Sequence diagram of UC-14.07 Delete Post

### 3.1.0.9 UC-14.08 – Like Post




Figure 36: Sequence diagram of UC-14.08 Like Post

### 3.1.0.10 UC-14.09 – Unlike Post




Figure 37: Sequence diagram of UC-14.09 Unlike Post

### 3.1.0.11 UC-14.10 – View Post Likes




Figure 38: Sequence diagram of UC-14.10 View Post Likes

### 3.1.0.12 UC-14.11 – View Post Comments




Figure 39: Sequence diagram of UC-14.11 View Post Comments

### 3.1.0.13 UC-14.12 – Create Comment




Figure 40: Sequence diagram of UC-14.12 Create Comment

### 3.1.0.14 UC-14.13 – Update Comment




Figure 41: Sequence diagram of UC-14.13 Update Comment

### 3.1.0.15 UC-14.14 – Delete Comment




Figure 42: Sequence diagram of UC-14.14 Delete Comment

### 3.1.0.16 UC-14.15 – Like Comment




Figure 43: Sequence diagram of UC-14.15 Like Comment

### 3.1.0.17 UC-14.16 – Unlike Comment




Figure 44: Sequence diagram of UC-14.16 Unlike Comment

### 3.1.0.18 UC-14.17 – Report Content




Figure 45: Sequence diagram of UC-14.17 Report Content

## 3.2 Job Browsing

Job Browsing allows guests and registered users to search, filter, and view the list of available jobs on the platform, as well as view comprehensive job details.

### 3.2.0.1 Class Diagram




Figure 46: Class diagram of Job Browsing

### 3.2.0.2 UC-10.01 – View Job List




Figure 47: Sequence diagram of UC-10.01 View Job List

#### 3.2.0.3 UC-10.02 – View Job Detail




Figure 48: Sequence diagram of UC-10.02 View Job Detail

## 3.3 Job Management

Job Management enables clients to manage their posted jobs throughout their lifecycle, including creating new jobs, editing job parameters, publishing drafts, closing completed or cancelled jobs, and soft-deleting job postings.

### 3.3.0.1 Class Diagram



Figure 49: Class diagram of Job Management

### 3.3.0.2 UC-11.01 – View My Jobs




Figure 50: Sequence diagram of UC-11.01 View My Jobs

### 3.3.0.3 UC-11.02 – Create Job




Figure 51: Sequence diagram of UC-11.02 Create Job

#### 3.3.0.4 UC-11.03 – Publish Job




Figure 52: Sequence diagram of UC-11.03 Publish Job

### 3.3.0.5 UC-11.04 – Update Job




Figure 53: Sequence diagram of UC-11.04 Update Job

### 3.3.0.6 UC-11.05 – Delete Job




Figure 54: Sequence diagram of UC-11.05 Delete Job

### 3.3.0.7 UC-11.06 – Change Job Status




Figure 55: Sequence diagram of UC-11.06 Change Job Status

## 3.4 Bookmarked Jobs Management

Bookmarked Jobs Management allows freelancers to save interesting job postings for later review, inspect their list of bookmarked jobs, and remove bookmarks when no longer needed.

### 3.4.0.1 Class Diagram




Figure 56: Class diagram of Bookmarked Jobs Management

### 3.4.0.2 UC-12.01 – View Bookmarked Job List




Figure 57: Sequence diagram of UC-12.01 View Bookmarked Job List

### 3.4.0.3 UC-12.02 – Bookmark Job




Figure 58: Sequence diagram of UC-12.02 Bookmark Job

#### 3.4.0.4 UC-12.03 – Remove Bookmark




Figure 59: Sequence diagram of UC-12.03 Remove Bookmark

## 3.5 Verify JWT

Verify JWT is the shared security guard protecting API endpoints across all modules. Every incoming HTTP request with a Bearer token is intercepted, validated for cryptographic signature and expiration time, and verified against the database to guarantee the associated session remains active and has not been revoked.

#### 3.5.0.1 Class Diagram




Figure 60: Class diagram of Verify JWT

#### 3.5.0.2 UC-00 – Verify JWT




Figure 61: Sequence diagram of UC-00 Verify JWT

## 3.6 Authentication

The authentication module covers account registration, email/password and Google OAuth login, logout, password recovery, and the JWT/session flow shared by all protected endpoints.

### 3.6.0.1 Class Diagram



Figure 62: Class diagram of Authentication

### 3.6.0.2 UC-01 – Login with Google



Figure 63: Sequence diagram of UC-01 Login with Google

### 3.6.0.3 UC-02 – Login




Figure 64: Sequence diagram of UC-02 Login

#### 3.6.0.4 UC-03 – Logout




Figure 65: Sequence diagram of UC-03 Logout

### 3.6.0.5 UC-04 – Register

Figure 66: Sequence diagram of UC-04 Register

### 3.6.0.6 UC-05 – Forgot Password




Figure 67: Sequence diagram of UC-05 Forgot Password

## 3.7 Role Management

Role Management lets an administrator inspect the role catalogue, maintain role metadata, and replace the permission set assigned to a role.

### 3.7.0.1 Class Diagram




Figure 68: Class diagram of Role Management

### 3.7.0.2 UC-06.01 – View Role List




Figure 69: Sequence diagram of UC-06.01 View Role List

### 3.7.0.3 UC-06.02 – View Role Detail




Figure 70: Sequence diagram of UC-06.02 View Role Detail

#### 3.7.0.4 UC-06.03 – Create Role




Figure 71: Sequence diagram of UC-06.03 Create Role

### 3.7.0.5 UC-06.04 – Update Role




Figure 72: Sequence diagram of UC-06.04 Update Role

### 3.7.0.6 UC-06.05 – Delete Role




Figure 73: Sequence diagram of UC-06.05 Delete Role

### 3.7.0.7 UC-06.06 – Update Role Permissions




Figure 74: Sequence diagram of UC-06.06 Update Role Permissions

## 3.8 Manage Conversation

Manage Conversation covers the UC-27 private messaging module: listing and starting one-to-one conversations, opening a conversation, sending text messages and files, marking messages as read, recalling a message, and pinning or unpinning a conversation. Delivery is served both by the REST endpoints and by the realtime gateway in the same namespace.

#### 3.8.0.1 Class Diagram



Figure 75: Class diagram of Manage Conversation

### 3.8.0.2 UC-27.01 – View Conversation List




Figure 76: Sequence diagram of UC-27.01 View Conversation List

### 3.8.0.3 UC-27.02 – Start Conversation




Figure 77: Sequence diagram of UC-27.02 Start Conversation

#### 3.8.0.4 UC-27.03 – View Conversation Detail




Figure 78: Sequence diagram of UC-27.03 View Conversation Detail

### 3.8.0.5 UC-27.04 – Send Message




Figure 79: Sequence diagram of UC-27.04 Send Message

### 3.8.0.6 UC-27.05 – Mark Message as Read




Figure 80: Sequence diagram of UC-27.05 Mark Message as Read

### 3.8.0.7 UC-27.06 – Delete/Recall Message




Figure 81: Sequence diagram of UC-27.06 Delete/Recall Message

### 3.8.0.8 UC-27.07 – Pin/Unpin Conversation




Figure 82: Sequence diagram of UC-27.07 Pin/Unpin Conversation

#### 3.8.0.9 UC-27.08 – Send File




Figure 83: Sequence diagram of UC-27.08 Send File

## 3.9 Saved Search Management

Saved Search Management allows freelancers to save complex job filter criteria, view their list of saved searches, inspect search details, update filter parameters, and remove obsolete searches.

### 3.9.0.1 Class Diagram




Figure 84: Class diagram of Saved Search Management

### 3.9.0.2 UC-22.01 – View Saved Search List




Figure 85: Sequence diagram of UC-22.01 View Saved Search List

#### 3.9.0.3 UC-22.02 – View Saved Search Detail




Figure 86: Sequence diagram of UC-22.02 View Saved Search Detail

#### 3.9.0.4 UC-22.03 – Create Saved Search




Figure 87: Sequence diagram of UC-22.03 Create Saved Search

### 3.9.0.5 UC-22.04 – Update Saved Search




Figure 88: Sequence diagram of UC-22.04 Update Saved Search

#### 3.9.0.6 UC-22.05 – Delete Saved Search




Figure 89: Sequence diagram of UC-22.05 Delete Saved Search

## 3.10 Job Alert Management

Job Alert Management enables freelancers to configure automated notifications based on job keywords, budget ranges, and category criteria, ensuring they receive prompt alerts when matching jobs are published.

### 3.10.0.1 Class Diagram




Figure 90: Class diagram of Job Alert Management

### 3.10.0.2 UC-23.01 – View Job Alert List




Figure 91: Sequence diagram of UC-23.01 View Job Alert List

### 3.10.0.3 UC-23.02 – View Job Alert Detail




Figure 92: Sequence diagram of UC-23.02 View Job Alert Detail

#### 3.10.0.4 UC-23.03 – Create Job Alert




Figure 93: Sequence diagram of UC-23.03 Create Job Alert

### 3.10.0.5 UC-23.04 – Update Job Alert




Figure 94: Sequence diagram of UC-23.04 Update Job Alert

#### 3.10.0.6 UC-23.05 – Delete Job Alert




Figure 95: Sequence diagram of UC-23.05 Delete Job Alert

## 3.11 Permission Management

Permission Management exposes the route-level permission catalogue so that an administrator can inspect the permissions available for role assignment.

### 3.11.0.1 Class Diagram




Figure 96: Class diagram of Permission Management

### 3.11.0.2 UC-15.01 – View Permission List




Figure 97: Sequence diagram of UC-15.01 View Permission List

#### 3.11.0.3 UC-15.02 – View Permission Detail




Figure 98: Sequence diagram of UC-15.02 View Permission Detail

## 3.12 Session Management

Session Management gives an authenticated user visibility over the devices that currently hold a refresh-token session and allows a session to be revoked remotely.

### 3.12.0.1 Class Diagram




Figure 99: Class diagram of Session Management

### 3.12.0.2 UC-16.01 – View Session List




Figure 100: Sequence diagram of UC-16.01 View Session List

### 3.12.0.3 UC-16.02 – View Session Detail




Figure 101: Sequence diagram of UC-16.02 View Session Detail

#### 3.12.0.4 UC-16.03 – Revoke Session




Figure 102: Sequence diagram of UC-16.03 Revoke Session

## 3.13 Forum Category Management

Forum Category Management covers the administrator-side category catalogue and the public category views used by the forum. Deletion is a soft delete, so a category can be restored later.

### 3.13.0.1 Class Diagram




Figure 103: Class diagram of Forum Category Management

### 3.13.0.2 UC-17.01 – Create Forum Category




Figure 104: Sequence diagram of UC-17.01 Create Forum Category

### 3.13.0.3 UC-17.02 – Update Forum Category




Figure 105: Sequence diagram of UC-17.02 Update Forum Category

### 3.13.0.4 UC-17.03 – Delete Forum Category




Figure 106: Sequence diagram of UC-17.03 Delete Forum Category

#### 3.13.0.5 UC-17.06 – Restore Forum Category




Figure 107: Sequence diagram of UC-17.06 Restore Forum Category

## 3.14 Manage Moderation

Manage Moderation covers the UC-34 review workflow of the administration console: listing the posts waiting for review, opening a flagged post and approving or rejecting it. A review writes the moderation status, score and reviewer back to the forum post.

### 3.14.0.1 Class Diagram



Figure 108: Class diagram of Manage Moderation

### 3.14.0.2 UC-34.01 – View Moderation Queue




Figure 109: Sequence diagram of UC-34.01 View Moderation Queue

### 3.14.0.3 UC-34.02 – View Moderation Item Detail




Figure 110: Sequence diagram of UC-34.02 View Moderation Item Detail

#### 3.14.0.4 UC-34.03 – Resolve Moderation Item




Figure 111: Sequence diagram of UC-34.03 Resolve Moderation Item

## 3.15 Manage ID Verification

Manage ID Verification covers the UC-35 identity review workflow: listing the submitted identity documents, opening a request with its uploaded file, and approving or rejecting the request. A decision updates the verification status and the reviewer of the identity document.

### 3.15.0.1 Class Diagram



Figure 112: Class diagram of Manage ID Verification

### 3.15.0.2 UC-35.01 – View ID Verification Request List




Figure 113: Sequence diagram of UC-35.01 View ID Verification Request List

### 3.15.0.3 UC-35.02 – View ID Verification Request Detail




Figure 114: Sequence diagram of UC-35.02 View ID Verification Request Detail

### 3.15.0.4 UC-35.03 – Approve ID Verification




Figure 115: Sequence diagram of UC-35.03 Approve ID Verification

### 3.15.0.5 UC-35.04 – Reject ID Verification




Figure 116: Sequence diagram of UC-35.04 Reject ID Verification

## 3.16 Manage Forum Trash

Manage Forum Trash covers the UC-36 recovery workflow: listing the soft-deleted posts and comments kept for review, opening one deleted item, and restoring it so that it becomes visible in the forum again.

### 3.16.0.1 Class Diagram




Figure 117: Class diagram of Manage Forum Trash

### 3.16.0.2 UC-36.01 – View Deleted Posts/Comments List




Figure 118: Sequence diagram of UC-36.01 View Deleted Posts/Comments List

### 3.16.0.3 UC-36.02 – View Deleted Posts/Comments Detail




Figure 119: Sequence diagram of UC-36.02 View Deleted Posts/Comments Detail

### 3.16.0.4 UC-36.03 – Restore Deleted Posts/Comments




Figure 120: Sequence diagram of UC-36.03 Restore Deleted Posts/Comments

## 3.17 Proposal Management

Proposal Management covers the full proposal workflow between freelancers and clients. Freelancers can submit proposals with cover letters, bid amounts, and delivery estimates, view their submitted proposals, modify pending proposals, or withdraw them. Clients can view all proposals submitted for their jobs, inspect detailed freelancer bids, and accept or reject proposals to initiate contracting.

### 3.17.0.1 Class Diagram




Figure 121: Class diagram of Freelancer Proposal Management




Figure 122: Class diagram of Client Proposal Management

### 3.17.0.2 UC-32.01 – View My Proposal List




Figure 123: Sequence diagram of UC-32.01 View My Proposal List

### 3.17.0.3 UC-32.02 – View My Proposal Detail




Figure 124: Sequence diagram of UC-32.02 View My Proposal Detail

### 3.17.0.4 UC-32.03 – Submit Proposal




Figure 125: Sequence diagram of UC-32.03 Submit Proposal

### 3.17.0.5 UC-32.04 – Update Proposal




Figure 126: Sequence diagram of UC-32.04 Update Proposal

### 3.17.0.6 UC-32.05 – Withdraw Proposal




Figure 127: Sequence diagram of UC-32.05 Withdraw Proposal

### 3.17.0.7 UC-32.06 – Accept Proposal




Figure 128: Sequence diagram of UC-32.06 Accept Proposal

### 3.17.0.8 UC-32.07 – Reject Proposal




Figure 129: Sequence diagram of UC-32.07 Reject Proposal

### 3.17.0.9 UC-32.08 – View Job Proposal List




Figure 130: Sequence diagram of UC-32.08 View Job Proposal List

#### 3.17.0.10 UC-32.09 – View Proposal Detail




Figure 131: Sequence diagram of UC-32.09 View Proposal Detail

## 3.18 User Management

User Management provides the administrator with a searchable user catalogue, a consolidated account detail view, and dedicated editors for the Client and Freelancer profiles attached to an account.

### 3.18.0.1 Class Diagram



Figure 132: Class diagram of User Management

### 3.18.0.2 UC-28.01 – View User List




Figure 133: Sequence diagram of UC-28.01 View User List

### 3.18.0.3 UC-28.02 – View User Detail




Figure 134: Sequence diagram of UC-28.02 View User Detail

### 3.18.0.4 UC-28.03 – Create User




Figure 135: Sequence diagram of UC-28.03 Create User

### 3.18.0.5 UC-28.04 – Update User




Figure 136: Sequence diagram of UC-28.04 Update User

### 3.18.0.6 UC-28.05 – Update Client Profile




Figure 137: Sequence diagram of UC-28.05 Update Client Profile

### 3.18.0.7 UC-28.06 – Update Freelancer Basic Info




Figure 138: Sequence diagram of UC-28.06 Update Freelancer Basic Info

### 3.18.0.8 UC-28.07 – Update Freelancer Skills




Figure 139: Sequence diagram of UC-28.07 Update Freelancer Skills

#### 3.18.0.9 UC-28.08 – Update Freelancer Portfolio




Figure 140: Sequence diagram of UC-28.08 Update Freelancer Portfolio

## 3.19 Banner Management

Banner Management maintains the advertisement banners shown in configured page positions. The module supports image upload, lifecycle dates, activation state, and hard deletion.

### 3.19.0.1 Class Diagram




Figure 141: Class diagram of Banner Management

### 3.19.0.2 UC-37.01 – View Banner List




Figure 142: Sequence diagram of UC-37.01 View Banner List

### 3.19.0.3 UC-37.02 – View Banner Detail




Figure 143: Sequence diagram of UC-37.02 View Banner Detail

### 3.19.0.4 UC-37.03 – Create Banner




Figure 144: Sequence diagram of UC-37.03 Create Banner

### 3.19.0.5 UC-37.04 – Update Banner




Figure 145: Sequence diagram of UC-37.04 Update Banner

#### 3.19.0.6 UC-37.05 – Delete Banner




Figure 146: Sequence diagram of UC-37.05 Delete Banner

## 3.20 Skill Management

Skill Management owns the master skill catalogue used by freelancer profiles and job postings. Skills are soft-deleted so that existing references remain valid, and a deleted skill can be restored.

### 3.20.0.1 Class Diagram




Figure 147: Class diagram of Skill Management

### 3.20.0.2 UC-38.01 – View Skill List




Figure 148: Sequence diagram of UC-38.01 View Skill List

### 3.20.0.3 UC-38.02 – View Skill Detail




Figure 149: Sequence diagram of UC-38.02 View Skill Detail

### 3.20.0.4 UC-38.03 – Create Skill




Figure 150: Sequence diagram of UC-38.03 Create Skill

### 3.20.0.5 UC-38.04 – Update Skill




Figure 151: Sequence diagram of UC-38.04 Update Skill

### 3.20.0.6 UC-38.05 – Delete Skill




Figure 152: Sequence diagram of UC-38.05 Delete Skill

#### 3.20.0.7 UC-38.06 – Restore Skill




Figure 153: Sequence diagram of UC-38.06 Restore Skill

### 3.21 Expert Profile Management

The administrator-side Expert Profile editor updates an expert account directly. Any pending self-service revision is superseded, and the account owner is notified of the administrative change.

### 3.21.0.1 Class Diagram



Figure 154: Class diagram of Expert Profile Management

### 3.21.0.2 UC-28.09 – Update Expert Profile




Figure 155: Sequence diagram of UC-28.09 Update Expert Profile

## 3.22 Job Category Management

Job Category Management maintains the taxonomy used by job postings. A category can be created, updated, soft-deleted, and restored; deletion is blocked while active jobs still reference the category.

### 3.22.0.1 Class Diagram



Figure 156: Class diagram of Job Category Management

### 3.22.0.2 UC-46.01 – View Job Category List




Figure 157: Sequence diagram of UC-46.01 View Job Category List

### 3.22.0.3 UC-46.02 – View Job Category Detail




Figure 158: Sequence diagram of UC-46.02 View Job Category Detail

### 3.22.0.4 UC-46.03 – Create Job Category




Figure 159: Sequence diagram of UC-46.03 Create Job Category

### 3.22.0.5 UC-46.04 – Update Job Category




Figure 160: Sequence diagram of UC-46.04 Update Job Category

#### 3.22.0.6 UC-46.05 – Delete Job Category




Figure 161: Sequence diagram of UC-46.05 Delete Job Category

# 4. Class Specification

## 4.1 AuthGuard Class

#### 4.1.0.1 ClassMethod

| No | Method | Description |
|---|---|---|
| 01 | `AuthGuard( reflector: Reflector, tokenService: Token Service, sessionRepo: Session Repository)` | A method to initialize the authentication guard with dependency services.<br>– `reflector`: `Reflector` – metadata reflector to check if a route is marked public.<br>– `tokenService`: `TokenService` – token decoding and verification utility.<br>– `sessionRepo`: `SessionRepository` – repository to query session active status.<br>– *Returns:* `void` – constructor. |
| 02 | `canActivate(context: ExecutionContext)` | A method to inspect the execution context, extract the Bearer token, verify its validity and expiration, and verify that the session has not been revoked.<br>– `context`: `ExecutionContext` – execution context containing HTTP request/response.<br>– *Returns:* `Promise<boolean>` – `true` if authentication succeeds, throws `UnauthorizedException (401)` otherwise. |
| 03 | `extractTokenFromHeader( request: Request)` | A helper method to extract the Bearer token from the incoming HTTP Authorization header.<br>– `request`: `Request` – current Express request object.<br>– *Returns:* `string \| null` – extracted raw token string, or `null` if not found. |

#### 4.1.0.2 ClassAttribute

| No | Attribute | Type |
|---|---|---|
| 01 | `reflector` | `Reflector` |
| 02 | `tokenService` | `TokenService` |
| 03 | `sessionRepo` | `SessionRepository` |

### 4.2 AuthController Class

#### 4.2.0.1 ClassMethod

| No | Method | Description |
|---|---|---|
| 01 | `AuthController(auth Service: AuthService)` | A method to initialize the controller with the authentication service.<br>– `authService`: `AuthService` – service that owns the authentication use cases.<br>– *Returns:* `void` – constructor, no return value. |
| 02 | `register(body: Register Dto)` | A method to create an email/password account after OTP verification.<br>– `body`: `RegisterDto` – email, OTP code, password, full name, and initial role.<br>– *Returns:* `Promise<RegisterResponseType>` – the created account without password fields.<br>– Route: `POST /auth/register`; public endpoint. |
| 03 | `sendOTP(body: SendOTP BodyDTO)` | A method to generate and email an OTP for registration or password reset.<br>– `body`: `SendOTPBodyDTO` – email and verification-code type.<br>– *Returns:* `Promise<MessageResType>` – a success message.<br>– Route: `POST /auth/otp`; public endpoint. |
| 04 | `login( body: LoginBodyDTO, userAgent: string, ip Address: string)` | A method to authenticate an email/password account and create a session.<br>– `body`: `LoginBodyDTO` – email and password.<br>– `userAgent`: `string` – device information used as session metadata.<br>– `ipAddress`: `string` – client IP stored with the session.<br>– *Returns:* `Promise<LoginResponseType>` – access and refresh tokens.<br>– Route: `POST /auth/login`; public endpoint. |
| 05 | `refreshToken( body: RefreshTokenBodyDT O, userAgent: string, ip Address: string)` | A method to rotate a valid refresh token into a new token pair.<br>– `body.refreshToken`: `string` – the current refresh token.<br>– `userAgent`: `string` – device information for the replacement session.<br>– `ipAddress`: `string` – client IP for the replacement session.<br>– *Returns:* `Promise<LoginResponseType>` – the new access and refresh tokens.<br>– Route: `POST /auth/refresh-token`; public endpoint. |

| No | Method | Description |
|---|---|---|
| 06 | `logout(body: LogoutBodyDTO)` | A method to terminate the session identified by a refresh token.<br>– `body.refreshToken`: `string` – refresh token of the session to remove.<br>– *Returns:* `Promise<MessageResType>` – a success message.<br>– Route: `POST /auth/logout`; public endpoint. |
| 07 | `forgotPassword(body: ForgotPasswordBodyDTO)` | A method to reset a password after validating a password-reset OTP.<br>– `body`: `ForgotPasswordBodyDTO` – email, OTP code, and new password.<br>– *Returns:* `Promise<MessageResType>` – a success message.<br>– Route: `POST /auth/forgot-password`; public endpoint. |
| 08 | `getGoogleLink( userAgent: string, ip: string)` | A method to build the Google OAuth consent URL.<br>– `userAgent`: `string` – encoded in the OAuth state.<br>– `ip`: `string` – encoded in the OAuth state.<br>– *Returns:* `GetAuthorizationUrlResType` – the authorization URL.<br>– Route: `GET /auth/google-link`; public endpoint. |
| 09 | `googleCallback( code: string, state: string, res: Response)` | A method to exchange the Google authorization code and redirect the browser.<br>– `code`: `string` – authorization code returned by Google.<br>– `state`: `string` – base64url payload with device and IP information.<br>– `res`: `Response` – Express response used for the redirect.<br>– *Returns:* `Promise<void>` – redirects to the web application with tokens or an error flag.<br>– Route: `GET /auth/google/callback`; public endpoint. |
| 10 | `getMe(userId: number)` | A method to return the authenticated account and its roles.<br>– `userId`: `number` – current user injected by `@UserActive('userId')`.<br>– *Returns:* `Promise<GetMeResType>` – account, profile summary, and roles.<br>– Route: `GET /auth/me`; authenticated endpoint. |

| No | Method | Description |
|---|---|---|
| 11 | `switchRole( userId: number, sessionId: number, body: SwitchRoleBodyDto)` | A method to make an already assigned role the primary role.<br>– `userId`: `number` – current user.<br>– `sessionId`: `number` – current session identifier.<br>– `body.role`: role name to activate.<br>– *Returns:* `Promise<SwitchRoleResponseType>` – a new access token for that role.<br>– Route: `POST /auth/switch-role`; authenticated endpoint. |
| 12 | `joinRole( userId: number, sessionId: number, body: JoinRoleBodyDto)` | A method to assign an additional Client or Freelancer role.<br>– `userId`: `number` – current user.<br>– `sessionId`: `number` – current session identifier.<br>– `body.role`: role name to join.<br>– *Returns:* `Promise<JoinRoleResponseType>` – a new access token for the joined role.<br>– Route: `POST /auth/join-role`; authenticated endpoint. |

#### 4.2.0.2 ClassAttribute

| No | Attribute | Type |
|---|---|---|
| 01 | `authService` | `AuthService` – private readonly authentication service. |
| 02 | `logger` | `Logger` – private readonly NestJS logger for OAuth callback errors. |

### 4.3 AuthService Class

#### 4.3.0.1 ClassMethod

| No | Method | Description |
|---|---|---|
| 01 | `AuthService( hashingService: HashingService, emailService: EmailService, sharedRoleRepository: SharedRoleRepository, authRepository: AuthRepository, tokenService: TokenService)` | A method to initialize the service and its Google OAuth client.<br>– `hashingService`: `HashingService` – password hashing and verification.<br>– `emailService`: `EmailService` – OTP delivery.<br>– `sharedRoleRepository`: `SharedRoleRepository` – resolves system role identifiers.<br>– `authRepository`: `AuthRepository` – account, OTP, session, and OAuth persistence.<br>– `tokenService`: `TokenService` – JWT signing and verification.<br>– *Returns:* `void` – constructor, no return value. |
| 02 | `register(body: RegisterBodyType)` | A method to validate registration data and create an account.<br>– `body`: `RegisterBodyType` – email, OTP, password, full name, and role.<br>– *Returns:* `Promise<UserType>` – the created account without sensitive fields.<br>– Throws `EmailAlreadyExistsException`, `UserBannedException`, `InvalidVerificationCodeException`, or `OTPExpiredException`. |
| 03 | `sendOTP(body: SendOTPBodyType)` | A method to issue an OTP while enforcing the attempt window.<br>– `body`: `SendOTPBodyType` – email and verification-code type.<br>– *Returns:* `Promise<MessageResType>` – a success message.<br>– Throws `EmailAlreadyExistsException`, `EmailNotFoundException`, or `TooManyAttemptsException`. |
| 04 | `login(body: LoginBodyType and session metadata)` | A method to verify credentials, ban state, and the primary role before issuing tokens.<br>– `body`: `LoginBodyType` – email, password, user agent, and IP address.<br>– *Returns:* `Promise<{ accessToken: string; refreshToken: string }>` – the token pair.<br>– Throws `IncorrectEmailException`, `IncorrectPasswordException`, `UserBannedException`, or `RoleNotFoundException`. |

| No | Method | Description |
|---|---|---|
| 05 | `generateAccessAndRefreshTokens(payload)` | A private method to sign a refresh token, persist a session, and sign the access token.<br>– `payload`: object – user id, role id, role name, user agent, and IP address.<br>– *Returns:* `Promise<{ accessToken: string; refreshToken: string }>` – the new token pair.<br>– The access token carries the persisted session id. |
| 06 | `refreshToken(payload)` | A method to validate and rotate a refresh token.<br>– `payload`: object – refresh token, user agent, and IP address.<br>– *Returns:* `Promise<{ accessToken: string; refreshToken: string }>` – the replacement token pair.<br>– Throws `RefreshTokenRevokedException` or `UserBannedException`. |
| 07 | `logout(refreshToken: string)` | A method to remove the session that owns a refresh token.<br>– `refreshToken`: `string` – token of the session to terminate.<br>– *Returns:* `Promise<MessageResType>` – a success message.<br>– Throws `RefreshTokenRevokedException` when the session is absent. |
| 08 | `forgotPassword(payload: ForgotPasswordBodyType)` | A method to validate a reset OTP, hash the new password, and remove the OTP.<br>– `payload`: `ForgotPasswordBodyType` – email, OTP, and new password.<br>– *Returns:* `Promise<MessageResType>` – a success message.<br>– Throws `EmailNotFoundException`, `UserBannedException`, or OTP validation errors. |
| 09 | `validateVerificationCode(uniqueValue)` | A method to load an OTP and reject missing or expired codes.<br>– `uniqueValue`: object – email, code, and verification type.<br>– *Returns:* `Promise<EmailVerificationType>` – the matching OTP record.<br>– Throws `InvalidVerificationCodeException` or `OTPExpiredException`. |

| No | Method | Description |
|---|---|---|
| 10 | `getMe(userId: number)` | A method to return the current account, profile summary, and roles.<br>– `userId`: `number` – current account identifier.<br>– *Returns:* `Promise<GetMeResType>` – the authenticated account view.<br>– Throws `NotFoundException` when absent or `UserBannedException` when banned. |
| 11 | `switchRole(userId, sessionId, body)` | A method to change the primary role and issue a new access token.<br>– `userId`: `number` – current account.<br>– `sessionId`: `number` – current session.<br>– `body`: `SwitchRoleBodyType` – target role.<br>– *Returns:* `Promise<{ accessToken: string }>` – the role-scoped access token.<br>– Throws `RoleNotFoundException`. |
| 12 | `joinRole(userId, sessionId, body)` | A method to assign an additional role and issue a new access token.<br>– `userId`: `number` – current account.<br>– `sessionId`: `number` – current session.<br>– `body`: `JoinRoleBodyType` – role to join.<br>– *Returns:* `Promise<{ accessToken: string }>` – the role-scoped access token.<br>– Throws `RoleNotFoundException` or `RoleAlreadyAssignedException`. |
| 13 | `getAuthorizationUrl(payload)` | A method to build the Google OAuth consent URL with a base64url state.<br>– `payload`: object – user agent and IP address.<br>– *Returns:* `GetAuthorizationUrlResType` – the authorization URL. |
| 14 | `googleCallback(payload)` | A method to exchange a Google code, create or load the account, and issue tokens.<br>– `payload`: object – Google authorization code and state.<br>– *Returns:* `Promise<{ accessToken: string; refreshToken: string }>` – the token pair.<br>– Creates a Client account and an OAuth account on first login; rejects banned accounts. |

#### 4.3.0.2 ClassAttribute

| No | Attribute | Type |
|---|---|---|
| 01 | `hashingService` | `HashingService` – private readonly password utility. |
| 02 | `emailService` | `EmailService` – private readonly OTP delivery utility. |
| 03 | `sharedRoleRepository` | `SharedRoleRepository` – private readonly system-role lookup. |
| 04 | `authRepository` | `AuthRepository` – private readonly authentication persistence. |
| 05 | `tokenService` | `TokenService` – private readonly JWT utility. |
| 06 | `oauth2Client` | `OAuth2Client` – public Google OAuth client. |
| 07 | `logger` | `Logger` – private readonly NestJS logger. |

## 4.4 AuthRepository Class

#### 4.4.0.1 ClassMethod

| No | Method | Description |
|---|---|---|
| 01 | `AuthRepository(prisma: PrismaService)` | A method to initialize the repository with the shared Prisma client.<br>– `prisma`: `PrismaService` – database client.<br>– *Returns:* `void` – constructor, no return value. |
| 02 | `findUserByEmail(email: string)` | A method to load a non-deleted account by email.<br>– `email`: `string` – unique account email.<br>– *Returns:* `Promise<UserType \| null>` – the account without password timestamps, or `null`. |
| 03 | `findUserByEmailIncludeRoles(email: string)` | A method to load an account with its role assignments.<br>– `email`: `string` – unique account email.<br>– *Returns:* `Promise<UserType and roles \| null>` – the account and ordered roles, or `null`. |
| 04 | `findVerificationCode(uniqueValue)` | A method to find an OTP by email, code, and type.<br>– `uniqueValue`: object – email, code, and verification type.<br>– *Returns:* `Promise<EmailVerificationType \| null>` – the matching OTP, or `null`. |

| No | Method | Description |
|---|---|---|
| 05 | `findVerificationCodeBy EmailAndType(email, type)` | A method to load the current OTP record for an email and type.<br>– `email`: `string` – account email.<br>– `type`: `VerificationCodeType` – registration or password-reset code.<br>– *Returns:* `Promise<EmailVerificationType \| null>` – the OTP record, or `null`. |
| 06 | `createUserAndRegister( deleteOtp, user)` | A method to delete the consumed OTP and create the account in one transaction.<br>– `deleteOtp`: object – OTP code, type, and email.<br>– `user`: object – email, password, full name, and initial role.<br>– *Returns:* `Promise<UserType>` – the created account. |
| 07 | `createUserAndRegister Google(user)` | A method to create a Google account with a Client role and profile.<br>– `user`: object – email, full name, and role identifier.<br>– *Returns:* `Promise<UserType and roles>` – the created account with roles. |
| 08 | `upsertVerificationCode( data)` | A method to create or replace an OTP record.<br>– `data`: object – email, type, code, expiry, and attempt count.<br>– *Returns:* `Promise<EmailVerificationType>` – the persisted OTP. |
| 09 | `findUserForLogin(email: string)` | A method to load an account and ordered roles for authentication.<br>– `email`: `string` – account email.<br>– *Returns:* `Promise<UserType and roles \| null>` – the account, or `null`. |
| 10 | `createSession(data)` | A method to persist a refresh-token session.<br>– `data`: object – user id, refresh token, device, IP address, and expiry.<br>– *Returns:* `Promise<Session>` – the created session with its identifier. |
| 11 | `deleteSessionByRefresh Token(data)` | A method to delete a session by refresh token and user id.<br>– `data`: object – refresh token and user id.<br>– *Returns:* `Promise<Session>` – the deleted session. |

| No | Method | Description |
|---|---|---|
| 12 | `findUniqueRefreshToken IncludeUserRole(data)` | A method to load a session, its account, and the account roles by refresh token.<br>– `data.refreshToken`: `string` – refresh token to resolve.<br>– *Returns:* `Promise<Session and user roles \| null>` – the session graph, or `null`. |
| 13 | `update(where, data)` | A method to update a non-deleted account.<br>– `where`: object – account identifier.<br>– `data`: `Partial<UserType>` – fields to change.<br>– *Returns:* `Promise<UserType \| null>` – the updated account. |
| 14 | `deleteVerifycationCode( uniqueValue)` | A method to delete an OTP after a successful password reset.<br>– `uniqueValue`: object – email and verification type.<br>– *Returns:* `Promise<EmailVerificationType>` – the deleted OTP. |
| 15 | `findUserById(userId: number)` | A method to load an account with profile and ordered roles.<br>– `userId`: `number` – account identifier.<br>– *Returns:* `Promise<UserType and profile and roles \| null>` – the account view, or `null`. |
| 16 | `switchPrimaryRole(userId, roleName)` | A method to make an assigned role primary in one transaction.<br>– `userId`: `number` – account identifier.<br>– `roleName`: `string` – role to activate.<br>– *Returns:* `Promise<RoleType \| null>` – the activated role, or `null` when not assigned. |
| 17 | `joinRole(userId, role Name)` | A method to assign a Client or Freelancer role and create its profile row.<br>– `userId`: `number` – account identifier.<br>– `roleName`: `JoinRoleBodyType['role']` – role to join.<br>– *Returns:* `Promise<{ status: 'joined' \| ' already-assigned'; role: RoleType } \| null>` – the assignment result, or `null` when the role is absent. |
| 18 | `createOauthAccount(data)` | A method to link a Google identity to an account.<br>– `data`: object – user id, provider, and provider user id.<br>– *Returns:* `Promise<OauthAccount>` – the created OAuth link. |

#### 4.4.0.2 ClassAttribute

| No | Attribute | Type |
|---|---|---|
| 01 | `prisma` | `PrismaService` – private readonly database client. |

### 4.5 RolesController Class

#### 4.5.0.1 ClassMethod

| No | Method | Description |
|---|---|---|
| 01 | `RolesController(rolesService: RolesService)` | A method to initialize the controller with the role service.<br>– `rolesService`: `RolesService` – service that owns role use cases.<br>– *Returns:* `void` – constructor, no return value. |
| 02 | `getRoles()` | A method to return all active roles.<br>– *Returns:* `Promise<RoleListResponseType>` – the role list.<br>– Route: `GET /roles`. |
| 03 | `getRoleById(id: number)` | A method to return one role with its permissions.<br>– `id`: `number` – role identifier parsed by `ParseIntPipe`.<br>– *Returns:* `Promise<RoleDetailResponseType>` – the role detail.<br>– Route: `GET /roles/:id`. |
| 04 | `createRole(body: CreateRoleBodyDto)` | A method to create a custom role.<br>– `body`: `CreateRoleBodyDto` – role name and optional description.<br>– *Returns:* `Promise<CreateRoleResponseType>` – the created role.<br>– Route: `POST /roles`. |
| 05 | `updateRole(id: number, body: UpdateRoleBodyDto)` | A method to update a role's name or description.<br>– `id`: `number` – role identifier.<br>– `body`: `UpdateRoleBodyDto` – optional name and description.<br>– *Returns:* `Promise<UpdateRoleResponseType>` – the updated role.<br>– Route: `PATCH /roles/:id`. |

| No | Method | Description |
|---|---|---|
| 06 | `setRolePermissions( id: number, body: SetRolePermissions BodyDto)` | A method to replace every permission assigned to a role. – `id: number` – role identifier. – `body.permissionIds: number[]` – the complete replacement set. – *Returns:* `Promise<SetRolePermissionsResponse Type>` – the updated role detail. – Route: `PUT /roles/:id/permissions`. |
| 07 | `deleteRole(id: number)` | A method to soft-delete an unused custom role. – `id: number` – role identifier. – *Returns:* `Promise<DeleteRoleResponseType>` – a success message. – Route: `DELETE /roles/:id`. |

#### 4.5.0.2 ClassAttribute

| No | Attribute | Type |
|---|---|---|
| 01 | `rolesService` | `RolesService` – private readonly role service. |

### 4.6 RolesService Class

#### 4.6.0.1 ClassMethod

| No | Method | Description |
|---|---|---|
| 01 | `RolesService(roles Repository: Roles Repository)` | A method to initialize the service with the role repository. – `rolesRepository: RolesRepository` – persistence dependency. – *Returns:* `void` – constructor, no return value. |
| 02 | `isSystemRoleName(name: string)` | A private method to detect the four built-in role names. – `name: string` – role name to test. – *Returns:* `boolean` – true for Admin, Client, Freelancer, or Expert. |
| 03 | `getRoles()` | A method to load the active role list. – *Returns:* `Promise<RoleListResponseType>` – the role list. – Failure is mapped to `FailedToLoadRolesException`. |

| No | Method | Description |
|---|---|---|
| 04 | `getRoleById(id: number)` | A method to load a role and its permissions.<br>– `id: number` – role identifier.<br>– *Returns:* `Promise<RoleDetailResponseType>` – the role detail.<br>– Prisma errors are mapped to `FailedToLoadRoleDetailException`. |
| 05 | `createRole(body: CreateRoleBodyType)` | A method to validate the name and create a custom role.<br>– `body: CreateRoleBodyType` – role name and optional description.<br>– *Returns:* `Promise<CreateRoleResponseType>` – the created role.<br>– Throws `CannotModifySystemRoleException` or `RoleAlreadyExistsException`. |
| 06 | `updateRole(id: number, body: UpdateRoleBodyType)` | A method to validate system-role and duplicate-name rules before updating.<br>– `id: number` – role identifier.<br>– `body: UpdateRoleBodyType` – optional name and description.<br>– *Returns:* `Promise<UpdateRoleResponseType>` – the updated role.<br>– Throws `CannotModifySystemRoleException` or `RoleAlreadyExistsException`. |
| 07 | `deleteRole(id: number)` | A method to soft-delete a custom role that is not assigned to any user.<br>– `id: number` – role identifier.<br>– *Returns:* `Promise<DeleteRoleResponseType>` – a success message.<br>– Throws `CannotModifySystemRoleException` or `RoleInUseException`. |
| 08 | `setRolePermissions(id, body)` | A method to validate permission ids and replace the role permission set.<br>– `id: number` – role identifier.<br>– `body: SetRolePermissionsBodyType` – permission ids to assign.<br>– *Returns:* `Promise<SetRolePermissionsResponseType>` – the updated role detail.<br>– Throws `InvalidPermissionIdsException`. |

#### 4.6.0.2 ClassAttribute

| No | Attribute | Type |
|---|---|---|
| 01 | `rolesRepository` | `RolesRepository` – private readonly persistence dependency. |
| 02 | `logger` | `Logger` – private readonly NestJS logger. |

## 4.7 RolesRepository Class

#### 4.7.0.1 ClassMethod

| No | Method | Description |
|---|---|---|
| 01 | `RolesRepository(prisma: PrismaService)` | A method to initialize the repository with the shared Prisma client.<br>– `prisma`: `PrismaService` – database client.<br>– *Returns:* `void` – constructor, no return value. |
| 02 | `findAll()` | A method to load all non-deleted roles ordered by id.<br>– *Returns:* `Promise<RoleListItemType[]>` – the role list. |
| 03 | `findById(id: number)` | A method to load a role and its active permissions.<br>– `id`: `number` – role identifier.<br>– *Returns:* `Promise<RoleDetailResponseType>` – the role detail.<br>– Throws `RoleNotFoundException`. |
| 04 | `findActiveByName(name, excludeId?)` | A method to find an active role by case-insensitive name.<br>– `name`: `string` – role name.<br>– `excludeId`: `number \| undefined` – optional role to exclude.<br>– *Returns:* `Promise<RoleListItemType \| null>` – the matching role, or `null`. |
| 05 | `createRole(body: CreateRoleBodyType)` | A method to insert a role.<br>– `body`: `CreateRoleBodyType` – name and optional description.<br>– *Returns:* `Promise<CreateRoleResponseType>` – the created role. |
| 06 | `updateRole(id: number, body: UpdateRoleBodyType)` | A method to update the provided role fields.<br>– `id`: `number` – role identifier.<br>– `body`: `UpdateRoleBodyType` – optional name and description.<br>– *Returns:* `Promise<UpdateRoleResponseType>` – the updated role. |

| No | Method | Description |
|---|---|---|
| 07 | `softDeleteRole(id: number)` | A method to set `deletedAt` on a role.<br>– `id`: `number` – role identifier.<br>– *Returns:* `Promise<void>` – no value. |
| 08 | `countAssignedUsers(roleId: number)` | A method to count user-role assignments.<br>– `roleId`: `number` – role identifier.<br>– *Returns:* `Promise<number>` – the assignment count. |
| 09 | `findActivePermissionIds(ids: number[])` | A method to filter permission ids down to active permissions.<br>– `ids`: `number[]` – requested permission ids.<br>– *Returns:* `Promise<number[]>` – the active ids. |
| 10 | `replaceRolePermissions(roleId, permissionIds)` | A method to delete the old role permissions and insert the new set in a transaction.<br>– `roleId`: `number` – role identifier.<br>– `permissionIds`: `number[]` – replacement permission ids.<br>– *Returns:* `Promise<void>` – no value. |

#### 4.7.0.2 ClassAttribute

| No | Attribute | Type |
|---|---|---|
| 01 | `prisma` | `PrismaService` – private readonly database client. |

### 4.8 PermissionsController Class

#### 4.8.0.1 ClassMethod

| No | Method | Description |
|---|---|---|
| 01 | `PermissionsController(permissionsService: PermissionsService)` | A method to initialize the controller with the permission service.<br>– `permissionsService`: `PermissionsService` – service that owns permission queries.<br>– *Returns:* `void` – constructor, no return value. |
| 02 | `getPermissions(query: PermissionFilterDto)` | A method to return a filtered page of route permissions.<br>– `query`: `PermissionFilterDto` – page, limit, search, method, module, and sort options.<br>– *Returns:* `Promise<PermissionListResponseType>` – permissions, pagination, and module names.<br>– Route: `GET /permissions`. |

| No | Method | Description |
|---|---|---|
| 03 | `getPermissionById(id: number)` | A method to return one permission.<br>– `id: number` – permission identifier parsed by `ParseIntPipe`.<br>– *Returns:* `Promise<PermissionDetailResponseType>` – the permission detail.<br>– Route: `GET /permissions/:id`. |

#### 4.8.0.2 ClassAttribute

| No | Attribute | Type |
|---|---|---|
| 01 | `permissionsService` | `PermissionsService` – private readonly permission service. |

### 4.9 PermissionsService Class

#### 4.9.0.1 ClassMethod

| No | Method | Description |
|---|---|---|
| 01 | `PermissionsService(permissionsRepository: PermissionsRepository)` | A method to initialize the service with the permission repository.<br>– `permissionsRepository: PermissionsRepository` – persistence dependency.<br>– *Returns:* `void` – constructor, no return value. |
| 02 | `getPermissions(filter: PermissionFilterType)` | A method to load a permission page and compute pagination metadata.<br>– `filter: PermissionFilterType` – page, limit, search, method, module, and sort options.<br>– *Returns:* `Promise<PermissionListResponseType>` – permissions, pagination, and module names.<br>– Failure is mapped to `FailedToLoadPermissionsException`. |
| 03 | `getPermissionById(id: number)` | A method to load one permission.<br>– `id: number` – permission identifier.<br>– *Returns:* `Promise<PermissionDetailResponseType>` – the permission detail.<br>– Prisma errors are mapped to `FailedToLoadPermissionDetailException`. |

#### 4.9.0.2 ClassAttribute

| No | Attribute | Type |
|---|---|---|
| 01 | `permissionsRepository` | `PermissionsRepository` – private readonly persistence dependency. |
| 02 | `logger` | `Logger` – private readonly NestJS logger. |

## 4.10 PermissionsRepository Class

#### 4.10.0.1 ClassMethod

| No | Method | Description |
|---|---|---|
| 01 | `PermissionsRepository( prisma: PrismaService)` | A method to initialize the repository with the shared Prisma client.<br>– `prisma`: `PrismaService` – database client.<br>– *Returns:* `void` – constructor, no return value. |
| 02 | `findAll(filter: PermissionFilterType)` | A method to query permissions, the matching total, and the distinct module list.<br>– `filter`: `PermissionFilterType` – page, limit, search, method, module, and sort options.<br>– *Returns:* `Promise<{ permissions: PermissionListItemType[]; total: number; modules: string[] }>` – the page and supporting data.<br>– Search matches name, path, or module case-insensitively. |
| 03 | `findById(id: number)` | A method to load one active permission.<br>– `id`: `number` – permission identifier.<br>– *Returns:* `Promise<PermissionDetailResponseType>` – the permission detail.<br>– Throws `PermissionNotFoundException`. |

#### 4.10.0.2 ClassAttribute

| No | Attribute | Type |
|---|---|---|
| 01 | `prisma` | `PrismaService` – private readonly database client. |

## 4.11 SessionsController Class

#### 4.11.0.1 ClassMethod

| No | Method | Description |
|---|---|---|
| 01 | `SessionsController( sessionsService: SessionsService)` | A method to initialize the controller with the session service.<br>– `sessionsService`: `SessionsService` – service that owns session queries.<br>– *Returns:* `void` – constructor, no return value. |
| 02 | `getMySessions( userId: number, sessionId: number, query: SessionFilterDto)` | A method to return the current user's sessions.<br>– `userId`: `number` – current user.<br>– `sessionId`: `number` – current session, used to mark the active row.<br>– `query`: `SessionFilterDto` – page, limit, search, and sort options.<br>– *Returns:* `Promise<SessionListResponseType>` – sessions and pagination.<br>– Route: `GET /sessions`; authenticated endpoint. |
| 03 | `getMySessionById( userId: number, sessionId: number, id: number)` | A method to return one owned session.<br>– `userId`: `number` – current user.<br>– `sessionId`: `number` – current session, used to mark the active row.<br>– `id`: `number` – session identifier.<br>– *Returns:* `Promise<SessionDetailResponseType>` – the session detail.<br>– Route: `GET /sessions/:id`; authenticated endpoint. |
| 04 | `revokeMySession( userId: number, sessionId: number, id: number)` | A method to revoke one owned session.<br>– `userId`: `number` – current user.<br>– `sessionId`: `number` – current session, used to compute `loggedOut`.<br>– `id`: `number` – session identifier.<br>– *Returns:* `Promise<RevokeSessionResponseType>` – a success message and logout flag.<br>– Route: `DELETE /sessions/:id`; authenticated endpoint. |

#### 4.11.0.2 ClassAttribute

| No | Attribute | Type |
|---|---|---|
| 01 | `sessionsService` | `SessionsService` – private readonly session service. |

### 4.12 SessionsService Class

#### 4.12.0.1 ClassMethod

| No | Method | Description |
|---|---|---|
| 01 | `SessionsService(sessionsRepository: SessionsRepository)` | A method to initialize the service with the session repository.<br>– `sessionsRepository`: `SessionsRepository` – persistence dependency.<br>– *Returns:* `void` – constructor, no return value. |
| 02 | `getMySessions(userId, filter, currentSessionId?)` | A method to load a page of the user's sessions.<br>– `userId`: `number` – current user.<br>– `filter`: `SessionFilterType` – page, limit, search, and sort options.<br>– `currentSessionId`: `number \| undefined` – session to mark as current.<br>– *Returns:* `Promise<SessionListResponseType>` – sessions and pagination.<br>– Failure is mapped to `FailedToLoadSessionsException`. |
| 03 | `getMySessionById(id, userId, currentSessionId?)` | A method to load one session owned by the user.<br>– `id`: `number` – session identifier.<br>– `userId`: `number` – current user.<br>– `currentSessionId`: `number \| undefined` – session to mark as current.<br>– *Returns:* `Promise<SessionDetailResponseType>` – the session detail.<br>– Prisma errors are mapped to `FailedToLoadSessionDetailException`. |
| 04 | `revokeMySession(id, userId, currentSessionId?)` | A method to delete an active session owned by the user.<br>– `id`: `number` – session identifier.<br>– `userId`: `number` – current user.<br>– `currentSessionId`: `number \| undefined` – current session used to compute `loggedOut`.<br>– *Returns:* `Promise<RevokeSessionResponseType>` – a success message and logout flag.<br>– Prisma errors are mapped to `FailedToRevokeSessionException`. |

#### 4.12.0.2 ClassAttribute

| No | Attribute | Type |
|---|---|---|
| 01 | `sessionsRepository` | `SessionsRepository` – private readonly persistence dependency. |

| No | Attribute | Type |
|---|---|---|
| 02 | `logger` | `Logger` – private readonly NestJS logger. |

### 4.13 SessionsRepository Class

#### 4.13.0.1 ClassMethod

| No | Method | Description |
|---|---|---|
| 01 | `SessionsRepository( prisma: PrismaService)` | A method to initialize the repository with the shared Prisma client.<br>– `prisma`: `PrismaService` – database client.<br>– *Returns:* `void` – constructor, no return value. |
| 02 | `findAllByUserId(userId, filter, currentSessionId? )` | A method to query the user's sessions and mark the current one.<br>– `userId`: `number` – owner identifier.<br>– `filter`: `SessionFilterType` – page, limit, search, and sort options.<br>– `currentSessionId`: `number \| undefined` – session to mark as current.<br>– *Returns:* `Promise<{ sessions: SessionListItem Type[]; total: number }>` – the page and total.<br>– Search matches device information or IP address. |
| 03 | `findByIdForUser(id, user Id, currentSessionId?)` | A method to load one session owned by the user.<br>– `id`: `number` – session identifier.<br>– `userId`: `number` – owner identifier.<br>– `currentSessionId`: `number \| undefined` – session to mark as current.<br>– *Returns:* `Promise<SessionDetailResponseType>` – the session detail.<br>– Throws `SessionNotFoundException`. |
| 04 | `deleteActiveByIdForUser( id, userId)` | A method to delete an unexpired session owned by the user.<br>– `id`: `number` – session identifier.<br>– `userId`: `number` – owner identifier.<br>– *Returns:* `Promise<void>` – no value.<br>– Throws `SessionNotFoundException` or `Session AlreadyExpiredException`. |

#### 4.13.0.2 ClassAttribute

| No | Attribute | Type |
|---|---|---|
| 01 | `prisma` | `PrismaService` – private readonly database client. |

### 4.14 Forum Category Administration (Shared Classes)

UC-14.01–14.02 and UC-17.01–17.06 use the shared `ForumAdminController`, `ForumAdminServi` and `ForumAdminRepository`. Their complete specifications, including the category list, detail, create, update, delete, and restore endpoints, are given once in the shared forum administration class specifications for Sprint 3 (see the `ForumAdminController` subsection).

### 4.15 UsersController Class

#### 4.15.0.1 ClassMethod

| No | Method | Description |
|---|---|---|
| 01 | `UsersController(service: UsersService)` | A method to initialize the controller with the user administration service.<br>– `service`: `UsersService` – service that owns admin user use cases.<br>– *Returns:* `void` – constructor, no return value. |
| 02 | `createUser(body: AdminCreateUserBodyDto)` | A method to create an account with an initial role.<br>– `body`: `AdminCreateUserBodyDto` – email, password, full name, and role.<br>– *Returns:* `Promise<AdminCreateUserResponseType>` – the created account.<br>– Route: `POST /users`. |
| 03 | `updateUser( id: number, actorId: number, body: AdminUpdateUserBodyDto)` | A method to update email, display name, or ban state.<br>– `id`: `number` – target user identifier.<br>– `actorId`: `number` – current administrator, used for the self-ban check.<br>– `body`: `AdminUpdateUserBodyDto` – optional email, full name, and ban flag.<br>– *Returns:* `Promise<AdminUpdateUserResponseType>` – the updated account.<br>– Route: `PATCH /users/:id`. |

| No | Method | Description |
|---|---|---|
| 04 | `updateClientProfile( id: number, body: AdminUpdateClient ProfileBodyDto)` | A method to update the Client profile attached to an account.<br>– `id: number` – target user identifier.<br>– `body: AdminUpdateClientProfileBodyDto` – company name, description, and website.<br>– *Returns:* `Promise<AdminClientProfileResponse Type>` – the updated Client profile.<br>– Route: `PATCH /users/:id/client-profile`. |
| 05 | `updateFreelancerProfile( id: number, body: AdminUpdate FreelancerProfileBodyDto)` | A method to update the Freelancer headline and biography.<br>– `id: number` – target user identifier.<br>– `body: AdminUpdateFreelancerProfileBodyDto` – title, bio, languages, education, and certifications.<br>– *Returns:* `Promise<MessageResType>` – a success message.<br>– Route: `PATCH /users/:id/freelancer-profile`. |
| 06 | `replaceFreelancerSkills( id: number, body: AdminReplace FreelancerSkillsBodyDto)` | A method to replace every skill on a Freelancer profile.<br>– `id: number` – target user identifier.<br>– `body.skills`: array of skill name and proficiency pairs.<br>– *Returns:* `Promise<MessageResType>` – a success message.<br>– Route: `PUT /users/:id/freelancer-profile/ skills`. |
| 07 | `createPortfolioItem( id: number, body: AdminCreate PortfolioItemBodyDto)` | A method to add a portfolio item to a Freelancer profile.<br>– `id: number` – target user identifier.<br>– `body: AdminCreatePortfolioItemBodyDto` – title, description, technologies, and project URL.<br>– *Returns:* `Promise<MessageResType>` – a success message.<br>– Route: `POST /users/:id/freelancer-profile/ portfolio-items`. |
| 08 | `updatePortfolioItem( id: number, itemId: number, body: AdminUpdate PortfolioItemBodyDto)` | A method to update one portfolio item owned by the Freelancer profile.<br>– `id: number` – target user identifier.<br>– `itemId: number` – portfolio item identifier.<br>– `body: AdminUpdatePortfolioItemBodyDto` – optional item fields.<br>– *Returns:* `Promise<MessageResType>` – a success message.<br>– Route: `PATCH /users/:id/freelancer-profile/ portfolio-items/:itemId`. |

| No | Method | Description |
|---|---|---|
| 09 | `deletePortfolioItem( id: number, itemId: number)` | A method to soft-delete one portfolio item.<br>– `id`: `number` – target user identifier.<br>– `itemId`: `number` – portfolio item identifier.<br>– *Returns:* `Promise<MessageResType>` – a success message.<br>– Route: `DELETE /users/:id/freelancer-profile/portfolio-items/:itemId`. |
| 10 | `getUsers(query: AdminUserQueryDto)` | A method to return a filtered, paginated user list.<br>– `query`: `AdminUserQueryDto` – page, limit, search, role, sort, and status filters.<br>– *Returns:* `Promise<AdminUserListResponseType>` – users and pagination.<br>– Route: `GET /users`. |
| 11 | `getSkillCatalog()` | A method to return the active skill catalogue for the profile editor.<br>– *Returns:* `Promise<AdminSkillCatalogListType>` – active skills ordered by name.<br>– Route: `GET /users/skills-catalog`. |
| 12 | `getUserById(id: number)` | A method to return a consolidated user detail.<br>– `id`: `number` – target user identifier.<br>– *Returns:* `Promise<AdminUserDetailResponseType>` – account, roles, and profile summaries.<br>– Route: `GET /users/:id`. |

#### 4.15.0.2 ClassAttribute

| No | Attribute | Type |
|---|---|---|
| 01 | `service` | `UsersService` – private readonly user administration service. |

### 4.16 UsersService Class

#### 4.16.0.1 ClassMethod

| No | Method | Description |
|---|---|---|
| 01 | `UsersService( repository: UsersRepository, hashingService: HashingService)` | A method to initialize the service with persistence and password hashing.<br>– `repository`: `UsersRepository` – user persistence dependency.<br>– `hashingService`: `HashingService` – password hashing utility.<br>– *Returns:* `void` – constructor, no return value. |
| 02 | `createUser(body: AdminCreateUserBodyType)` | A method to validate the email and role, hash the password, and create the account.<br>– `body`: `AdminCreateUserBodyType` – email, password, full name, and role id.<br>– *Returns:* `Promise<AdminCreateUserResponseType>` – the created account.<br>– Throws `EmailAlreadyExistsException`, `CreateUserRoleNotFoundException`, `CannotAssignAdminRoleException`, or `FailedToCreateUserException`. |
| 03 | `getUsers(query: AdminUserQueryType)` | A method to load a user page.<br>– `query`: `AdminUserQueryType` – page, limit, search, role, sort, and status filters.<br>– *Returns:* `Promise<AdminUserListResponseType>` – users and pagination.<br>– Failure is mapped to `FailedToGetUsersException`. |
| 04 | `getUserById(id: number)` | A method to load a consolidated account detail.<br>– `id`: `number` – target user identifier.<br>– *Returns:* `Promise<AdminUserDetailResponseType>` – account, roles, and profiles.<br>– Throws `UserNotFoundException` when absent or `FailedToGetUserException` on an unexpected read failure. |
| 05 | `listSkillCatalog()` | A method to return the active skill catalogue.<br>– *Returns:* `Promise<AdminSkillCatalogListType>` – active skills ordered by name. |

| No | Method | Description |
|---|---|---|
| 06 | `updateUser(id, actorId, body)` | A method to update account fields while enforcing the self-ban and email rules.<br>– `id`: `number` – target user identifier.<br>– `actorId`: `number` – current administrator.<br>– `body`: `AdminUpdateUserBodyType` – optional email, full name, and ban flag.<br>– *Returns:* `Promise<AdminUpdateUserResponseType>` – the updated account.<br>– Throws `CannotBanSelfException`, `EmailAlreadyExistsException`, `UserNotFoundException`, or `FailedToUpdateUserException`. |
| 07 | `updateClientProfile(userId, body)` | A method to validate the Client profile context and upsert the profile.<br>– `userId`: `number` – target user identifier.<br>– `body`: `AdminUpdateClientProfileBodyType` – company fields.<br>– *Returns:* `Promise<AdminClientProfileResponseType>` – the updated Client profile.<br>– Throws `UserNotFoundException`, `NoClientRoleForClientProfileException`, or `FailedToUpdateClientProfileException`. |
| 08 | `updateFreelancerProfile(userId, body)` | A method to validate the Freelancer context and upsert profile fields.<br>– `userId`: `number` – target user identifier.<br>– `body`: `AdminUpdateFreelancerProfileBodyType` – title, bio, languages, education, and certifications.<br>– *Returns:* `Promise<MessageResType>` – a success message.<br>– Throws `NoFreelancerRoleForProfileException` or `FailedToUpdateFreelancerProfileException`. |
| 09 | `replaceFreelancerSkills(userId, body)` | A method to replace all Freelancer skills and create missing catalogue skills.<br>– `userId`: `number` – target user identifier.<br>– `body`: `AdminReplaceFreelancerSkillsBodyType` – skill name and proficiency pairs.<br>– *Returns:* `Promise<MessageResType>` – a success message.<br>– Throws `NoFreelancerRoleForProfileException` or `FailedToSaveSkillsException`. |

| No | Method | Description |
|---|---|---|
| 10 | `createPortfolioItem(userId, body)` | A method to create a portfolio item on the Freelancer profile.<br>– `userId`: `number` – target user identifier.<br>– `body`: `AdminCreatePortfolioItemBodyType` – item fields.<br>– *Returns:* `Promise<MessageResType>` – a success message.<br>– Throws `FailedToCreatePortfolioItemException`. |
| 11 | `updatePortfolioItem(userId, itemId, body)` | A method to update an owned portfolio item.<br>– `userId`: `number` – target user identifier.<br>– `itemId`: `number` – portfolio item identifier.<br>– `body`: `AdminUpdatePortfolioItemBodyType` – optional item fields.<br>– *Returns:* `Promise<MessageResType>` – a success message.<br>– Throws `PortfolioItemNotFoundException` or `FailedToUpdatePortfolioItemException`. |
| 12 | `deletePortfolioItem(userId, itemId)` | A method to soft-delete an owned portfolio item.<br>– `userId`: `number` – target user identifier.<br>– `itemId`: `number` – portfolio item identifier.<br>– *Returns:* `Promise<MessageResType>` – a success message.<br>– Throws `PortfolioItemNotFoundException` or `FailedToDeletePortfolioItemException`. |
| 13 | `getFreelancerProfileContext(userId)` | A private method to load the profile and role context for a Freelancer edit.<br>– `userId`: `number` – target user identifier.<br>– *Returns:* `Promise<context>` – profile id, Freelancer profile id, and role flag.<br>– Throws `UserNotFoundException` or `NoFreelancerRoleForProfileException`. |
| 14 | `ensureFreelancerProfileRow(userId, context)` | A private method to create the Profile and FreelancerProfile rows when missing.<br>– `userId`: `number` – target user identifier.<br>– `context`: object – profile id and role context.<br>– *Returns:* `Promise<number \| null>` – the Freelancer profile id.<br>– Used by skill and portfolio editors before writing child rows. |

#### 4.16.0.2 ClassAttribute

| No | Attribute | Type |
|---|---|---|
| 01 | `repository` | `UsersRepository` – private readonly persistence dependency. |
| 02 | `hashingService` | `HashingService` – private readonly password utility. |

### 4.17 UsersRepository Class

#### 4.17.0.1 ClassMethod

| No | Method | Description |
|---|---|---|
| 01 | `UsersRepository(prisma: PrismaService)` | A method to initialize the repository with the shared Prisma client.<br>– `prisma`: `PrismaService` – database client.<br>– *Returns:* `void` – constructor, no return value. |
| 02 | `getUsers(query: AdminUserQueryType)` | A method to query users with search, role, status, sorting, and pagination.<br>– `query`: `AdminUserQueryType` – list filters.<br>– *Returns:* `Promise<AdminUserListResponseType>` – users and pagination. |
| 03 | `createUserByAdmin(data)` | A method to create the account, profile, and primary role in one write.<br>– `data`: object – email, hashed password, full name, role id, and role name.<br>– *Returns:* `Promise<AdminCreateUserResponseType>` – the created account.<br>– Creates an empty Expert profile when the role is Expert. |
| 04 | `findUserByEmail(email)` | A method to find a non-deleted account by email.<br>– `email`: `string` – account email.<br>– *Returns:* `Promise<{ id: number } \| null>` – the account id, or `null`. |
| 05 | `findActiveRoleById(id)` | A method to load an active role by id.<br>– `id`: `number` – role identifier.<br>– *Returns:* `Promise<{ id: number; name: string } \| null>` – the role, or `null`. |

| No | Method | Description |
|---|---|---|
| 06 | `updateUserByAdmin(id, data)` | A method to update account fields, profile name, and sessions on ban.<br>– `id`: `number` – target account.<br>– `data`: object – optional email, full name, and ban flag.<br>– *Returns:* `Promise<AdminUpdateUserResponseType \| null>` – the updated account, or `null` when absent.<br>– Setting `isBanned` to true deletes every session in the same transaction. |
| 07 | `findClientProfileEditContext(id)` | A method to load the profile context required by the Client editor.<br>– `id`: `number` – target account.<br>– *Returns:* `Promise<context \| null>` – profile id, Client profile id, and role flag. |
| 08 | `upsertClientProfileByAdmin(userId, data)` | A method to create or update the Client profile.<br>– `userId`: `number` – target account.<br>– `data`: object – company name, description, and website.<br>– *Returns:* `Promise<ClientProfile \| null>` – the persisted Client profile. |
| 09 | `findFreelancerProfileEditContext(id)` | A method to load the profile context required by the Freelancer editor.<br>– `id`: `number` – target account.<br>– *Returns:* `Promise<context \| null>` – profile id, Freelancer profile id, and role flag. |
| 10 | `updateFreelancerProfileByAdmin(userId, data)` | A method to update Profile biography and Freelancer profile fields.<br>– `userId`: `number` – target account.<br>– `data`: object – title, bio, languages, education, and certifications.<br>– *Returns:* `Promise<void>` – no value. |
| 11 | `ensureFreelancerProfile(userId, profileId)` | A method to create the missing Profile or FreelancerProfile row.<br>– `userId`: `number` – target account.<br>– `profileId`: `number \| null` – existing profile id, or `null`.<br>– *Returns:* `Promise<number \| null>` – the Freelancer profile id. |

| No | Method | Description |
|---|---|---|
| 12 | `replaceFreelancerSkills( freelancerProfileId, skills)` | A method to replace all skills and create missing catalogue skills in a transaction.<br>– `freelancerProfileId`: `number` – Freelancer profile identifier.<br>– `skills`: array of skill name and proficiency pairs.<br>– *Returns:* `Promise<void>` – no value.<br>– Free-text names are matched case-insensitively; missing skills receive a generated slug. |
| 13 | `createPortfolioItem( freelancerProfileId, data)` | A method to insert a portfolio item.<br>– `freelancerProfileId`: `number` – Freelancer profile identifier.<br>– `data`: object – title, description, technologies, and project URL.<br>– *Returns:* `Promise<PortfolioItem>` – the created item. |
| 14 | `findPortfolioItemOwned( id)` | A method to load a portfolio item with its owner and delete state.<br>– `id`: `number` – portfolio item identifier.<br>– *Returns:* `Promise<{ id: number; freelancer ProfileId: number; deletedAt: Date \| null } \| null>` – the ownership record, or `null`. |
| 15 | `updatePortfolioItemBy Admin(id, data)` | A method to update only the provided portfolio item fields.<br>– `id`: `number` – portfolio item identifier.<br>– `data`: object – optional item fields.<br>– *Returns:* `Promise<PortfolioItem>` – the updated item. |
| 16 | `softDeletePortfolioItem( id)` | A method to set the portfolio item delete timestamp.<br>– `id`: `number` – portfolio item identifier.<br>– *Returns:* `Promise<PortfolioItem>` – the soft-deleted item. |
| 17 | `listActiveSkillCatalog()` | A method to return active skills ordered by name.<br>– *Returns:* `Promise<AdminSkillCatalogListType>` – the catalogue. |
| 18 | `getUserById(id)` | A method to load the full account graph for the detail page.<br>– `id`: `number` – target account.<br>– *Returns:* `Promise<AdminUserDetailResponseType \| null>` – the detail view, or `null`. |

#### 4.17.0.2 ClassAttribute

| No | Attribute | Type |
|---|---|---|
| 01 | `prisma` | `PrismaService` – private readonly database client. |

### 4.18 BannersAdminController Class

#### 4.18.0.1 ClassMethod

| No | Method | Description |
|---|---|---|
| 01 | `BannersAdminController(service: BannersAdminService)` | A method to initialize the controller with the banner administration service.<br>– `service`: `BannersAdminService` – service that owns banner use cases.<br>– *Returns:* `void` – constructor, no return value. |
| 02 | `listBanners(query: BannerAdminQueryDto)` | A method to return a filtered, paginated banner list.<br>– `query`: `BannerAdminQueryDto` – page, limit, search, position, active, and sort options.<br>– *Returns:* `Promise<BannerAdminListResponseType>` – banners and pagination.<br>– Route: `GET /admin/banners`. |
| 03 | `createBanner(body: CreateBannerBodyDto)` | A method to create an advertisement banner.<br>– `body`: `CreateBannerBodyDto` – title, image URL, link, position, active state, and dates.<br>– *Returns:* `Promise<BannerAdminDetailResponseType>` – the created banner.<br>– Route: `POST /admin/banners`. |
| 04 | `updateBanner(id: number, body: UpdateBannerBodyDto)` | A method to update a banner.<br>– `id`: `number` – banner identifier.<br>– `body`: `UpdateBannerBodyDto` – optional banner fields.<br>– *Returns:* `Promise<BannerAdminDetailResponseType>` – the updated banner.<br>– Route: `PATCH /admin/banners/:id`. |
| 05 | `deleteBanner(id: number)` | A method to permanently delete a banner.<br>– `id`: `number` – banner identifier.<br>– *Returns:* `Promise<BannerAdminDeleteResponseType>` – a success message.<br>– Route: `DELETE /admin/banners/:id`. |

| No | Method | Description |
|---|---|---|
| 06 | `uploadImage(file?: Express.Multer.File)` | A method to upload a banner image and return its URL. – `file`: `Express.Multer.File \| undefined` – multipart image field named `file`. – *Returns:* `Promise<{ imageUrl: string; publicId: string }>` – the stored image reference. – Route: `POST /admin/banners/upload-image`; multipart field `file`; maximum 10 MB. |
| 07 | `getBannerDetail(id: number)` | A method to return one banner. – `id`: `number` – banner identifier. – *Returns:* `Promise<BannerAdminDetailResponseType>` – the banner detail. – Route: `GET /admin/banners/:id`. |

#### 4.18.0.2 ClassAttribute

| No | Attribute | Type |
|---|---|---|
| 01 | `service` | `BannersAdminService` – private readonly banner administration service. |

### 4.19 BannersAdminService Class

#### 4.19.0.1 ClassMethod

| No | Method | Description |
|---|---|---|
| 01 | `BannersAdminService(repository: BannersAdminRepository, cloudinaryService: CloudinaryService)` | A method to initialize the service with persistence and image storage. – `repository`: `BannersAdminRepository` – banner persistence dependency. – `cloudinaryService`: `CloudinaryService` – remote image storage. – *Returns:* `void` – constructor, no return value. |

| No | Method | Description |
|---|---|---|
| 02 | `uploadImage(file?: Express.Multer.File)` | A method to validate an image and store it on Cloudinary or the local upload directory.<br>– `file`: `Express.Multer.File \| undefined` – multipart image.<br>– *Returns:* `Promise<{ imageUrl: string; publicId: string }>` – the stored image reference.<br>– Throws `BannerImageRequiredException`, `BannerImageInvalidTypeException`, `BannerImageTooLargeException`, or `FailedToUploadBannerImageException`. |
| 03 | `listBanners(query: BannerAdminQueryType)` | A method to load a banner page.<br>– `query`: `BannerAdminQueryType` – list filters.<br>– *Returns:* `Promise<BannerAdminListResponseType>` – banners and pagination.<br>– Failure is mapped to `FailedToLoadBannerListException`. |
| 04 | `getBannerDetail(id: number)` | A method to load one banner.<br>– `id`: `number` – banner identifier.<br>– *Returns:* `Promise<BannerAdminDetailResponseType>` – the banner detail.<br>– Throws `BannerAdminNotFoundException` or `FailedToLoadBannerDetailException`. |
| 05 | `createBanner(body: BannerCreateBodyType)` | A method to create a banner after validating its position.<br>– `body`: `BannerCreateBodyType` – banner fields.<br>– *Returns:* `Promise<BannerAdminDetailResponseType>` – the created banner.<br>– Throws `BannerPositionTakenException` or `FailedToCreateBannerException`. |
| 06 | `updateBanner(id: number, body: BannerUpdateBodyType)` | A method to update a banner after validating its position.<br>– `id`: `number` – banner identifier.<br>– `body`: `BannerUpdateBodyType` – optional banner fields.<br>– *Returns:* `Promise<BannerAdminDetailResponseType>` – the updated banner.<br>– Throws `BannerAdminNotFoundException`, `BannerPositionTakenException`, or `FailedToUpdateBannerException`. |

| No | Method | Description |
|---|---|---|
| 07 | `deleteBanner(id: number)` | A method to permanently delete a banner.<br>– `id: number` – banner identifier.<br>– *Returns:* `Promise<BannerAdminDeleteResponseType>` – a success message.<br>– Throws `BannerAdminNotFoundException` or `FailedToDeleteBannerException`. |

#### 4.19.0.2 ClassAttribute

| No | Attribute | Type |
|---|---|---|
| 01 | `repository` | `BannersAdminRepository` – private readonly persistence dependency. |
| 02 | `cloudinaryService` | `CloudinaryService` – private readonly image storage dependency. |

### 4.20 BannersAdminRepository Class

#### 4.20.0.1 ClassMethod

| No | Method | Description |
|---|---|---|
| 01 | `BannersAdminRepository(prisma: PrismaService)` | A method to initialize the repository with the shared Prisma client.<br>– `prisma: PrismaService` – database client.<br>– *Returns:* `void` – constructor, no return value. |
| 02 | `listBanners(query: BannerAdminQueryType)` | A method to query banners with search, position, active-state, and sorting filters.<br>– `query: BannerAdminQueryType` – list filters.<br>– *Returns:* `Promise<BannerAdminListResponseType>` – banners and pagination. |
| 03 | `getBannerDetail(id: number)` | A method to load one banner.<br>– `id: number` – banner identifier.<br>– *Returns:* `Promise<BannerAdminDetailResponseType \| null>` – the banner, or `null`. |
| 04 | `createBanner(data: BannerCreateBodyType)` | A method to validate the position constraint and insert a banner.<br>– `data: BannerCreateBodyType` – banner fields.<br>– *Returns:* `Promise<BannerAdminDetailResponseType>` – the created banner.<br>– Throws `BannerPositionTakenException`. |

| No | Method | Description |
|---|---|---|
| 05 | `updateBanner(id, data)` | A method to validate the position constraint and update a banner.<br>– `id`: `number` – banner identifier.<br>– `data`: `BannerUpdateBodyType` – optional banner fields.<br>– *Returns:* `Promise<BannerAdminDetailResponse Type>` – the updated banner.<br>– Throws `BannerAdminNotFoundException` or `Banner PositionTakenException`. |
| 06 | `deleteBanner(id: number)` | A method to delete a banner and report whether a row was removed.<br>– `id`: `number` – banner identifier.<br>– *Returns:* `Promise<BannerAdminDeleteResponse Type>` – a success message.<br>– Throws `BannerAdminNotFoundException`. |

#### 4.20.0.2 ClassAttribute

| No | Attribute | Type |
|---|---|---|
| 01 | `prisma` | `PrismaService` – private readonly database client. |

### 4.21 SkillsAdminController Class

#### 4.21.0.1 ClassMethod

| No | Method | Description |
|---|---|---|
| 01 | `SkillsAdminController( service: SkillsAdmin Service)` | A method to initialize the controller with the skill administration service.<br>– `service`: `SkillsAdminService` – service that owns skill use cases.<br>– *Returns:* `void` – constructor, no return value. |
| 02 | `listSkills(query: Skill AdminQueryDto)` | A method to return a filtered, paginated skill list.<br>– `query`: `SkillAdminQueryDto` – page, limit, search, active, and sort options.<br>– *Returns:* `Promise<SkillAdminListResponseType>` – skills and pagination.<br>– Route: `GET /admin/skills`. |

| No | Method | Description |
|---|---|---|
| 03 | `createSkill(body: CreateSkillBodyDto)` | A method to create a skill.<br>– `body`: `CreateSkillBodyDto` – name and optional description.<br>– *Returns:* `Promise<SkillAdminDetailResponseType>` – the created skill.<br>– Route: `POST /admin/skills`. |
| 04 | `updateSkill(id: number, body: UpdateSkillBodyDto)` | A method to update a skill.<br>– `id`: `number` – skill identifier.<br>– `body`: `UpdateSkillBodyDto` – optional name, description, and active state.<br>– *Returns:* `Promise<SkillAdminDetailResponseType>` – the updated skill.<br>– Route: `PATCH /admin/skills/:id`. |
| 05 | `restoreSkill(id: number)` | A method to restore a soft-deleted skill.<br>– `id`: `number` – skill identifier.<br>– *Returns:* `Promise<SkillAdminDetailResponseType>` – the restored skill.<br>– Route: `PATCH /admin/skills/:id/restore`. |
| 06 | `deleteSkill(id: number)` | A method to soft-delete a skill.<br>– `id`: `number` – skill identifier.<br>– *Returns:* `Promise<SkillAdminDeleteResponseType>` – a success message.<br>– Route: `DELETE /admin/skills/:id`. |
| 07 | `getSkillDetail(id: number)` | A method to return one skill.<br>– `id`: `number` – skill identifier.<br>– *Returns:* `Promise<SkillAdminDetailResponseType>` – the skill detail.<br>– Route: `GET /admin/skills/:id`. |

#### 4.21.0.2 ClassAttribute

| No | Attribute | Type |
|---|---|---|
| 01 | `service` | `SkillsAdminService` – private readonly skill administration service. |

### 4.22 SkillsAdminService Class

#### 4.22.0.1 ClassMethod

| No | Method | Description |
|---|---|---|
| 01 | `SkillsAdminService( repository: SkillsAdmin Repository)` | A method to initialize the service with the skill repository. – `repository`: `SkillsAdminRepository` – persistence dependency. – *Returns:* `void` – constructor, no return value. |
| 02 | `listSkills(query: Skill AdminQueryType)` | A method to load a skill page. – `query`: `SkillAdminQueryType` – list filters. – *Returns:* `Promise<SkillAdminListResponseType>` – skills and pagination. – Failure is mapped to `FailedToLoadSkillList Exception`. |
| 03 | `getSkillDetail(id: number)` | A method to load one skill. – `id`: `number` – skill identifier. – *Returns:* `Promise<SkillAdminDetailResponse Type>` – the skill detail. – Throws `SkillAdminNotFoundException` or `Failed ToLoadSkillDetailException`. |
| 04 | `createSkill(body: Admin CreateSkillBodyType)` | A method to create a skill and handle a concurrent duplicate. – `body`: `AdminCreateSkillBodyType` – name and optional description. – *Returns:* `Promise<SkillAdminDetailResponse Type>` – the created skill. – Throws `SkillNameAlreadyExistsException` or `FailedToCreateSkillException`. |
| 05 | `updateSkill(id, body)` | A method to update a skill and handle a concurrent duplicate. – `id`: `number` – skill identifier. – `body`: `AdminUpdateSkillBodyType` – optional name, description, and active state. – *Returns:* `Promise<SkillAdminDetailResponse Type>` – the updated skill. – Throws `SkillAdminNotFoundException`, `SkillName AlreadyExistsException`, or `FailedToUpdateSkill Exception`. |
| 06 | `deleteSkill(id: number)` | A method to soft-delete a skill. – `id`: `number` – skill identifier. – *Returns:* `Promise<SkillAdminDeleteResponse Type>` – a success message. – Throws `SkillAdminNotFoundException` or `Failed ToDeleteSkillException`. |

| No | Method | Description |
|---|---|---|
| 07 | `restoreSkill(id: number)` | A method to restore a soft-deleted skill.<br>– `id: number` – skill identifier.<br>– *Returns:* `Promise<SkillAdminDetailResponseType>` – the restored skill.<br>– Throws `SkillAdminNotFoundException`, `SkillNameAlreadyExistsException`, or `FailedToRestoreSkillException`. |

#### 4.22.0.2 ClassAttribute

| No | Attribute | Type |
|---|---|---|
| 01 | `repository` | `SkillsAdminRepository` – private readonly persistence dependency. |

### 4.23 SkillsAdminRepository Class

#### 4.23.0.1 ClassMethod

| No | Method | Description |
|---|---|---|
| 01 | `SkillsAdminRepository(prisma: PrismaService)` | A method to initialize the repository with the shared Prisma client.<br>– `prisma: PrismaService` – database client.<br>– *Returns:* `void` – constructor, no return value. |
| 02 | `listSkills(query: SkillAdminQueryType)` | A method to query skills with search, active-state, sorting, and pagination.<br>– `query: SkillAdminQueryType` – list filters.<br>– *Returns:* `Promise<SkillAdminListResponseType>` – skills and pagination.<br>– Search matches name, slug, or description. |
| 03 | `getSkillDetail(id: number)` | A method to load one skill.<br>– `id: number` – skill identifier.<br>– *Returns:* `Promise<SkillAdminDetailResponseType \| null>` – the skill, or `null`. |
| 04 | `createSkill(data: AdminCreateSkillBodyType)` | A method to generate a unique slug and insert a skill.<br>– `data: AdminCreateSkillBodyType` – name and optional description.<br>– *Returns:* `Promise<SkillAdminDetailResponseType>` – the created skill.<br>– Throws `SkillNameAlreadyExistsException`. |

| No | Method | Description |
|---|---|---|
| 05 | `updateSkill(id, data)` | A method to update a skill and regenerate its slug when the name changes.<br>– `id`: `number` – skill identifier.<br>– `data`: `AdminUpdateSkillBodyType` – optional name, description, and active state.<br>– *Returns:* `Promise<SkillAdminDetailResponse Type>` – the updated skill.<br>– Throws `SkillAdminNotFoundException` or `Skill NameAlreadyExistsException`. |
| 06 | `deleteSkill(id: number)` | A method to set the skill delete timestamp.<br>– `id`: `number` – skill identifier.<br>– *Returns:* `Promise<SkillAdminDeleteResponse Type>` – a success message.<br>– Throws `SkillAdminNotFoundException`. |
| 07 | `restoreSkill(id: number)` | A method to clear the skill delete timestamp after checking name conflicts.<br>– `id`: `number` – skill identifier.<br>– *Returns:* `Promise<SkillAdminDetailResponse Type>` – the restored skill.<br>– Throws `SkillAdminNotFoundException` or `Skill NameAlreadyExistsException`. |
| 08 | `generateUniqueSlug(name: string)` | A private method to derive a slug and append a numeric suffix on collision.<br>– `name`: `string` – skill name.<br>– *Returns:* `Promise<string>` – the unique slug. |

#### 4.23.0.2 ClassAttribute

| No | Attribute | Type |
|---|---|---|
| 01 | `prisma` | `PrismaService` – private readonly database client. |

### 4.24 AdminExpertProfileController Class

#### 4.24.0.1 ClassMethod

| No | Method | Description |
|---|---|---|
| 01 | `AdminExpertProfile Controller(service: ExpertProfileService)` | A method to initialize the controller with the expert profile service.<br>– `service`: `ExpertProfileService` – service that owns expert profile use cases.<br>– *Returns:* `void` – constructor, no return value. |
| 02 | `update( userId: number, adminId: number, body: AdminUpdateExpert ProfileDto)` | A method for an administrator to update an expert profile directly.<br>– `userId`: `number` – expert account identifier.<br>– `adminId`: `number` – current administrator, recorded on superseded revisions.<br>– `body`: `AdminUpdateExpertProfileDto` – display name, bio, title, expertise, experience, education, certifications, website, and active state.<br>– *Returns:* `Promise<MessageResType>` – a success message.<br>– Route: `PATCH /users/:id/expert-profile`. |

#### 4.24.0.2 ClassAttribute

| No | Attribute | Type |
|---|---|---|
| 01 | `service` | `ExpertProfileService` – private readonly expert profile service. |

### 4.25 ExpertProfileService Class

#### 4.25.0.1 ClassMethod

| No | Method | Description |
|---|---|---|
| 01 | `ExpertProfileService( repository: Expert ProfileRepository, revisions: Profile RevisionService)` | A method to initialize the service with persistence and revision handling.<br>– `repository`: `ExpertProfileRepository` – expert profile persistence.<br>– `revisions`: `ProfileRevisionService` – self-service revision workflow.<br>– *Returns:* `void` – constructor, no return value. |
| 02 | `cleanList(values: string[])` | A private method to trim, de-duplicate, and preserve the first casing of a string list.<br>– `values`: `string[]` – raw list values.<br>– *Returns:* `string[]` – the cleaned list. |

| No | Method | Description |
|---|---|---|
| 03 | `sanitize(input)` | A private method to clean list fields and normalize the website value.<br>– `input`: `UpdateExpertProfileType` – profile input.<br>– *Returns:* `UpdateExpertProfileType` – the sanitized input. |
| 04 | `context(userId: number)` | A private method to load an expert account and verify its Expert role.<br>– `userId`: `number` – target account.<br>– *Returns:* `Promise<user context>` – account, profile, and roles.<br>– Throws `ExpertProfileNotFoundException` or `NotAnExpertAccountException`. |
| 05 | `getMine(userId: number)` | A method to return the authenticated expert's profile.<br>– `userId`: `number` – current expert account.<br>– *Returns:* `Promise<ExpertProfileType>` – profile and expert fields.<br>– Used by the self-service profile page, not by the admin endpoint. |
| 06 | `submitUpdate(userId, input)` | A method to submit a self-service expert profile revision.<br>– `userId`: `number` – current expert account.<br>– `input`: `UpdateExpertProfileType` – requested profile changes.<br>– *Returns:* `Promise<revision result>` – the pending revision.<br>– Throws `ExpertProfilePendingRevisionException` when a revision is already pending. |
| 07 | `updateByAdmin(userId, adminId, input)` | A method to update an expert profile directly and supersede pending revisions.<br>– `userId`: `number` – target expert account.<br>– `adminId`: `number` – current administrator.<br>– `input`: `AdminUpdateExpertProfileType` – administrative profile changes.<br>– *Returns:* `Promise<MessageResType>` – a success message.<br>– Throws `ExpertProfileNotFoundException` or `NotAnExpertAccountException`. |

#### 4.25.0.2 ClassAttribute

| No | Attribute | Type |
|---|---|---|
| 01 | `repository` | `ExpertProfileRepository` – private readonly persistence dependency. |
| 02 | `revisions` | `ProfileRevisionService` – private readonly revision workflow dependency. |

## 4.26 ExpertProfileRepository Class

#### 4.26.0.1 ClassMethod

| No | Method | Description |
|---|---|---|
| 01 | `ExpertProfileRepository( prisma: PrismaService)` | A method to initialize the repository with the shared Prisma client.<br>– `prisma`: `PrismaService` – database client.<br>– *Returns:* `void` – constructor, no return value. |
| 02 | `findByUserId(userId: number)` | A method to load an expert account with its profile and roles.<br>– `userId`: `number` – target account.<br>– *Returns:* `Promise<user context \| null>` – the account graph, or `null`. |
| 03 | `updateDirect(userId, adminId, input, profile CompletionPercent)` | A method to supersede pending revisions, update the profile, and upsert the expert row in one transaction.<br>– `userId`: `number` – target expert account.<br>– `adminId`: `number` – reviewing administrator.<br>– `input`: `AdminUpdateExpertProfileType` – sanitized profile changes.<br>– `profileCompletionPercent`: `number` – recalculated completeness.<br>– *Returns:* `Promise<void>` – no value.<br>– Creates a system notification when a pending revision was superseded. |
| 04 | `hasPendingRevision(user Id: number)` | A method to check for a pending expert revision.<br>– `userId`: `number` – target account.<br>– *Returns:* `Promise<{ id: number } \| null>` – the pending revision, or `null`. |
| 05 | `findPublicMany(query: PublicExpertQueryType)` | A method to query active public expert profiles.<br>– `query`: `PublicExpertQueryType` – expertise, search, and pagination filters.<br>– *Returns:* `Promise<public expert page>` – public expert cards. |

| No | Method | Description |
|---|---|---|
| 06 | `findPublicById(id: number)` | A method to load one active public expert profile.<br>– `id: number` – expert identifier.<br>– *Returns:* `Promise<public expert \| null>` – the public profile, or `null`. |

#### 4.26.0.2 ClassAttribute

| No | Attribute | Type |
|---|---|---|
| 01 | `prisma` | `PrismaService` – private readonly database client. |

### 4.27 JobCategoriesAdminController Class

#### 4.27.0.1 ClassMethod

| No | Method | Description |
|---|---|---|
| 01 | `JobCategoriesAdmin Controller(service: Job CategoriesAdminService)` | A method to initialize the controller with the job category service.<br>– `service: JobCategoriesAdminService` – service that owns job category use cases.<br>– *Returns:* `void` – constructor, no return value. |
| 02 | `listJobCategories(query: JobCategoryAdminQueryDto)` | A method to return a filtered, paginated job category list.<br>– `query: JobCategoryAdminQueryDto` – page, limit, search, status, deleted, and sort options.<br>– *Returns:* `Promise<JobCategoryAdminListResponse Type>` – categories and pagination.<br>– Route: `GET /admin/job-categories`. |
| 03 | `createJobCategory(body: CreateJobCategoryBodyDto)` | A method to create a job category.<br>– `body: CreateJobCategoryBodyDto` – name, description, icon, and status.<br>– *Returns:* `Promise<JobCategoryAdminDetail ResponseType>` – the created category.<br>– Route: `POST /admin/job-categories`. |
| 04 | `updateJobCategory(id: number, body: UpdateJob CategoryBodyDto)` | A method to update a job category.<br>– `id: number` – category identifier.<br>– `body: UpdateJobCategoryBodyDto` – optional category fields.<br>– *Returns:* `Promise<JobCategoryAdminDetail ResponseType>` – the updated category.<br>– Route: `PATCH /admin/job-categories/:id`. |

| No | Method | Description |
|---|---|---|
| 05 | `restoreJobCategory(id: number)` | A method to restore a soft-deleted job category.<br>– `id: number` – category identifier.<br>– *Returns:* `Promise<JobCategoryAdminDetail ResponseType>` – the restored category.<br>– Route: `PATCH /admin/job-categories/:id/restore`. |
| 06 | `deleteJobCategory(id: number)` | A method to soft-delete a job category that has no active jobs.<br>– `id: number` – category identifier.<br>– *Returns:* `Promise<JobCategoryAdminDelete ResponseType>` – a success message.<br>– Route: `DELETE /admin/job-categories/:id`. |
| 07 | `getJobCategoryDetail(id: number)` | A method to return one job category.<br>– `id: number` – category identifier.<br>– *Returns:* `Promise<JobCategoryAdminDetail ResponseType>` – the category detail.<br>– Route: `GET /admin/job-categories/:id`. |

#### 4.27.0.2 ClassAttribute

| No | Attribute | Type |
|---|---|---|
| 01 | `service` | `JobCategoriesAdminService` – private readonly job category service. |

### 4.28 JobCategoriesAdminService Class

#### 4.28.0.1 ClassMethod

| No | Method | Description |
|---|---|---|
| 01 | `JobCategoriesAdmin Service( repository: Job CategoriesAdmin Repository)` | A method to initialize the service with the job category repository.<br>– `repository: JobCategoriesAdminRepository` – persistence dependency.<br>– *Returns:* `void` – constructor, no return value. |
| 02 | `listJobCategories(query: JobCategoryAdminQuery Type)` | A method to load a job category page.<br>– `query: JobCategoryAdminQueryType` – list filters.<br>– *Returns:* `Promise<JobCategoryAdminListResponse Type>` – categories and pagination.<br>– Failure is mapped to `FailedToLoadJobCategoryList Exception`. |

| No | Method | Description |
|---|---|---|
| 03 | `getJobCategoryDetail(id: number)` | A method to load one job category.<br>– `id: number` – category identifier.<br>– *Returns:* `Promise<JobCategoryAdminDetail ResponseType>` – the category detail.<br>– Throws `JobCategoryAdminNotFoundException` or `FailedToLoadJobCategoryDetailException`. |
| 04 | `createJobCategory(body: AdminCreateJobCategory BodyType)` | A method to create a category and handle a concurrent duplicate.<br>– `body: AdminCreateJobCategoryBodyType` – category fields.<br>– *Returns:* `Promise<JobCategoryAdminDetail ResponseType>` – the created category.<br>– Throws `JobCategoryNameAlreadyExistsException` or `FailedToCreateJobCategoryException`. |
| 05 | `updateJobCategory(id, body)` | A method to update a category and handle a concurrent duplicate.<br>– `id: number` – category identifier.<br>– `body: AdminUpdateJobCategoryBodyType` – optional category fields.<br>– *Returns:* `Promise<JobCategoryAdminDetail ResponseType>` – the updated category.<br>– Throws `JobCategoryAdminNotFoundException`, `Job CategoryNameAlreadyExistsException`, or `FailedTo UpdateJobCategoryException`. |
| 06 | `deleteJobCategory(id: number)` | A method to soft-delete a category after checking active job references.<br>– `id: number` – category identifier.<br>– *Returns:* `Promise<JobCategoryAdminDelete ResponseType>` – a success message.<br>– Throws `JobCategoryAdminNotFoundException`, `Job CategoryHasJobsException`, or `FailedToDeleteJob CategoryException`. |
| 07 | `restoreJobCategory(id: number)` | A method to restore a soft-deleted category.<br>– `id: number` – category identifier.<br>– *Returns:* `Promise<JobCategoryAdminDetail ResponseType>` – the restored category.<br>– Throws `JobCategoryAdminNotFoundException`, `Job CategoryNameAlreadyExistsException`, or `FailedTo RestoreJobCategoryException`. |

#### 4.28.0.2 ClassAttribute

| No | Attribute | Type |
|---|---|---|
| 01 | `repository` | `JobCategoriesAdminRepository` – private readonly persistence dependency. |

### 4.29 JobCategoriesAdminRepository Class

#### 4.29.0.1 ClassMethod

| No | Method | Description |
|---|---|---|
| 01 | `JobCategoriesAdmin Repository(prisma: PrismaService)` | A method to initialize the repository with the shared Prisma client.<br>– `prisma`: `PrismaService` – database client.<br>– *Returns:* `void` – constructor, no return value. |
| 02 | `listJobCategories(query: JobCategoryAdminQuery Type)` | A method to query categories with search, status, deleted-state, sorting, and pagination.<br>– `query`: `JobCategoryAdminQueryType` – list filters.<br>– *Returns:* `Promise<JobCategoryAdminListResponse Type>` – categories and pagination.<br>– Search matches name, slug, or description. |
| 03 | `getJobCategoryDetail(id: number)` | A method to load one category with its job count.<br>– `id`: `number` – category identifier.<br>– *Returns:* `Promise<JobCategoryAdminDetail ResponseType \| null>` – the category, or `null`. |
| 04 | `createJobCategory(data)` | A method to generate a unique slug and insert a category.<br>– `data`: `AdminCreateJobCategoryBodyType` – category fields.<br>– *Returns:* `Promise<JobCategoryAdminDetail ResponseType>` – the created category.<br>– Throws `JobCategoryNameAlreadyExistsException`. |
| 05 | `updateJobCategory(id, data)` | A method to update a category and regenerate its slug when the name changes.<br>– `id`: `number` – category identifier.<br>– `data`: `AdminUpdateJobCategoryBodyType` – optional category fields.<br>– *Returns:* `Promise<JobCategoryAdminDetail ResponseType>` – the updated category.<br>– Throws `JobCategoryAdminNotFoundException` or `JobCategoryNameAlreadyExistsException`. |

| No | Method | Description |
|---|---|---|
| 06 | `deleteJobCategory(id: number)` | A method to check active job references and set the delete timestamp.<br>– `id`: `number` – category identifier.<br>– *Returns:* `Promise<JobCategoryAdminDelete ResponseType>` – a success message.<br>– Throws `JobCategoryAdminNotFoundException` or `JobCategoryHasJobsException`. |
| 07 | `restoreJobCategory(id: number)` | A method to clear the delete timestamp after checking name conflicts.<br>– `id`: `number` – category identifier.<br>– *Returns:* `Promise<JobCategoryAdminDetail ResponseType>` – the restored category.<br>– Throws `JobCategoryAdminNotFoundException` or `JobCategoryNameAlreadyExistsException`. |
| 08 | `generateUniqueSlug(name: string)` | A private method to derive a slug and append a numeric suffix on collision.<br>– `name`: `string` – category name.<br>– *Returns:* `Promise<string>` – the unique slug. |

#### 4.29.0.2 ClassAttribute

| No | Attribute | Type |
|---|---|---|
| 01 | `prisma` | `PrismaService` – private readonly database client. |