API Document
CaHongBan - Capital Franchise Supply Chain Management System

Prepared by

SE192160 - Trang Thuận Đức

SE192427 - Lê Hoàng Duy

SE190552 - Hồ Trạch Khoa

SE190838 - Mai Văn Tiến Phát

SE190586 - Lê Đăng Nguyên

SS180069 - Đặng Thành Hưng

SE182422 - Văn Châu Trường Thuận

Team02 - HCM_CPL_NET_01
FPT Software Academy

Swagger Supported by SMARTBEAR

Select a definition: ALL SERVICES

Capital Franchise Supply Chain Management System API Document

1.0 OAS 2.0

[Base URL: /api]
/api-docs/all/all_swagger.json

API docs for CHD Gateway.

Terms of service
Contact API Support

Authorize

Auth

POST `/auth/change-password` Change Password

Allows the logged-in user to change their password. Requires a valid Access Token.

Parameters Try it out

Name	Description
request * required `object` *(body)*	Old and New Password **Example Value** | Model `{ "confirmNewPassword": "string", "forgetAll": true, "newPassword": "string", "oldPassword": "string" }` **Parameter content type** application/json

Responses Response content type: application/json

Code	Description
200	Returns success status **Example Value** | Model `{ "additionalProp1": {} }`

Code	Description
400	Validation error **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`
401	Unauthorized or missing token **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`

POST `/auth/forgot-password` Request Password Reset

Initiates the password reset process by sending an OTP to the provided email address.

Parameters Try it out

Name	Description
request * required `object` *(body)*	Email address **Example Value** | Model `{ "email": "string" }` **Parameter content type** application/json

Responses Response content type application/json

Code	Description
200	Returns success message **Example Value** | Model `{ "additionalProp1": {} }`
400	Validation error **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string",`

Code	Description

```
  "additionalProp3": "string"
}
```

500 Internal server error

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

POST /auth/forgot-password/confirm-otp Verify Password Reset OTP

Verifies the OTP sent to the email. If successful, a 'forgot_password_token' HttpOnly cookie will be set, which is required for setting the new password.

Parameters Try it out

Name	Description
request * required `object` *(body)*	Email and OTP **Example Value** | Model `{ "email": "string", "otp": "string" }` **Parameter content type** application/json

Responses Response content type application/json

Code	Description
200	Returns success message and sets cookie **Example Value** | Model `{ "additionalProp1": {} }`
400	Invalid OTP or validation error **Example Value** | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

POST /auth/forgot-password/new-password Set New Password

Finalizes the password reset process. This endpoint requires the 'forgot_password_token' cookie obtained from the OTP verification step.

Parameters Try it out

Name	Description
request * required `object` *(body)*	New Password **Example Value** | Model `{ "confirmPassword": "string", "newPassword": "string" }` **Parameter content type** application/json

Responses Response content type application/json

Code	Description
200	Returns success status **Example Value** | Model `{ "additionalProp1": {} }`
400	Missing cookie or validation error **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`
401	Invalid or expired token **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`

POST /auth/forgot-password/resend-otp Resend Password Reset OTP

Resends the OTP for password reset if the previous one expired.

Parameters Try it out

Name	Description
request * required object *(body)*	Email address **Example Value** | Model `{ "email": "string" }` **Parameter content type** application/json

Responses — Response content type: application/json

Code	Description
200	Returns success message **Example Value** | Model `{ "additionalProp1": {} }`
400	Validation error **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`

POST /auth/login Login

Enter username/email and password to get access token

Parameters — Try it out

Name	Description
request * required object *(body)*	Login Request Body **Example Value** | Model `{ "emailOrUsername": "string", "password": "string" }` **Parameter content type** application/json

Responses Response content type: application/json

Code	Description
200	OK

Example Value | Model

```
{
  "additionalProp1": {}
}
```

Code	Description
400	Bad Request

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

POST /auth/logout Logout user

Invalidates the current access token and clears the refresh token cookie.

Parameters Try it out

No parameters

Responses Response content type: application/json

Code	Description
200	Returns success status

Example Value | Model

```
{
  "additionalProp1": {}
}
```

Code	Description
401	Unauthorized or invalid token

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

POST /auth/refresh-token Refresh Access Token

Obtains a new access token using the valid refresh token stored in the HttpOnly cookie.

Parameters Try it out

No parameters

Responses Response content type: application/json

Code	Description
200	Returns new Access Token **Example Value** | Model `{ "additionalProp1": {} }`
400	Missing cookie **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`
401	Invalid refresh token **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`

POST /auth/register Register a new account

Create a new user account. After successful registration, an OTP will be sent to the email for verification.

Parameters Try it out

Name	Description
request * required object *(body)*	Registration details **Example Value** | Model `{ "address": "string", "confirmPassword": "string", "dateOfBirth": "string", "email": "string", "firstName": "string", "gender": 0, "lastName": "string", "password": "string", "phone": "string", "username": "string" }` **Parameter content type** application/json

Responses Response content type: application/json

Code	Description
200	Returns success message

Example Value | Model

```
{
  "additionalProp1": {}
}
```

Code	Description
400	Validation error

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

Code	Description
500	Internal server error

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

POST /auth/register/confirm-otp Verify Registration OTP

Verify the OTP sent to email to activate the new account.

Parameters Try it out

Name	Description
request * required object *(body)*	Email and OTP

Example Value | Model

```
{
  "email": "string",
  "otp": "string"
}
```

Parameter content type: application/json

Responses Response content type: application/json

Code	Description
200	Returns success status and message

Code	Description

Example Value | Model

```
{
  "additionalProp1": {}
}
```

400 Invalid OTP or validation error

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

POST /auth/register/resend-otp Resend Registration OTP

Resend the activation OTP if the previous one expired or was not received.

Parameters

Try it out

Name	Description
request * required `object` *(body)*	Email address **Example Value** | Model `{ "email": "string" }` **Parameter content type** application/json

Responses

Response content type: application/json

Code	Description

200 Returns success message

Example Value | Model

```
{
  "additionalProp1": {}
}
```

400 Validation error

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

Campaigns

GET /campaigns Get all campaigns

Retrieve a list of all existing campaigns / promotional programs in the system.

Parameters Try it out

No parameters

Responses Response content type application/json

Code	Description
200	Danh sách chiến dịch thành công

Example Value | Model


```
[
  {
    "createdAt": "string",
    "description": "string",
    "endDate": "string",
    "id": "string",
    "isActive": true,
    "name": "string",
    "startDate": "string",
    "updatedAt": "string",
    "vouchers": [
      {
        "code": "string",
        "createdAt": "string",
        "currentQuantity": 0,
        "discountValue": "string",
        "endDate": "string",
        "id": "string",
        "initQuantity": 0,
        "isActive": true,
        "maxDiscountValue": "string",
        "maxUsagePerUser": 0,
        "minOrderValue": "string",
        "pointCost": "string",
        "type": 0,
        "updatedAt": "string",
        "voucherItems": [
          {
```


Code	Description
500	Internal Server Error

Example Value | Model


```
{}
```


POST /campaigns Create a new campaign

Create a new campaign or voucher hunting event.

Parameters Try it out

Name	Description
body * required `object` *(body)*	Campaign initialization data **Example Value** | Model `{ "description": "string", "endDate": "string", "name": "string", "startDate": "string", "voucherIds": [ "string" ] }` **Parameter content type** application/json

Responses Response content type: application/json

Code	Description
201	{"message": "Tạo chiến dịch thành công"} **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`
400	Validation Error (Bad Request) **Example Value** | Model `{}`
401	Unauthorized **Example Value** | Model `{}`
500	Internal Server Error **Example Value** | Model `{}`

GET /campaigns/active Get active campaigns

Retrieve a list of currently active campaigns / promotional programs.

Parameters Try it out

No parameters

Responses Response content type: application/json

Code	Description
200	Danh sách chiến dịch

Example Value | Model


```
[
  {
    "createdAt": "string",
    "description": "string",
    "endDate": "string",
    "id": "string",
    "isActive": true,
    "name": "string",
    "startDate": "string",
    "updatedAt": "string",
    "vouchers": [
      {
        "code": "string",
        "createdAt": "string",
        "currentQuantity": 0,
        "discountValue": "string",
        "endDate": "string",
        "id": "string",
        "initQuantity": 0,
        "isActive": true,
        "maxDiscountValue": "string",
        "maxUsagePerUser": 0,
        "minOrderValue": "string",
        "pointCost": "string",
        "type": 0,
        "updatedAt": "string",
        "voucherItems": [
          {
```


Code	Description
500	Internal Server Error

Example Value | Model


```
{}
```


POST /campaigns/vouchers/{voucherId}/redeem Redeem voucher from campaign

User redeems points for a voucher or claims a free voucher from a specific campaign.

Parameters Try it out

Name	Description
voucherId * required string *(path)*	Voucher ID voucherId

Responses Response content type: application/json

Code	Description
200	{"message": "Đổi thành công!"} **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`
400	Invalid ID or bad request data **Example Value** | Model `{}`
401	Unauthorized **Example Value** | Model `{}`
403	Insufficient points or Forbidden **Example Value** | Model `{}`
404	Campaign or voucher not found **Example Value** | Model `{}`
500	Internal Server Error **Example Value** | Model `{}`

GET /campaigns/{id} Get campaign details

Retrieve detailed information of a specific campaign by its ID.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Campaign ID id

Responses Response content type: application/json

Code	Description
200	Chi tiết chiến dịch **Example Value** | Model


```
{
  "createdAt": "string",
  "description": "string",
  "endDate": "string",
  "id": "string",
  "isActive": true,
  "name": "string",
  "startDate": "string",
  "updatedAt": "string",
  "vouchers": [
    {
      "code": "string",
      "createdAt": "string",
      "currentQuantity": 0,
      "discountValue": "string",
      "endDate": "string",
      "id": "string",
      "initQuantity": 0,
      "isActive": true,
      "maxDiscountValue": "string",
      "maxUsagePerUser": 0,
      "minOrderValue": "string",
      "pointCost": "string",
      "type": 0,
      "updatedAt": "string",
      "voucherItems": [
        {
          "id": "string",
```


Code	Description
400	Invalid ID (Bad Request) **Example Value** | Model


```
{}
```


Code	Description
404	Campaign Not Found **Example Value** | Model


```
{}
```


Code	Description
500	Internal Server Error **Example Value** | Model


```
{}
```


PATCH `/campaigns/{id}/active` Update campaign active status

Enable or disable the active status of a specific campaign.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Campaign ID id
body * required `object` *(body)*	Status update data **Example Value** | Model `{ "isActive": true }` **Parameter content type** application/json

Responses Response content type application/json

Code	Description
200	{"message": "Cập nhật trạng thái chiến dịch thành công"} **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`
400	Invalid input data or ID **Example Value** | Model `{}`
401	Unauthorized **Example Value** | Model `{}`
404	Campaign Not Found **Example Value** | Model `{}`
500	Internal Server Error **Example Value** | Model

Code	Description
	{}

Categories

GET `/categories` Get All Categories

Retrieve a list of all available product categories.

Parameters Try it out

No parameters

Responses Response content type: application/json

Code	Description

200	List of categories
	Example Value | Model
	{
	"additionalProp1": {}
	}

500	Internal server error
	Example Value | Model
	{
	"additionalProp1": "string",
	"additionalProp2": "string",
	"additionalProp3": "string"
	}

POST `/categories` Create Category

Create a new product category.

Parameters Try it out

Name	Description

request * required
object
(body)
	Category details
	Example Value | Model
	{
	"description": "string",
	"name": "string"
	}

Name	Description

Parameter content type

application/json

Responses Response content type application/json

Code	Description
200	Success

Example Value | Model

```
{
  "additionalProp1": {}
}
```

400	Validation error

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

GET /categories/{id} Get Category by ID

Retrieve details of a specific category using its UUID.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Category UUID id

Responses Response content type application/json

Code	Description
200	Category details

Example Value | Model

```
{
  "additionalProp1": {}
}
```

400	Invalid ID format

Example Value | Model

Code	Description

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

404 Category not found

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

DELETE /categories/{id} Delete Category

Permanently delete a category by its ID.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Category UUID id

Responses Response content type application/json

Code	Description

200 Success

Example Value | Model

```
{
  "additionalProp1": {}
}
```

400 Invalid ID format

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

PATCH /categories/{id} Update Category

Update an existing category by its ID.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Category UUID id
request * required `object` *(body)*	Updated details **Example Value** | Model `{ "description": "string", "name": "string" }` **Parameter content type** application/json

Responses — **Response content type** application/json

Code	Description
200	Success **Example Value** | Model `{ "additionalProp1": {} }`
400	Validation error or Invalid ID **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`

Franchise: Applications

GET `/franchise/applications` Get all franchise applications (Admin)

Retrieve all franchise applications (supports pagination, filtering by status).

Parameters — Try it out

Name	Description
page `integer` *(query)*	page
pageSize `integer` *(query)*	pageSize

Name	Description
searchKey `string` *(query)*	searchKey
status `integer` *(query)*	status

Responses — Response content type: application/json

Code	Description
200	OK

Example Value | Model


```
{
  "items": [
    {
      "adminNote": "string",
      "contracts": [
        {
          "applicationId": "string",
          "contractPdfUrl": "string",
          "createdAt": "string",
          "depositAmount": 0,
          "depositStatus": 0,
          "docuSealSubmissionId": 0,
          "franchiseFee": 0,
          "id": "string",
          "revenueSharePercentage": 0,
          "setupStatus": 0,
          "status": 0,
          "updatedAt": "string",
          "validFrom": "string",
          "validUntil": "string"
        }
      ],
      "createdAt": "string",
      "districtId": "string",
      "email": "string",
      "fullName": "string",
      "id": "string",
      "identityNumber": "string",
```


POST /franchise/applications — Submit franchise application

Partner submits application (personal info, premise address) along with storefront and land certificate images.

Parameters — Try it out

Name	Description
fullName * required `string` *(formData)*	Full name fullName
email * required `string` *(formData)*	Contact email email
phone * required `string`	Phone number

Name	Description
(formData)	phone
identityNumber * required `string` *(formData)*	Identity card number (CMND/CCCD) identityNumber
provinceId * required `string` *(formData)*	Province/City ID provinceId
districtId * required `string` *(formData)*	District ID districtId
wardId * required `string` *(formData)*	Ward ID wardId
storeName * required `string` *(formData)*	Proposed store name storeName
storeAddress * required `string` *(formData)*	Detailed premise address storeAddress
storeLatitude `number` *(formData)*	Latitude storeLatitude
storeLongitude `number` *(formData)*	Longitude storeLongitude
storeSizeSqm `number` *(formData)*	Premise area (sqm) storeSizeSqm
storeFront `file` *(formData)*	Storefront image (1 file) Choose File No file chosen
landCerts `file` *(formData)*	Land certificate images (Multiple files) Choose File No file chosen

Responses Response content type: application/json

Code	Description
201	Created application

Example Value | Model


```
{
  "adminNote": "string",
  "contracts": [
    {
      "applicationId": "string",
      "contractPdfUrl": "string",
      "createdAt": "string",
      "depositAmount": 0,
      "depositStatus": 0,
```

Code	Description


```
      "docuSealSubmissionId": 0,
      "franchiseFee": 0,
      "id": "string",
      "revenueSharePercentage": 0,
      "setupStatus": 0,
      "status": 0,
      "updatedAt": "string",
      "validFrom": "string",
      "validUntil": "string"
    }
  ],
  "createdAt": "string",
  "districtId": "string",
  "email": "string",
  "fullName": "string",
  "id": "string",
  "identityNumber": "string",
  "landCertificateUrls": [
    "string"
```


400 Validation error (Bad Request)

Example Value | Model


```
{}
```


GET /franchise/applications/{id} Get application details (Admin)

View application details including the list of contracts generated from this application.

Parameters Try it out

Name	Description
id * required string *(path)*	Application ID id

Responses Response content type: application/json

Code	Description

200 OK

Example Value | Model


```
{
  "application": {
    "adminNote": "string",
    "contracts": [
      {
        "applicationId": "string",
        "contractPdfUrl": "string",
        "createdAt": "string",
        "depositAmount": 0,
        "depositStatus": 0,
        "docuSealSubmissionId": 0,
        "franchiseFee": 0,
        "id": "string",
        "revenueSharePercentage": 0,
        "setupStatus": 0,
        "status": 0,
        "updatedAt": "string",
        "validFrom": "string",
        "validUntil": "string"
```

Code	Description


```
    }
  ],
  "createdAt": "string",
  "districtId": "string",
  "email": "string",
  "fullName": "string",
  "id": "string",
  "identityNumber": "string",
  "landCertificateUrls": [
```


PATCH /franchise/applications/{id}/review Review franchise application (Admin)

Admin approves or rejects the application. If approved, the system automatically generates a Contract and sends a DocuSeal link.

Parameters

Try it out

Name	Description
id * required `string` *(path)*	Application ID id
body * required `object` *(body)*	Review decision & contract parameters **Example Value** | Model


```
{
  "action": 0,
  "depositAmount": 0,
  "franchiseFee": 0,
  "note": "string",
  "revenueSharePercentage": 0,
  "validFrom": "string",
  "validUntil": "string"
}
```


Parameter content type: application/json

Responses

Response content type: application/json

Code	Description
200	OK **Example Value** | Model


```
{
  "contractId": "string",
  "docuSealSubmissionId": 0,
  "message": "string"
}
```


GET /franchise/me/applications Get my franchise applications

Retrieve all franchise applications submitted by the current user.

Parameters Try it out

No parameters

Responses Response content type application/json

Code	Description
200	OK

Example Value | Model


```
[
  {
    "adminNote": "string",
    "contracts": [
      {
        "applicationId": "string",
        "contractPdfUrl": "string",
        "createdAt": "string",
        "depositAmount": 0,
        "depositStatus": 0,
        "docuSealSubmissionId": 0,
        "franchiseFee": 0,
        "id": "string",
        "revenueSharePercentage": 0,
        "setupStatus": 0,
        "status": 0,
        "updatedAt": "string",
        "validFrom": "string",
        "validUntil": "string"
      }
    ],
    "createdAt": "string",
    "districtId": "string",
    "email": "string",
    "fullName": "string",
    "id": "string",
    "identityNumber": "string",
    "landCertificateUrls": [
```


Franchise: Contracts

GET `/franchise/contracts` Get all contracts (Admin/Accountant)

Retrieve all franchise contracts (supports pagination, filtering by status).

Parameters Try it out

Name	Description
page integer *(query)*	page
pageSize integer *(query)*	pageSize
status integer *(query)*	status

Responses Response content type: application/json

Code	Description
200	OK

Example Value | Model


```
{
  "items": [
    {
      "applicationId": "string",
      "contractPdfUrl": "string",
      "createdAt": "string",
      "depositAmount": 0,
      "depositStatus": 0,
      "docuSealSubmissionId": 0,
      "franchiseFee": 0,
      "id": "string",
      "revenueSharePercentage": 0,
      "setupStatus": 0,
      "status": 0,
      "updatedAt": "string",
      "validFrom": "string",
      "validUntil": "string"
    }
  ],
  "totalCount": 0,
  "totalPages": 0
}
```


GET /franchise/contracts/{id} Get contract details

Retrieve detailed information of a franchise contract.

Parameters Try it out

Name	Description
id * required string *(path)*	Contract ID id

Responses Response content type: application/json

Code	Description
200	OK

Example Value | Model


```
{
  "applicationId": "string",
  "contractPdfUrl": "string",
  "createdAt": "string",
  "depositAmount": 0,
  "depositStatus": 0,
  "docuSealSubmissionId": 0,
  "franchiseFee": 0,
  "id": "string",
  "revenueSharePercentage": 0,
  "setupStatus": 0,
  "status": 0,
```

Code	Description

```
  "updatedAt": "string",
  "validFrom": "string",
  "validUntil": "string"
}
```

POST /franchise/contracts/{id}/payment Confirm deposit payment (Accountant)

Change contract status to Active, create a new Store, and grant Manager role to the partner.

Parameters

Try it out

Name	Description
id * required `string` *(path)*	Contract ID id
body * required `object` *(body)*	Transaction notes **Example Value** | Model `{ "note": "string" }` **Parameter content type** application/json

Responses

Response content type: application/json

Code	Description
200	{"message": "Xác nhận thanh toán thành công. Hợp đồng đã có hiệu lực."} **Example Value** | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

POST /franchise/contracts/{id}/renew Renew franchise contract

Add valid years to the current contract.

Parameters

Try it out

Name	Description
id * required `string`	Contract ID

Name	Description
(path)	id

body * required
`object`
(body)

Years to renew

Example Value | Model

```
{
  "extensionYears": 0,
  "note": "string"
}
```

Parameter content type

application/json

Responses

Response content type application/json

Code	Description
200	OK

Example Value | Model

```
{
  "applicationId": "string",
  "contractPdfUrl": "string",
  "createdAt": "string",
  "depositAmount": 0,
  "depositStatus": 0,
  "docuSealSubmissionId": 0,
  "franchiseFee": 0,
  "id": "string",
  "revenueSharePercentage": 0,
  "setupStatus": 0,
  "status": 0,
  "updatedAt": "string",
  "validFrom": "string",
  "validUntil": "string"
}
```

PATCH /franchise/contracts/{id}/setup Update store setup status

Admin updates the construction status (Design -> Construction -> Inspection -> Ready).

Parameters

Try it out

Name	Description
id * required `string` *(path)*	Contract ID id

body * required
`object`
(body)

Setup status

Example Value | Model

```
{
  "setupStatus": 0
}
```

Parameter content type

Name	Description
	application/json

Responses Response content type: application/json

Code	Description
200	OK

Example Value | Model


```
{
  "applicationId": "string",
  "contractPdfUrl": "string",
  "createdAt": "string",
  "depositAmount": 0,
  "depositStatus": 0,
  "docuSealSubmissionId": 0,
  "franchiseFee": 0,
  "id": "string",
  "revenueSharePercentage": 0,
  "setupStatus": 0,
  "status": 0,
  "updatedAt": "string",
  "validFrom": "string",
  "validUntil": "string"
}
```


PATCH /franchise/contracts/{id}/status Suspend / Terminate contract

Admin changes the contract status (Suspended, Terminated) with a reason.

Parameters Try it out

Name	Description
id * required string *(path)*	Contract ID id
body * required object *(body)*	Status and reason **Example Value** | Model


```
{
  "reason": "string",
  "status": 0
}
```


Parameter content type: application/json

Responses Response content type: application/json

Code	Description
200	OK

Example Value | Model


```
{
  "applicationId": "string",
  "contractPdfUrl": "string",
  "createdAt": "string",
  "depositAmount": 0,
  "depositStatus": 0,
  "docuSealSubmissionId": 0,
  "franchiseFee": 0,
  "id": "string",
  "revenueSharePercentage": 0,
  "setupStatus": 0,
  "status": 0,
  "updatedAt": "string",
  "validFrom": "string",
  "validUntil": "string"
}
```


GET /franchise/me/contracts Get my contracts

Retrieve all franchise contracts of the current user.

Parameters Try it out

No parameters

Responses Response content type application/json

Code	Description
200	OK

Example Value | Model


```
[
  {
    "applicationId": "string",
    "contractPdfUrl": "string",
    "createdAt": "string",
    "depositAmount": 0,
    "depositStatus": 0,
    "docuSealSubmissionId": 0,
    "franchiseFee": 0,
    "id": "string",
    "revenueSharePercentage": 0,
    "setupStatus": 0,
    "status": 0,
    "updatedAt": "string",
    "validFrom": "string",
    "validUntil": "string"
  }
]
```


Franchise: Webhooks

POST /franchise/webhook/docuseal Handle DocuSeal Webhook (Internal)

Update contract status (Signed) based on the webhook sent from DocuSeal. Uses HMAC Header instead of Token authentication.

Parameters Try it out

No parameters

Responses Response content type application/json

Code	Description
200	{"message": "Webhook processed"} **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`

Ingredients

GET `/ingredients` Get All Ingredients

Retrieve a list of ingredients with optional filtering and pagination.

Parameters Try it out

Name	Description
categoryId `string` *(query)*	categoryId
page `integer` *(query)*	page
pageSize `integer` *(query)*	pageSize

Responses Response content type application/json

Code	Description
200	List of ingredients **Example Value** | Model

Code	Description

```
{
  "additionalProp1": {}
}
```

500 Internal server error

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

POST /ingredients Create Ingredient

Add a new ingredient to the inventory.

Parameters

Try it out

Name	Description
request * required `object` *(body)*	Ingredient details **Example Value** | Model `{ "baseUnit": "string", "categoryId": "string", "name": "string" }` **Parameter content type** application/json

Responses

Response content type: application/json

Code	Description
200	Success **Example Value** | Model `{ "additionalProp1": {} }`
400	Validation error **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`

DELETE /ingredients/{id} Delete Ingredient

Remove an ingredient from the inventory.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Ingredient UUID id

Responses Response content type: application/json

Code	Description
200	Success **Example Value** | Model `{ "additionalProp1": {} }`
400	Invalid ID format **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`

PATCH /ingredients/{id} Update Ingredient

Update details of an existing ingredient by its ID.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Ingredient UUID id

Name	Description
request * required `object` *(body)*	Updated details **Example Value** | Model `{ "baseUnit": "string", "categoryId": "string", "name": "string" }` **Parameter content type** application/json

Responses — Response content type: application/json

Code	Description
200	Success **Example Value** | Model `{ "additionalProp1": {} }`
400	Validation error or Invalid ID **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`

Ingredient Categories

GET `/ingredients/categories` Get All Ingredient Categories

Retrieve a list of all ingredient categories.

Parameters — Try it out

No parameters

Responses — Response content type: application/json

Code	Description
200	List of categories **Example Value** | Model `{ "additionalProp1": {}`

Code	Description

	}
	{
	"additionalProp1": "string",
	"additionalProp2": "string",
	"additionalProp3": "string"
	}

500	Internal server error **Example Value** | Model

POST `/ingredients/categories` Create Ingredient Category

Create a new category for ingredients.

Parameters Try it out

Name	Description

request * required
`object`
(body)
	Category details
	Example Value | Model
	{
	"description": "string",
	"name": "string"
	}
	Parameter content type
	application/json

Responses Response content type application/json

Code	Description

200	Success
	Example Value | Model
	{
	"additionalProp1": {}
	}

400	Validation error
	Example Value | Model
	{
	"additionalProp1": "string",
	"additionalProp2": "string",
	"additionalProp3": "string"
	}

DELETE `/ingredients/categories/{id}` Delete Ingredient Category

Permanently remove an ingredient category.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Category UUID id

Responses Response content type: application/json

Code	Description
200	Success **Example Value** | Model `{ "additionalProp1": {} }`
400	Invalid ID format **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`

PATCH `/ingredients/categories/{id}` Update Ingredient Category

Update an existing ingredient category by its ID.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Category UUID id

Name	Description
request * required `object` *(body)*	Updated details **Example Value** | Model `{ "description": "string", "name": "string" }` **Parameter content type** application/json

Responses — Response content type: application/json

Code	Description
200	Success **Example Value** | Model `{ "additionalProp1": {} }`
400	Validation error or Invalid ID **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`

Loyalty

GET `/loyalty/accounts` Search Loyalty Accounts

Retrieve loyalty accounts by user phone or email.

Parameters — Try it out

Name	Description
email `string` *(query)*	email
phoneNumber `string` *(query)*	phoneNumber

Responses — Response content type: application/json

Code	Description
200	List of loyalty accounts **Example Value** | Model


```
[
  {
    "availablePoints": "string",
    "currentTier": {
      "amountPerPoint": "string",
      "discountRate": 0,
      "id": "string",
      "minSpendRequired": "string",
      "name": "string",
      "valuePerPoint": "string"
    },
    "id": "string",
    "totalSpent": "string",
    "userName": "string"
  }
]
```


400	Validation error **Example Value** | Model


```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```


401	Unauthorized **Example Value** | Model


```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```


GET `/loyalty/reports` Get Loyalty Report Summary (JSON)

Get statistics like total members, points, and tier distribution for dashboard.

Parameters Try it out

Name	Description
format **integer** *(query)*	format
fromDate **string** *(query)*	fromDate
tierId **string** *(query)*	tierId
toDate **string** *(query)*	toDate

Responses Response content type: application/json

Code	Description
200	Loyalty summary data

Example Value | Model


```
{
  "tierDistribution": [
    {
      "memberCount": 0,
      "tierName": "string"
    }
  ],
  "totalMembers": 0,
  "totalPointsEarned": 0,
  "totalPointsRedeemed": 0
}
```


GET /loyalty/reports/export Export Loyalty Report (PDF/CSV)

Download loyalty statistics as a PDF or CSV file.

Parameters Try it out

Name	Description
format integer *(query)*	format
fromDate string *(query)*	fromDate
tierId string *(query)*	tierId
toDate string *(query)*	toDate
format integer *(query)*	format

Responses Response content type: application/octet-stream

Code	Description
200	Report file

Example Value | Model


```
(no example available
```

Code	Description
	[redacted]

Cart

GET `/me/cart` Get My Cart

Retrieve current user's shopping cart.

Parameters Try it out

No parameters

DELETE `/me/cart` Clear My Cart

Parameters Try it out

No parameters

PUT `/me/cart/items` Update Item in My Cart

Parameters Try it out

Name	Description
request * required `object` *(body)*	Update details **Example Value** | Model `{ "quantity": 0, "sku": "string" }` **Parameter content type** application/json

POST `/me/cart/items` Add Item to My Cart

Parameters Try it out

Name	Description
request * required object *(body)*	Item details **Example Value** | Model `{ "quantity": 0, "sku": "string" }` **Parameter content type** application/json

DELETE `/me/cart/items` Remove Items from My Cart

Parameters Try it out

Name	Description
request * required object *(body)*	List of Item IDs **Example Value** | Model `{ "skus": [ "string" ] }` **Parameter content type** application/json

Orders

GET `/me/orders` Get My Order History

Retrieve a list of orders placed by the current logged-in customer.

Parameters Try it out

Name	Description
page integer *(query)*	page
pageSize integer *(query)*	pageSize

Responses Response content type: application/json

Code	Description
200	Llist of user's orders

Example Value | Model


```
[
  {
    "address": "string",
    "code": "string",
    "createdAt": "string",
    "customerId": "string",
    "deliveryMan": {
      "avatarUrl": "string",
      "email": "string",
      "firstName": "string",
      "id": "string",
      "lastName": "string",
      "phone": "string",
      "username": "string"
    },
    "distance": 0,
    "id": "string",
    "latitude": 0,
    "longitude": 0,
    "notes": "string",
    "paidAmount": 0,
    "paidAt": "string",
    "paymentMethod": 0,
    "scheduledTime": "string",
    "shippingFee": 0,
    "status": 0,
    "store": {
      "address": "string",
```


400 Validation Error (Bad Request)

Example Value | Model


```
{}
```


401 Unauthorized

Example Value | Model


```
{}
```


500 Internal Server Error

Example Value | Model


```
{}
```


GET /me/orders/payments Get my payment history

Retrieve the payment history for the currently logged-in customer.

Parameters Try it out

Name	Description
endDate **string** *(query)*	endDate
page **integer** *(query)*	page
pageSize **integer** *(query)*	pageSize
startDate **string** *(query)*	ISO-8601 startDate
status **integer** *(query)*	0=Pending, 1=Paid, 2=Failed; omit for all status

Responses

Response content type: application/json

Code	Description
200	User's payment history

Example Value | Model


```
{
  "items": [
    {
      "amount": 0,
      "currency": "string",
      "id": "string",
      "orderCode": "string",
      "orderId": "string",
      "paymentDate": "string",
      "paymentMethod": 0,
      "status": 0
    }
  ],
  "totalCount": 0,
  "totalPages": 0
}
```


400 Validation Error (Bad Request)

Example Value | Model


```
{}
```


401 Unauthorized

Example Value | Model


```
{}
```


500 Internal Server Error

Example Value | Model

Code	Description
	{}

GET /orders Get Orders History

Retrieve a paginated list of all orders with optional filtering parameters (Admin/Manager view).

Parameters Try it out

Name	Description
code string *(query)*	code
fromDate string *(query)*	fromDate
page integer *(query)*	page
pageSize integer *(query)*	pageSize
paymentMethod integer *(query)*	paymentMethod
status integer *(query)*	status
storeId string *(query)*	storeId
toDate string *(query)*	toDate

Responses Response content type application/json

Code	Description
200	Paginated list of orders **Example Value** | Model


```
{
  "items": [
    {
      "address": "string",
      "code": "string",
```

Code	Description


```
  "createdAt": "string",
  "customerId": "string",
  "deliveryMan": {
    "avatarUrl": "string",
    "email": "string",
    "firstName": "string",
    "id": "string",
    "lastName": "string",
    "phone": "string",
    "username": "string"
  },
  "distance": 0,
  "id": "string",
  "latitude": 0,
  "longitude": 0,
  "notes": "string",
  "paidAmount": 0,
  "paidAt": "string",
  "paymentMethod": 0,
  "scheduledTime": "string",
  "shippingFee": 0,
  "status": 0,
  "store": {
```


400 Validation Error (Bad Request)

Example Value | Model


```
{}
```


401 Unauthorized

Example Value | Model


```
{}
```


500 Internal Server Error

Example Value | Model


```
{}
```


POST /orders Place New Order

Create a new order based on the provided items, store, and shipping information.

Parameters Try it out

Name	Description
request * required `object` *(body)*	Order creation details **Example Value** | Model


```
{
  "address": "string",
  "items": [
    {
      "quantity": 100000,
      "sku": "string"
    }
  ],
  "notes": "string",
  "scheduledTime": "string",
  "storeId": "string",
```

Name	Description


```
  "type": 0
}
```


Parameter content type

application/json

Responses Response content type: application/json

Code	Description

200 — Created Order Data

Example Value | Model


```
{
  "checkStockResponse": {
    "isEnough": true,
    "shortageItems": [
      {
        "maxFeasibleQuantity": 0,
        "sku": "string",
        "variantId": "string"
      }
    ]
  },
  "customerId": "string",
  "orderCode": "string",
  "orderId": "string",
  "storeId": "string",
  "totalAmount": 0
}
```


400 — Validation Error (Bad Request)

Example Value | Model


```
{}
```


401 — Unauthorized

Example Value | Model


```
{}
```


500 — Internal Server Error

Example Value | Model


```
{}
```


GET /orders/payments Get all payments (Admin)

Retrieve the payment history of the entire system (Intended for Administrators and Accountants).

Parameters Try it out

Name	Description
page **integer** *(query)*	page
pageSize **integer** *(query)*	pageSize

Responses Response content type: application/json

Code	Description
200	List of payments **Example Value** | Model


```
{
  "items": [
    {
      "amount": 0,
      "code": "string",
      "createdAt": "string",
      "currency": "string",
      "id": "string",
      "method": 0,
      "orderId": "string",
      "paidAt": "string",
      "status": 0
    }
  ],
  "totalCount": 0,
  "totalPages": 0
}
```


Code	Description
400	Validation Error (Bad Request) **Example Value** | Model


```
{}
```


Code	Description
401	Unauthorized **Example Value** | Model


```
{}
```


Code	Description
500	Internal Server Error **Example Value** | Model


```
{}
```


GET `/orders/reports/revenue` Get Revenue Report (JSON)

Get a detailed revenue breakdown by product and category, primarily used for rendering dashboard charts.

Parameters

Try it out

Name	Description
categoryId **string** *(query)*	categoryId
fromDate **string** *(query)*	*Example* : 2024-01-01T00:00:00Z fromDate
storeId **string** *(query)*	storeId
toDate **string** *(query)*	*Example* : 2024-01-31T23:59:59Z toDate

Responses

Response content type: application/json

Code	Description
200	Revenue report data **Example Value** | Model


```
{
  "categoryId": "string",
  "fromDate": "2024-01-01T00:00:00Z",
  "items": [
    {
      "productName": "string",
      "quantitySold": 0,
      "sku": "string",
      "storeId": "string",
      "totalRevenue": 0,
      "unitPrice": 0
    }
  ],
  "overallTotalRevenue": 0,
  "toDate": "2024-01-31T23:59:59Z"
}
```


400	Validation Error (Bad Request) **Example Value** | Model


```
{}
```


401	Unauthorized **Example Value** | Model


```
{}
```


500	Internal Server Error **Example Value** | Model


```
{}
```

Code	Description

GET `/orders/reports/revenue/export` Export Revenue Report (CSV)

Download the revenue report as a CSV file for bookkeeping and offline analysis.

Parameters Try it out

Name	Description
categoryId `string` *(query)*	categoryId
fromDate `string` *(query)*	*Example* : 2024-01-01T00:00:00Z fromDate
storeId `string` *(query)*	storeId
toDate `string` *(query)*	*Example* : 2024-01-31T23:59:59Z toDate

Responses Response content type text/csv

Code	Description
200	CSV File containing revenue data **Example Value** | Model `(no example available`
400	Validation Error (Bad Request) **Example Value** | Model `{}`
401	Unauthorized **Example Value** | Model `{}`
500	Internal Server Error **Example Value** | Model

Code	Description
	{}

GET `/orders/reports/sales-trend` Get Sales Trend Chart Data

Retrieve sales trend data (revenue, order volume) grouped by a specific time aggregation (hour/day/week).
AUTHORIZATION NOTE (StoreId):

- **Admin:** Can provide a `storeId` to view a specific store, or leave it blank to view system-wide data.
- **Manager/Staff:** Even if a `storeId` is provided, the system will securely override it with the store ID associated with the logged-in user's token.

Parameters Try it out

Name	Description
aggregation `integer` *(query)*	Mức độ gom nhóm dữ liệu. 0 = Hour, 1 = Day, 2 = Week. *Available values* : 0, 1, 2 *Default value* : 1 *Example* : 1 1
categoryId `string` *(query)*	ID Danh mục sản phẩm (Tùy chọn) *Example* : cat-001 categoryId
fromDate * required `string` *(query)*	Thời gian bắt đầu. Bắt buộc nhập. *Example* : 2024-03-01T00:00:00Z fromDate
storeId `string` *(query)*	ID Cửa hàng (Tùy chọn) *Example* : 123e4567-e89b-12d3-a456-426614174000 storeId
toDate * required `string` *(query)*	Thời gian kết thúc. Bắt buộc nhập. *Example* : 2024-03-05T23:59:59Z toDate

Responses Response content type application/json

Code	Description
200	Trend data including peak/low time labels **Example Value** | Model `{ "dataPoints": [ { "orderVolume": 0, "revenue": 0, "timeLabel": "string" } ], "peakPeriodLabel": "string", "slowPeriodLabel": "string" }`
400	Validation Error (Bad Request) **Example Value** | Model `{}`
401	Unauthorized **Example Value** | Model `{}`
500	Internal Server Error **Example Value** | Model `{}`

GET `/orders/reports/sales-trend/export` Export Sales Trend (CSV)

Download sales trend data (revenue, order volume) as a CSV file.
Supports the same filtering and storeId authorization logic as the JSON endpoint.

Parameters Try it out

Name	Description
aggregation `integer` *(query)*	Mức độ gom nhóm dữ liệu. 0 = Hour, 1 = Day, 2 = Week. *Available values* : 0, 1, 2 *Default value* : 1 *Example* : 1 1
categoryId `string` *(query)*	ID Danh mục sản phẩm (Tùy chọn) *Example* : cat-001

Name	Description
	categoryId
fromDate * required `string` *(query)*	Thời gian bắt đầu. Bắt buộc nhập. *Example* : 2024-03-01T00:00:00Z fromDate
storeId `string` *(query)*	ID Cửa hàng (Tùy chọn) *Example* : 123e4567-e89b-12d3-a456-426614174000 storeId
toDate * required `string` *(query)*	Thời gian kết thúc. Bắt buộc nhập. *Example* : 2024-03-05T23:59:59Z toDate

Responses — **Response content type** text/csv

Code	Description
200	CSV File containing sales trend data **Example Value** | Model `(no example available`
400	Validation Error (Bad Request) **Example Value** | Model `{}`
401	Unauthorized **Example Value** | Model `{}`
500	Internal Server Error **Example Value** | Model `{}`

GET `/orders/reports/volume` Get Order Volume Statistics (JSON)

Get daily order counts and status breakdown, primarily used for rendering line charts on the dashboard.

Parameters Try it out

Name	Description
fromDate `string` *(query)*	*Example* : 2024-05-20 fromDate
status `integer($int32)` *(query)*	*Available values* : 0, 1, 2, 3, 4, 5, 6, 7 --
storeId `string` *(query)*	storeId
toDate `string` *(query)*	*Example* : 2024-05-27 toDate

Responses Response content type application/json

Code	Description
200	Order volume statistics data **Example Value** | Model

```
{
  "orders": [
    {
      "canceledOrder": 0,
      "completedOrder": 0,
      "date": "2024-05-20",
      "statusCounts": {
        "additionalProp1": 0,
        "additionalProp2": 0,
        "additionalProp3": 0
      },
      "storeId": "string",
      "totalOrders": 0
    }
  ]
}
```

400	Validation Error (Bad Request) **Example Value** | Model

```
{}
```

401	Unauthorized **Example Value** | Model

```
{}
```

500	Internal Server Error

Code	Description

Example Value | Model

```
{}
```

GET `/orders/reports/volume/export` Export Order Volume (CSV)

Download daily order statistics as a CSV file.

Parameters Try it out

Name	Description
fromDate `string` *(query)*	*Example* : 2024-05-20 fromDate
status `integer($int32)` *(query)*	*Available values* : 0, 1, 2, 3, 4, 5, 6, 7 --
storeId `string` *(query)*	storeId
toDate `string` *(query)*	*Example* : 2024-05-27 toDate

Responses Response content type: text/csv

Code	Description
200	CSV File containing order volume data **Example Value** | Model `(no example available`
400	Validation Error (Bad Request) **Example Value** | Model `{}`
401	Unauthorized **Example Value** | Model `{}`

Code	Description
500	Internal Server Error

Example Value | Model

```
{}
```

GET /orders/{id} Get Order Details

Retrieve full details of a specific order by its ID, including items, store info, and delivery personnel.

Parameters

Try it out

Name	Description
id * required `string` *(path)*	Order UUID id

Responses

Response content type: application/json

Code	Description
200	Detailed order information

Example Value | Model

```
{
  "address": "string",
  "code": "string",
  "createdAt": "string",
  "customerId": "string",
  "deliveryMan": {
    "avatarUrl": "string",
    "email": "string",
    "firstName": "string",
    "id": "string",
    "lastName": "string",
    "phone": "string",
    "username": "string"
  },
  "distance": 0,
  "id": "string",
  "items": [
    {
      "id": "string",
      "imageUrl": "string",
      "productId": "string",
      "productName": "string",
      "quantity": 0,
      "sku": "string",
      "unitPrice": 0,
      "variantId": "string"
    }
  ],
```

Code	Description
400	Invalid ID format

Example Value | Model

```
{}
```

Code	Description
401	Unauthorized **Example Value** | Model `{}`
404	Order not found **Example Value** | Model `{}`
500	Internal Server Error **Example Value** | Model `{}`

PUT `/orders/{id}` Update Order Items

Update the list of items in an existing order (typically allowed only when the order is in a 'Pending' state).

Parameters Try it out

Name	Description
id * required `string` *(path)*	Order UUID id
request * required `array<object>` *(body)*	List of items to update **Example Value** | Model `[ { "quantity": 100000, "sku": "string" } ]` **Parameter content type** application/json

Responses Response content type application/json

Code	Description
200	Updated Order Data

Code	Description

Example Value | Model


```
{
  "checkStockResponse": {
    "isEnough": true,
    "shortageItems": [
      {
        "maxFeasibleQuantity": 0,
        "sku": "string",
        "variantId": "string"
      }
    ]
  },
  "customerId": "string",
  "orderCode": "string",
  "orderId": "string",
  "storeId": "string",
  "totalAmount": 0
}
```


400 Validation Error or Invalid ID

Example Value | Model


```
{}
```


401 Unauthorized

Example Value | Model


```
{}
```


404 Order Not Found

Example Value | Model


```
{}
```


500 Internal Server Error

Example Value | Model


```
{}
```


POST /orders/{id}/delivery/assign Assign Staff To Delivery

Manager assigns a specific staff member (delivery man) to handle an order's delivery.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Order UUID id
request * required `object`	Staff ID to be assigned **Example Value** | Model

Name	Description
(body)	<pre>{ "staffId": "string" }</pre>

Parameter content type

application/json

Responses — Response content type: application/json

Code	Description
200	Successfully assigned staff **Example Value** | Model <pre>{ "additionalProp1": {} }</pre>
400	Validation Error or Invalid ID **Example Value** | Model <pre>{}</pre>
401	Unauthorized **Example Value** | Model <pre>{}</pre>
404	Order or Staff Not Found **Example Value** | Model <pre>{}</pre>
500	Internal Server Error **Example Value** | Model <pre>{}</pre>

POST /orders/{id}/delivery/me/assign Self Assign Staff To Delivery

A delivery staff member assigns themselves to handle an order's delivery. Staff ID is automatically extracted from the Token.

Parameters — Try it out

Name	Description
id * required `string` *(path)*	Order UUID id
request * required `object` *(body)*	Optional assignment notes **Example Value** | Model `{ "staffId": "string" }` **Parameter content type** application/json

Responses

Response content type: application/json

Code	Description
200	Successfully self-assigned **Example Value** | Model `{ "additionalProp1": {} }`
400	Validation Error or Invalid ID **Example Value** | Model `{}`
401	Unauthorized **Example Value** | Model `{}`
404	Order Not Found **Example Value** | Model `{}`
500	Internal Server Error **Example Value** | Model `{}`

POST `/orders/{id}/payment` Generate Payment URL

Generate a payment link (VNPay) for the specific order.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Order UUID id
request * required `object` *(body)*	Payment details **Example Value** | Model `{ "appliedWalletAmount": 0, "paymentMethod": 0, "point": 0, "returnUrl": "string", "voucherDiscountCode": "string", "voucherShipCode": "string" }` **Parameter content type** application/json

Responses Response content type application/json

Code	Description
200	Payment URL **Example Value** | Model `{ "additionalProp1": {} }`
400	Validation Error (Bad Request) **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`
401	Unauthorized **Example Value** | Model `{}`
500	Internal Server Error **Example Value** | Model `{}`

Code	Description

PATCH `/orders/{id}/status` Update Order Status

Change the lifecycle status of an order (e.g., to 'Processing', 'Cancelled', 'Completed').

Parameters Try it out

Name	Description
id * required `string` *(path)*	Order UUID id
request * required `object` *(body)*	New Status details **Example Value** | Model `{ "status": 0 }` **Parameter content type** application/json

Responses Response content type application/json

Code	Description
200	Successfully updated status **Example Value** | Model `{ "additionalProp1": {} }`
400	Validation Error or Invalid ID **Example Value** | Model `{}`
401	Unauthorized **Example Value** | Model `{}`
404	Order Not Found **Example Value** | Model

Code	Description
	{}
500	Internal Server Error

Example Value | Model

```
{}
```

Points

GET `/me/points/logs` Get My Point History

Retrieve pagination list of point transaction logs for the current authenticated user.

Parameters Try it out

Name	Description
fromDate `string` *(query)*	fromDate
page `integer` *(query)*	page
pageSize `integer` *(query)*	pageSize
toDate `string` *(query)*	toDate

Responses Response content type application/json

Code	Description
200	List of point logs

Example Value | Model


```
{
  "items": [
    {
      "actionType": "string",
      "amount": "string",
      "balanceAfter": "string",
      "balanceBefore": "string",
      "createdAt": "string",
      "description": "string",
      "expiredAt": "string",
      "id": "string",
      "reasonCode": "string",
```

Code	Description


```
      "referenceId": "string",
      "userId": "string"
    }
  ],
  "totalCount": 0,
  "totalPages": 0
}
```


401 Unauthorized

Example Value | Model


```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```


Refunds

GET `/me/refunds` Get my refund requests

Retrieve a paginated list of refund tickets created by the currently logged-in user.

Parameters Try it out

Name	Description
page **integer** *(query)*	page
pageSize **integer** *(query)*	pageSize
status **integer($int32)** *(query)*	*Available values* : 1, 2, 3, 4, 5, 6, 7 --

Responses Response content type application/json

Code	Description

200 List of refund tickets

Example Value | Model


```
{
  "items": [
    {
      "amount": "string",
      "createdAt": "string",
      "id": "string",
      "reason": "string",
      "refundAmount": "string",
      "status": 1,
      "ticketCode": "string",
      "transactionId": "string",
      "updatedAt": "string",
      "userId": "string"
    }
```

Code	Description

```
  ],
  "totalCount": 0,
  "totalPages": 0
}
```

400 Validation Error (Bad Request)

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

401 Unauthorized

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

500 Internal Server Error

Example Value | Model

```
{}
```

POST `/me/refunds` Create a new refund request

Customer proactively creates a refund request (ticket) for a specific transaction or order.

Parameters Try it out

Name	Description
request * required `object` *(body)*	Refund request details **Example Value** | Model

```
{
  "amount": "string",
  "reason": "string"
}
```

Parameter content type

application/json

Responses Response content type application/json

Code	Description
200	{"message": "Tạo yêu cầu hoàn tiền thành công"} **Example Value** | Model

Code	Description

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

400 Validation Error (Bad Request)

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

401 Unauthorized

Example Value | Model

```
{}
```

500 Internal Server Error

Example Value | Model

```
{}
```

GET `/refunds` Get all refund requests (Admin)

Retrieve a list of all refund tickets (Intended for Staff, Manager, Admin). Can optionally pass a `userId` in the query to filter by a specific user.

Parameters Try it out

Name	Description
userId `string` *(query)*	Filter by specific User UUID (Optional) userId
page `integer` *(query)*	page
pageSize `integer` *(query)*	pageSize
status `integer($int32)` *(query)*	*Available values* : 1, 2, 3, 4, 5, 6, 7 --

Responses Response content type application/json

Code	Description
200	List of refund tickets **Example Value** | Model


```
{
  "items": [
    {
      "amount": "string",
      "createdAt": "string",
      "id": "string",
      "reason": "string",
      "refundAmount": "string",
      "status": 1,
      "ticketCode": "string",
      "transactionId": "string",
      "updatedAt": "string",
      "userId": "string"
    }
  ],
  "totalCount": 0,
  "totalPages": 0
}
```


400	Validation Error (Bad Request) **Example Value** | Model


```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```


401	Unauthorized **Example Value** | Model


```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```


500	Internal Server Error **Example Value** | Model


```
{}
```


GET /refunds/{id} Get refund ticket details

Retrieve detailed information of a specific refund ticket. The service layer handles authorization based on the user's role and token.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Refund ticket UUID id

Responses Response content type: application/json

Code	Description
200	Refund ticket details **Example Value** | Model

```
{
  "amount": "string",
  "createdAt": "string",
  "id": "string",
  "originalTransactionId": "string",
  "reason": "string",
  "refundAmount": "string",
  "refundMethod": 1,
  "refundReason": 1,
  "rejectionReason": "string",
  "status": 1,
  "ticketCode": "string",
  "transactionId": "string",
  "updatedAt": "string",
  "userId": "string",
  "walletId": "string"
}
```

401 Unauthorized

Example Value | Model

```
{}
```

404 Refund ticket not found

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

500 Internal Server Error

Example Value | Model

```
{}
```

PATCH /refunds/{id}/approve Approve refund request (Admin)

Accept and process the refund request for the customer.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Refund ticket UUID id
request * required `object` *(body)*	Approval details/reason **Example Value** | Model

Name	Description

```
{
  "approvalNotes": "string"
}
```

Parameter content type

application/json

Responses

Response content type: application/json

Code	Description
200	{"message": "Đã duyệt yêu cầu hoàn tiền"}

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

400	Validation Error or Invalid ID

Example Value | Model

```
{}
```

401	Unauthorized

Example Value | Model

```
{}
```

500	Internal Server Error

Example Value | Model

```
{}
```

PATCH /refunds/{id}/cancel Cancel refund request

Cancel an active refund ticket (usually performed by the customer if they change their mind).

Parameters Try it out

Name	Description
id * required `string` *(path)*	Refund ticket UUID id

Name	Description
request * required `object` *(body)*	Cancellation reason **Example Value** | Model `{ "cancellationReason": "string" }` **Parameter content type** application/json

Responses — Response content type: application/json

Code	Description
200	{"message": "Đã hủy yêu cầu hoàn tiền"} **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`
400	Validation Error or Invalid ID **Example Value** | Model `{}`
401	Unauthorized **Example Value** | Model `{}`
500	Internal Server Error **Example Value** | Model `{}`

PATCH `/refunds/{id}/complete` Mark refund as complete (Admin)

Confirm that the money transfer process is successful and close the refund ticket.

Parameters — Try it out

Name	Description
id * required `string` *(path)*	Refund ticket UUID id
request * required `object` *(body)*	Completion notes **Example Value** | Model `{ "completeNotes": "string" }` **Parameter content type** application/json

Responses — Response content type: application/json

Code	Description
200	{"message": "Đã đánh dấu hoàn tất yêu cầu hoàn tiền"} **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`
400	Validation Error or Invalid ID **Example Value** | Model `{}`
401	Unauthorized **Example Value** | Model `{}`
500	Internal Server Error **Example Value** | Model `{}`

PATCH `/refunds/{id}/reject` Reject refund request (Admin)

Reject a refund request and provide a specific reason to the customer.

Parameters

Try it out

Name	Description
id * required `string` *(path)*	Refund ticket UUID id
request * required `object` *(body)*	Rejection reason **Example Value** | Model `{ "rejectNotes": "string" }` **Parameter content type** application/json

Responses Response content type application/json

Code	Description
200	{"message": "Đã từ chối yêu cầu hoàn tiền"} **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`
400	Validation Error or Invalid ID **Example Value** | Model `{}`
401	Unauthorized **Example Value** | Model `{}`
500	Internal Server Error **Example Value** | Model `{}`

Shifts: Availabilities

GET `/me/shift-availabilities` Get my shift availability history

Retrieve the paginated list of registered availability/unavailability for the current employee.

Parameters Try it out

Name	Description
dayOfWeek **integer** *(query)*	dayOfWeek
fromDate **string** *(query)*	fromDate
isAvailable **boolean** *(query)*	--
isRecurring **boolean** *(query)*	--
keyword **string** *(query)*	keyword
page **integer** *(query)*	page
pageSize **integer** *(query)*	pageSize
storeId **string** *(query)*	storeId
toDate **string** *(query)*	toDate
userId **string** *(query)*	userId

Responses Response content type application/json

Code	Description
200	Successful retrieval

Example Value | Model


```
{
  "items": [
    {
      "createdAt": "string",
      "dayOfWeek": 0,
      "endTime": "string",
      "id": "string",
```

Code	Description


```
      "isAvailable": true,
      "isRecurring": true,
      "note": "string",
      "specificDate": "string",
      "startTime": "string",
      "updatedAt": "string",
      "userId": "string"
    }
  ],
  "totalCount": 0,
  "totalPages": 0
}
```


400 Bad Request

Example Value | Model


```
{}
```


401 Unauthorized

Example Value | Model


```
{}
```


500 Internal Server Error

Example Value | Model


```
{}
```


GET /shift-availabilities Manage all shift availabilities (Manager)

Managers view the complete list of employee availabilities to facilitate shift scheduling.

Parameters Try it out

Name	Description
dayOfWeek **integer** *(query)*	dayOfWeek
fromDate **string** *(query)*	fromDate
isAvailable **boolean** *(query)*	--
isRecurring **boolean** *(query)*	--
keyword **string** *(query)*	keyword

Name	Description
page **integer** *(query)*	page
pageSize **integer** *(query)*	pageSize
storeId **string** *(query)*	storeId
toDate **string** *(query)*	toDate
userId **string** *(query)*	userId

Responses Response content type: application/json

Code	Description
200	Successful retrieval **Example Value** | Model


```
{
  "items": [
    {
      "createdAt": "string",
      "dayOfWeek": 0,
      "endTime": "string",
      "id": "string",
      "isAvailable": true,
      "isRecurring": true,
      "note": "string",
      "specificDate": "string",
      "startTime": "string",
      "updatedAt": "string",
      "userId": "string"
    }
  ],
  "totalCount": 0,
  "totalPages": 0
}
```


400	Bad Request **Example Value** | Model


```
{}
```


401	Unauthorized **Example Value** | Model


```
{}
```


500	Internal Server Error **Example Value** | Model

Code	Description
	{}

POST /shift-availabilities Register new shift availability

Submit a request for available or unavailable time to assist managers in scheduling.

Parameters

Try it out

Name	Description

body * required
object
(body)
	Availability registration data
	Example Value | Model
	{
	"dayOfWeek": 0,
	"endTime": "string",
	"isAvailable": true,
	"isRecurring": true,
	"note": "string",
	"specificDate": "string",
	"startTime": "string"
	}
	Parameter content type
	application/json

Responses

Response content type: application/json

Code	Description

201	Successfully created
	Example Value | Model
	{
	"additionalProp1": {}
	}

400	Validation Error (Bad Request) **Example Value** | Model {}
401	Unauthorized **Example Value** | Model {}
500	Internal Server Error

Code	Description

Example Value | Model

```
{}
```

DELETE `/shift-availabilities/{id}` Delete shift availability

Remove a previously submitted availability request.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Availability ID id

Responses Response content type: application/json

Code	Description
200	Successfully deleted

Example Value | Model

```
{
  "additionalProp1": {}
}
```

400	Invalid ID

Example Value | Model

```
{}
```

401	Unauthorized

Example Value | Model

```
{}
```

500	Internal Server Error

Example Value | Model

```
{}
```

PATCH `/shift-availabilities/{id}` Update shift availability

Edit a submitted availability/unavailability request by its ID.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Availability ID id
body * required `object` *(body)*	Update data **Example Value** | Model `{ "dayOfWeek": 0, "endTime": "string", "isAvailable": true, "isRecurring": true, "note": "string", "specificDate": "string", "startTime": "string" }` **Parameter content type** application/json

Responses Response content type application/json

Code	Description
200	Successfully updated **Example Value** | Model `{ "additionalProp1": {} }`
400	Invalid ID or Bad Request **Example Value** | Model `{}`
401	Unauthorized **Example Value** | Model `{}`
500	Internal Server Error **Example Value** | Model `{}`

Code	Description

Shifts: Swaps

GET `/me/shift-swaps` Get my shift swaps

Retrieve all shift swap requests where the current logged-in user is either the sender or the receiver.

Parameters Try it out

No parameters

Responses Response content type: application/json

Code	Description
200	List of user's swap requests **Example Value** | Model


```
[
  {
    "createdAt": "string",
    "endTime": "string",
    "expiresAt": "string",
    "id": "string",
    "reason": "string",
    "rejectReason": "string",
    "shiftDate": "string",
    "shiftId": "string",
    "sourceUserId": "string",
    "sourceUserName": "string",
    "startTime": "string",
    "status": 0,
    "targetUserId": "string",
    "targetUserName": "string"
  }
]
```


401	Unauthorized **Example Value** | Model


```
{}
```


500	Internal Server Error **Example Value** | Model


```
{}
```


GET `/shift-swaps` Get all shift swaps

Retrieve a complete list of all shift swap requests (typically for managers).

Parameters Try it out

Name	Description
status `integer` *(query)*	status
storeId `string` *(query)*	storeId

Responses Response content type: application/json

Code	Description
200	List of swap requests

Example Value | Model

```
[
  {
    "createdAt": "string",
    "endTime": "string",
    "expiresAt": "string",
    "id": "string",
    "reason": "string",
    "rejectReason": "string",
    "shiftDate": "string",
    "shiftId": "string",
    "sourceUserId": "string",
    "sourceUserName": "string",
    "startTime": "string",
    "status": 0,
    "targetUserId": "string",
    "targetUserName": "string"
  }
]
```

400 Validation Error (Bad Request)

Example Value | Model

```
{}
```

401 Unauthorized

Example Value | Model

```
{}
```

Code	Description
500	Internal Server Error **Example Value** | Model `{}`

PATCH `/shift-swaps/{id}/approvals` Approve a shift swap (Manager)

After both employees agree to the swap, the Manager gives final approval to officially update the schedule.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Swap Request ID id
body * required `object` *(body)*	Manager's approval decision **Example Value** | Model `{ "approve": true, "rejectReason": "string" }` **Parameter content type** application/json

Responses Response content type application/json

Code	Description
200	{"message": "Đã hoàn tất duyệt đổi ca"} **Example Value** | Model `{ "additionalProp1": {} }`
400	Validation Error or Invalid ID **Example Value** | Model `{}`
401	Unauthorized **Example Value** | Model `{}`

Code	Description
500	Internal Server Error **Example Value** | Model {}

PATCH `/shift-swaps/{id}/cancel` Cancel a sent swap request

The requesting employee can cancel their swap request if it hasn't been approved yet.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Swap Request ID id

Responses Response content type application/json

Code	Description
204	No Content (Cancelled successfully)
400	Invalid ID or Bad Request **Example Value** | Model {}
401	Unauthorized **Example Value** | Model {}
500	Internal Server Error **Example Value** | Model {}

PATCH `/shift-swaps/{id}/responses` Respond to a shift swap request

Employee B receives the swap request and chooses to Accept or Reject it.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Swap Request ID id
body * required `object` *(body)*	Respondent's reply data **Example Value** | Model `{ "accept": true, "rejectReason": "string" }` **Parameter content type** application/json

Responses Response content type application/json

Code	Description
200	{"message": "Đã ghi nhận phản hồi đổi ca"} **Example Value** | Model `{ "additionalProp1": {} }`
400	Validation Error or Invalid ID **Example Value** | Model `{}`
401	Unauthorized **Example Value** | Model `{}`
500	Internal Server Error **Example Value** | Model `{}`

PATCH /shifts/{id}/releases Release a shift to the Shift Pool

The employee releases an assigned shift so other staff members can apply for it.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Assignment ID id

Responses Response content type: application/json

Code	Description
200	{"message": "Đã nhả ca thành công"} **Example Value** | Model `{ "additionalProp1": {} }`
400	Invalid ID or Bad Request **Example Value** | Model `{}`
401	Unauthorized **Example Value** | Model `{}`
500	Internal Server Error **Example Value** | Model `{}`

POST /shifts/{id}/swaps Request a shift swap

Employee A selects one of their assignments and requests a swap with Employee B.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Assignment ID (Sender's shift) id
body * required `object` *(body)*	Swap request details **Example Value** | Model `{ "reason": "string", "targetUserId": "string" }` **Parameter content type** application/json

Responses — Response content type: application/json

Code	Description
201	{"message": "Đã gửi yêu cầu đổi ca"} **Example Value** | Model `{ "additionalProp1": {} }`
400	Validation Error (Bad Request) **Example Value** | Model `{}`
401	Unauthorized **Example Value** | Model `{}`
500	Internal Server Error **Example Value** | Model `{}`

Shifts: Staff

GET `/me/shifts` Get staff shift agenda

Retrieve the shift schedule within a specified date range for the logged-in staff member.

Parameters Try it out

Name	Description
startDate * required `string` *(query)*	Start Date (YYYY-MM-DD) startDate
endDate * required `string` *(query)*	End Date (YYYY-MM-DD) endDate

Responses Response content type application/json

Code	Description
200	List of scheduled shifts **Example Value** | Model


```
[
  {
    "checkInAt": "string",
    "checkOutAt": "string",
    "coWorkers": [
      {
        "avatar": "string",
        "firstName": "string",
        "id": "string",
        "lastName": "string",
        "phone": "string"
      }
    ],
    "date": "string",
    "endTime": "string",
    "id": "string",
    "shiftId": "string",
    "startTime": "string",
    "store": {
      "address": "string",
      "id": "string",
      "imageUrl": "string",
      "isOpenNow": true,
      "latitude": 0,
      "longitude": 0,
      "name": "string",
      "phone": "string"
    }
```


Code	Description
400	Validation Error (Bad Request) **Example Value** | Model


```
{}
```


Code	Description
401	Unauthorized **Example Value** | Model


```
{}
```

Code	Description
500	Internal Server Error **Example Value** | Model `{}`

PUT `/me/shifts/assignments/{id}/check-in` Staff check-in

Check-in to a specific shift assignment using GPS location data.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Assignment ID id
body * required `object` *(body)*	GPS coordinates and notes **Example Value** | Model `{ "latitude": 0, "longitude": 0, "note": "string" }` **Parameter content type** application/json

Responses Response content type application/json

Code	Description
200	Check-in successful **Example Value** | Model `{ "additionalProp1": {} }`
400	Validation Error or Invalid ID **Example Value** | Model `{}`
401	Unauthorized **Example Value** | Model

Code	Description
	{}
500	Internal Server Error **Example Value** | Model {}

GET `/me/shifts/current` Get current active shift

Retrieve the current active shift details for the logged-in user.

Parameters Try it out

No parameters

Responses Response content type: application/json

Code	Description
200	Current shift details **Example Value** | Model


```
{
  "assignmentId": "string",
  "canCheckIn": true,
  "canCheckOut": true,
  "checkInAt": "string",
  "checkOutAt": "string",
  "currentLogId": "string",
  "endTime": "string",
  "hasShiftToday": true,
  "isOvertime": true,
  "serverTime": "string",
  "shiftId": "string",
  "startTime": "string",
  "storeId": "string",
  "storeLat": 0,
  "storeLong": 0,
  "storeName": "string"
}
```


401	Unauthorized **Example Value** | Model


```
{}
```

Code	Description
500	Internal Server Error **Example Value** | Model `{}`

PUT `/me/shifts/logs/{id}/check-out` Staff check-out

Check-out from an active shift log using GPS location data.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Time Log ID id
body * required `object` *(body)*	GPS coordinates and notes **Example Value** | Model `{ "latitude": 0, "longitude": 0, "note": "string" }` **Parameter content type** application/json

Responses Response content type application/json

Code	Description
200	Check-out successful **Example Value** | Model `{ "additionalProp1": {} }`
400	Validation Error or Invalid ID **Example Value** | Model `{}`
401	Unauthorized **Example Value** | Model

Code	Description
	{}
500	Internal Server Error **Example Value** | Model {}

GET `/me/shifts/time-logs` Get my time log history

Staff views their own time log history. The Gateway automatically binds the StaffID from the Token to ensure security.

Parameters Try it out

Name	Description
fromDate `string` *(query)*	Format: YYYY-MM-DD fromDate
page `integer` *(query)*	page
pageSize `integer` *(query)*	pageSize
staffId `string` *(query)*	staffId
status `integer` *(query)*	*Available values* : 0, 1, 2 --
storeId `string` *(query)*	storeId
toDate `string` *(query)*	toDate

Responses Response content type application/json

Code	Description
200	Paginated time log history **Example Value** | Model

Code	Description


```
{
  "items": [
    {
      "checkInAt": "string",
      "checkInImageUrl": "string",
      "checkInLat": 0,
      "checkInLong": 0,
      "checkOutAt": "string",
      "checkOutImageUrl": "string",
      "checkOutLat": 0,
      "checkOutLong": 0,
      "createdAt": "string",
      "dailyOtMinutes": 0,
      "id": "string",
      "managerNote": "string",
      "regularMinutes": 0,
      "shift": {
        "endTime": "string",
        "id": "string",
        "note": "string",
        "shiftDate": "string",
        "startTime": "string"
      },
      "shiftAssignmentId": "string",
      "staff": {
        "avatarUrl": "string",
        "email": "string",
        "firstName": "string",
```


400 Validation Error (Bad Request)

Example Value | Model

```
{}
```

401 Unauthorized

Example Value | Model

```
{}
```

500 Internal Server Error

Example Value | Model

```
{}
```

Vouchers

GET `/me/vouchers` Get My Vouchers

Retrieve a list of all vouchers available in my account.

Parameters Try it out

No parameters

Responses Response content type application/json

Code	Description
200	List of vouchers

Example Value | Model


```
[
  {
    "code": "string",
    "createdAt": "string",
    "currentQuantity": 0,
    "discountValue": "string",
    "endDate": "string",
    "id": "string",
    "initQuantity": 0,
    "isActive": true,
    "maxDiscountValue": "string",
    "maxUsagePerUser": 0,
    "minOrderValue": "string",
    "pointCost": "string",
    "type": 0,
    "updatedAt": "string",
    "voucherItems": [
      {
        "id": "string",
        "quantity": 0,
        "sku": "string",
        "type": 0
      }
    ]
  }
]
```


POST /me/vouchers/{id}/redeem Redeem Points for Voucher

Allows the authenticated user to redeem their accumulated points to claim a specific voucher.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Voucher UUID id

Responses Response content type: application/json

Code	Description
200	Redemption successful

Example Value | Model


```
{
  "additionalProp1": {}
}
```


Code	Description
400	Invalid Voucher ID format

Example Value | Model


```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
```

Code	Description


```
  "additionalProp3": "string"
}
```


401 Unauthorized - Valid token required

Example Value | Model


```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```


GET /vouchers Get All Vouchers

Retrieve a list of all vouchers available in the system.

Parameters Try it out

No parameters

Responses Response content type: application/json

Code	Description

200 List of vouchers

Example Value | Model


```
[
  {
    "code": "string",
    "createdAt": "string",
    "currentQuantity": 0,
    "discountValue": "string",
    "endDate": "string",
    "id": "string",
    "initQuantity": 0,
    "isActive": true,
    "maxDiscountValue": "string",
    "maxUsagePerUser": 0,
    "minOrderValue": "string",
    "pointCost": "string",
    "type": 0,
    "updatedAt": "string",
    "voucherItems": [
      {
        "id": "string",
        "quantity": 0,
        "sku": "string",
        "type": 0
      }
    ]
  }
]
```


POST /vouchers Create New Voucher

Create a new discount voucher with items and rules.

Parameters Try it out

Name	Description
request * required `object` *(body)*	Voucher details **Example Value** | Model

```
{
  "code": "string",
  "discountValue": "string",
  "endDate": "string",
  "initQuantity": 0,
  "maxDiscountValue": "string",
  "maxUsagePerUser": 0,
  "minOrderValue": "string",
  "pointCost": "string",
  "type": 0,
  "voucherItems": [
    {
      "quantity": 0,
      "sku": "string",
      "type": 0
    }
  ]
}
```

Parameter content type: application/json

Responses — Response content type: application/json

Code	Description
201	Voucher details **Example Value** | Model

```
{
  "code": "string",
  "createdAt": "string",
  "currentQuantity": 0,
  "discountValue": "string",
  "endDate": "string",
  "id": "string",
  "initQuantity": 0,
  "isActive": true,
  "maxDiscountValue": "string",
  "maxUsagePerUser": 0,
  "minOrderValue": "string",
  "pointCost": "string",
  "type": 0,
  "updatedAt": "string",
  "voucherItems": [
    {
      "id": "string",
      "quantity": 0,
      "sku": "string",
      "type": 0
    }
  ]
}
```

GET /vouchers/code/{code} Get Voucher by Code

Retrieve voucher details using its unique string code (e.g., 'SALE50').

Parameters — Try it out

Name	Description
code * required `string` *(path)*	Voucher Code code

Responses Response content type: application/json

Code	Description
200	Voucher details **Example Value** | Model


```
{
  "code": "string",
  "createdAt": "string",
  "currentQuantity": 0,
  "discountValue": "string",
  "endDate": "string",
  "id": "string",
  "initQuantity": 0,
  "isActive": true,
  "maxDiscountValue": "string",
  "maxUsagePerUser": 0,
  "minOrderValue": "string",
  "pointCost": "string",
  "type": 0,
  "updatedAt": "string",
  "voucherItems": [
    {
      "id": "string",
      "quantity": 0,
      "sku": "string",
      "type": 0
    }
  ]
}
```


404	Voucher not found **Example Value** | Model


```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```


DELETE /vouchers/{id} Delete Voucher

Permanently remove a voucher from the system.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Voucher UUID id

Responses Response content type: application/json

Code	Description
200	Success

Example Value | Model

```
{
  "additionalProp1": {}
}
```

PATCH /vouchers/{id} Update Voucher

Update details of an existing voucher. Fields are optional (patch-like behavior).

Parameters Try it out

Name	Description
id * required `string` *(path)*	Voucher UUID id
request * required `object` *(body)*	Updated fields

Example Value | Model

```
{
  "discountValue": "string",
  "endDate": "string",
  "maxDiscountValue": "string",
  "maxUsagePerUser": 0,
  "minOrderValue": "string",
  "pointCost": "string",
  "voucherItems": [
    {
      "id": "string",
      "quantity": 0,
      "sku": "string",
      "type": 0
    }
  ]
}
```

Parameter content type: application/json

Responses Response content type: application/json

Code	Description
200	Success

Example Value | Model

```
{
  "additionalProp1": {}
}
```

PATCH `/vouchers/{id}/status` Update Voucher Status

Activate or deactivate a voucher.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Voucher UUID id
request * required `object` *(body)*	New status **Example Value** | Model `{ "isActive": true }` **Parameter content type** application/json

Responses Response content type application/json

Code	Description
200	Success **Example Value** | Model `{ "additionalProp1": {} }`

Wallets

GET `/me/wallet` Get my wallet details

Retrieve the wallet information and current balance of the logged-in user.

Parameters Try it out

No parameters

Responses Response content type application/json

Code	Description
200	Detailed wallet information **Example Value** | Model `{ "balance": "string", "createdAt": "string", "id": "string", "status": 1, "updatedAt": "string", "userId": "string" }`
401	Unauthorized or invalid token **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`
500	Internal Server Error **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`

POST /me/wallet/top-up Top up wallet balance

Generate a VNPay payment link to allow the user to deposit funds into their personal wallet.

Parameters

Try it out

Name	Description
request * required `object` *(body)*	Top-up details (e.g., amount) **Example Value** | Model `{ "amount": 0, "returnUrl": "string" }` **Parameter content type** application/json

Responses

Response content type: application/json

Code	Description
200	Returns the VNPay URL { paymentUrl: '...' } **Example Value** | Model

Code	Description

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

400 Validation Error (Bad Request)

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

401 Unauthorized

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

500 Internal Server Error or Payment Gateway connection issue

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

GET /wallets/users/{userId} Get user wallet details (Admin)

Intended for Staff, Manager, or Admin to retrieve wallet information of a specific user by their User ID.

Parameters

Try it out

Name	Description
userId * required `string` *(path)*	Target User UUID userId

Responses

Response content type: application/json

Code	Description

200 Detailed wallet information

Example Value | Model

```
{
  "balance": "string",
  "createdAt": "string",
  "id": "string",
  "status": 1,
  "updatedAt": "string",
  "userId": "string"
}
```

Code	Description
400	Invalid User UUID format **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`
401	Unauthorized **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`
403	Forbidden (Insufficient permissions) **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`
404	Wallet not found for this user **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`

GET `/wallets/vnpay/return` Handle VNPay Return URL (Wallet Top-up)

Callback endpoint for VNPay after a customer completes a wallet top-up payment. Validates the gRPC signature and redirects the user to the Frontend UI with the transaction status.

Parameters Try it out

Name	Description
redirectTo **string** *(query)*	Frontend path to redirect to (e.g., /my-wallet) redirectTo
vnp_Amount **string** *(query)*	Transaction Amount (multiplied by 100) vnp_Amount
vnp_ResponseCode **string** *(query)*	VNPay Response Code (00 means success) vnp_ResponseCode
vnp_TxnRef **string** *(query)*	Internal Transaction Reference vnp_TxnRef
vnp_SecureHash **string**	Checksum Security Hash

Name	Description
(query)	vnp_SecureHash

Responses — Response content type: text/html

Code	Description
302	Redirects to the Frontend application

PATCH /wallets/{id}/status Update wallet status (Admin)

Intended for Administrators to lock (suspend) or unlock a user's wallet.

Parameters — Try it out

Name	Description
id * required `string` *(path)*	Target Wallet UUID id
request * required `object` *(body)*	New status information **Example Value** | Model

```
{
  "adminNotes": "string",
  "newStatus": 1,
  "reason": "string"
}
```

Parameter content type: application/json

Responses — Response content type: application/json

Code	Description
200	{"message": "Cập nhật trạng thái ví thành công"} **Example Value** | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

400	Validation Error or Invalid Wallet UUID **Example Value** | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
```

Code	Description

```
  "additionalProp3": "string"
}
```

401 Unauthorized

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

403 Forbidden (Insufficient permissions)

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

Wallet Transactions

GET `/me/wallet/transactions` Get my wallet transaction history

Retrieve a paginated list of wallet transactions (top-ups, deductions, refunds, etc.) for the currently logged-in user.

Parameters Try it out

Name	Description
page `integer` *(query)*	page
pageSize `integer` *(query)*	pageSize

Responses Response content type: application/json

Code	Description

200 List of transactions

Example Value | Model

```
{
  "items": [
    {
      "amount": "string",
      "balanceAfter": "string",
      "balanceBefore": "string",
      "completedAt": "string",
      "createdAt": "string",
      "description": "string",
      "externalTransactionId": "string",
      "failedAt": "string",
      "failureReason": "string",
      "id": "string",
      "initiatedBy": "string",
```

Code	Description


```
      "metadata": "string",
      "notes": "string",
      "orderId": "string",
      "parentTransactionId": "string",
      "paymentMethod": 1,
      "processedAt": "string",
      "processedBy": "string",
      "referenceId": "string",
      "referenceType": 1,
      "status": 1,
      "transactionCode": "string",
      "transactionType": 1,
      "updatedAt": "string",
      "userId": "string",
```


400 Validation Error (Bad Request)

Example Value | Model


```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```


401 Unauthorized

Example Value | Model


```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```


500 Internal Server Error

Example Value | Model


```
{}
```


GET /wallets/transactions Get all system wallet transactions (Admin)

Intended for Staff, Manager, or Admin to retrieve a list of all wallet transactions. Can optionally pass a `userId` in the query to filter transactions for a specific user.

Parameters

Try it out

Name	Description
userId **string** *(query)*	Filter by specific User UUID (Optional) userId
page **integer** *(query)*	page
pageSize **integer** *(query)*	pageSize

Responses

Response content type: application/json

Code	Description
200	List of transactions

Example Value | Model


```
{
  "items": [
    {
      "amount": "string",
      "balanceAfter": "string",
      "balanceBefore": "string",
      "completedAt": "string",
      "createdAt": "string",
      "description": "string",
      "externalTransactionId": "string",
      "failedAt": "string",
      "failureReason": "string",
      "id": "string",
      "initiatedBy": "string",
      "metadata": "string",
      "notes": "string",
      "orderId": "string",
      "parentTransactionId": "string",
      "paymentMethod": 1,
      "processedAt": "string",
      "processedBy": "string",
      "referenceId": "string",
      "referenceType": 1,
      "status": 1,
      "transactionCode": "string",
      "transactionType": 1,
      "updatedAt": "string",
      "userId": "string",
```


400 Validation Error (Bad Request)

Example Value | Model


```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```


401 Unauthorized

Example Value | Model


```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```


403 Forbidden (Insufficient permissions)

Example Value | Model


```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```


500 Internal Server Error

Example Value | Model


```
{}
```


GET `/wallets/transactions/code/{code}` Get transaction details by Code

View details of a specific wallet transaction using its unique code (e.g., WT-12345).

Parameters Try it out

Name	Description
code * required `string` *(path)*	Transaction Code code

Responses Response content type: application/json

Code	Description
200	Transaction details **Example Value** | Model


```
{
  "amount": "string",
  "balanceAfter": "string",
  "balanceBefore": "string",
  "completedAt": "string",
  "createdAt": "string",
  "description": "string",
  "externalTransactionId": "string",
  "failedAt": "string",
  "failureReason": "string",
  "id": "string",
  "initiatedBy": "string",
  "metadata": "string",
  "notes": "string",
  "orderId": "string",
  "parentTransactionId": "string",
  "paymentMethod": 1,
  "processedAt": "string",
  "processedBy": "string",
  "referenceId": "string",
  "referenceType": 1,
  "status": 1,
  "transactionCode": "string",
  "transactionType": 1,
  "updatedAt": "string",
  "userId": "string",
  "walletId": "string"
}
```


Code	Description
400	Validation Error (Bad Request) **Example Value** | Model


```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```


Code	Description
401	Unauthorized **Example Value** | Model


```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```


Code	Description
404	Transaction not found **Example Value** | Model

Code	Description

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

500 Internal Server Error

Example Value | Model

```
{}
```

GET /wallets/transactions/{id} Get transaction details by ID

View details of a specific wallet transaction using its UUID. The service layer verifies if the requesting user has permission to view this transaction.

Parameters

Try it out

Name	Description
id * required `string` *(path)*	Transaction UUID id

Responses

Response content type: application/json

Code	Description
200	Transaction details

Example Value | Model

```
{
  "amount": "string",
  "balanceAfter": "string",
  "balanceBefore": "string",
  "completedAt": "string",
  "createdAt": "string",
  "description": "string",
  "externalTransactionId": "string",
  "failedAt": "string",
  "failureReason": "string",
  "id": "string",
  "initiatedBy": "string",
  "metadata": "string",
  "notes": "string",
  "orderId": "string",
  "parentTransactionId": "string",
  "paymentMethod": 1,
  "processedAt": "string",
  "processedBy": "string",
  "referenceId": "string",
  "referenceType": 1,
  "status": 1,
  "transactionCode": "string",
  "transactionType": 1,
  "updatedAt": "string",
  "userId": "string",
  "walletId": "string"
}
```

401 Unauthorized

Code	Description

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

404 Transaction not found

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

500 Internal Server Error

Example Value | Model

```
{}
```

Withdrawals

GET `/me/withdrawals` Get my withdrawal requests

Retrieve the paginated withdrawal history for the currently logged-in user.

Parameters Try it out

Name	Description
page `integer` *(query)*	page
pageSize `integer` *(query)*	pageSize
status `integer($int32)` *(query)*	*Available values* : 1, 2, 3, 4, 5, 6, 7 --

Responses Response content type application/json

Code	Description

200 List of user's withdrawal requests

Example Value | Model

```
{
  "items": [
    {
```

Code	Description


```
      "accountName": "string",
      "amount": "string",
      "bankCode": "string",
      "bankName": "string",
      "createdAt": "string",
      "feeAmount": "string",
      "id": "string",
      "maskedAccountNumber": "string",
      "requestCode": "string",
      "status": 1,
      "userId": "string"
    }
  ],
  "totalCount": 0,
  "totalPages": 0
}
```


400 Validation Error (Bad Request)

Example Value | Model


```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```


401 Unauthorized

Example Value | Model


```
{}
```


500 Internal Server Error

Example Value | Model


```
{}
```


POST /me/withdrawals Create a new withdrawal request

Customer creates a request to withdraw funds from their wallet to a bank account. The requested amount is temporarily deducted immediately.
Use the API https://api.vietqr.io/v2/banks to fetch bank codes and names for the customer to select.
Provide a manual input field for the bank name in case the API fails or the bank is not listed.
If the customer enters the bank name manually, the bank code is not required.

Parameters Try it out

Name	Description
request * required `object` *(body)*	Withdrawal request details **Example Value** | Model


```
{
  "accountName": "string",
  "accountNumber": "string",
  "amount": "string",
  "bankCode": "string",
  "bankName": "string",
  "notes": "string"
}
```

Name	Description

Parameter content type

application/json

Responses Response content type application/json

Code	Description
200	Successfully created

Example Value | Model

```
{
  "id": "string",
  "message": "string"
}
```

400	Validation Error (Bad Request)

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

401	Unauthorized

Example Value | Model

```
{}
```

500	Internal Server Error

Example Value | Model

```
{}
```

PATCH `/me/withdrawals/{id}/cancel` Cancel my withdrawal request

User cancels their own withdrawal request before it is processed by an Admin (PENDING status). Funds are refunded back to the wallet.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Withdrawal request UUID id
request * required `object` *(body)*	Cancellation reason **Example Value** | Model

Name	Description

```
{
  "cancellationReason": "string"
}
```

Parameter content type

application/json

Responses Response content type application/json

Code	Description
200	{"message": "Đã hủy yêu cầu rút tiền thành công và hoàn tiền vào ví."}

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

400	Validation Error or Invalid ID

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

401	Unauthorized

Example Value | Model

```
{}
```

500	Internal Server Error

Example Value | Model

```
{}
```

GET /withdrawals Get all withdrawal requests (Admin)

Intended for administrators and accountants to view and filter the withdrawal requests of all users across the system.

Parameters Try it out

Name	Description
page integer *(query)*	page

Name	Description
pageSize **integer** *(query)*	pageSize
status **integer($int32)** *(query)*	*Available values* : 1, 2, 3, 4, 5, 6, 7 --
userId **string** *(query)*	userId

Responses Response content type: application/json

Code	Description
200	List of system withdrawal requests

Example Value | Model


```
{
  "items": [
    {
      "accountName": "string",
      "amount": "string",
      "bankCode": "string",
      "bankName": "string",
      "createdAt": "string",
      "feeAmount": "string",
      "id": "string",
      "maskedAccountNumber": "string",
      "requestCode": "string",
      "status": 1,
      "userId": "string"
    }
  ],
  "totalCount": 0,
  "totalPages": 0
}
```


400	Validation Error (Bad Request)

Example Value | Model


```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```


401	Unauthorized

Example Value | Model


```
{}
```


500	Internal Server Error

Example Value | Model


```
{}
```

GET `/withdrawals/{id}` Get withdrawal request details

Retrieve full details of a withdrawal request, including the raw bank account number and the processing history.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Withdrawal request UUID id

Responses Response content type: application/json

Code	Description
200	Detailed withdrawal information **Example Value** | Model


```
{
  "accountName": "string",
  "amount": "string",
  "approvalNotes": "string",
  "bankCode": "string",
  "bankName": "string",
  "bankTransactionId": "string",
  "cancellationReason": "string",
  "completedAt": "string",
  "createdAt": "string",
  "feeAmount": "string",
  "id": "string",
  "internalNotes": "string",
  "maskedAccountNumber": "string",
  "notes": "string",
  "processedById": "string",
  "processedByName": "string",
  "rawAccountNumber": "string",
  "receiptImageUrl": "string",
  "rejectionReason": "string",
  "requestCode": "string",
  "status": 1,
  "transactionId": "string",
  "updatedAt": "string",
  "userId": "string"
}
```


Code	Description
400	Invalid UUID format **Example Value** | Model


```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```


Code	Description
401	Unauthorized **Example Value** | Model


```
{}
```


Code	Description
404	Withdrawal request not found **Example Value** | Model

Code	Description

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

500 Internal Server Error

Example Value | Model

```
{}
```

PATCH `/withdrawals/{id}/approve` Approve withdrawal request (Admin)

Confirm that the request is valid and prepare for the fund transfer. The status changes to APPROVED.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Withdrawal request UUID id
request * required `object` *(body)*	Approval notes **Example Value** | Model `{ "approvalNotes": "string" }` **Parameter content type** application/json

Responses Response content type application/json

Code	Description
200	{"message": "Đã duyệt yêu cầu rút tiền"} **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`
400	Validation Error or Invalid ID **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`

Code	Description
401	Unauthorized **Example Value** | Model `{}`
500	Internal Server Error **Example Value** | Model `{}`

PATCH `/withdrawals/{id}/cancel` Cancel withdrawal request (Admin)

Cancel a withdrawal request at any stage (Pending, Approved, Processing) UNLESS it is already completed or cancelled. The system automatically refunds the amount to the user's wallet.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Withdrawal request UUID id
request * required `object` *(body)*	Cancellation reason from Admin **Example Value** | Model `{ "cancellationReason": "string" }` **Parameter content type** application/json

Responses Response content type application/json

Code	Description
200	{"message": "Admin đã hủy lệnh và hoàn tiền thành công."} **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`
400	Validation Error or Invalid ID **Example Value** | Model

Code	Description

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

401 Unauthorized

Example Value | Model

```
{}
```

500 Internal Server Error

Example Value | Model

```
{}
```

PATCH /withdrawals/{id}/complete Complete withdrawal request (Admin)

Confirm that the bank transfer was successful. A receipt image (receiptFile) must be uploaded as proof.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Withdrawal request UUID id
receiptFile * required `file` *(formData)*	Transfer receipt image (Bill) Choose File No file chosen
bankTransactionId * required `string` *(formData)*	Bank transaction ID bankTransactionId

Responses Response content type application/json

Code	Description

200 {"message": "Đã hoàn tất yêu cầu rút tiền và cập nhật bằng chứng chuyển khoản."}

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

400 Missing required file or transaction ID

Example Value | Model

Code	Description

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

401 Unauthorized

Example Value | Model

```
{}
```

500 Internal Server Error

Example Value | Model

```
{}
```

PATCH /withdrawals/{id}/reject Reject withdrawal request (Admin)

Reject a PENDING withdrawal request. The system automatically refunds the deducted amount back to the user's wallet.

Parameters

Try it out

Name	Description
id * required `string` *(path)*	Withdrawal request UUID id
request * required `object` *(body)*	Rejection reason **Example Value** | Model `{ "rejectionReason": "string" }` **Parameter content type** application/json

Responses

Response content type: application/json

Code	Description
200	{"message": "Đã từ chối yêu cầu rút tiền và hoàn tiền vào ví."} **Example Value** | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

Code	Description
400	Validation Error or Invalid ID

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

Code	Description
401	Unauthorized

Example Value | Model

```
{}
```

Code	Description
500	Internal Server Error

Example Value | Model

```
{}
```

Membership Tiers

GET `/membership-tiers` Get All Membership Tiers

Retrieve a list of all available membership tiers

Parameters Try it out

No parameters

Responses Response content type application/json

Code	Description
200	List of tiers

Example Value | Model

```
[
  {
    "amountPerPoint": "string",
    "discountRate": 0,
    "id": "string",
    "minSpendRequired": "string",
    "name": "string",
    "valuePerPoint": "string"
  }
]
```

POST `/membership-tiers` Create Membership Tier

Define a new membership tier with spending requirements and benefits.

Parameters Try it out

Name	Description
request * required `object` *(body)*	Tier details **Example Value** | Model `{ "amountPerPoint": "string", "discountRate": 0, "minSpendRequired": "string", "name": "string", "valuePerPoint": "string" }` **Parameter content type** application/json

Responses Response content type application/json

Code	Description
201	Success **Example Value** | Model `{ "additionalProp1": {} }`
400	Validation error **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`

DELETE `/membership-tiers/{id}` Delete Membership Tier

Remove a membership tier from the system.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Tier UUID id

Responses Response content type: application/json

Code	Description
200	Success

Example Value | Model

```
{
  "additionalProp1": {}
}
```

Code	Description
400	Invalid ID format

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

PATCH /membership-tiers/{id} Update Membership Tier

Update benefits or requirements for an existing tier.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Tier UUID id
request * required `object` *(body)*	Updated details

Example Value | Model

```
{
  "amountPerPoint": "string",
  "discountRate": 0,
  "minSpendRequired": "string",
  "name": "string",
  "valuePerPoint": "string"
}
```

Parameter content type: application/json

Responses Response content type: application/json

Code	Description
200	Success

Example Value | Model

Code	Description
	<pre>{ "additionalProp1": {} }</pre>
400	Invalid ID or validation error **Example Value** | Model <pre>{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }</pre>

Payments

GET `/orders/vnpay/return` Handle VNPay Return URL

Endpoint for VNPay to redirect the browser after payment. Verifies the signature via gRPC and redirects to the Frontend UI.

Parameters Try it out

Name	Description
vnp_Amount **string** *(query)*	Transaction Amount vnp_Amount
vnp_BankCode **string** *(query)*	Bank Code vnp_BankCode
vnp_OrderInfo **string** *(query)*	Order Information vnp_OrderInfo
vnp_ResponseCode **string** *(query)*	VNPAY Response Code vnp_ResponseCode
vnp_TxnRef **string** *(query)*	Transaction Reference vnp_TxnRef
vnp_SecureHash **string** *(query)*	Security Hash vnp_SecureHash
redirectTo **string** *(query)*	Frontend URL path to redirect to after processing redirectTo

Responses Response content type text/html

Code	Description
302	Redirects to the Frontend application with payment status
400	Bad Request or Invalid Signature

GET `/vnpay/ipn` Handle VNPay IPN Webhook

Receive Instant Payment Notification (IPN) callbacks from VNPay. Acts as a dispatcher to classify the transaction type (e.g., Customer Orders vs. Supplier Purchase Orders) and securely route the payload to the appropriate underlying Microservice via gRPC.

Parameters Try it out

No parameters

Responses Response content type application/json

Code	Description
200	Always returns HTTP 200 with VNPay standard RspCode and Message

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

Permissions

GET `/permissions` Get All Permissions (Grouped)

Retrieve a list of all system permissions, grouped by their module or category.

Parameters Try it out

No parameters

Responses Response content type application/json

Code	Description
200	List of permissions grouped by module

Example Value | Model

```
{
  "additionalProp1": {}
```

Code	Description

	}
	{
	"additionalProp1": "string",
	"additionalProp2": "string",
	"additionalProp3": "string"
	}

500	Internal server error **Example Value** | Model

PATCH `/permissions/{id}` Update Permission

Update details (e.g., description, name) of a specific permission by its ID.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Permission UUID id

request * required
`object`
(body)
	Updated details
	Example Value | Model
	{
	"description": "string",
	"name": "string"
	}
	Parameter content type
	application/json

Responses Response content type application/json

Code	Description

200	Success
	Example Value | Model
	{
	"additionalProp1": {}
	}

400	Validation error or Invalid ID
	Example Value | Model
	{
	"additionalProp1": "string",
	"additionalProp2": "string",
	"additionalProp3": "string"
	}

Products

GET /products Get All Products

Retrieve a list of products with pagination and keyword search support.

Parameters Try it out

Name	Description
categoryId **string** *(query)*	categoryId
keyword **string** *(query)*	keyword
page **integer** *(query)*	page
pageSize **integer** *(query)*	pageSize

Responses Response content type application/json

Code	Description
200	List of products **Example Value** | Model `{ "additionalProp1": {} }`
500	Internal server error **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`

POST /products Create New Product

Add a new product to the catalog.

Parameters Try it out

Name	Description
request * required object *(body)*	Product details **Example Value** | Model

```
{
  "categoryId": "string",
  "description": "string",
  "imaageUrl": "string",
  "name": "string",
  "variants": [
    {
      "attributes": "string",
      "basePrice": 0,
      "cost": 0,
      "isActive": true,
      "name": "string",
      "sku": "string"
    }
  ]
}
```

Parameter content type: application/json

Responses — Response content type: application/json

Code	Description
200	Success **Example Value** | Model

```
{
  "additionalProp1": {}
}
```

400	Validation error **Example Value** | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

GET /products/variants Get products by skus

Retrieve a list of product variants with simple info

Parameters — Try it out

Name	Description
skus array<string> *(query)*	

Responses Response content type: application/json

Code	Description
200	List of products

Example Value | Model

```
[
  {
    "attributes": "string",
    "basePrice": 0,
    "imageUrl": "string",
    "productId": "string",
    "productName": "string",
    "sku": "string",
    "variantId": "string"
  }
]
```

Code	Description
500	Internal server error

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

GET /products/{id} Get Product Details

Retrieve full details of a specific product by its ID.

Parameters Try it out

Name	Description
id * required string *(path)*	Product UUID id

Responses Response content type: application/json

Code	Description
200	Product details

Example Value | Model

```
{
  "additionalProp1": {}
}
```

Code	Description
400	Invalid ID format

Example Value | Model

Code	Description

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

404 Product not found

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

DELETE /products/{id} Delete Product

Permanently remove a product from the catalog.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Product UUID id

Responses Response content type application/json

Code	Description

200 Success

Example Value | Model

```
{
  "additionalProp1": {}
}
```

400 Invalid ID format

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

PATCH /products/{id} Update Product

Update details of an existing product.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Product UUID id
request * required `object` *(body)*	Updated details **Example Value** | Model

```
{
  "categoryId": "string",
  "description": "string",
  "imageUrl": "string",
  "isActive": true,
  "name": "string",
  "variants": [
    {
      "attributes": "string",
      "basePrice": 0,
      "cost": 0,
      "isActive": true,
      "name": "string",
      "sku": "string"
    }
  ]
}
```

Parameter content type

application/json

Responses — **Response content type**: application/json

Code	Description
200	Success **Example Value** | Model

```
{
  "additionalProp1": {}
}
```

400	Validation error or Invalid ID **Example Value** | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

PUT `/products/{id}/images` Upload Product Image

Upload an image for a specific product. Supports JPG, PNG, and WebP formats. Max file size is 10MB.

Parameters — Try it out

Name	Description
id * required	Product UUID

Name	Description
string *(path)*	id
image * required file *(formData)*	Image file to upload Choose File No file chosen
file_name string *(formData)*	Custom file name (Optional) file_name

Responses Response content type: application/json

Code	Description
200	Returns the uploaded image URL **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`
400	Invalid ID or unsupported image format **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`
413	Request entity too large **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`
500	Internal server error **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`

Recipes

GET `/recipes` Get All Recipes

Retrieve a list of recipes with optional filtering.

Parameters Try it out

Name	Description
variantIds `array<string>` *(query)*	

Responses Response content type: application/json

Code	Description
200	List of recipes **Example Value** | Model `{ "additionalProp1": {} }`
500	Internal server error **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`

PUT /variants/{id}/recipes Update Variant Recipe

Define or update the list of ingredients (recipe) for a specific product variant.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Variant UUID id
request * required `array<object>` *(body)*	List of ingredients and quantities **Example Value** | Model `[ { "ingredientId": "string", "quantity": 0 } ]` **Parameter content type** application/json

Responses Response content type: application/json

Code	Description
200	Success **Example Value** | Model `{ "additionalProp1": {} }`
400	Validation error or Invalid ID **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`
401	Unauthorized **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`

Roles

GET /roles Get All Roles

Retrieve a list of all defined roles in the system.

Parameters Try it out

No parameters

Responses Response content type: application/json

Code	Description
200	List of roles **Example Value** | Model `{ "additionalProp1": {} }`
500	Internal server error **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`

POST /roles Create New Role

Define a new role with a specific name and description.

Parameters Try it out

Name	Description
request * required `object` *(body)*	Role details **Example Value** | Model `{ "description": "string", "name": "string", "slug": "string" }` **Parameter content type** application/json

Responses Response content type: application/json

Code	Description
200	Success

Example Value | Model

```
{
  "additionalProp1": {}
}
```

400	Validation error

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

PATCH /roles/{id} Update Role

Update details (name, description) of an existing role.

Parameters

Try it out

Name	Description
id * required `string` *(path)*	Role UUID id
request * required `object` *(body)*	Updated details

Example Value | Model

```
{
  "description": "string",
  "name": "string"
}
```

Parameter content type

application/json

Responses

Response content type: application/json

Code	Description
200	Success

Example Value | Model

```
{
  "additionalProp1": {}
}
```

400	Validation error or Invalid ID

Example Value | Model

Code	Description

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

GET /roles/{id}/permissions Get Role Permissions

Retrieve all permissions assigned to a specific role.

Parameters

Try it out

Name	Description
id * required `string` *(path)*	Role UUID id

Responses

Response content type: application/json

Code	Description
200	List of permissions **Example Value** | Model

```
{
  "additionalProp1": {}
}
```

Code	Description
400	Invalid ID format **Example Value** | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

PUT /roles/{id}/permissions Assign Permissions to Role

Update the list of permissions assigned to a specific role.

Parameters

Try it out

Name	Description
id * required `string` *(path)*	Role UUID id
request * required	List of Permission IDs

Name	Description
object *(body)*	**Example Value** | Model

```
{
  "permissionsToGrant": [
    "string"
  ],
  "permissionsToRevoke": [
    "string"
  ]
}
```

Parameter content type

application/json

Responses — **Response content type** application/json

Code	Description
200	Success

Example Value | Model

```
{
  "additionalProp1": {}
}
```

400	Validation error or Invalid ID

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

Shifts: Applications

PATCH `/shift-applications/{id}/review` Review shift application

Manager reviews an application and updates its status (Approved/Rejected). The application ID is provided in the path.

Parameters — Try it out

Name	Description
id * required string *(path)*	Application ID id
body * required object *(body)*	Review decision and status

Example Value | Model

```
{
  "isApproved": true,
  "reviewNote": "string"
}
```

Name	Description

Parameter content type

application/json

Responses Response content type application/json

Code	Description
200	{"message": "Đã cập nhật trạng thái đơn đăng ký"}

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

400 Validation Error (Bad Request)

Example Value | Model

```
{}
```

401 Unauthorized

Example Value | Model

```
{}
```

500 Internal Server Error

Example Value | Model

```
{}
```

GET /shifts/{id}/applications Get applications by shift ID

Manager views the list of applicants for a specific shift, along with their Smart Scores, to make approval decisions.

Parameters Try it out

Name	Description
id * required string (path)	Shift ID id

Responses

Response content type: application/json

Code	Description
200	List of shift applications

Example Value | Model

```
[
  {
    "appliedAt": "string",
    "avatarUrl": "string",
    "email": "string",
    "hourlyWage": 0,
    "id": "string",
    "note": "string",
    "shiftId": "string",
    "smartScore": 0,
    "status": 0,
    "userId": "string",
    "username": "string",
    "weeklyHoursWorked": 0
  }
]
```

Code	Description
400	Invalid Shift ID (Bad Request)

Example Value | Model

```
{}
```

Code	Description
401	Unauthorized

Example Value | Model

```
{}
```

Code	Description
500	Internal Server Error

Example Value | Model

```
{}
```

POST /shifts/{id}/applications Apply for a shift

Employee applies for a specific shift. Creates a new ShiftApplication record. UserId is extracted from the authentication token.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Shift ID id
body * required `object` *(body)*	Application notes and details

Example Value | Model

```
{
  "note": "string"
```

Name	Description

```
}
```

Parameter content type

application/json

Responses Response content type: application/json

Code	Description
201	{"message": "Gửi đơn đăng ký nhận ca thành công"}

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

Code	Description
400	Validation Error (Bad Request)

Example Value | Model

```
{}
```

Code	Description
401	Unauthorized

Example Value | Model

```
{}
```

Code	Description
500	Internal Server Error

Example Value | Model

```
{}
```

Shifts: Rule

GET `/shift-rules` Get shift rule settings

Retrieve shift rule configurations (Global and Store-specific) to display on the settings page.

Parameters Try it out

Name	Description
storeId `string` *(query)*	Store ID (Optional, to filter by a specific store) storeId

Responses Response content type: application/json

Code	Description
200	Configuration data **Example Value** | Model


```
{
  "global": {
    "allowShiftSwap": true,
    "allowShuttle": true,
    "dailyOtThresholdHours": 0,
    "gracePeriodMinutes": 0,
    "id": "string",
    "maxHoursPerWeek": 0,
    "minHoursBetweenShifts": 0,
    "storeId": "string",
    "updatedAt": "string",
    "weeklyOtThresholdHours": 0
  },
  "stores": [
    {
      "allowShiftSwap": true,
      "allowShuttle": true,
      "dailyOtThresholdHours": 0,
      "gracePeriodMinutes": 0,
      "id": "string",
      "maxHoursPerWeek": 0,
      "minHoursBetweenShifts": 0,
      "storeId": "string",
      "updatedAt": "string",
      "weeklyOtThresholdHours": 0
    }
  ]
}
```


400	Validation Error (Bad Request) **Example Value** | Model


```
{}
```


401	Unauthorized **Example Value** | Model


```
{}
```


500	Internal Server Error **Example Value** | Model


```
{}
```


PUT `/shift-rules` Save shift rule settings

Create or update shift rules and constraints (e.g., maximum working hours, required break times).

Parameters Try it out

Name	Description
payload * required `object` *(body)*	Rule configuration data to save **Example Value** | Model `{ "allowShiftSwap": true, "allowShuttle": true, "dailyOtThresholdHours": 0, "gracePeriodMinutes": 0, "maxHoursPerWeek": 0, "minHoursBetweenShifts": 0, "storeId": "string", "weeklyOtThresholdHours": 0 }` **Parameter content type** application/json

Responses Response content type application/json

Code	Description
200	Successfully saved rule settings **Example Value** | Model `{ "additionalProp1": {} }`
400	Validation Error (Bad Request) **Example Value** | Model `{}`
401	Unauthorized **Example Value** | Model `{}`
500	Internal Server Error **Example Value** | Model `{}`

Shifts: Template

GET `/shift-templates` Get all shift templates

Retrieve a complete list of shift templates (e.g., Morning, Afternoon, Night) for a specific store.

Parameters Try it out

Name	Description
isActive **boolean** *(query)*	--
keyword **string** *(query)*	keyword
storeId **string** *(query)*	storeId

Responses Response content type: application/json

Code	Description
200	List of shift templates **Example Value** | Model


```
[
  {
    "breakDurationMinutes": 0,
    "code": "string",
    "createdAt": "string",
    "endTime": "string",
    "id": "string",
    "isActive": true,
    "name": "string",
    "startTime": "string",
    "storeId": "string"
  }
]
```


400	Validation Error (Bad Request) **Example Value** | Model


```
{}
```


401	Unauthorized **Example Value** | Model


```
{}
```


500	Internal Server Error **Example Value** | Model

Code	Description
	{}

POST `/shift-templates` Create a new shift template

Define a new standard shift timeframe (including code, name, and start/end times).

Parameters Try it out

Name	Description

body * required
object
(body)
	Shift template data
	Example Value | Model
	{
	"breakDurationMinutes": 0,
	"code": "string",
	"endTime": "string",
	"name": "string",
	"startTime": "string",
	"storeId": "string"
	}
	Parameter content type
	application/json

Responses Response content type application/json

Code	Description

201	Successfully created template
	Example Value | Model
	{
	"additionalProp1": {}
	}

400	Validation Error (Bad Request) **Example Value** | Model {}
401	Unauthorized **Example Value** | Model {}
500	Internal Server Error

Code	Description

Example Value | Model

```
{}
```

GET /shift-templates/{id} Get shift template details

Retrieve the detailed configuration of a specific shift template by its ID.

Parameters

Try it out

Name	Description
id * required `string` *(path)*	Template ID id

Responses

Response content type: application/json

Code	Description
200	Template details

Example Value | Model

```
{
  "breakDurationMinutes": 0,
  "code": "string",
  "createdAt": "string",
  "endTime": "string",
  "id": "string",
  "isActive": true,
  "name": "string",
  "startTime": "string",
  "storeId": "string"
}
```

400	Invalid ID (Bad Request)

Example Value | Model

```
{}
```

401	Unauthorized

Example Value | Model

```
{}
```

404	Template Not Found

Example Value | Model

```
{}
```

Code	Description
500	Internal Server Error **Example Value** | Model `{}`

DELETE `/shift-templates/{id}` Delete a shift template

Completely remove a shift template from the system.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Template ID id

Responses Response content type: application/json

Code	Description
200	Successfully deleted template **Example Value** | Model `{ "additionalProp1": {} }`
400	Invalid ID (Bad Request) **Example Value** | Model `{}`
401	Unauthorized **Example Value** | Model `{}`
404	Template Not Found **Example Value** | Model `{}`

Code	Description
500	Internal Server Error **Example Value** | Model `{}`

PATCH `/shift-templates/{id}` Update a shift template

Modify the timeframe configuration or the name of an existing shift template.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Template ID id
body * required `object` *(body)*	Update data **Example Value** | Model `{ "breakDurationMinutes": 0, "code": "string", "endTime": "string", "isActive": true, "name": "string", "startTime": "string" }` **Parameter content type** application/json

Responses Response content type application/json

Code	Description
200	Successfully updated template **Example Value** | Model `{ "additionalProp1": {} }`
400	Validation Error or Invalid ID **Example Value** | Model `{}`
401	Unauthorized

Code	Description
	Example Value | Model `{}`
404	Template Not Found **Example Value** | Model `{}`
500	Internal Server Error **Example Value** | Model `{}`

Shifts

GET `/shifts` Get all shifts

Retrieve a list of shifts with applied filters (Used for Calendar/List view).

Parameters Try it out

Name	Description
fromDate `string` *(query)*	fromDate
status `integer` *(query)*	ShiftStatus enum status
storeId `string` *(query)*	storeId
toDate `string` *(query)*	toDate

Responses Response content type application/json

Code	Description
200	List of shifts **Example Value** | Model

Code	Description


```
[
  {
    "assignedStaffCount": 0,
    "assignments": [
      {
        "avatarUrl": "string",
        "email": "string",
        "firstName": "string",
        "hourlyWage": 0,
        "id": "string",
        "lastName": "string",
        "shiftId": "string",
        "status": 0,
        "userId": "string"
      }
    ],
    "breakDurationMinutes": 0,
    "endTime": "string",
    "id": "string",
    "note": "string",
    "requiredStaffCount": 0,
    "shiftDate": "string",
    "shiftTemplateId": "string",
    "startTime": "string",
    "status": 0,
    "storeId": "string"
  }
]
```


400 Validation Error (Bad Request)

Example Value | Model


```
{}
```


401 Unauthorized

Example Value | Model


```
{}
```


500 Internal Server Error

Example Value | Model


```
{}
```


POST `/shifts` Create a new shift

Create a new working shift for the store.

Parameters Try it out

Name	Description
body * required `object` *(body)*	Shift information **Example Value** | Model


```
{
  "breakDurationMinutes": 0,
  "endTime": "string",
  "note": "string",
  "requiredStaffCount": 0,
```

Name	Description


```
  "shiftDate": "string",
  "shiftTemplateId": "string",
  "startTime": "string",
  "storeId": "string"
}
```


Parameter content type

application/json

Responses Response content type application/json

Code	Description
200	Shift created successfully

Example Value | Model


```
{
  "additionalProp1": {}
}
```


400	Validation Error (Bad Request)

Example Value | Model


```
{}
```


401	Unauthorized

Example Value | Model


```
{}
```


500	Internal Server Error

Example Value | Model


```
{}
```


GET /shifts/{id} Get shift details

Retrieve detailed information about a specific shift and its assigned staff.

Parameters Try it out

Name	Description
id * required string *(path)*	Shift ID id

Responses Response content type: application/json

Code	Description
200	Shift details

Example Value | Model


```
{
  "assignedStaffCount": 0,
  "assignments": [
    {
      "avatarUrl": "string",
      "email": "string",
      "firstName": "string",
      "hourlyWage": 0,
      "id": "string",
      "lastName": "string",
      "shiftId": "string",
      "status": 0,
      "userId": "string"
    }
  ],
  "breakDurationMinutes": 0,
  "endTime": "string",
  "id": "string",
  "note": "string",
  "requiredStaffCount": 0,
  "shiftDate": "string",
  "shiftTemplateId": "string",
  "startTime": "string",
  "status": 0,
  "storeId": "string"
}
```


400 Invalid Shift ID (Bad Request)

Example Value | Model


```
{}
```


401 Unauthorized

Example Value | Model


```
{}
```


404 Shift Not Found

Example Value | Model


```
{}
```


500 Internal Server Error

Example Value | Model


```
{}
```


DELETE `/shifts/{id}` Delete a shift

Delete a specific shift (Only allowed if it is in Draft or Planning status).

Parameters Try it out

Name	Description
id * required `string` *(path)*	Shift ID id

Responses Response content type: application/json

Code	Description
200	Shift deleted successfully **Example Value** | Model `{ "additionalProp1": {} }`
400	Invalid ID or Bad Request **Example Value** | Model `{}`
401	Unauthorized **Example Value** | Model `{}`
403	Forbidden (Cannot delete published shift) **Example Value** | Model `{}`
500	Internal Server Error **Example Value** | Model `{}`

PATCH `/shifts/{id}` Update a shift

Update shift timings or the required number of staff.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Shift ID id
body * required `object` *(body)*	Update data **Example Value** | Model `{ "breakDurationMinutes": 0, "endTime": "string", "note": "string", "requiredStaffCount": 0, "shiftDate": "string", "shiftTemplateId": "string", "startTime": "string", "status": 0 }` **Parameter content type** application/json

Responses Response content type application/json

Code	Description
200	Shift updated successfully **Example Value** | Model `{ "additionalProp1": {} }`
400	Validation Error or Invalid ID **Example Value** | Model `{}`
401	Unauthorized **Example Value** | Model `{}`
404	Shift Not Found **Example Value** | Model `{}`

Code	Description
500	Internal Server Error **Example Value** | Model `{}`

PUT `/shifts/{id}/publish` Publish a single shift

Change the shift status to Published, making it visible to employees on the schedule.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Shift ID id

Responses Response content type: application/json

Code	Description
200	Shift published successfully **Example Value** | Model `{ "additionalProp1": {} }`
400	Invalid ID or Bad Request **Example Value** | Model `{}`
401	Unauthorized **Example Value** | Model `{}`

Code	Description
500	Internal Server Error **Example Value** | Model `{}`

Shifts: Assignment

PUT `/shifts/auto-fill` Auto-fill shift assignments

System automatically calculates and assigns suitable staff to empty (Draft) shifts based on availability and scheduling rules.

Parameters Try it out

Name	Description
body * required `object` *(body)*	Time range for auto-filling shifts **Example Value** | Model `{ "endDate": "string", "startDate": "string" }` **Parameter content type** application/json

Responses Response content type application/json

Code	Description
200	Auto-fill result summary **Example Value** | Model `{ "filledCount": 0, "success": true, "totalSlots": 0, "unfilledShiftIds": [ "string" ] }`
400	Validation Error (Bad Request) **Example Value** | Model `{}`
401	Unauthorized **Example Value** | Model

Code	Description
	{}
500	Internal Server Error

Example Value | Model

```
{}
```

PUT /shifts/{id}/assign Update staff assignments

Modify the list of employees assigned to a specific shift.

Parameters

Try it out

Name	Description
id * required `string` *(path)*	Shift ID id
body * required `array<string>` *(body)*	List of User IDs to assign

Example Value | Model

```
[
  "string"
]
```

Parameter content type

application/json

Responses

Response content type application/json

Code	Description
200	Assignment update result

Example Value | Model

```
{
  "success": true,
  "warnings": [
    {
      "code": "string",
      "message": "string",
      "severity": "string"
    }
  ]
}
```

400	Validation Error (Bad Request)

Example Value | Model

```
{}
```

Code	Description
401	Unauthorized **Example Value** | Model {}
500	Internal Server Error **Example Value** | Model {}

GET `/stores/{id}/shifts/{shiftId}/candidates` Get available staff candidates

Check schedule conflicts and shift rules to suggest suitable staff members for a specific shift.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Store ID id
shiftId * required `string` *(path)*	Shift ID shiftId

Responses Response content type application/json

Code	Description
200	List of available staff **Example Value** | Model


```
[
  {
    "avatarUrl": "string",
    "currentHourlyWage": 0,
    "firstName": "string",
    "id": "string",
    "isAssigned": true,
    "isAvailable": true,
    "isConflict": true,
    "lastName": "string",
    "note": "string",
    "validation": {
      "isOverLimit": true,
      "isRestTimeInvalid": true,
      "isShuttleInvalid": true,
      "restHours": 0,
      "weeklyHours": 0
    }
```

Code	Description
	<pre> }]</pre>
400	Invalid ID (Bad Request) **Example Value** | Model <pre>{}</pre>
401	Unauthorized **Example Value** | Model <pre>{}</pre>
500	Internal Server Error **Example Value** | Model <pre>{}</pre>

Shifts: Bulk action

DELETE `/shifts/bulk-delete` Bulk delete shifts

Delete multiple shifts simultaneously (Only applicable for shifts currently in Draft status).

Parameters Try it out

Name	Description
body * required `array<string>` *(body)*	List of shift IDs to delete **Example Value** | Model <pre>["string"]</pre> **Parameter content type** application/json

Responses Response content type application/json

Code	Description
200	Successfully deleted shifts **Example Value** | Model

Code	Description

```
{
  "additionalProp1": {}
}
```

400 Validation Error (Bad Request)

Example Value | Model

```
{}
```

401 Unauthorized

Example Value | Model

```
{}
```

500 Internal Server Error

Example Value | Model

```
{}
```

POST `/shifts/bulk-manual` Bulk create manual shifts

Create multiple shifts simultaneously based on selected time frames and days of the week.

Parameters Try it out

Name	Description

body * required
`object`
(body)

Bulk creation data

Example Value | Model

```
{
  "breakDurationMinutes": 0,
  "daysOfWeek": [
    0
  ],
  "endDate": "string",
  "endTime": "string",
  "note": "string",
  "requiredStaffCount": 0,
  "startDate": "string",
  "startTime": "string",
  "storeId": "string"
}
```

Parameter content type

application/json

Responses Response content type application/json

Code	Description
201	Successfully created shifts **Example Value** | Model `{ "additionalProp1": {} }`
400	Validation Error (Bad Request) **Example Value** | Model `{}`
401	Unauthorized **Example Value** | Model `{}`
500	Internal Server Error **Example Value** | Model `{}`

PUT /shifts/bulk-open Bulk open shifts to Shift Pool

Change the status of multiple shifts from Draft to Open, allowing employees to apply for them in the Shift Pool. StoreId is automatically extracted from the Manager's Token.

Parameters Try it out

Name	Description
body * required `array<string>` *(body)*	List of shift IDs to open **Example Value** | Model `[ "string" ]` **Parameter content type** application/json

Responses Response content type application/json

Code	Description
200	Returns the count of successfully opened shifts **Example Value** | Model `{ "additionalProp1": {} }`
400	Validation Error (Bad Request) **Example Value** | Model `{}`
401	Unauthorized **Example Value** | Model `{}`
500	Internal Server Error **Example Value** | Model `{}`

PUT `/shifts/bulk-publish` Bulk publish shifts

Change the status of multiple shifts from Draft to Published, making them visible to employees on the schedule.

Parameters Try it out

Name	Description
body * required `array<string>` *(body)*	List of shift IDs to publish **Example Value** | Model `[ "string" ]` **Parameter content type** application/json

Responses Response content type application/json

Code	Description
200	Successfully published shifts **Example Value** | Model `{ "additionalProp1": {} }`
400	Validation Error (Bad Request) **Example Value** | Model `{}`
401	Unauthorized **Example Value** | Model `{}`
500	Internal Server Error **Example Value** | Model `{}`

POST `/shifts/bulk-template` Bulk create shifts from template

Create multiple shifts over a specified period based on existing Shift Templates.

Parameters Try it out

Name	Description
body * required `object` *(body)*	Template creation data **Example Value** | Model `{ "endDate": "string", "requiredStaffCount": 0, "startDate": "string", "storeId": "string", "templateId": "string" }` **Parameter content type** application/json

Responses Response content type application/json

Code	Description
201	Successfully created shifts from template **Example Value** | Model `{ "additionalProp1": {} }`
400	Validation Error (Bad Request) **Example Value** | Model `{}`
401	Unauthorized **Example Value** | Model `{}`
500	Internal Server Error **Example Value** | Model `{}`

Shifts: Time log

GET `/shifts/time-logs` Get time logs

Manager retrieves all time logs within the Store, applying optional filters.

Parameters Try it out

Name	Description
fromDate `string` *(query)*	Format: YYYY-MM-DD fromDate
page `integer` *(query)*	page
pageSize `integer` *(query)*	pageSize
staffId `string` *(query)*	staffId
status	*Available values* : 0, 1, 2

Name	Description
integer *(query)*	--
storeId string *(query)*	storeId
toDate string *(query)*	toDate

Responses Response content type: application/json

Code	Description
200	Paginated list of time logs

Example Value | Model


```
{
  "items": [
    {
      "checkInAt": "string",
      "checkInImageUrl": "string",
      "checkInLat": 0,
      "checkInLong": 0,
      "checkOutAt": "string",
      "checkOutImageUrl": "string",
      "checkOutLat": 0,
      "checkOutLong": 0,
      "createdAt": "string",
      "dailyOtMinutes": 0,
      "id": "string",
      "managerNote": "string",
      "regularMinutes": 0,
      "shift": {
        "endTime": "string",
        "id": "string",
        "note": "string",
        "shiftDate": "string",
        "startTime": "string"
      },
      "shiftAssignmentId": "string",
      "staff": {
        "avatarUrl": "string",
        "email": "string",
        "firstName": "string",
```


Code	Description
400	Validation Error (Bad Request)

Example Value | Model


```
{}
```


Code	Description
401	Unauthorized

Example Value | Model


```
{}
```


Code	Description
500	Internal Server Error

Example Value | Model


```
{}
```

Code	Description

PATCH `/shifts/time-logs/{id}` Review or update time log

Manager approves (Valid) or rejects (Invalid) an employee's actual worked shift.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Time log ID id
body * required `object` *(body)*	Update data **Example Value** | Model `{ "managerNote": "string", "status": 0 }` **Parameter content type** application/json

Responses Response content type application/json

Code	Description
200	Time log updated successfully **Example Value** | Model `{ "additionalProp1": {} }`
400	Validation Error (e.g., missing rejection reason) **Example Value** | Model `{}`
401	Unauthorized **Example Value** | Model `{}`
500	Internal Server Error **Example Value** | Model

Code	Description
	{}

Stores

GET `/stores` Get All Stores

Retrieve a list of stores with optional filtering (e.g., by city, district).

Parameters Try it out

Name	Description
keyword `string` *(query)*	Tìm theo tên keyword
page `integer` *(query)*	page
pageSize `integer` *(query)*	pageSize

Responses Response content type: application/json

Code	Description
200	List of stores **Example Value** | Model


```
{
  "items": [
    {
      "address": "string",
      "id": "string",
      "imageUrl": "string",
      "isOpenNow": true,
      "latitude": 0,
      "longitude": 0,
      "name": "string",
      "phone": "string"
    }
  ],
  "totalCount": 0,
  "totalPages": 0
}
```

Code	Description
500	Internal server error

Example Value | Model


```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```


GET /stores/nearby Find Nearby Stores

Find stores based on current location (Lat/Long) and radius.

Parameters

Try it out

Name	Description
limit integer *(query)*	Mặc định 10 quán limit
radiusKm number *(query)*	Mặc định 5km nếu không truyền radiusKm
userLat * required number *(query)*	userLat
userLong * required number *(query)*	userLong

Responses

Response content type: application/json

Code	Description
200	List of nearby stores

Example Value | Model


```
{
  "items": [
    {
      "address": "string",
      "id": "string",
      "imageUrl": "string",
      "isOpenNow": true,
      "latitude": 0,
      "longitude": 0,
      "name": "string",
      "phone": "string"
    }
  ],
  "totalCount": 0,
  "totalPages": 0
}
```


400	Validation error

Example Value | Model

Code	Description

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

GET /stores/{id} Get Store Details

Retrieve full details of a specific store by its ID.

Parameters

Try it out

Name	Description
id * required `string` *(path)*	Store UUID id

Responses

Response content type: application/json

Code	Description
200	Store details **Example Value** | Model

```
{
  "address": "string",
  "id": "string",
  "imageUrl": "string",
  "isOpenNow": true,
  "latitude": 0,
  "longitude": 0,
  "name": "string",
  "phone": "string"
}
```

Code	Description
400	Invalid ID format **Example Value** | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

Code	Description
404	Store not found **Example Value** | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

GET /stores/{id}/availability Check Store Availability

Check if a store is currently open or active.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Store UUID id

Responses Response content type: application/json

Code	Description
200	Availability status **Example Value** | Model `{ "additionalProp1": {} }`
400	Invalid ID format **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`

GET /stores/{id}/staffs/active Get Active Staffs At Store

Lấy danh sách staff đang trong ca làm hiện tại của store

Parameters Try it out

Name	Description
id * required `string` *(path)*	Store UUID id

Responses Response content type: application/json

Code	Description
200	Danh sách nhân viên **Example Value** | Model

Code	Description


```
[
  {
    "avatarUrl": "string",
    "email": "string",
    "firstName": "string",
    "id": "string",
    "lastName": "string"
  }
]
```


400 Invalid ID format

Example Value | Model


```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```


Store Stock

GET `/stores/stock` Get All Global Stock

Retrieve inventory levels of ingredients across all stores (Management view).

Parameters Try it out

Name	Description
categoryIds `array<string>` *(query)*	StoreIds []string `form:"storeIds"`
ingredientIds `array<string>` *(query)*	
page `integer` *(query)*	page
pageSize `integer` *(query)*	pageSize
stockStatus `integer` *(query)*	stockStatus

Responses Response content type application/json

Code	Description
200	Global inventory list

Example Value | Model

Code	Description

```
{
  "additionalProp1": {}
}
```

500 Internal server error

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

GET /stores/{id}/stock Get Store Stock

Retrieve the current inventory of ingredients for a specific store.

Parameters

Try it out

Name	Description
id * required `string` *(path)*	Store UUID id
categoryIds `array<string>` *(query)*	StoreIds []string `form:"storeIds"`
ingredientIds `array<string>` *(query)*	
page `integer` *(query)*	page
pageSize `integer` *(query)*	pageSize
stockStatus `integer` *(query)*	stockStatus

Responses

Response content type application/json

Code	Description

200 Store inventory list

Example Value | Model

```
{
  "additionalProp1": {}
}
```

Code	Description
400	Invalid ID format **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`
404	Store not found **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`

PUT `/stores/{id}/stock` Increase Ingredient Stock

Add quantity to specific ingredients in a store's inventory.

Parameters

Try it out

Name	Description
id * required `string` *(path)*	Store UUID id
request * required `array<object>` *(body)*	List of ingredients to add **Example Value** | Model `[ { "ingredientId": "string", "minThreshold": 0, "quantity": 0 } ]` **Parameter content type** application/json

Responses

Response content type: application/json

Code	Description
200	Success **Example Value** | Model `{ "additionalProp1": {} }`
400	Validation error or Invalid ID

Code	Description

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

401 Unauthorized

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

Suppliers

GET `/suppliers` Get all suppliers

Retrieve a paginated list of all suppliers in the system.

Parameters Try it out

Name	Description
code `string` *(query)*	GET dùng form tag cho Query String code
isActive `boolean` *(query)*	--
name `string` *(query)*	name
page `integer` *(query)*	page
pageSize `integer` *(query)*	pageSize

Responses Response content type application/json

Code	Description
200	List of suppliers

Example Value | Model

```
{
  "items": [
    {
```

Code	Description


```
      "code": "string",
      "contactPerson": "string",
      "id": "string",
      "isActive": true,
      "name": "string",
      "phone": "string"
    }
  ],
  "totalCount": 0,
  "totalPages": 0
}
```


400 Validation Error (Bad Request)

Example Value | Model


```
{}
```


401 Unauthorized

Example Value | Model


```
{}
```


500 Internal Server Error

Example Value | Model


```
{}
```


POST /suppliers Create a new supplier

Add a new supplier to the system.

Parameters

Try it out

Name	Description
request * required `object` *(body)*	Supplier information **Example Value** | Model


```
{
  "address": "string",
  "code": "string",
  "contactPerson": "string",
  "email": "string",
  "name": "string",
  "phone": "string",
  "taxCode": "string"
}
```


Parameter content type: application/json

Responses

Response content type: application/json

Code	Description
200	Successfully created

Example Value | Model

```
{
  "code": "string",
  "id": "string",
  "message": "string"
}
```

400	Validation Error (Bad Request)

Example Value | Model

```
{}
```

401	Unauthorized

Example Value | Model

```
{}
```

500	Internal Server Error

Example Value | Model

```
{}
```

GET /suppliers/{id} Get supplier details

Retrieve detailed information of a specific supplier by their UUID.

Parameters

Try it out

Name	Description
id * required `string` *(path)*	Supplier UUID id

Responses

Response content type: application/json

Code	Description
200	Detailed supplier information

Example Value | Model

```
{
  "address": "string",
  "code": "string",
  "contactPerson": "string",
```

Code	Description


```
  "createdAt": "string",
  "email": "string",
  "id": "string",
  "isActive": true,
  "name": "string",
  "phone": "string",
  "taxCode": "string",
  "updatedAt": "string"
}
```


400 Invalid UUID format

Example Value | Model


```
{}
```


401 Unauthorized

Example Value | Model


```
{}
```


404 Supplier Not Found

Example Value | Model


```
{}
```


500 Internal Server Error

Example Value | Model


```
{}
```


DELETE /suppliers/{id} Delete a supplier

Remove a supplier from the system.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Supplier UUID id

Responses Response content type application/json

Code	Description
200	Successfully deleted

Code	Description

Example Value | Model

```
{
  "code": "string",
  "id": "string",
  "message": "string"
}
```

400 Invalid UUID format

Example Value | Model

```
{}
```

401 Unauthorized

Example Value | Model

```
{}
```

404 Supplier Not Found

Example Value | Model

```
{}
```

500 Internal Server Error

Example Value | Model

```
{}
```

PATCH /suppliers/{id} Update a supplier

Modify the details of an existing supplier.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Supplier UUID id
request * required `object` *(body)*	Updated information **Example Value** | Model

```
{
  "address": "string",
  "code": "string",
  "contactPerson": "string",
  "email": "string",
  "isActive": true,
  "name": "string",
  "phone": "string",
```

Name	Description


```
  "taxCode": "string"
}
```


Parameter content type

application/json

Responses

Response content type: application/json

Code	Description
200	Successfully updated

Example Value | Model


```
{
  "code": "string",
  "id": "string",
  "message": "string"
}
```


400	Validation Error or Invalid ID

Example Value | Model


```
{}
```


401	Unauthorized

Example Value | Model


```
{}
```


404	Supplier Not Found

Example Value | Model


```
{}
```


500	Internal Server Error

Example Value | Model


```
{}
```


Suppliers / Payments

GET `/suppliers/payments` Get all supplier payments

Retrieve the complete payment history for suppliers (Intended for Admins/Accountants to track cash flow).

Parameters Try it out

Name	Description
page **integer** *(query)*	page
pageSize **integer** *(query)*	pageSize
purchaseOrderId **string** *(query)*	purchaseOrderId
supplierId **string** *(query)*	supplierId

Responses Response content type: application/json

Code	Description
200	List of supplier payments **Example Value** | Model


```
{
  "items": [
    {
      "amount": 0,
      "code": "string",
      "createdAt": "string",
      "id": "string",
      "method": 0,
      "paidAt": "string",
      "purchaseOrderCode": "string",
      "purchaseOrderId": "string",
      "status": 0
    }
  ],
  "totalCount": 0,
  "totalPages": 0
}
```


400	Validation Error (Bad Request) **Example Value** | Model


```
{}
```


401	Unauthorized **Example Value** | Model


```
{}
```

Code	Description
500	Internal Server Error

Example Value | Model

```
{}
```

POST /suppliers/payments Create purchase order payment

Initialize a payment using Cash or generate a VNPay payment URL for a purchase order.

Parameters

Try it out

Name	Description
request * required object *(body)*	Payment information

Example Value | Model

```
{
  "method": 0,
  "purchaseOrderId": "string",
  "returnUrl": "string"
}
```

Parameter content type

application/json

Responses

Response content type application/json

Code	Description
200	Successfully created payment

Example Value | Model

```
{
  "code": "string",
  "paymentId": "string",
  "url": "string"
}
```

Code	Description
400	Validation Error (Bad Request)

Example Value | Model

```
{}
```

Code	Description
401	Unauthorized

Example Value | Model

```
{}
```

Code	Description
500	Internal Server Error

Example Value | Model

```
{}
```

GET /suppliers/payments/vnpay/return Handle VNPay Return URL (Supplier Payment)

Callback endpoint for VNPay after a payment. Verifies the gRPC signature and redirects the browser to the Frontend UI with the payment status.

Parameters

Try it out

Name	Description
vnp_Amount string *(query)*	Transaction Amount vnp_Amount
vnp_BankCode string *(query)*	Bank Code vnp_BankCode
vnp_OrderInfo string *(query)*	Order Information vnp_OrderInfo
vnp_ResponseCode string *(query)*	VNPAY Response Code vnp_ResponseCode
vnp_TxnRef string *(query)*	Transaction Reference (Payment Code) vnp_TxnRef
vnp_SecureHash string *(query)*	Checksum Security Hash vnp_SecureHash
redirectTo string *(query)*	Frontend path to redirect to (e.g., /suppliers/purchase-orders/123) redirectTo

Responses

Response content type: text/html

Code	Description
302	Redirects to the Frontend application
400	Bad Request or Invalid Signature

GET `/suppliers/purchase-orders/{id}/payments` Get payments by Purchase Order ID

Retrieve the payment history (installments/transactions) for a specific Purchase Order.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Purchase Order UUID id

Responses Response content type: application/json

Code	Description
200	List of payments for the PO **Example Value** | Model

```
[
  {
    "amount": 0,
    "code": "string",
    "createdAt": "string",
    "id": "string",
    "method": 0,
    "notes": "string",
    "paidAt": "string",
    "purchaseOrderId": "string",
    "status": 0
  }
]
```

400	Invalid UUID format **Example Value** | Model

```
{}
```

401	Unauthorized **Example Value** | Model

```
{}
```

404	Purchase Order not found **Example Value** | Model

```
{}
```

500	Internal Server Error **Example Value** | Model

```
{}
```

Code	Description

Suppliers / PurchaseOrders

GET `/suppliers/purchase-orders` Get all purchase orders

Retrieve a paginated list of purchase orders. Supports filtering by Supplier, Store, or Status.

Parameters Try it out

Name	Description
page integer *(query)*	page
pageSize integer *(query)*	pageSize
status integer *(query)*	status
storeId string *(query)*	storeId
supplierId string *(query)*	supplierId

Responses Response content type: application/json

Code	Description
200	List of purchase orders **Example Value** | Model


```
{
  "items": [
    {
      "code": "string",
      "createdAt": "string",
      "id": "string",
      "netAmount": 0,
      "orderDate": "string",
      "paymentStatus": 0,
      "status": 0,
      "supplierName": "string",
      "totalAmount": 0
    }
  ],
  "totalCount": 0,
  "totalPages": 0
}
```


400	Validation Error (Bad Request)

Code	Description

Example Value | Model

```
{}
```

401 Unauthorized

Example Value | Model

```
{}
```

500 Internal Server Error

Example Value | Model

```
{}
```

POST /suppliers/purchase-orders Create a new purchase order

Create a new purchase order record with an initial status of PENDING.

Parameters

Try it out

Name	Description
request * required object *(body)*	Purchase order information **Example Value** | Model

```
{
  "discountAmount": 0,
  "expectedDeliveryDate": "string",
  "items": [
    {
      "ingredientId": "string",
      "quantity": 0
    }
  ],
  "notes": "string",
  "referenceCode": "string",
  "storeId": "string",
  "supplierId": "string"
}
```

Parameter content type: application/json

Responses

Response content type: application/json

Code	Description
200	Successfully created

Example Value | Model

Code	Description

```
{
  "code": "string",
  "id": "string",
  "message": "string"
}
```

400 Validation Error (Bad Request)

Example Value | Model

```
{}
```

401 Unauthorized

Example Value | Model

```
{}
```

500 Internal Server Error

Example Value | Model

```
{}
```

POST /suppliers/purchase-orders/latest-prices Get latest ingredient prices

Look up the most recent import prices for a provided list of ingredient IDs based on the latest purchase order records.

Parameters

Try it out

Name	Description
request * required object *(body)*	List of ingredient IDs **Example Value** | Model `{ "ingredientIds": [ "string" ] }` **Parameter content type** application/json

Responses

Response content type: application/json

Code	Description
200	Map of ingredient IDs to their latest prices **Example Value** | Model

Code	Description


```
{
  "additionalProp1": 0,
  "additionalProp2": 0,
  "additionalProp3": 0
}
```


400 Validation Error (Bad Request)

Example Value | Model


```
{}
```


401 Unauthorized

Example Value | Model


```
{}
```


500 Internal Server Error

Example Value | Model


```
{}
```


GET /suppliers/purchase-orders/{id} Get purchase order details

Retrieve detailed information of a specific purchase order, including the list of imported ingredients.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Purchase Order UUID id

Responses Response content type: application/json

Code	Description

200 Detailed purchase order information

Example Value | Model


```
{
  "code": "string",
  "completedAt": "string",
  "createdAt": "string",
  "discountAmount": 0,
  "id": "string",
  "items": [
    {
      "id": "string",
      "ingredientId": "string",
      "quantity": 0,
```

Code	Description


```
      "totalPrice": 0,
      "unitPrice": 0
    }
  ],
  "netAmount": 0,
  "notes": "string",
  "orderDate": "string",
  "paidAmount": 0,
  "paymentStatus": 0,
  "status": 0,
  "storeId": "string",
  "supplierId": "string",
  "supplierName": "string",
  "totalAmount": 0,
  "updatedAt": "string"
}
```


400 Invalid UUID format

Example Value | Model


```
{}
```


401 Unauthorized

Example Value | Model


```
{}
```


404 Purchase Order Not Found

Example Value | Model


```
{}
```


500 Internal Server Error

Example Value | Model


```
{}
```


PATCH /suppliers/purchase-orders/{id} Update a purchase order

Modify the details of an existing purchase order (only allowed when the PO is in an updatable status).

Parameters Try it out

Name	Description
id * required `string` *(path)*	Purchase Order UUID id
request * required `object` *(body)*	Updated information **Example Value** | Model


```
{
  "discountAmount": 0,
```

Name	Description


```
  "expectedDeliveryDate": "string",
  "items": [
    {
      "ingredientId": "string",
      "quantity": 0
    }
  ],
  "notes": "string",
  "referenceCode": "string",
  "storeId": "string",
  "supplierId": "string"
}
```


Parameter content type

application/json

Responses

Response content type: application/json

Code	Description

200 — Successfully updated

Example Value | Model


```
{
  "code": "string",
  "id": "string",
  "message": "string"
}
```


400 — Validation Error or Invalid ID

Example Value | Model


```
{}
```


401 — Unauthorized

Example Value | Model


```
{}
```


404 — Purchase Order Not Found

Example Value | Model


```
{}
```


500 — Internal Server Error

Example Value | Model


```
{}
```


PATCH `/suppliers/purchase-orders/{id}/cancel` Cancel a purchase order

Cancel an active purchase order and record the specific cancellation reason.

Parameters Try it out

Name	Description
id * required `string` *(path)*	Purchase Order UUID id
request * required `object` *(body)*	Cancellation reason **Example Value** | Model `{ "reason": "string" }` **Parameter content type** application/json

Responses Response content type application/json

Code	Description
200	Successfully cancelled **Example Value** | Model `{ "code": "string", "id": "string", "message": "string" }`
400	Validation Error or Invalid ID **Example Value** | Model `{}`
401	Unauthorized **Example Value** | Model `{}`
404	Purchase Order Not Found **Example Value** | Model `{}`
500	Internal Server Error **Example Value** | Model

Code	Description
	{}

PATCH `/suppliers/purchase-orders/{id}/complete` Complete a purchase order

Confirm that all goods have been successfully received and finalize the purchase order (typically triggers an inventory restock).

Parameters Try it out

Name	Description
id * required `string` *(path)*	Purchase Order UUID id

Responses Response content type: application/json

Code	Description

200	Successfully completed
	Example Value | Model
	{
	"code": "string",
	"id": "string",
	"message": "string"
	}

400	Invalid ID format **Example Value** | Model {}
401	Unauthorized **Example Value** | Model {}
404	Purchase Order Not Found **Example Value** | Model {}
500	Internal Server Error **Example Value** | Model

Code	Description
	{}

Users

GET `/users` Get All Users

Retrieve a list of users with optional filtering (Admin).

Parameters Try it out

Name	Description
endAt number *(query)*	endAt
hasHourlyWage boolean *(query)*	--
homeStoreId string *(query)*	homeStoreId
ids array<string> *(query)*	
keyword string *(query)*	keyword
orderCount integer *(query)*	orderCount
page integer *(query)*	page
pageSize integer *(query)*	pageSize
roleSlug string *(query)*	roleSlug
startAt number *(query)*	startAt
tierId string *(query)*	tierId

Responses Response content type: application/json

Code	Description
200	List of users **Example Value** | Model

```
{
  "additionalProp1": {}
}
```

Code	Description
500	Internal server error **Example Value** | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

POST /users Create New User (Admin)

Manually create a new user (e.g., for employees or admin accounts).

Parameters Try it out

Name	Description
request * required object *(body)*	User creation details **Example Value** | Model

```
{
  "address": "string",
  "currentHourlyWage": 0,
  "dateOfBirth": "string",
  "email": "string",
  "firstName": "string",
  "gender": 0,
  "homeStoreId": "string",
  "lastName": "string",
  "phone": "string",
  "roleSlug": "string",
  "username": "string"
}
```

Parameter content type: application/json

Responses Response content type: application/json

Code	Description
200	Created user details **Example Value** | Model

Code	Description

```
{
  "additionalProp1": {}
}
```

400 Validation error

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

GET /users/{id} Get User by ID

Retrieve details of a specific user by their ID.

Parameters

Try it out

Name	Description
id * required `string` *(path)*	User UUID id

Responses

Response content type: application/json

Code	Description

200 User details

Example Value | Model

```
{
  "additionalProp1": {}
}
```

400 Invalid ID format

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

404 User not found

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

PATCH /users/{id} Update User

Update a specific user info.

Parameters

Try it out

Name	Description
id * required `string` *(path)*	User UUID id
request * required `object` *(body)*	New User Info **Example Value** | Model

```
{
  "address": "string",
  "currentHourlyWage": 0,
  "dateOfBirth": "string",
  "firstName": "string",
  "gender": 0,
  "homeStoreId": "string",
  "isBlocked": true,
  "lastName": "string",
  "phone": "string",
  "roleSlug": "string",
  "username": "string"
}
```

Parameter content type: application/json

Responses

Response content type: application/json

Code	Description
200	Updated user details **Example Value** | Model

```
{
  "additionalProp1": {}
}
```

400	Validation error **Example Value** | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

PATCH /users/{id}/role Update User Role

Change the role (permission level) of a specific user.

Parameters

Try it out

Name	Description
id * required `string` *(path)*	User UUID id
request * required `object` *(body)*	New Role Slug **Example Value** | Model `{ "roleSlug": "string" }` **Parameter content type** application/json

Responses — Response content type: application/json

Code	Description
200	Updated user details **Example Value** | Model `{ "additionalProp1": {} }`
400	Validation error **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`

Profile

GET `/users/me` Get My Profile

Retrieve the profile information of the currently logged-in user.

Parameters — Try it out

No parameters

Responses — Response content type: application/json

Code	Description
200	User profile details **Example Value** | Model `{ "additionalProp1": {} }`
401	Unauthorized **Example Value** | Model `{ "additionalProp1": "string", "additionalProp2": "string", "additionalProp3": "string" }`

PATCH /users/me Update My Profile

Update personal information (Email, Phone, Address, etc.) for the logged-in user.

Parameters

Try it out

Name	Description
request * required `object` *(body)*	Updated profile details **Example Value** | Model `{ "address": "string", "dateOfBirth": "string", "firstName": "string", "gender": 0, "lastName": "string", "phone": "string" }` **Parameter content type** application/json

Responses

Response content type: application/json

Code	Description
200	Updated profile **Example Value** | Model `{ "additionalProp1": {} }`
400	Validation error **Example Value** | Model

Code	Description

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

401 Unauthorized

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

PUT `/users/me/avatar` Upload My Avatar

Upload my avatar. Supports JPG, PNG, and WebP formats. Max file size is 10MB.

Parameters Try it out

Name	Description
image * required `file` *(formData)*	Image file to upload Choose File No file chosen

Responses Response content type application/json

Code	Description

200 OK

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

401 Unauthorized

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

413 Request entity too large

Example Value | Model

```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```

500 Internal server error

Code	Description

Example Value | Model


```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```


DELETE `/users/me/avatar` Delete My Avatar

Delete my avatar.

Parameters Try it out

No parameters

Responses Response content type: application/json

Code	Description
200	OK

Example Value | Model


```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```


401	Unauthorized

Example Value | Model


```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```


500	Internal server error

Example Value | Model


```
{
  "additionalProp1": "string",
  "additionalProp2": "string",
  "additionalProp3": "string"
}
```


Models