

Part Number: 1042240820

Product Description: nano-SIM Card Connector, 6 Circuit, Push/Pull Type, 1.11mm


Height

Series Number: 104224

**Status:** Active

Product Category: Memory / SIM Card

Connectors



#### **Documents & Resources**

#### **Drawings**

1042240820\_sd.pdf

3D Models and Design Files

1042240820\_stp.zip

#### **Specifications**

PK-104224-001-001.pdf PS-104224-001-001.pdf

# **Product Environment Compliance**

### Compliance

| GADSL/IMDS         | Compliant with Exemption 34; 33                   |
|--------------------|---|
| China RoHS         | <b>©</b>  |
| EU ELV             | Not Relevant                                      |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21                    |
| REACH SVHC         | Not Contained per D(2024)6225-DC<br>(07 Nov 2024) |
| EU RoHS            | Compliant per EU 2015/863                         |

## Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D

- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

# EU RoHS Certificate of Compliance

# Part Details

#### General

| Status       | Active  |
|--------------|---|
| Category     | Memory / SIM Card Connectors  |
| Series       | 104224  |
| Description  | nano-SIM Card Connector, 6<br>Circuit, Push/Pull Type, 1.11mm<br>Height |
| Product Name | nano-SIM  |
| Style        | Push-Pull   |
| UPC          | 889056084116  |

### Electrical

| Current - Maximum per Contact | 0.5A            |
|-------------------------------|-----------------|
| Voltage - Maximum             | 10V AC (RMS)/DC |

# Physical

| Card Detection Switch          | No                             |
|--------------------------------|--------------------------------|
| Card Entry Location            | Front                          |
| Circuits (Loaded)              | 6                              |
| Circuits (maximum)             | 6                              |
| Color - Resin                  | Natural                        |
| Durability (mating cycles max) | 5000                           |
| Ejector Button Side            | N/A                            |
| Material - Contact             | Copper Alloy                   |
| Material - Plating Mating      | Gold over Palladium Nickel     |
| Material - Plating Termination | Gold                           |
| Material - Resin               | High Temperature Thermoplastic |
| Material - Shell               | Stainless Steel                |
| Net Weight                     | 0.138/g                        |
| Packaging Type                 | Embossed Tape on Reel          |

| PCB Retention                 | Yes           |
|-------------------------------|---------------|
| Pitch - Mating Interface      | 2.54mm        |
| Temperature Range - Operating | -25° to +85°C |
| Termination Interface Style   | Surface Mount |

## Use with Part(s)

| Description | Part Number   |
|-------------|---------------|
| Use With    | nano-SIM Card |

This document was generated on Mar 11, 2025