

File Actions Edit View Help

(kali@kali)-[~]

\$ ip a

```
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN group default qlen 1000
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
        valid_lft forever preferred_lft forever
    inet6 ::1/128 scope host noprefixroute
        valid_lft forever preferred_lft forever
2: eth0: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc fq_codel state UP group default qlen 1000
    link/ether 08:00:27:1e:36:4a brd ff:ff:ff:ff:ff:ff
    inet 192.168.50.100/24 brd 192.168.50.255 scope global noprefixroute eth0
        valid_lft forever preferred_lft forever
    inet6 fe80::a00:27ff:fe1e:364a/64 scope link proto kernel_ll
        valid_lft forever preferred_lft forever
```

(kali@kali)-[~]

\$ ping -c4 192.168.50.101

```
PING 192.168.50.101 (192.168.50.101) 56(84) bytes of data.
64 bytes from 192.168.50.101: icmp_seq=1 ttl=64 time=8.25 ms
64 bytes from 192.168.50.101: icmp_seq=2 ttl=64 time=0.543 ms
64 bytes from 192.168.50.101: icmp_seq=3 ttl=64 time=0.677 ms
64 bytes from 192.168.50.101: icmp_seq=4 ttl=64 time=1.03 ms
```

— 192.168.50.101 ping statistics —

```
4 packets transmitted, 4 received, 0% packet loss, time 3059ms
rtt min/avg/max/mdev = 0.543/2.625/8.252/3.253 ms
```

(kali@kali)-[~]

\$ ping -c4 192.168.50.102

```
PING 192.168.50.102 (192.168.50.102) 56(84) bytes of data.
64 bytes from 192.168.50.102: icmp_seq=1 ttl=128 time=1.25 ms
64 bytes from 192.168.50.102: icmp_seq=2 ttl=128 time=0.445 ms
64 bytes from 192.168.50.102: icmp_seq=3 ttl=128 time=0.893 ms
64 bytes from 192.168.50.102: icmp_seq=4 ttl=128 time=0.881 ms
```

— 192.168.50.102 ping statistics —

```
4 packets transmitted, 4 received, 0% packet loss, time 3023ms
rtt min/avg/max/mdev = 0.445/0.866/1.247/0.284 ms
```

(kali@kali)-[~]

\$