

To develop these experiments we used the database created in the paper "Extraction of UML Class Diagrams from Natural Language Specification" (Yang et al. 2022) that consists of class diagrams labeled with the specification. It contains images of the diagrams and the PlantUML code.

The list of specifications (requirements) selected:

<A category has a value

News have dates. Each date contains the day of the week, the month, the hours and the seconds

News have titles and links

A newspaper is published on a specific date

a newspaper is written in a language

A newspaper reports many news

A news is published on a specific date

News are related to one Newspaper and a newspaper can only include one instance of news.

A class named "News", containing an attribute called "author", of type "String".>

We employed these requirements in three different prompt engineering techniques Zero-shot, Few-shot, and CoT. We used 4 different models of OpenAI, some are free (ChatGPT 4) and others are paid (ChatGPT o1, ChatGPT 3o), we also employed the free version of Gemini (Gemini 2.0 flash), and we employed the new LLM in the market Deepseek.

We also found it would be interesting to test one of the ChatGPT agents available for UML modeling.

Besides employing the different prompt techniques we wanted to see how well could ChatGPT identify which requirements correspond to class specification or relation specification

Prompt engineering techniques

Zero-shot:

Act as requirement engineer,

Generate a class diagram for these requirements

<A category has a value

News have dates. Each date contains the day of the week, the month, the hours and the seconds

News have titles and links

A newspaper is published on a specific date

a newspaper is written in a language

A newspaper reports many news

A news is published on a specific date

News are related to one Newspaper and a newspaper can only include one instance of news.

A class named "News", containing an attribute called "author", of type "String".>.

Generate a detail class diagram in PlantUML format.

ChatGPT o1 model that used advanced reflection:

Below is an example of a detailed class diagram in PlantUML format that captures the stated requirements.

```
@startuml
' === Classes ===
class Category {
    - value : String
}

class DateInfo {
    - dayOfWeek : String
    - month : String
    - hours : int
    - seconds : int
}

class Newspaper {
    - language : String
    ' A Newspaper is published on a specific date
    - publicationDate : DateInfo
}

class News {
    - title : String
    - link : String
    - author : String
    ' A News is published on a specific date
    - publishedOn : DateInfo
}
```

```
' === Relationships ===

' A newspaper reports many news; each news is related to exactly one newspaper
Newspaper "1" -- "0..*" News : reports >

' A category has a value; assume each News belongs to one Category
News "1" -- "1" Category : has category >

@enduml
```

Explanation of Key Points

1. Category
 - Has an attribute value (String), representing the category's label (e.g., "Sports", "Politics", etc.).
2. DateInfo
 - Encapsulates date-related attributes: dayOfWeek, month, hours, and seconds.
 - Used to model both a Newspaper's publication date and a News item's publication date.
3. Newspaper
 - Has a language attribute (String).
 - Has a publicationDate of type DateInfo, indicating when the newspaper is published.
 - One Newspaper can report many News items (1 -- 0..*).
4. News
 - Includes title (String), link (String), author (String), and a publishedOn date (of type DateInfo).
 - Each News is associated with exactly one Newspaper.
 - Each News belongs to exactly one Category (the diagram assumes one category per news item to integrate the "A category has a value" requirement).
5. Multiplicity Constraints
 - Newspaper to News is 1 -> 0..*. A single Newspaper can contain multiple News items.
 - News to Newspaper is 1 -> 1. Every News item must appear in exactly one Newspaper.
 - News to Category is 1 -> 1. In this model, every News item is assigned exactly one Category.

This diagram should satisfy all requirements related to dates, titles, links, authors, language, and the one-to-many relationship between Newspaper and News.

ChatGPT 3o-mini-high (good with programming and logic):

Below is an example of a detailed PlantUML class diagram that reflects the requirements. In this design, a separate Date class is defined to capture the components of a date (day of the week, month, hours, seconds). The News class has attributes for title, link, and (per requirement) author, plus an association with Date (its published date). A Newspaper is written in a language and is published on a Date, and it "reports" many news items. Each News instance is related to one Newspaper (and appears only once within that Newspaper). Also, a Category class is included (with its "value") and is associated to News (assuming each News is categorized). You can adjust the associations (e.g. cardinalities or naming) if needed.

```
@startuml
' Category definition
class Category {
    - value : String
}

' Date value object capturing day, month, hours, seconds
class Date {
    - dayOfWeek : String
    - month : String
    - hours : int
    - seconds : int
}

' News item with title, link, author and its published date.
class News {
    - title : String
    - link : String
    - author : String
    - publishedDate : Date
}

' Newspaper with language and a published date.
class Newspaper {
    - language : String
    - publishedDate : Date
}

' Associations
' A Newspaper reports many News. Each News is published by exactly one Newspaper.
Newspaper "1" o-- "0..*" News : reports
News "1" --> "1" Newspaper : publishedIn
```

```
' Both News and Newspaper are published on a specific Date.
News *-- "1" Date : publishedOn
Newspaper *-- "1" Date : publishedOn

' (Optional) Each News is categorized.
News --> "1" Category : categorizedAs
```

@endum1

Explanation

- Category:
 - Contains a single attribute value : String.
- Date:
 - Represents the published date details with attributes for dayOfWeek, month, hours, and seconds.
- News:
 - Contains attributes title, link, and author : String.
 - Associated with a Date (its published date).
 - Related to one Newspaper (each news item appears only once in a newspaper).
 - Optionally associated with a Category.
- Newspaper:
 - Has attributes language : String and a published Date.
 - Reports (has many) News items.

This design satisfies the given requirements and is ready to be rendered using PlantUML.

ChatGPT 4o:

Here is a detailed class diagram in PlantUML format based on your requirements:

```
@startuml

class Category {
    + value: String
}

class Date {
    + dayOfWeek: String
    + month: String
    + hours: int
    + seconds: int
}

enduml
```

```

class News {
  + title: String
  + link: String
  + author: String
  + publishedDate: Date
}

class Newspaper {
  + language: String
  + publicationDate: Date
}

Category "1" -- "*" News : categorizes
News "1" -- "1" Newspaper : belongs_to
Newspaper "1" -- "*" News : reports
Newspaper "1" -- "1" Date : published_on
News "1" -- "1" Date : published_on

@enduml

```

This diagram correctly models:

- Categories with a value that can be associated with multiple News items.
- News with attributes including title, link, author, and a publication date.
- Dates, which are composed of day of the week, month, hours, and seconds.
- Newspapers, which are published on a specific date and written in a language.
- News belonging to a single Newspaper, ensuring only one instance of a particular news article exists in a newspaper.

Would you like any modifications or refinements? 🚀

ChatGPT 4:

Based on your requirements, I will create a class diagram using PlantUML syntax. This will include classes for Category, News, Newspaper, and Date, detailing their relationships and attributes.

Here's the detailed class diagram in PlantUML format:

```

@startuml

class Category {
  +String value
}

class Date {
  +String dayOfWeek
  +String month
  +int hours
  +int seconds
}

```

```

class News {
    +String title
    +String link
    +Date publishDate
    +String author
    +Newspaper newspaper
}

class Newspaper {
    +Date publicationDate
    +String language
    +Set<News> newsList
}

News "1" -- "1" Newspaper : contains >
News "1" -- "1" Date : published on >
Newspaper "1" -- "1" Date : published on >

@enduml

```

Explanation of the Diagram:

1. Category Class: Contains a single attribute, **value**, representing the category value.
2. Date Class: Represents the publication date and contains attributes for the day of the week, month, hours, and seconds.
3. News Class: Contains attributes for the title, link, the date it was published (**publishDate**), and the author. It also has a relationship with the **Newspaper** class indicating that each news item is related to exactly one newspaper.
4. Newspaper Class: Has a publication date, a language, and a set of news items (**newsList**). It has a one-to-many relationship with **News**, indicating that a newspaper can report many news items, but each news item is linked to exactly one newspaper.

This diagram satisfies the requirement where each class and its relationships are defined according to the details provided.

Using chatGPT agent UML Diagram Expert (by Antoine Boucher):

Here is the PlantUML class diagram based on the given requirements:

```

@startuml
class Category {
    +value: String
}

class Date {
    +dayOfWeek: String
    +month: String
}

```

```

    +hours: int
    +seconds: int
}

class News {
    +title: String
    +link: String
    +author: String
    +publishedOn: Date
}

class Newspaper {
    +language: String
    +publishedOn: Date
}

Newspaper "1" --> "*" News : reports >
News --> "1" Newspaper : belongs to >
News --> "1" Date : "published on"
Newspaper --> "1" Date : "published on"
Category --> News : categorizes >

@enduml

```

Explanation:

1. Category: Has a value attribute.
2. Date: Stores detailed time information including dayOfWeek, month, hours, and seconds.
3. News:
 - Attributes: title, link, author, publishedOn
 - Each News belongs to exactly one Newspaper
 - News is categorized by a Category
 - News is published on a specific Date
4. Newspaper:
 - Attributes: language, publishedOn
 - Reports multiple News
 - Published on a specific Date

Would you like to refine or extend the model further? 🚀

GEMINI 2.0 FLASH

```

@startuml
class Category {
    value : String
}

class News {

```

```
    title : String
    link : String
    author : String
    date : Date
}

class Date {
    dayOfWeek : String
    month : String
    hours : int
    seconds : int
}

class Newspaper {
    publicationDate : Date
    language : String
}

Category "1" -- "*" News : contains

News "1" -- "1" Newspaper : belongs to

News "1" -- "1" Date : published on

Newspaper "1" -- "*" News : reports

@enduml
```

Deepsheek with DeepThink:

Few-shot:

Act as requirement engineer,

Generate a class diagram for this requirements:

<A category has a value

News have dates. Each date contains the day of the week, the month, the hours and the seconds

News have titles and links

A newspaper is published on a specific date

a newspaper is written in a language

A newspaper reports many news

A news is published on a specific date

News are related to one Newspaper and a newspaper can only include one instance of news.

A class named "News", containing an attribute called "author", of type "String".>

Generate a detail class diagram in PlantUML format

Example 1:

A company contains one back office for each store

A company structure model has stores

In a company structure model, stores have exactly one back office

A company structure model has cash registers

A store is composed by zero or more cash registers

Each corporate HQs manages a certain number of stores

A company structure model has corporate HQ

A company structure model has companies

A company is composed by one and only one corporate HQ

The employees that are working in the company.

A company structure model has back offices

Output 1:

```
@startuml
!theme plain
package CompanyStructure {
class Company {
}
Company "corporateHQ 1..1" *--> CorporateHQ
Company "Store 0..*" *--> Store
class CorporateHQ {
}
CorporateHQ "manages 0..*" --> Store
CorporateHQ "corporateHQBackOffice 1..1" *--> CorporateHQBackOffice
class Store {
}
Store "storeBackOffice 1..1" *--> StoreBackOffice
Store "employee 0..*" *--> Employee
Store "cashRegister 0..*" *--> CashRegister
class CorporateHQBackOffice {
}
class StoreBackOffice {
}
class Employee {
}
class CashRegister {
}
}
@enduml
```

Example 3:

A Cristal package has a class named Condition.

Drawing Interchange Format

a Mesh has a name of type String

a Mesh may have any number of points

a point maps to only one Mesh

a point has a name of type String and coordinates X and Z of type Double

a Drawing Interchange model may have multiple meshes

Output 3:

```
@startuml
!theme plain
package DXF {
class DXF {
}
DXF "meshes 0..*" *--> Mesh
class Mesh {
    name : String
}
Mesh "points 0..*" *-- "mesh 1..1" Point
class Point {
    name : String
    x : Double
    y : Double
    z : Double
}
}
}
@enduml
```

Example 4:

The EAI Sink which is also a FCMSink has a list of zero or more EAIResource.

Each EAI Source has zero or more resources of type EAIResource.

The EAI model has a class of type FCMSource.

The EAI Model has an EAI Source class that extends FCMSource.

A concrete class named FCMSink in a package named EAI.

A concrete class named EAI Sink in a package named EAI.

The EAI model has a class that is EAIResource

Class EAIQueue has an integer attribute maxLength

Output 4:

```
@startuml
!theme plain
package EAI {
class FCMSource {
}
class EAISource {
}
FCMSource <|-- EAISource
EAISource "resources 0..*" --> EAIRResource
class FCMSink {
}
class EAISink {
}
FCMSink <|-- EAISink
EAISink "resources 0..*" --> EAIRResource
class EAIRResource {
}
class EAIQueue {
    maxLength : Integer
    name : String
}
EAIRResource <|-- EAIQueue
}
@enduml
```

ChatGPT 4

Based on your provided requirements for the class diagram involving categories, news, dates, and newspapers, here is the PlantUML code for the detailed class diagram:

```
@startuml
!theme plain

class Category {
    value : String
}

class Date {
    dayOfWeek : String
    month : String
    hour : Int
    second : Int
}

class News {
    title : String
    link : String
    author : String
    date : Date
}

class Newspaper {
    publicationDate : Date
    language : String
}

News "1" *-- "1" Date : contains >
Newspaper "1" *-- "1" Date : published on >
Newspaper "0..*" -- "0..*" News : reports >
News "1" -- "1" Newspaper : published in >

@enduml
```

This diagram defines the relationships and attributes based on your description:

1. **Category Class:** Holds a single attribute `value`.
2. **Date Class:** Encapsulates information about the date, including day of the week, month, hour, and second.
3. **News Class:** Includes attributes for title, link, and author. It also contains a date showing the specifics of when the news was published.
4. **Newspaper Class:** Defined by a publication date and the language it's written in. A newspaper has multiple news items, but each news item can only relate to one newspaper instance.

This setup captures the essence of the relationships like publication dates and linguistic details while connecting news items to their respective newspapers.

ChatGPT 3o-mini-high (good with programming and logic):

Below is a PlantUML class diagram that models the requirements:

- **Category** has a single attribute called *value*.
- **Date** is used for both news and newspaper publication dates. It contains attributes for the day of the week, month, hours, and seconds.
- **Language** represents the language in which a newspaper is written.
- **Newspaper** is published on a specific Date and is written in a Language. It “reports” many News items.
- **News** has attributes *title*, *link*, and (per requirement) *author*. Each news item is published on a specific Date and is related to one Newspaper. In addition, a news item is associated with one Category.

The following PlantUML code reflects these associations and multiplicities:

```
@startuml
!theme plain
package NewsDomain {

    class Category {
        +value : String
    }

    class Date {
        +dayOfWeek : String
        +month : String
        +hours : Integer
        +seconds : Integer
    }

    class Language {
        +name : String
    }

    class Newspaper {
    }

    class News {
        +title : String
        +link : String
        +author : String
    }

    ' Newspaper associations
    Newspaper "publishedOn 1..1" *-- Date
    Newspaper "writtenIn 1..1" *-- Language
    Newspaper "reports 0..*" --> News

    ' News associations
    News "publishedOn 1..1" *-- Date
    News "relatedTo 1..1" --> Newspaper
    News "hasCategory 1..1" *-- Category
}
@enduml
```

Explanation of the Diagram

- **Category**: Defined with an attribute *value*.

- **Date:** Encapsulates all the required parts of a date (dayOfWeek, month, hours, seconds). It is composed within both Newspaper and News.
- **Language:** A Newspaper is written in one Language.
- **Newspaper:**
 - Has a composition association with Date (publishedOn).
 - Has a composition association with Language (writtenIn).
 - Reports many News items (0..*), while each News item is related to exactly one Newspaper.
- **News:**
 - Contains the attributes *title*, *link*, and *author*.
 - Has its own Date (publishedOn).
 - Is related to exactly one Newspaper.
 - Is associated with exactly one Category (hasCategory).

This diagram captures the details and relationships as specified in your requirements.

ChatGPT o1 model that used advanced reflection:

Below is one possible interpretation of the requirements in UML, following the style shown in your examples. The diagram models:

- A separate **Date** class with attributes for day of week, month, hours, and seconds (used both by **Newspaper** and **News**).
- A **Newspaper** class with a **language** attribute and a mandatory association to one **Date** (the publication date).
- A **News** class with **title**, **link**, **author**, and a mandatory association to one **Date** (the publication date).
- A **Category** class with a single attribute **value** (interpreted as a category name).
- A one-to-many link from **Newspaper** to **News** ("A newspaper reports many news"), with the understanding that each **News** item belongs to exactly one **Newspaper**.
- An optional or mandatory link from **News** to **Category** (the requirement "A category has a value" is minimally satisfied by giving Category its own class; whether or not every News must have a Category can be decided by the cardinality 0..1 or 1..1).

```
@startuml
!theme plain

package NewsDomain {

    class Category {
        value : String
    }

    class Date {
        dayOfWeek : String
        month : String
        hours : Integer
        seconds : Integer
    }

    class Newspaper {
        language : String
    }

    class News {
```

```

    title : String
    link : String
    author : String
}

'
' A Newspaper is published on a specific Date
'
Newspaper "publishedOn 1..1" *--> Date

'
' A News is published on a specific Date
'
News "publishedOn 1..1" *--> Date

'
' A Newspaper reports many News (and each News relates to exactly one Newspaper)
'
Newspaper "reports 1..*" *--> News

'
' Optional or mandatory Category for News (choose 0..1 or 1..1 as needed)
'
News "category 0..1" --> Category
}

@enduml

```

Notes

- If you interpret that every News must belong to exactly one Category, change `0..1` to `1..1`.
- The `*-->` notation has been used for composition/containment in the style of your examples. Depending on your exact modeling needs, you could use a simpler association arrow (`-->`) if you do not wish to imply composition.
- The requirement “A newspaper can only include one instance of news” is taken here to mean that a given **News** item does not appear in multiple **Newspaper** objects; it is enforced by the `1..* ↔ 1..1` association.

ChatGPT 4o:

Aqui está o diagrama de classes detalhado em formato PlantUML para os requisitos fornecidos:

```

@startuml
!theme plain
package NewsSystem {

    class Category {

```

```

        value : String
    }

    class Date {
        dayOfWeek : String
        month : String
        hours : Integer
        seconds : Integer
    }

    class News {
        title : String
        link : String
        author : String
    }

    class Newspaper {
        language : String
    }

    // Associações
    News "1" --> "1" Date : publishedOn
    Newspaper "1" --> "1" Date : publishedOn
    Newspaper "1" --> "0..*" News : reports
    News "1" --> "1" Newspaper : belongsTo
}
@enduml

```

Explicação:

1. Classes Criadas:

- Category com um atributo value.
- Date que contém dayOfWeek, month, hours e seconds.
- News com title, link e author.
- Newspaper com language.

2. Relações:

- News é publicada em uma Date (associação 1-1).
- Newspaper é publicado em uma Date (associação 1-1).
- Um Newspaper pode relatar várias News, mas cada News pertence a um único Newspaper (associação 1-*).
- Um Newspaper só pode ter uma instância de cada News.

Se precisar de ajustes ou adições, me avise!

GEMINI 2.0 FLASH

```
@startuml
!theme plain

package Newspaper {
class Category {
    value : String
}

class News {
    title : String
    link : String
    author : String
}

class Date {
    dayOfWeek : String
    month : String
    hours : String
    seconds : String
}

class Newspaper {
    language : String
}

Newspaper "published on 1" *-- Date : publicationDate
News "published on 1" *-- Date : publicationDate
News "related to 1" *-- Newspaper : reportedIn

News "belongs to 1" *-- Category

}

@enduml
```

ChatGPT Agent UML Diagram Expert (by Antoine Boucher):

Here's the class diagram in PlantUML format based on your requirements:

```
@startuml
!theme plain
```

```

package NewsSystem {

  class Category {
    value : String
  }

  class Date {
    dayOfWeek : String
    month : String
    hours : int
    seconds : int
  }

  class News {
    title : String
    link : String
    author : String
  }

  class Newspaper {
    language : String
  }

  // Relationships
  News "1" *--> "1" Date : publishedOn
  Newspaper "1" *--> "1" Date : publishedOn
  Newspaper "1" *--> "0..*" News : reports
  News "1" *--> "1" Newspaper : belongsTo

}

@enduml

```

Explanation:

1. Category has a single attribute value of type String.
2. Date contains dayOfWeek, month, hours, and seconds.
3. News includes title, link, and author.
4. Newspaper has an attribute language.
5. Relationships:
 - A News is always published on a specific Date.
 - A Newspaper is published on a Date.
 - A Newspaper reports multiple News.
 - A News belongs to one Newspaper, and a Newspaper includes only one instance of a specific News.

Would you like any modifications or additional details? 🚀

Deepsheek with DeepThink:

CoT

Act as requirement engineer,

Question:

Generate a class diagram for this requirements:

<The number of a cell phone number is encoded as a String

A land line number is mapped to exactly one contact

A cell phone number is mapped to a single contact

The phone number of a land line is encoded as a String

A contact has a name

A Contact may have any number of land line numbers>

Presented using PlantUML code.

Answer :

First identify the classes. The classes present in the requirements are Contact, cell phone number and land line number.

The the attributes of each class are Contact has a name as string and prenom as string also. The cell phone number class has a number as string and the land line number also has a attribute number as string.

Then we identify the relationships, the contact is composed by 0 or more cell phone numbers and land line numbers. And each cell phone number and line line numbers only have one contact

Now we represent the result using Plant UML code:

```
@startuml
!theme plain
package Contact {
class Contact {
    nom : String
    prenom : String
}
}
```

```

Contact "num_fixes 0..*" *-- "contact_fixe 1..1" Num_fixe
Contact "num_portables 0..*" *-- "contact_portable 1..1" Num_portable
class Num_fixe {
    numero : String
}
class Num_portable {
    numero : String
}
}
@enduml

```

Question:

Generate a class diagram for this requirements

<A category has a value

News have dates. Each date contains the day of the week, the month, the hours and the seconds

News have titles and links

A newspaper is published on a specific date

a newspaper is written in a language

A newspaper reports many news

A news is published on a specific date

News are related to one Newspaper and a newspaper can only include one instance of news.

A class named "News", containing an attribute called "author", of type "String".>

Generate a detail class diagram in PlantUML format and follow the steps used in the example

ChatGPT o1 model that used advanced reflection:

1. Identify the Classes

From the requirements, we see the following classes:

1. Category
 - Has a value.
2. Date
 - Has day of the week, month, hours, and seconds.
3. News
 - Has a title (String)
 - Has a link (String)
 - Has an author (String)
 - Is published on a specific Date
4. Newspaper
 - Is published on a specific Date
 - Is written in a language (String)
 - Reports many News

Note on Contradiction:

The requirements say both “A newspaper reports many news” and “a newspaper can only include one instance of news.” These are contradictory. A common interpretation is that *one newspaper can have multiple news items*, each news item belonging to exactly one newspaper.

We will therefore treat it as “one newspaper” can have “0..*” news, and each news relates to exactly one newspaper.

2. Identify the Attributes of Each Class

1. Category
 - o value : String
 2. Date
 - o dayOfWeek : String
 - o month : String
 - o hours : int
 - o seconds : int
 3. News
 - o title : String
 - o link : String
 - o author : String
 4. Newspaper
 - o language : String
-

3. Identify the Relationships

1. A Newspaper is published on a specific Date
We will show this as a composition from Newspaper to Date because each newspaper *has* one date object.
2. A Newspaper reports many News
A one-to-many relationship from Newspaper to News. We can show that as 0..* on the News side and 1..1 on the Newspaper side (i.e., each News belongs to exactly one Newspaper).
3. A News is published on a specific Date
Similarly, we will show this as a composition from News to Date, indicating each News has one specific Date.
4. News are related to one Newspaper
This is the other side of the one-to-many relationship from above, specifying that each News item points back to exactly one Newspaper.

5. A Category has a value
The requirement mentions a Category class but does not explicitly define how it is related to News or Newspaper. If you need to model an association (for example, each News might have a Category), you can add that. If there is no stated relationship, you can leave Category standalone.

4. PlantUML Diagram

Below is the PlantUML code that incorporates all the classes, their attributes, and the relationships described:

```
@startuml
!theme plain

package Press {

    ' --- 1. Classes with attributes ---
    class Category {
        value : String
    }

    class Date {
        dayOfWeek : String
        month : String
        hours : int
        seconds : int
    }

    class News {
        title : String
        link : String
        author : String
    }

    class Newspaper {
        language : String
    }

    ' --- 2. Relationships ---
    '
    ' Newspaper *-- Date means: Newspaper is composed of one Date (publication date).
    Newspaper "publicationDate 1..1" *-- "date_for_newspaper 1..1" Date

    ' A Newspaper can have 0..* News, each News has exactly 1 Newspaper
    Newspaper "news 0..*" *-- "newspaper 1..1" News

    ' A News has exactly 1 Date (the publication date of that news)
    News "newsDate 1..1" *-- "date_for_news 1..1" Date

    ' Optionally, if you decide News needs a Category or multiple Categories:
    ' News "0..*" -- Category
}

@enduml
```

Notes on the Diagram

- The *-- arrow represents composition (as in the phone-number example), where one class is considered part of or strongly owned by the other.
- The role names (e.g., publicationDate 1..1 and date_for_newspaper 1..1) after the quotes are optional but can help clarify which side of the relationship is which.

- You can remove or adjust the Category association if you later decide how News or Newspaper uses Category.

This completes the step-by-step approach to creating a detailed class diagram in PlantUML for the given requirements.

ChatGPT 3o-mini-high (good with programming and logic):

note: is more slow

Step 1. Identify the Classes and Attributes

1. **Category**
 - o Attribute:
 - `value : String`
(The requirement "A category has a value" makes this a simple class with one attribute.)
2. **Date**
 - o Attributes (as specified by "News have dates. Each date contains the day of the week, the month, the hours and the seconds"):
 - `dayOfWeek : String`
 - `month : String`
 - `hours : String`
 - `seconds : String`
3. **News**
 - o Attributes (from "News have titles and links" and the additional "News" class with an author attribute):
 - `title : String`
 - `link : String`
 - `author : String`
4. **Newspaper**
 - o Attributes:
 - `language : String`
(As "a newspaper is written in a language.")

Step 2. Identify the Relationships

- **Newspaper and Date (for publication date):**
 - o A newspaper is published on a specific date. In our diagram, a *Newspaper* is composed with one *Date* that represents its publication date.
- **News and Date (for publication date):**
 - o Each news is published on a specific date. So, each *News* is composed with one *Date* as its publication date.
- **Newspaper and News:**
 - o "A newspaper reports many news" means that a *Newspaper* is composed of 0 or more *News* items.
 - o "News are related to one Newspaper" indicates that each *News* belongs to exactly one *Newspaper*.
- **News and Category:**
 - o Although the requirement only states "A category has a value," it is natural to assume that each news is associated with a single category (and one category may group several news items).

Step 3. Represent the Design in PlantUML

Below is the PlantUML code reflecting the above classes, attributes, and relationships. (Note how we use composition (the "*"-" arrow) for the dates and the "reports" relationship, and a plain association (the "-->" arrow) for the category relation.)

```
@startuml
!theme plain
package NewspaperSystem {

    class Category {
        value : String
    }

    class Date {
        dayOfWeek : String
        month : String
        hours : String
        seconds : String
    }

    class News {
```

```

    title : String
    link : String
    author : String
}

class Newspaper {
    language : String
}

' A newspaper is published on a specific date
Newspaper "publishedDate 1..1" *-- "dateOfNewspaper 1..1" Date

' A news is published on a specific date
News "publishedDate 1..1" *-- "dateOfNews 1..1" Date

' A newspaper reports many news, while each news is related to one newspaper
Newspaper "news 0..*" *-- "newspaper 1..1" News

' Each news is associated with one category while a category can group many news items
News "category 1..1" --> "news 0..*" Category
}
@enduml

```

Explanation

- **Classes and Attributes:**
Each class is defined with its attributes (for example, the *News* class includes *title*, *link*, and *author*).
- **Relationships:**
 - The composition lines (using **--*) show that both *Newspaper* and *News* "own" a specific *Date* instance for their publication date.
 - The association between *Newspaper* and *News* shows that one newspaper can report many news items and each news belongs to exactly one newspaper.
 - The arrow between *News* and *Category* expresses that each news item is assigned one category, and one category may be linked to many news.

This PlantUML code provides a complete and detailed class diagram following the steps similar to the provided example.

ChatGPT 4o:

Here is the detailed class diagram in PlantUML format, following the structure used in your example:

```

@startuml
!theme plain
package NewspaperSystem {

class Category {
    value : String
}

class Date {
    day_of_week : String
    month : String
    hours : String
    seconds : String
}

class News {
    title : String
    link : String
    author : String
}

class Newspaper {
    language : String
}

}

```

```

Newspaper "1" *-- "1" Date : published_on
Newspaper "1" *-- "1..*" News : reports
News "1" *-- "1" Date : published_on
News "1" *-- "1" Newspaper : related_to
News "1" *-- "1" Category : categorized_as

}
@enduml

```

Explanation:

1. Identifying Classes:
 - Category with an attribute value (String).
 - Date containing day_of_week, month, hours, and seconds (all Strings).
 - News with title, link, and author (all Strings).
 - Newspaper with language (String).
2. Defining Relationships:
 - A Newspaper is published on a specific Date (1 to 1).
 - A Newspaper reports multiple News (1 to many).
 - A News is published on a specific Date (1 to 1).
 - A News is related to exactly one Newspaper (1 to 1).
 - A News is categorized under a Category (1 to 1).

This diagram fully represents your requirements using PlantUML syntax. 🚀

ChatGPT 4:

To create a detailed class diagram for the specified requirements, we'll first break down the requirements into classes, attributes, and relationships as follows:

Classes and Attributes

1. Category:
 - value: String
2. Date:
 - dayOfWeek: String
 - month: String
 - hours: Int
 - seconds: Int
3. News:
 - title: String
 - link: String
 - author: String
4. Newspaper:
 - publicationDate: Date
 - language: String

Relationships

- A Newspaper reports many News.
- Each News is related to exactly one Newspaper.
- News have a Date indicating when they are published.
- A Newspaper is published on a specific Date.

- News can belong to a Category.

Now, using PlantUML, we can represent these relationships and classes:

```
@startuml
!theme plain

class Category {
    value : String
}

class Date {
    dayOfWeek : String
    month : String
    hours : Int
    seconds : Int
}

class News {
    title : String
    link : String
    author : String
}

class Newspaper {
    language : String
}

' Relationships
News "1" -- "0..1" Category : has >
News "1" -- "1" Date : published on >
Newspaper "1" -- "*" News : reports >
Newspaper "1" -- "1" Date : publicationDate >

@enduml
```

This diagram uses standard UML notation to represent the classes and their relationships. It clearly shows how different classes are interconnected through various associations and the attributes they hold, following the requirements you've provided.

ChatGPT Agent UML Diagram Expert (by Antoine Boucher):

Based on your requirements, here's the breakdown of the class diagram:

1. Identifying the Classes:
 - Category with an attribute value: String
 - Date with attributes:
 - dayOfWeek: String
 - month: String
 - hours: String

- seconds: String
 - News with attributes:
 - title: String
 - link: String
 - author: String
 - Newspaper with attributes:
 - language: String
 - Relationships:
 - A News has one Date
 - A Newspaper has one Date
 - A Newspaper has multiple News
 - Each News belongs to only one Newspaper
-

PlantUML Representation

```
@startuml
!theme plain
package "News System" {
    class Category {
        value : String
    }

    class Date {
        dayOfWeek : String
        month : String
        hours : String
        seconds : String
    }

    class News {
        title : String
        link : String
        author : String
    }

    class Newspaper {
        language : String
    }

    // Relationships
    News "1" --> "1" Date : published on
    Newspaper "1" --> "1" Date : published on
    Newspaper "1" o-- "0..*" News : reports
    News "1" --> "1" Newspaper : belongs to
}
@enduml
```

This diagram represents the relationships and attributes exactly as required. Do you need any modifications or additional details? 😊

GEMINI 2.0 FLASH

Here's the class diagram generation process, following a structured approach:

1. Identify Classes:

- Category
- News
- Date
- Newspaper

2. Identify Attributes:

- Category: value (String)
- News: title (String), link (String), author (String)
- Date: dayOfWeek (String), month (String), hours (String), seconds (String)
- Newspaper: language (String)

3. Identify Relationships:

- A Newspaper is published on a specific Date.
- A Newspaper reports many News.
- A News is published on a specific Date.
- A News is related to one Newspaper.
- A News belongs to one Category.

4. Cardinality of Relationships:

- Newspaper to Date: 1 to 1
- Newspaper to News: 1 to * (many)
- News to Date: 1 to 1
- News to Newspaper: 1 to 1
- News to Category: 1 to 1

5. PlantUML Representation:

```
@startuml
!theme plain

package Newspaper {

class Category {
    value : String
}

class News {
    title : String
    link : String
    author : String
}

class Date {
    dayOfWeek : String
}
```

```

    month : String
    hours : String
    seconds : String
}

class Newspaper {
    language : String
}

Newspaper "published on 1" *-- Date : publicationDate
Newspaper "reports 1..*" -- News : includes
News "published on 1" *-- Date : publicationDate
News "related to 1" *-- Newspaper : reportedIn
News "belongs to 1" *-- Category

}
@enduml

```

Explanation of PlantUML Code:

- package Newspaper { ... }: Groups the classes within a package named "Newspaper" for better organization.
- class ClassName { attributes }: Defines a class with its attributes and their types.
- Class1 "cardinality1" -- "cardinality2" Class2 : relationshipName: Defines a relationship between two classes with specified cardinalities and an optional relationship name. The * indicates "many". 1 indicates "one". The direction of the line indicates the direction of the relationship. *-- is a solid line with an arrowhead on the right, meaning aggregation or composition.

This PlantUML code accurately reflects the requirements provided, showing the classes, their attributes, and the relationships between them, including cardinalities.

Deepsheek with DeepThink:

```

@startuml
!theme plain

class Category {
    value : String
}

class News {
    title : String
    link : String
    author : String
}

class Newspaper {
    language : String
}

```

```

}

class Date {
    dayOfWeek : String
    month : String
    hours : Integer
    seconds : Integer
}

News "1" *-- "1" Date : publishes on
Newspaper "1" *-- "1" Date : published on
Newspaper "1" *-- "*" News : reports >

@enduml

```

****Step-by-Step Explanation:****

1. **Identify Classes:**

- ****Category****: From "A category has a value".
- ****News****: From multiple requirements about titles, links, dates, and relation to Newspaper.
- ****Newspaper****: From requirements about publication date, language, and reporting news.
- ****Date****: Encapsulates date components (day of week, month, hours, seconds) for News and Newspaper.

2. **Define Attributes:**

- ****Category****: `value : String`.
- ****News****: `title`, `link`, `author` (all Strings).
- ****Newspaper****: `language : String`.
- ****Date****: `dayOfWeek`, `month` (Strings); `hours`, `seconds` (Integers).

3. **Establish Relationships:**

- ****News ↔ Date****: Composition (1-to-1) since each News has its own publication date.
- ****Newspaper ↔ Date****: Composition (1-to-1) for the newspaper's publication date.
- ****Newspaper → News****: One-to-many composition (1 Newspaper reports * News, each News belongs to 1 Newspaper).

4. **Exclusion of Category Relationships:**

- The problem does not specify how Category interacts with other classes, so it remains isolated.