



DEPARTMENT OF
COMPUTER SCIENCE

TIAGO GONÇALO BANDOS RODRIGUES

BSc in Informatics Engineering

GENERATIVE AI FOR CLASS DIAGRAM MODELING FROM SOFTWARE REQUIREMENTS

Dissertation Plan
MASTER IN COMPUTER SCIENCE AND ENGINEERING
NOVA University Lisbon
February, 2025



DEPARTMENT OF
COMPUTER SCIENCE

GENERATIVE AI FOR CLASS DIAGRAM MODELING FROM SOFTWARE REQUIREMENTS

TIAGO GONÇALO BANDOS RODRIGUES

BSc in Informatics Engineering

Advisers: João Araujo

Associate Professor, NOVA University Lisbon

Ana Moreira

Full professor, NOVA University Lisbon

Dissertation Plan

MASTER IN COMPUTER SCIENCE AND ENGINEERING

NOVA University Lisbon

February, 2025

ABSTRACT

Software modeling demands a good understanding of the solution domain, as well as requirements specification. The resulting design models serve as blueprints for the implementation phase, outlining system architecture, hardware and software requirements, and the overall system structure. To automate the creation of such design models various methods have been proposed over the years, including approaches based on model-driven development, linguistic rules and patterns, rule-based systems, and statistical or machine learning techniques. More recently, Large Language Models (LLMs) have gained prominence. While LLMs often show promising results they commonly lack sufficient contextual awareness — an essential factor in accurately transforming requirement specifications into models such as class diagrams. This dissertation will, employ prompt engineering techniques and a Retrieval-Augmented Generation framework to enhance the contextual awareness and accuracy of LLMs when generating models from a requirement specification. As a first step, we conducted a systematic mapping study to better understand the existing body of knowledge. Building on our findings, we began experimenting with various prompt engineering strategies. Our aim is to develop an improved method that enhances the contextual understanding of LLMs and streamlines the automated creation of design models from requirement specifications.

Keywords: LLM, Requirement modeling, Retrieval-Augmented Generation, UML diagrams, GAI

RESUMO

A modelação de software exige uma compreensão aprofundada do domínio da solução, bem como das especificações de requisitos. Os modelos de design resultantes servem como “blueprints” para a fase de implementação, definindo a arquitetura do sistema, os requisitos de hardware e software, e a estrutura global do sistema. Para automatizar a criação destes modelos de design, foram propostas várias abordagens ao longo dos anos, incluindo estratégias baseadas em desenvolvimento orientado por modelos, regras e padrões linguísticos, sistemas baseados em regras e técnicas estatísticas ou de aprendizagem automática. Mais recentemente, os Large Language Models (LLMs) ganharam destaque. Embora estes modelos apresentem frequentemente resultados promissores, carecem muitas vezes de consciência contextual suficiente — um fator essencial para transformar corretamente as especificações de requisitos em modelos, como por exemplo diagramas de classes. Esta dissertação irá recorrer a técnicas de prompt engineering e a uma framework de Retrieval-Augmented Generation para reforçar a consciência contextual e a precisão dos LLMs na geração de modelos a partir de uma especificação de requisitos. Como primeiro passo, foi realizado um estudo de mapeamento sistemático para compreender melhor o estado atual do conhecimento. Com base nessas conclusões, começámos a experimentar várias técnicas de prompt engineering. O nosso objetivo é desenvolver um método aprimorado que aprofunde a compreensão contextual dos LLMs e facilite a criação automática de modelos de design a partir de especificações de requisitos.

Palavras-chave: LLM, Modelação de requisitos, Retrieval-Augmented Generation, diagramas UML, GAI

CONTENTS

List of Figures	ix
1 Introduction	1
1.1 Context and Motivation	1
1.2 Problem statement and objectives	1
1.3 Expected contributions	3
1.4 Document structure	3
2 Background	5
2.1 Software Modeling	5
2.1.1 Benefits for developers and stakeholders	6
2.1.2 Core components of UML class diagrams	6
2.1.3 UML design class diagrams	7
2.2 Large Language models (LLMs)	8
2.2.1 Architecture of LLMs	8
2.3 Techniques used to improve output of LLMs	9
2.3.1 Prompting engineering	9
2.3.2 Retrieval augmented generation	10
2.4 Systematic mapping studies	12
2.4.1 Planning stage	13
2.4.2 Conducting stage	13
2.4.3 Discussion of results	13
2.5 Summary	14
3 State of the Art	15
3.1 Research Methodology	15
3.1.1 Planning Stage	16
3.1.2 Conducting stage	18
3.1.3 Discussion of the results	18
3.2 Synthesis of the results	23

3.3	Threats to validity	24
3.4	Related Work	24
3.5	Summary	27
4	Experiments with Generative AI techniques and tools	29
4.1	Experiments with prompt techniques and different LLM models	29
4.1.1	Evaluation protocol	30
4.1.2	Results and Discussion	31
4.2	Experiments with a Retrieval-Augmented Generation (RAG) Tool	32
4.2.1	Experimental Setup	32
4.2.2	Results and Discussion	33
4.3	Experimenting Self-improving	34
4.3.1	Experimental Setup	35
4.3.2	Results and Discussion	40
4.4	Summary	41
5	An approach to automate the modeling class diagrams	43
5.1	Prompt technique and Model used	43
5.2	Retrieval Augmented Generation System implemented	43
5.3	Self-improve approach	43
5.4	Agent implementation	43
5.5	Challenges	43
5.6	Practical Demonstration	43
5.7	Summary	43
6	Evaluation	45
6.1	Experiment Purpose and Procedure	45
6.2	Results	45
6.3	Discussion	45
6.4	Summary	45
7	Conclusions	47
7.1	Contributions	47
7.2	Limitations	47
7.3	Future Work	47
	Bibliography	49
	Appendices	
A	Papers selected during the systematic mapping study	55
B	Prompts used for Experiments	57

B.1	Zero-shot Prompt	57
B.2	Few-shot Prompt	58
B.3	Few-shot Chain-of-thought Prompt	63

LIST OF FIGURES

2.1	UML notation for relationships on a class diagram [9]	7
2.2	Example of relationships on a class diagram [9]	7
2.3	Basic architecture of a RAG system [30]	11
2.4	Naive RAG [34]	12
2.5	Advanced RAG [34]	12
3.1	Process of Identifying and Collecting Studies	19
4.1	Qualitative results of prompt techniques and LLM tests	31
4.2	Qualitative results of overall performance of LLMs tests	32
4.3	Different class diagrams generated using NotebookLM compared to the ground truth	34
4.4	Threshold hold test	40
4.5	Effect of the self-improvement loop on the class diagram	42

LISTINGS

4.1	System Description	29
4.2	Adapted Zero-shot prompt	33
4.3	Self improve	35
4.4	Self evaluation	37
B.1	Zero-shot prompt	57
B.2	Few-shot prompt	58
B.3	Few-shot Chain-of-thought Prompt	63

LIST OF LISTINGS

4.1	System Description	29
4.2	Adapted Zero-shot prompt	33
4.3	Self improve	35
4.4	Self evaluation	37
B.1	Zero-shot prompt	57
B.2	Few-shot prompt	58
B.3	Few-shot Chain-of-thought Prompt	63

INTRODUCTION

This research was inspired by recent advancements in General Artificial Intelligence (GAI) and the ongoing need to automate the process of requirement modelling. Automating this process could significantly improve communication with stakeholders and streamline requirement management. This introductory chapter provides an overview of the context and motivation of this dissertation, defines the problem statement and the associated challenges, and presents the objectives of this thesis preparation along with the expected contributions.

1.1 Context and Motivation

Software modeling an essential process in software engineering, that involves creating abstract representations of the most significant aspects of the software, facilitating the identification of potential issues early, improving design consistency, and providing a blueprint for implementation and maintenance. Traditionally, this process is carried out manually by software engineers, which can be time-consuming and heavily reliant on human expertise [1].

Over the past two years, several approaches with a combination of LLM and rule-based system [2] or machine-learning systems [3] have been developed to automate the process of generating design models from requirements, with the goal of improving efficiency and minimizing dependence on manual effort. Although these approaches have shown promising results, they still present limitation in terms of accurately identifying complex relationships, often producing hallucinated output [4]. Additionally, issues such as ambiguity in natural language [5] and limited domain-specific knowledge [6] limit the adaptability and accuracy of these techniques in practical real-world scenarios.

1.2 Problem statement and objectives

We defined the problem statement as **the lack of knowledge domain, and the quality of the requirements presented by LLM, which lead to incomplete and inaccurate requirement**

models. The problem statement was based on the findings of the systematic mapping study we conducted. The discussion that follows identifies and justifies the main problem that comprises the problem statement, the challenges that arise from these problems, and a brief description of what we can do to solve them.

Problem: The lack of domain-specific knowledge and the quality of the requirements presented by LLM lead to incomplete and inaccurate requirement models.

Our systematic mapping study highlights key challenges impacting the completeness and accuracy of requirement models generated. Main issues include ambiguity, vagueness, and inconsistency in the input requirements, which affect the model's ability to produce reliable output. [7]. To mitigate these issues, clear and well-structured input specifications, combined with iterative prompting, are critical measures to enhance the accuracy and relevance of generated models [5]. In this context, prompt engineering plays a crucial role in addressing input-related challenges, helping to guide models toward more precise and contextually appropriate results. Beyond input quality, LLMs exhibit problems in identifying complex relationships and attributes, which often leads to lower correctness rates in the generated models [8]. This limitation can be associated with the fact that the models lack domain-specific knowledge, resulting in outputs that are not only incomplete but sometimes hallucinated or contextually incorrect. Furthermore, the restricted scope of an LLM's training dataset limits its ability to generalize effectively across diverse or specialized domains. The identification of these difficulties led to the definitions of the following challenges:

Challenge 1: Define the best prompt to generate models from requirements.

The performance of LLMs depends heavily on the quality of the prompts, as noted in the systematic mapping study. Techniques like zero-shot, few-shot and chain-of-thought (CoT) prompting have shown potential to guide LLMs in generating more accurate and relevant outputs. It's important the prompts are clear, detail and domain-specific to ensure accurate and complete models.

Challenge 2: Defining the data relevant to improve the domain knowledge.

LLMs often struggle with domain-specific tasks due to the general nature of their training data. This can lead to hallucinations and incomplete outputs, specially for complex or specialized requirements. Incorporating domain-specific knowledge is a critical step in addressing this limitation. This can be done by implementing a Retrieval Augmented Generation (RAG) system. Identifying and collect relevant data for augmenting LLMs can improve their contextual understanding and ability to generate accurate models.

Challenge 3: Avoid ambiguity, vagueness, and incompleteness in the requirements.

Natural language requirements are naturally ambiguous, vague or inconsistent, which can lead to errors in automated model generation. This challenge ties on the analysing

the requirements in order to mitigate the ambiguity and vagueness of the requirements by refining it. Its important to have clear and consistent initial requirements before automating the creation of the model.

Objectives

The main objective of this thesis is to propose an approach to automate the design modelling from requirements. To achieve our purpose, we initially focus on creating prompts that can improve the quality of the requirements. Furthermore, we aim to implement a RAG system and a process to deal with the ambiguity, vagueness, and incompleteness in the requirements before generating design models.

1.3 Expected contributions

Through this dissertation, we expect to contribute to the requirements engineering and software engineering fields with the following:

- A structured prompt template designed to improve the translation of natural language requirements into design models with better accuracy and coherence.
- A systematic evaluation of prompt techniques to identify the most appropriate for generating and comprehensive class diagrams.
- A domain-aware system that enhances generated models by incorporating contextual domain knowledge, improving relevance and precision.
- An automated modelling framework that improves the efficiency and reliability of the requirement-to-model translation process.

1.4 Document structure

This document includes three chapters and is structured as follows:

- Chapter 2, Background, provides an overview of software modeling, large language models, and the principles underlying systematic mapping studies, along with an introduction to their methodology.
- Chapter 3, State of the art, presents the conducted systematic mapping study and a discussion of its results, and provides an overview of the current state.
- Chapter 4, Automation of design modeling using LLMs and RAG approach, presents the approach thought to automate design modeling and the results of the early experiments conducted.

BACKGROUND

The present research work aims to propose an approach to improve requirements modeling by leveraging Generative AI (GAI) techniques to automate the generation of UML diagrams during the software design phase. The purpose of this chapter is to briefly introduce the main concepts in the field of software modeling that serve as the foundation for this thesis, namely tools, techniques, and approaches for translating requirements into design models, with a particular focus on UML class diagrams and their key components (classes, attributes, operations, and relationships). Additionally, we provide an overview of Generative AI and Retrieval-Augmented Generation (RAG), which form the core technologies employed in this research. This chapter also discusses related work and systematic methodologies, such as systematic mapping study, conducted to identify gaps and opportunities addressed in this thesis.

2.1 Software Modeling

Modelling is a fundamental practice in science and engineering, used to create abstract representations of a system at varying levels of precision and detail. These models serve as analytical tools, enabling a deeper understanding of the system's structure, behaviour, and constraints throughout its development process [9] This thesis will use Unified Modelling Language (UML) to produce design models from requirements.

Unified modelling language was developed to provide a standardized graphical language and notation for describing object-oriented models. UML notation is one of the most use language for describing software requirements, analysis and design models. The first time UML was introduced was by Grady Booch, James Rumbaugh, and Ivar Jacobson in 1999 [10] and after was officially adopted in January 1997 by OMG. In the OMG'S view, "modeling is the designing of software applications before coding."

Unified Modeling Language (UML) is not only used for object-oriented design but also for modeling and functional aspects of systems [11]. The current standard version, UML 2.5.1, continues to evolve and supports various diagrams for application development, including use case diagrams, class diagrams, object diagrams, communication diagrams,

sequence diagrams, state machine diagrams, activity diagrams, composite structure diagrams, and deployment diagrams. In this thesis, we focus on class diagrams for design modeling. Class diagrams are the most widely used UML diagrams [12], providing a visual representation of a system's structure by illustrating classes, their attributes, methods, and the relationships among them. In addition to aiding system visualization, class diagrams also serve as a documentation tool and design blueprint, ensuring consistency and alignment with the system's intended functionality.

2.1.1 Benefits for developers and stakeholders

Class diagrams present benefits for the developers and the stakeholders both benefit from clear communication, as it acts as a universal language, reducing the gap between technical and non-technical stakeholders. By providing a clear and concise visual representation, it guarantees that everyone involved is in understanding. Also, it helps identifying potential design issues early in the development process because of the clear and concise visualization of the design. Additionally, class diagrams help assuring quality by for example ensuring that the system respects certain design principles or patterns, which can further improve the quality and maintenance of the software [13].

2.1.2 Core components of UML class diagrams

In UML Class diagram, classes are represented as rectangular boxes, with their attributes and operations detailed inside. The relationships between class are represented using different types of connectors, which demonstrate structural and behavioural associations within the system. There are four primary types of relationships: associations, whole/part relationships, and generalization/specialization relationships and dependencies. An association represents a static structural relationship between two or more classes. It defines how instances of one class are related to instances of another class [9]. Associations can have multiplicity, which specifies how many instance of one class can be associated with instance of another class, (see Figure 2.1 a). The multiplicity of an association can be optional (0..1), exactly one (1), zero or more (*), numerically specified (m..n), or one or more (1..*) Whole/part relationships define hierarchical relationships between objects. There are, two types, Aggregation and Composition. Aggregation represents a weak relationship between the whole and its parts, where the part can exist independently of the whole. It is portrayed with a hollow diamond at the end of the association. In contrast, composition represents a strong relationship where the part cannot exist independently of the whole. It is presented as a filled diamond at the end of the association (see Figure 2.1 b). Generalization/Specialization Hierarchy is an inheritance relationship, where a subclass inherits properties from a superclass. This allows for the reuse of common attributes and behaviors. It is represented by an arrow joining the subclass (child) to the superclass (parent) (see Figure 2.1 c) A dependency relationship, is often used to show how packages

are related, and represents a weaker relationship where one class depends on another for its operation




Figure 2.1: UML notation for relationships on a class diagram [9]




Figure 2.2: Example of relationships on a class diagram [9]

2.1.3 UML design class diagrams

The design process involves several key steps to ensure that the diagram accurately models the system's domain and behavior. By following a structured approach, designers can systematically identify the key components, define their relationships, and establish clear interactions within the system. The following steps outline a methodical process for designing a UML class diagram:

1. **Requirements Analysis:** understand the system's requirements by identifying the main entities or classes that will be part of the system.
2. **Identifying Relationships:** identify how the class will interact with the others by determining the type of relationships.

3. **Define Multiplicity:** determine the multiplicity of the association, i.e. specify how many instances of one class may relate to a single instance of another class [9].
4. **Add attributes and methods:** for each class list attribute (properties, fields) and methods (functions), it will have.
5. **Draw the diagram:** begin by creating class boxes with their names. Next, add attributes and methods to define each class's structure and behavior. Finally, establish relationships between classes, ensuring proper associations, generalizations, and dependencies, while specifying multiplicity where necessary.
6. **Review and refine:** review the diagram for accuracy, completeness, and consistency. Refine it as needed to ensure clarity and correctness.

There exists many different tools and software used to representing class diagrams, the most popular are Microsoft Visio [14], StarUML [15], PlantUML [16], and Lucidchart [17].

2.2 Large Language models (LLMs)

LLMs are models trained on vast amounts of textual data that excel in NLP tasks [18]. They started to gain popularity after the release of OpenAI's ChatGPT model in November 2022, which is built using the transformer architecture. It exhibits capabilities such as creative writing, translation, instruction following, summarizing.

While the LLMs can be powerful tools, they are only as good as the data they are trained on. If the training data is biased the outputs will be biased [19]. Therefore, overreliance on LLMs can lead to skill degradation and incorrect assessment [20]. It is important to consider and assess the risk of using LLMs for specific use cases and check their outputs for errors.

2.2.1 Architecture of LLMs

The general architecture consists of multiple layers, including feedforward layers, embedding layers, and attention layers. The Transformer architecture, introduced by Vaswani et al. in 2017 [21], revolutionized NLP by enabling efficient parallel processing of tokens. This capability is achieved through its multi-head self-attention mechanism, which allows for parallelized model training on large datasets. Their architecture is composed of the following key components:

1. **Input Embeddings:** This layer divides the input text into tokens that are embedded into a continuous vector representation that works as a lookup table.
2. **Positional Encoding:** Encoding does not naturally encode the word order; therefore, positional information is added to each word's vector representation so that it keeps the order of the words as in the text input.

3. **Encoder:** Analyzes the input text and creates several hidden states that preserve the context and meaning of the text data. It processes the input sequence into a representation of all the information the model has learned. This layer consists of two key components:
 - **Multi-head attention:** Self-attention mechanisms are employed, allowing the model to capture different types of relationships and attend to various parts of the input sequence simultaneously.
 - **Fully connected layer:** Processes the attention output further to improve representation. It also includes a normalization component that is applied after each sub-component or layer, helping stabilize the learning process and improve the model's generalization.
4. **Decoder Layer:** The output from the encoder is fed into the decoder, which generates text sequences using two multi-headed attention layers, a feed-forward layer, and a linear layer that acts as a classifier. A SoftMax layer then computes the word probabilities. The decoder runs N times, using the encoder's output and the sentence decoded so far, to ensure coherence in the generated text.

2.3 Techniques used to improve output of LLMs

The quality of a prompt plays a crucial role in determining the output of a LLM. A prompt is a textual input that provides a context to the model, guiding it to generate a response based on pre-trained knowledge. [22]. For optimal performance, prompts must be well-structured, accurate, coherent and contextually appropriate. To enhance the effectiveness of LLM outputs, various techniques have been developed, including prompt engineering, which involves crafting optimized inputs for better responses, and Retrieval-Augmented Generation (RAG), which enhances responses by integrating external knowledge sources.

2.3.1 Prompting engineering

It's very important to find the right prompt, as LLMs are sensitive to prompt design [23]. Finding the right prompt normally requires extensive manual effort. Prompting engineering goal is to find a prompt that achieves the best performance on a given dataset when using a given LLM as the task model. These are the most used techniques:

- **Zero-shot prompting:** involves crafting a single clear and concise instruction without providing examples of the task at hand, taking advantage of the pre-trained knowledge of LLMs. Since it depends on the pre-trained knowledge, it can struggle with complex tasks requiring nuanced understanding. This method is better suited for straightforward tasks and is simple and efficient. It eliminates the need for task-specific fine-tuning, dramatically expanding the range of tasks a model can perform.

- **Few-shot prompting:** introduces a few examples of the task within the prompt to provide better context and clarify expectations. It typically follows a structure of input-output pairs, consisting of an input and the corresponding output, as well as the prompt describing the task the model must perform. This approach leads to better accuracy and increased relevance, as it provides the expected structure of the output. However, there is a risk of overfitting depending on the quality and relevance of the examples.
- **Chain-of-thought prompting:** guides the model to work through intermediate reasoning steps, making it more adept at solving complex tasks such as math problems, commonsense reasoning, and symbolic manipulation. The prompts typically include examples where the problem is decomposed into manageable steps, breaking down complex questions and demonstrating reasoning steps.

2.3.2 Retrieval augmented generation

RAG is a hybrid technique that combines information retrieval with language model generation, to improve the accuracy and contextual relevance of outputs, addressing common issues like hallucination problem [24]. Hallucination occurs when a language model generates inaccurate or fabricated information, particularly when handling queries beyond their training data or requiring current information[25]. RAG mitigates this by integrating external knowledge bases, thereby enhancing the performance of LLMs on knowledge-intensive task [26]. RAG integrates two key components [27] as demonstrate in the Figure 2.3.

- **Retrieval mechanism:** This component is responsible for retrieving relevant documents or information from an external knowledge source. Several mechanisms are commonly used, ranging from more traditional methods such as BM25 [28] to more sophisticated techniques like Dense Passage Retrieval (DPR) [29].
- **Generation module:** The generation module processes the retrieved information and produces human-like text by combining the contextual input with the retrieved knowledge.

RAG operates with two distinct types of memory parametric and non-parametric [31]:

- **Parametric memory:** Refers to the internal knowledge already present in the model's parameters during training, represented in the weight embeddings.
- **Non-parametric memory:** Refers to the external knowledge source that the model retrieves during inference. These external sources can include databases, web pages (e.g., Wikipedia), or structured knowledge graphs, enabling the model to answer queries with current or domain-specific information.




Figure 2.3: Basic architecture of a RAG system [30]

This distinction allows to combine static with dynamic information, significantly enhancing flexibility and accuracy.

RAG models can be classified as two main types, based on how they handle retrieved documents during the generation process [32]:

- **RAG-Sequence Model:** Only the retrieved document is used throughout the generation of an entire sentence or response.
- **RAG-Token Model:** This model allows retrieving different documents for each target token. It selects a distinct latent document for each generated token, retrieves the top k documents, and produces the output sequence probability for each document.

There are three main categories of RAG approaches [33]:

- **Naïve RAG:** The first paradigm of RAG being adopted. It follows a process that includes indexing, retrieving, augmenting, and generating responses (see Figure 2.4).
- **Advanced RAG:** In addition to the steps involved in Naïve RAG, pre-retrieval and post-retrieval processes are included to improve the quality of responses (see Figure 2.5).
 - **Pre-retrieval process:** The main goal is to improve the quality of the content being indexed.
 - **Post-retrieval process:** The main goal is to enhance the way the chunks retrieved are merged with the user query to form the prompt. Techniques such as re-ranking and prompt compression are used to achieve this.
- **Modular RAG:** Divides the retrieval and generation components into independent, interchangeable modules. This allows each module to be independently developed, optimized, or swapped out, enabling experimentation with various retrieval techniques and generation models.




Figure 2.4: Naive RAG [34]




Figure 2.5: Advanced RAG [34]

2.4 Systematic mapping studies

Systematic mapping studies, also referred as scoping studies, are a structured and unbiased methodology for identifying, categorizing, and analyzing the existing literature on a specific research topic [35]. The main goal is to give a wide overview of a research area, to understand the extent of existing studies and identify gaps in knowledge. This methodology consists of systematically searching the literature to determine which topics have been covered, where has been published and in what form [36]. The systematic mapping studies are typically divided into three main stages: planning, conducting and discussion of results. Each stage has a defined process to ensure the reliability and validity of the study. We are going to implement a systematic mapping study to identify the current

state of the art in the use of LLMs for requirements engineering, this way understanding better the gaps and possible improvements in the current state of the art.

2.4.1 Planning stage

The first part of the systematic mapping study is to define the research questions that will be driving the research. These questions are crucial, as they are going to guide the search process, help identify relevant studies and establish the focus of data extraction and analysis. Effective research questions, give an overview of the current practices regarding the specific topic and identifying current gaps in knowledge [37].

Additionally, we must define the search strategy to guarantee a comprehensive coverage. This involves composing a search string with a set of keywords based on the main terms of the research questions and driven by their objectives. A properly designed search string assures a search process that is systematic, replicable and unbiased.

Inclusively, we define the inclusion and exclusion criteria with the focus on the research questions to ensure an appropriate and reliable classification. Inclusion criteria focus on determine studies that address the research questions while exclusion criteria filter out unrelated or irrelevant studies. For example:

- **Inclusion criteria:** Studies that respond to the main research question.
- **Exclusion criteria:** Studies that are in other languages then English.

2.4.2 Conducting stage

In this stage, implement the defined search strategy, by applying the search string in digital libraries and conducting the screening process. Articles that correspond to the exclusion criteria are excluded, similarly, those that provide relevant information, corresponding to the inclusion criteria, are included.

Studies can be considered unrelated to our research just by reading their title and abstract, therefore, they can be excluded without further reading. However, if the abstract isn't clear if corresponds to research questions, the conclusions or any part of the full paper should be read to clarify how it should be classified.

After the initial screening, data extraction is performed. Relevant information from the selected studies is collected, such as methodology implemented, conclusions, publication details, and relationship to the research questions.

Data extraction must be conducted systematically to guarantee the reliability and reproducibility of the results.

2.4.3 Discussion of results

Discussion phase involves analyzing the results of the conducting stage and the responses to the research questions, to gain a deeper understanding of state literature, identify the

gaps, trends and underexplored areas on the topic. This phase includes three main tasks, analyzing trends, identifying gaps and documenting results.

For example, a systematic study in natural language processing for requirements engineering might analyze the natural language processing tools being developed in the requirement engineering field, such as OICSI [38].

2.5 Summary

This chapter gives an overview of the main concepts to automating the creation of design models from requirements. It starts by introducing the importance of software modeling and the use of UML class diagrams to represent the structure of a system. Software modeling is explain with a focus on UML class diagrams, explaining their components, relationships, benefits for developers and stakeholders, and describing the design process, highlighting key steps such as requirement analysis, identifying relationships, defining multiplicity, adding attributes/methods, and refining the model. The chapter then explores LLMs, describing their Transformer-based architecture and key components like multi head self-attention, embeddings and decoders. While LLMs have advanced NLP applications, they face challenges such as context limitations, hallucinations, and dependency on training data. To improve their performance in requirement modeling, two techniques are examined: prompt engineering (zero-shot, few-shot, and chain-of-thought prompting) and RAG, which integrates external knowledge to enhance accuracy. Finally, the chapter discusses systematic mapping studies, a structured method for analyzing existing research. It describes the planning, conducting, and discussion stages of the study conducted in this work, which aims to identify gaps in LLM-based requirement modeling. These insights serve as the foundation for the research, helping define strategies to enhance LLM-driven software modeling automation.

STATE OF THE ART

This dissertation explores the automation of requirements modelling, with the systematic mapping study being useful to identify the state of art and understand possible improvement to implement. The systematic mapping study provides an overview of existing knowledge on the topic while uncovering gaps that require further exploration [36]. It starts with the specification of the research questions and the implementation of the research methodology. Then, a search strategy is defined to detect relevant literature, that in turn will be submitted to an inclusion and exclusion criteria and a quality assessment to select the final primary studies. Lastly, data from the selected studies is extracted and analysed to assess the existing evidence regarding the topics of the previously defined research questions. The results offer insight into the advancements and limitations in the field, giving a better understanding of possible improvements in automations of requirements modelling. This chapter outlines the steps taken to conduct the systematic mapping study and elaborates on the key findings that inform this dissertation.

3.1 Research Methodology

The overall approach of the research methodology was to analyze current approaches used to automate requirements modeling and design modeling, with a particular focus on methods utilizing LLMs. The goal is to explore the capabilities and challenges of leveraging LLMs in transforming requirements into design models, as well as their role in automation within the software development modeling process.

To achieve this, we conducted a systematic mapping study methodology composed by three key stages: planning, conducting, and reporting. The planning stage involved establishing research questions, defining search and study selection strategies, performing a quality assessment of studies, and developing a data collection and extraction strategy. In the conducting stage, we apply the plan prepared and analyse the preliminary results obtained from the execution of the search strategy. Finally, the reporting stage included a thorough analysis and discussion of the findings.

3.1.1 Planning Stage

The first phase of the systematic mapping study, comprises five main activities defining research questions, formulating a search strategy, establishing a study selection approach, developing a quality assessment strategy, and determining data collection and extraction methods.

Research Questions The objective of this study is to provide a comprehensive overview of the existing approaches for automating design modeling. Consequently, the research questions were designed to address key aspects of automating design modeling using LLMs and GAI. These questions aim to offer a structured understanding of the state-of-the-art in this domain while identifying gaps and opportunities for future improvements. In the Table 3.1, the research questions and the motivation behind are presented.

Research Questions	Motivation
RQ1. How have LLMs been used to derive design models from requirements?	To investigate how LLMs are applied to transform textual requirements into design models, providing insight into practical applications.
RQ2. What are the strengths and limitations of using LLMs in this context? (deriving design models from requirements)	To gain an overview of the potential benefits and challenges of using LLMs.
RQ3. What GAI tools have been applied for producing class diagrams and object-oriented artifacts in software development?	To identify which GAI models are most commonly used.
RQ4. What are the key approaches in automating functional requirements into design models using AI?	To discover methodologies that leverage AI to automate the process of requirement modeling.

Table 3.1: Research Questions

Search Strategy The search strategy involved identifying primary studies using an automatic search method. The search string was constructed with three key elements, examples of LLMs widely used in the industry, terms conveying the concept of requirement modeling, and synonyms for methodologies. The search string is presented in Table 3.2.

The search string was run as a query on IEEE Xplore [39] and ACM Digital Library [40]. These libraries were selected for their comprehensive collections of peer-reviewed publications in software engineering and their user-friendly interfaces that allow bulk downloading of search results in CSV format. Besides the search question we implemented a filter to only show papers from 2019 and forward because we believe that the most

Concept	Keywords
Large Language Models	("Large Language Models" OR "LLMs" OR "Chat-GPT" OR "LLAMA" OR "Gemini")
Requirement Modeling	("design model*" OR "requirement model*" OR "class diagram" OR "requirement specification" OR "architecture model" OR "component diagram" OR "sequence diagram")
Related terms for methodologies	("approach" OR "method" OR "technique" OR "tool" OR "process")

Table 3.2: Search keywords for requirement modeling

relevant papers are the most recent ones and do to the limit time-line we had to conduct this systematic mapping study.

Study Selection Strategy Studies identified through automatic searches were evaluated using inclusion and exclusion criteria to ensure relevance to the research questions. The evaluation was conducted in two iterations. The inclusion and exclusion criteria used in the study selection process are presented in Table 3.3. Given the prevalence of English in the scientific community, we decided to only select papers written in English. We also excluded duplicate papers, informal literature, and secondary studies to ensure the quality and relevance of the selected studies. The study selection process was conducted in two iterations. In the first iteration, the title and abstract of each study were reviewed, selecting those that met all inclusion criteria while discarding those that matched any exclusion criterion. In the second iteration, the full text of the pre-selected studies was analyzed, ensuring that only those fully aligning with the inclusion criteria were retained as final primary studies.

ID	Inclusion Criteria
IC1	Papers that answer at least one the research questions.
IC2	Peer-reviewed papers from journals, conferences, and workshops.
Exclusion Criteria	
EC1	Papers not written in English.
EC2	Duplicate papers, such as short and long versions of the same study.
EC3	Informal literature (e.g., slide shows, conference reviews, informal reports), secondary studies (e.g., reviews, surveys), and studies without practical applications.

Table 3.3: Inclusion and exclusion criteria

Data Collection and Extraction To simultaneously collect all the information needed to answer the research questions and manage the data that was extracted, we created a spreadsheet to record the content of each selected study. This way, we can ensure that all selected papers are subjected to the same extraction criteria. The spreadsheet can be accessed through the following link.

3.1.2 Conducting stage

The process to identify and collect the studies that provide answers to our research questions was conducted by following the steps of the Planning Stage 3.1.1. As mentioned previously, initially, was performed the automatic search by using a predefined search string on the IEEE Xplorer and ACM Digital Library, yielding a total of 419 papers from ACM and 591 from IEEE. Next, we read and analyzed the titles and abstracts of each potential paper to apply the first iteration of inclusion and exclusion criteria, narrowing the selection down to 32 papers. These 32 papers were then read in full during second iteration, leading to the final 15 papers. Lastly, we validated and extracted the data that answered the research questions from all the selected papers. The figure 3.1 summarizes the process and the table of the papers selected is presented in appendix A.

3.1.3 Discussion of the results

In the following subsections, we answer to each research questions, based on the analysis of the data extracted from the selected studies.

RQ1: How have LLMs been used to derive design models from requirements?

Through the analysed papers, several methods were identified in which LLMs have been employed to derive design models from requirements. Direct code generation is one of the most used methods, studies such De Bari et al. [41], Jahan et al. [2], and Ferrari et al. [5] used ChatGPT to generate PlantUML [16] code directly from requirements and user stories. Babaalla et al. [3] employed multiple models, including GPT-2, BERT and LLaMA-2, to transform textual tokens into vector representations. Basically encoding entities such as classes attribute and relationships. This vectors are then inputted into layers trained on bidirectional Long-short-term memory (LSTM) recurrent neural networks and tree structures. Eisenreich et al. [42] proposed utilization of LLMs to generate domain models, scenarios and architecture candidates, incorporating iterative human interactions to refine the outputs and evaluate architecture options. Requirements elements extraction is also used by Ruan et al. [6], Omar et al. [7] and Li et al [43]. The proposed platform “ Wisdom Requirement Communication” presented by Wang et al. [44] also does requirement elements extraction. Also, using techniques such as tokenization and part-of-speech tagging to pre process the requirements, it uses GLM 4-LLM to conduct advanced requirements analysis, identifying actors, use cases, and processes which are then converted into Mermaid format for visualization. Bernadi et al.




Figure 3.1: Process of Identifying and Collecting Studies

[45] combined LLaMA models with a Retrieval Augmented Generation (RAG) system to analyze and enhance UML diagrams, leveraging domain-knowledge to improve feedback. Chaaben et al. [46] applied LLMs to complete domain models by transforming incomplete models into textual representation using semantic mapping. These representations were used to generate suggested modelling elements missing, which were refined by applying a frequency-based ranking.

RQ2: What are the strengths and limitations of using LLMs in this context?

The strengths of using LLMs in this context identify are automation of design process, by allowing to generate UML diagrams, design models, architectural components and evaluation scenarios from textual requirements it reduces manual effort [2, 41, 42, 47]. Using prompt-based techniques enhanced efficiency of creation of design artifacts [43, 46].

Method/Approach	Studies	Techniques and Models employed	Output/Design Model Derived
Direct Code Generation	[2, 5, 41]	ChatGPT is used to directly generate PlantUML code from requirements and user stories.	PlantUML code representing design models.
Vector-Based Representation & LSTM Analysis	[3]	GPT-2, BERT, and LLaMA-2 transform textual tokens into vector representations; these vectors are then fed into bidirectional LSTM networks and tree structures.	Encoded entities (classes, attributes, relationships) that inform design models.
Iterative Domain Model Generation	[42]	LLMs generate initial domain models, scenarios, and architecture candidates, refined through iterative human interactions.	Refined domain models, scenarios, and architecture candidates.
Requirements Elements Extraction	[6, 7, 43]	LLM-based extraction techniques to identify key requirement elements.	Identification of actors, use cases, and processes from requirements.
Advanced Requirements Analysis	[44]	Utilizes tokenization, part-of-speech tagging, and GLM4-LLM for advanced requirements analysis; outputs are converted into Mermaid format for visualization.	Visual representations (via Mermaid) of actors, use cases, and processes.
UML Diagram Enhancement via RAG	[45]	Combines LLaMA models with a Retrieval Augmented Generation (RAG) system to integrate domain knowledge and enhance UML diagrams.	Enhanced UML diagrams with improved feedback based on domain knowledge.
Domain Model Completion	[46]	Transforms incomplete domain models into textual representations using semantic mapping; suggests missing modeling elements refined by frequency-based ranking.	Completed domain models with additional suggested modeling elements.

Table 3.4: RQ1:Methods for Deriving Design Models from Requirements Using LLMs

General-purpose LLMs like GPT-4 Chat-3.5 and LLaMA can be applied across various domains, making them versatile for software modelling task [42, 44] LLMs can produce code in formats like PlantUML and Mermaid can produce code in formats like PlantUML and Mermaid which give visualization support [7, 42]. LLMs gives flexibility in model generation by having the ability to extract and represent complex entities, attributes and relationships from natural language [3, 6].

On the other hand, LLMs show limitation such as semantic and domain knowledge gaps [5, 7, 41, 44]. Also, LLMs show issues with relationships, often incorrectly identifying and modelling relationships between entities [3, 8] or omitting key elements or misrepresenting it. [2, 46]. LLMs tend to incompletely handle requirements, due to complex or

incomplete input conditions [5, 42] or ambiguities and inconsistencies in textual requirements [6, 46]. The outputs are highly dependent on the quality of prompts are require expert guidance make harder the possibility of fully automated processes [8, 45]. Another limitation is the variability in the performance, as the results depend on factors such as input formats, prompting techniques, and the specific LLM versions being used. This leads to inconsistent performance in generations of modelling features like abstract classes or precise architectural patterns [3, 46, 47]. Additionally, the performance is strongly influenced by the training of each model [48]. The effectiveness of LLMs depends heavily on the availability and quality of external knowledge bases and example is the approach Bernardi et al. that improve the quality of the model generated by using RAG techniques [45].

Strengths	Key References
Automation of design process	Reduces manual effort by generating UML diagrams, architectural components, and evaluation scenarios from textual requirements [2, 41, 42, 47].
Improved efficiency via prompt-based techniques	Enhances speed of creating design artifacts [43, 46].
General-purpose applicability	LLMs (e.g., GPT-4, ChatGPT-3.5, LLaMA) are versatile across multiple domains [42, 44].
Visualization support	LLMs can produce code in PlantUML or Mermaid formats for diagram generation [7, 42].
Flexibility in model generation	Can extract and represent complex entities, attributes, and relationships from text [3, 6].

Table 3.5: RQ2: Strengths of using LLMs in software modeling

Limitations	Key References
Semantic and domain knowledge gaps	May misunderstand complex domain-specific information [5, 7, 41, 44].
Incorrect or omitted relationships	Often misidentifies or omits key relationships among entities [2, 3, 8, 46].
Incomplete handling of requirements	Struggles with complex, ambiguous, or inconsistent textual requirements [5, 6, 42, 46].
Reliance on prompt quality and expert guidance	Outputs depend heavily on carefully engineered prompts, limiting full automation [8, 45].
Performance variability	Depends on input formats, prompting techniques, LLM versions, and training data, leading to inconsistent results [3, 46–48].
Dependency on external knowledge bases	Quality can improve through Retrieval-Augmented Generation (RAG) or similar methods (e.g., Bernardi et al.) [45].

Table 3.6: RQ2: Limitations of using LLMs in software modeling

RQ3: What GAI models have been applied for producing class diagrams in the

context of software development?

The most use GAI model was the one developed by OpenAI, ChatGPT, different versions of the model were used in different applications [49]. The second most popular was LLaMA developed by Meta [50]. Also, in the Wang framework [44] it was used the GLM-4 model, developed by THU DM (Tsinghua University Distributed Machine Learning group) and supported by Zhipu AI [51].

GAI model	Papers
ChatGPT models	[1–3, 5–8, 41–43, 46, 47]
LLaMA models	[3, 42, 45]
GLM-4 model	[44]

Table 3.7: R3: Generative AI models used in the papers analysed

RQ4: What are the key approaches in the automation of functional and non-functional requirements into design models using AI?

One of the key approaches was using LLMs for automating the design models. The use of prompting engineering is fundamental in order to enhance the extraction and synthesis of design. Chaaben et al. use few-shot prompt learning to overcome the scarcity of specialized datasets required for traditional deep-learning approaches [46]. Ruan et al. [6] proposed a framework that uses zero-shot learning to extract the elements of requirements descriptions. Or the study of Chen et al. [6] that compares the performance of different prompting engineering. The prompt employed included a task description, a detailed domain specification, a format description and, depending on the technique used, reference examples with reasoning steps to guide the model's response. Another is a rule-based approach like the one presented in the study by Jahan et al. that uses preprocessing methods to deal with compound sentences and grouping consecutive nouns, then applying NLP heuristic that extract the elements from the requirements. He then compared a rule-based approach with a LLM approach [2]. A machine learning hybrid approach such as the one used by Babaalla in his study where it was combined bidirectional LSTMs, tree structures and LLMs. This multi-layered architecture jointly extracts UML fragments (e.g., classes, attributes, methods) and relationships, thereby mitigating error propagation often seen in staged approaches [3]. Another Hybrid approach was developed by Eisenreich et al. [42] and Ahmad et al. [47] that implemented iteratively refinement through human feedback in their approaches. Another approach was the use of Retrieval-Augmented generation. Bernardi et al. used Retrieval-Augmented Generation (RAG) to improve the domain knowledge of the LLM in order to improve the feedback about the models [45].

Approach	Studies	Techniques Employed	Key Aspects/Outcome
LLM-based Prompting	[1, 6, 46]	Few-shot and zero-shot learning; prompts including a task description, detailed domain specification, format guidelines, and (when applicable) reference examples with reasoning steps.	Enhances the extraction and synthesis of design models from requirements.
Rule-based approach	Ap- [2]	Preprocessing techniques (handling compound sentences, grouping consecutive nouns) combined with NLP heuristics.	Extracts requirement elements; used as a baseline for comparing LLM approaches.
Hybrid ML approach	Ap- [3]	Integration of bidirectional LSTMs, tree structures, and LLMs to jointly extract UML fragments (classes, attributes, methods) and relationships.	Mitigates error propagation typical of staged approaches.
Hybrid with Iterative Human Feedback	[42, 47]	Iterative refinement of LLM outputs through human feedback.	Improves the accuracy and relevance of the generated design models.
Retrieval-Augmented Generation (RAG)	[45]	Combines LLMs with a retrieval system to enhance domain knowledge integration.	Enhances model feedback and improves the quality of generated designs.

Table 3.8: R4: Key Approaches in the Automation of Functional and Non-Functional Requirements into Design Models Using AI

3.2 Synthesis of the results

The results of the systematic aimed to understand the current state of research on the use of LLMs and GAI for automating requirement modelling. We have identified that there are hybrid approach that take leverage of machine learning models [3], others introduce a iterative human-refinement in order to improve the result [42, 47], or rule-based methods to improve extraction of design elements [2], or a implementation of a RAG system to improve the domain knowledge of the LLM [45]. A common factor was the importance of good prompts to achieve good results. Therefore, many of the studies employed prompt engineering techniques such as zero-shot learning [6], few-shot learning [46] and CoT [1]. The analysis showed that the most frequently used LLM was ChatGPT, developed by OpenAI. Its widespread application shows its strong versatility and robust performance across various task. Following closely, was LLaMA , owned by Meta. Its frequently used in task requiring domain-specific understanding. It's noticing that the LLMs can improve the manual effort in requirement modelling. However, they still face limitations. These includes difficulties identifying relationships between entities, variability in output quality, struggle with handling domain-specific knowledge, and poor performs when dealing with ambiguous or incomplete requirements.

3.3 Threats to validity

Internal Validity In systematic mapping studies there is always the risk of not including all relevant studies. While defining the search string, we made an effort to include synonyms and alternative terms related to the research questions. Although this efforts, the results may miss some relevant studies that do not use the specified keywords. To mitigate this risk, we text several search strings based on the number of relevant results they retrieved and chose the most optimal.

Additionally, there is the potential risk of excluding relevant studies during the selection. As the study selection and data extraction were conducted by a single person, and the volume of studies was substantial, the inclusion criteria and exclusion criteria were defined to avoid, at least to some extent, introducing selection bias in the process.

External Validity To ensure we had the maximum of relevant research work regarding our goal, we obtained the studies through the digital libraires, IEEE Xplore and ACM Digital Library, that are well established digital libraries in the software engineering field and ensured a large set of peer-to-peer reviewed papers. However, a potential limitation arises from the exclusive reliance on these two digital libraries, as other relevant studies may be present in different sources such as Springer and ArXiv were not considered. This may have led to the omission of relevant studies, introducing a potential bias in the selecting process. Additionally, we did not consider Non-English or papers published after 2019. While this constraints were implemented to maintain focus and ensure high-quality sources, they introduce a risk of missing valuable contributions outside our selected databases and timeframe.

Conclusion Validity A challenge to validity was the fact we do not have the knowledge of how the search engines of the used digital libraries work. To address this, we documented the exact search string used and we extracted a csv file with the results of the search to ensure consistency across searches and to facilitate systematic data organization. However, as the study selection and data extraction were conducted by one person, there remains a potential for subjective bias. Although these challenges, the structured methodology and tools used contribute to the reliability of the conclusions drawn.

3.4 Related Work

NLP and LLMs have show potential to change the software engineering field, particularly in requirements engineering, architecture design, conceptual modelling, taxonomy construction, code generation and test case generation. The systematic study on NLP for requirements Engineering (NLP4RE) [52] published in 2021 identifies the analysis phase as the most researched followed by management, elicitation, and modeling, while validation verification, testing, and design receive the least attention. The study also identifies that

requirements specification documents are the most common input, and that tools developed are mainly focused on modelling, detection and extraction, although only 13.08% of the tools are accessible online. An the most widely used NLP technologies include POS tagging, tokenization, parsing with tools such as StanfordCoreNLP, GATE, and NLTK. A significant challenge discovered on the systematic study is the absence of RE-specific resources, which prevent the development of effective domain-specific solutions. The authors believe that transfer learning techniques can help addressing this gap.

LLMs have been employed for different tasks related to software engineering. One of them is generate architectural designs [53], in this paper the authors used three different approaches (zero-shot, few-shot prompting, and fine-tuning), and different models to evaluate the performance of the LLMs. The results showed that GPT-4 excels in generating structured and relevant ADDs. However, smaller models can achieve comparable results. After fine-tuning, Flan-T5-Base with fewer parameters achieves comparable performance to GPT-3.5 in a few-shot approach, suggesting its utility for organizations prioritizing cost efficiency, privacy, and minimal hosting infrastructure. Although, LLMs are not entirely reliable for ADR generation but can effectively assist architects in documenting ADDs. Despite advancements, even the best fine-tuned models cannot match GPT-4 in adhering to the ADR markdown format. The findings suggest that smaller models like text-davinci-003, when used with a few-shot approach, can offer a cost-effective alternative to larger models like GPT-4, although their generalizability remains uncertain. This underscores the trade-offs between cost, infrastructure, and performance when using LLMs for ADD generation.

Similar, Chen's et al. [54] compares the use of prompting and fine-tuning to enhance the performance of Large Language Models for taxonomy construction. The users used two techniques to fine-tune the model, layer-wise fine-tuning, which updates parameters in the last few layers, and LoRA, which uses low-rank decomposition to update all parameters. In contrast for prompting, to deal with variation of outcomes when generating taxonomies with prompting, they use majority voting to aggregate outcomes from multiple runs. The results of the comparative study indicate that the prompting method outperformed fine-tuning when compared using F1 score. The gap between the two approaches increases when the training dataset is smaller because is more challenging to fine-tune. Although, neither approach surpassed the current state-of-art performance achieved by BERT-based models on WordNet, suggesting that model architecture significantly influences task performance. The study emphasizes the importance of selecting appropriate methods based on dataset size and resource constraints while acknowledging the need for further advancements to address existing limitations in taxonomy generation using LLMs.

Another task where LLMs can be used is in establishing traceability between natural language requirements and software. Ali et al. approach [55] used LLMs combined with RAGs to compact the ambiguities within requirements engineering. It offers the knowledge to be dynamically incorporated in a scalable, plug-in fashion compared to traditional models in which the knowledge is parametrized. Another advantage is that

by using human-authored texts incorporate in the generation, it simplifies the generation process and may improve out quality. The effectiveness of RAG relies heavily on the quality of its index, which serves as a contextual bridge, helping LLMs disambiguate requirements by providing precise context. The RAG system was implemented in two stages: the indexing stage, which creates and stores code summaries as indexes for fast and relevant matches, and the querying stage, which retrieves relevant documents to provide contextual input for LLMs in predicting classes aligned with a given requirement. This approach ensures that retrieved documents demonstrate high relevance accuracy, which is critical for reliable requirements traceability. By prioritizing precision over recall, the RAG mechanism minimizes irrelevant links between requirements and code, reducing the risks of misleading connections and supporting efficient maintenance and verification processes.

Similarly, Arora's et al. approach [56] also employs a retrieval augmented system to generate a test scenario from natural language requirements. The choice of employing a RAG system is due to LLMs facing challenges with domain-specific queries, often producing inaccurate or incomplete outputs. By incorporating domain-specific context into prompts, improves the accuracy and relevance of generated TSs. The industrial case study presented by Arora's [56] in collaboration with Austrian Post Group IT, revealed that bilingual and domain-specific requirements, such as proprietary internal processes, are particularly challenging for LLMs due to limited public data. As in Dhar's et al. explanatory empirical study [53] it was used the BLUE, ROUGE and METEOR evaluation metrics, providing unique insights into similarity, recall, and alignment with human judgment. A notable indirect advantage found in this study was that when the generated tested scenarios presented major issues, it was due to the original requirements were incomplete and poor-quality. In both studies the approach presented great promises, but which are constrained by the quality of input, preciseness of prompts and effective contextual integration.

A exploratory study conducted on the task of using LLMs [57] for conceptual modelling showed that the user is aware of the lack of contextual memory, inaccuracy and unreliability reliance on precise inputs of LLMs, aligned with those observed in [54]. Addressing these limitations is essential to improving usability and reliability across application domains.

In conclusion, the integration NLP and LLMs into the different areas of software engineering domain shows potential to transform those areas. Despite the advancements made in different areas, several common themes and challenges emerge across studies. First, the lack of domain-specific resources and datasets is a recurring limitation as observed in systematic mapping NLP4RE [52], taxonomy generation [54], and test case generation [56]. This restricts the ability to create reliable and effective tools for software engineering tasks. Second, there is a trade-off between cost, infrastructure, and performance. Smaller models often are cost-effective solutions but often fall short in terms of generalization and accuracy compared to large models like GPT-4. Additionally, contextual integration plays a critical role in the effectiveness of these models. Whether through RAG systems [53, 56], or the structured use of prompts, incorporating domain-specific knowledge significantly

improves the relevance and accuracy of outputs. Nevertheless, these approaches depend on the quality of input data and the precision of prompt engineering. As suggested in by Ali's [57] its fundamental to address limitations such as lack of contextual memory, inaccuracy, and dependence on precise inputs in LLMs, to improve usability, reliability, and integration into broader software engineering practises.

3.5 Summary

This chapter describes the systematic mapping study done during this first part of this thesis. The systematic mapping study aimed to understand how the LLMs have been used for deriving design models from textual requirements. The research methodology applied followed a three key phases: planning, conducting, and reporting. The study identified various techniques used to leverage LLM in design modeling. Direct code generation was one of the most common approaches, where LLMs like ChatGPT and LLaMA were used to generate UML diagrams from textual descriptions. A significant finding was the increasing integration of RAG systems, which improve LLMs' capabilities by integrating domain-specific knowledge. However, the study also highlighted key challenges, including the ambiguity and incompleteness of natural language requirements, the dependency on high-quality prompts, and the limitations of LLMs in capturing complex software design patterns. Despite the promising applications of LLMs, challenges such as limited contextual memory, variability in output quality, and difficulty in handling domain-specific knowledge remain a struggle. These findings underscore the need for improved prompt engineering techniques, more structured data augmentation, and further advancements in contextual awareness and domain specific knowledge integration to enhance the usability and reliability of LLMs in design modeling.

EXPERIMENTS WITH GENERATIVE AI TECHNIQUES AND TOOLS

This chapter explained preliminary tests done in order to find the best configurations possible to create a automate tool to generate class diagrams.

4.1 Experiments with prompt techniques and different LLM models

To probe how prompt engineering and model choice interact when converting natural-language requirements into UML class diagrams, we designed a controlled experiment centred on a single, medium-sized specification drawn from the dataset of Daniele De Bari *et al.* [41]. Listing 4.1 shows the excerpt; it contains multiple actors, artefacts, and life-cycle constraints—enough complexity to exercise class identification, attribute extraction, and relationship mapping.

```
A project manager uses the project management system to manage a project. The project
  manager leads a team to execute the project within the project's start and end dates.
Once a project is created in the project management system, a manager may initiate and
  later terminate the project due to its completion or for some other reason.
As input, a project uses requirements. As output, a project produces a system (or part of
  a system). The requirements and system are work products: things that are created,
  used, updated, and elaborated on throughout a project.
Every work product has a description, is of some percent complete throughout the effort,
  and may be validated.
However, validation is dependent on the type of work product. For example, the
  requirements are validated with users in workshops, and the system is validated by
  being tested against the requirements.
Furthermore, requirements may be published using various types of media, including on an
  intranet or in paper form; and systems may be deployed onto specific platforms.
```

Listing 4.1: System Description

Prompting conditions Each model was queried under three canonical strategies:

1. **Zero-shot** – task instruction only;
2. **Few-shot** – three worked examples followed by the target specification;
3. **Chain-of-thought Few-shot (CoT)** – the few-shot template augmented with an explicit, step-by-step reasoning scaffold.

The prompts used for testing can be found in the Appendix B paragraph Language models. We considered five commercially hosted models that can be accessed without a local GPU:

1. ChatGPT-4o,
2. Claude Sonnet 4,
3. Deepseek XL,
4. Gemini 2.5 Flash, and
5. Grok 1.5.

Several open-source models (Mistral 7B, Qwen 7B, Falcon 7B) were piloted but discarded because the presented results were weak. Some generated PlantUML code had syntax errors that did not allow to compile, other were not able to generate PlantUML code. Besides this, when we used few-shot prompting some models generated class diagrams not related with the system description but related with the examples presented in the prompt. We still tried using opensource models with more parameters, although they had better results, they were significantly worse than those obtained with the commercial models. Therefore, due to weak results and hardware limitations to run powerful opensource models we end up discarding opensource for this tests.

4.1.1 Evaluation protocol

The generated diagrams were assessed along three complementary axes:

1. **Structure.** We compared each diagram to the ground-truth model via a confusion matrix over classes, attributes, and relationships, computing precision, recall, and F_1 .
2. **Semantic and pragmatic adequacy.** We adopted G-Eval [58] with Llama-3 as the grader, requesting two rubric items: *semantic fidelity* (correctness + completeness of domain concepts) and *pragmatic usefulness* (clarity, UML idioms, multiplicities).
3. **Lexical overlap.** ROUGE-L recall [59] was computed between the generated PlantUML and the reference code. Although surface-oriented, ROUGE helps detect omissions that structural matching alone may miss (e.g., lost attributes).

4.1.2 Results and Discussion

Figures 4.1 and 4.2 visualise the outcome. We narrate the main findings below.

Prompt strategy effects CoT delivers the highest mean G-Eval and the strongest recall, confirming that an explicit reasoning trace helps models surface low-salience entities such as *WorkProduct*. However, its ROUGE score lags behind few-shot because the additional prose dilutes lexical overlap with the gold PlantUML. Few-shot, in contrast, attains the best ROUGE and the second-best recall, suggesting that concise demonstrations strike a balance between coverage and verbosity. Zero-shot performs adequately on ChatGPT-4o but drops in both recall and G-Eval for the remaining models.

Model behaviour

- **Claude Sonnet 4** consistently tops the G-Eval table and ranks second in structural recall, making it the most balanced performer.
- **Deepseek** yields the highest recall and F_1 , albeit with slightly lower G-Eval—an indicator that it enumerates more elements but lacks the polish of Claude.
- **ChatGPT-4o** excels in zero-shot but gains little from additional prompting
- **Gemini 2.5 Flash** shows moderate scores across metrics, hampered by occasional length truncation in CoT mode.
- **Grok 1.5** underperforms structurally and, in CoT mode, returned an image instead of code, highlighting alignment gaps for specialised tasks.




Figure 4.1: Qualitative results of prompt techniques and LLM tests




Figure 4.2: Qualitative results of overall performance of LLMs tests

4.2 Experiments with a Retrieval-Augmented Generation (RAG) Tool

To further understand if implementing a RAG system would be beneficial for generation of class diagrams we conducted experiments using the new google tool, NotebookLM.¹ NotebookLM grounds its responses in a user-supplied document collection, thereby enabling context-aware retrieval during generation [60].

4.2.1 Experimental Setup

To conduct this experiment we configured a notebook by adding the following documents, the goal is to simulate the reference material available to a professional modeller:

1. Buku-learning UML 2.0 – A pedagogical guide to UML concepts.
2. OMG UML specification – The official UML language specification.
3. PlantUML reference guide – Syntax and rendering documentation for PlantUML.
4. Examples from the UML modeling dataset – Simulating models created in previous projects

An important limitation found is that the NotebookLM imposes constraints the number of tokens, limiting the possibilities of using prompting engineering. Therefore we were only able to use zero-shot prompt supported by RAG context.

We directly prompt the zero shot prompt used in the previous experiment but we deleted the last part where is the information about PlantUML syntax because of the token limitations and because we had added to the database knowledge the PlantUML

¹Formerly “Project Tailwind,” an AI-assisted research and note-taking environment released by Google Labs.

guidance. Looking at the result we could see that a class diagram was no different from the previously generated in the first experiment. Having similar results to the one presented by the Google model (gemini).

We decided to rewrite the zero-shot prompt to be more appropriate for using in a RAG tool, by adding an explicit rag reference, direct instruction to use knowledge base Utilization, added specific instruction and restructured the format to be better organize for RAG parsing. The second result were better then the ones obtained in the first prompt. Besides identifying one relationship that was not expressed in the first diagram it also become more similar to the ground truth benchmark. A common thing is that both situations struggled to identify all the necessary attributes (Prompt 4.2). Will the first generated diagram represented the attributes plataform and mediatype as a class which increased the difficult of legibility, the second diagram did not have any representation of Media and Plataform present in the groundtruth as it can be seen in the Figure 4.3

```
You are an experienced software engineer specializing in UML modeling. Based on the UML
specifications, PlantUML documentation, and modeling examples available in your
knowledge base, create a class diagram for a project management system.

**System Requirements:**
The project manager leads a team to execute projects within defined start and end dates.
Once created in the system, a manager may initiate and later terminate projects due
to completion or other reasons. The team executes the project using requirements as
input to produce a system as output.

Requirements and systems are work products with descriptions, completion percentages, and
validation capabilities. Requirements are validated through user workshops, while
systems are validated by testing against requirements. Requirements may be published
via various media (intranet, paper), and systems may be deployed on specific
platforms.

**Instructions:**
- Follow UML class diagram principles from your knowledge base
- Use PlantUML syntax as documented in your references
- Generate clean PlantUML code without comments or references
- Focus on: classes, attributes, methods, relationships, and multiplicities
- Ensure all entities mentioned in requirements are properly modeled

Output only valid PlantUML code.
```

Listing 4.2: Adapted Zero-shot prompt

4.2.2 Results and Discussion

Comparing to the results obtained in the first experiment we can see that the generated class diagram with the adapted prompt is the most close to the ground truth. Obtaining the best precision, recall, and F1-score in all elements of the class diagram besides attributes.




Figure 2-15. Class diagram




Figure 4.3: Different class diagrams generated using NotebookLM compared to the ground truth

This results suggest that RAG can be beneficial to generate class diagrams from system descriptions.

4.3 Experimenting Self-improving

An emerging technique in the field of generative artificial intelligence is self-refinement, a process wherein large language models (LLMs) iteratively improve their own outputs by generating feedback and revising responses without human intervention. This paradigm mirrors the structure of human-in-the-loop feedback systems but replaces the human evaluator with the model itself, thereby enabling a form of autonomous self-improvement. Madaan et al. (2023) formalized this approach through the Self-Refine framework, demonstrating that an LLM can act simultaneously as generator, critic, and refiner via prompt chaining. Their experiments across diverse tasks—including mathematical reasoning and open-domain question answering—revealed an average absolute improvement of approximately 20% in performance compared to traditional one-shot generation methods [61]. A key advantage of this technique is its ability to enhance model performance entirely at inference time, leveraging prompt engineering and in-context feedback, without resorting to computationally expensive fine-tuning or additional training [61]. This makes it particularly suitable for our setting with limited computational resources. Motivated by these

promising results, we conducted a series of experiments to assess whether self-refinement could enhance the performance of our own generative system. Specifically, we aimed to explore the impact of iterative self-evaluation and refinement on the quality and accuracy of generated outputs within our use case.

4.3.1 Experimental Setup

To implement the self-refinement methodology, we developed a Python-based experimental pipeline that leverages the Anthropic Claude API to simulate a reflective reasoning loop. This loop enables a generative model to not only produce UML class diagrams from natural language system descriptions but also to autonomously evaluate and iteratively improve its own output based on structured critique. The Anthropic Claude model was selected due to its strong performance in prior experiments (see Section 4.1) and its free-tier access, which allowed us to execute multiple inference rounds without incurring computational or financial overhead. These practical and performance-based criteria rendered Claude an appropriate model for experimentation in resource-constrained environments. The self-refinement loop is implemented as a three-step iterative process capped at a maximum of three iterations. The sequence is as follows:

1. **Initial Generation:** Firstly, the system uses a chain-of-thought (CoT) prompt—previously evaluated and available in Appendix B—to generate the class diagram based system description. This response constitutes the starting output to be refined.
2. **Self-Evaluation:** The generated diagram is passed to a structured evaluation function (see Prompt 4.4) which queries the Claude model to assess the quality of the diagram across four rigorously defined dimensions: UML completeness, UML syntax and quality, requirement coverage, and clarity and pragmatics. Each dimension is weighted, and an overall evaluation score is computed. The response includes both scalar scores and detailed natural language feedback in JSON format, ensuring both interpretability and machine-readability.
3. **Self-Improvement:** If the initial output does not meet the quality threshold—defined or higher a refinement step is triggered. In this step, the previously generated diagram, the system description, and the evaluation feedback are incorporated into an improvement prompt (Prompt 4.3). This prompt instructs the model to revise the class diagram to resolve the identified issues and implement the suggested enhancements. The revised output is then subjected to a new round of self-evaluation.

#SYSTEM PROMPT

You are an expert UML software architect tasked with improving a PlantUML class diagram based on specific feedback and evaluation criteria.

Your Task

Analyze the provided feedback and systematically improve the class diagram to address all identified issues while maintaining the original system requirements.

Improvement Guidelines

1. UML Completeness Improvements

- Add missing classes, attributes, or methods identified in feedback
- Ensure all entities from system description are represented
- Include proper visibility modifiers (-, +, #)
- Add missing relationships and associations

2. UML Quality Enhancements

- Fix naming convention issues (PascalCase for classes, camelCase for attributes/methods)
- Correct relationship types (association, aggregation, composition, inheritance)
- Improve multiplicity specifications
- Enhance method signatures with proper parameters and return types

3. Requirement Coverage Improvements

- Map every requirement explicitly mentioned in system description
- Ensure behavioral aspects are captured through appropriate methods
- Add missing domain-specific attributes and operations
- Include all stated constraints and business rules

4. Clarity & Pragmatic Improvements

- Improve relationship labels for better understanding
- Organize classes logically (group related classes)
- Add stereotypes where appropriate (<<interface>>, <<abstract>>, etc.)
- Ensure proper abstraction levels

Output Instructions

1. Provide the complete improved PlantUML diagram
2. Start with @startuml and end with @enduml
3. Include all improvements addressing the feedback
4. Maintain syntactic correctness
5. Ensure the diagram is more comprehensive than the original

Critical Requirements

- Address ALL issues mentioned in the feedback
- Implement ALL recommendations provided
- Ensure the improved diagram scores higher in all evaluation dimensions
- Maintain or enhance requirement coverage
- Keep PlantUML syntax error-free

##Important Note:

- Follow strictly the System Description. Keep the diagram simple and direct.

USER PROMPT

Improve the following PlantUML class diagram based on the following feedback:

```

## Current PlantUML Class Diagram
{current_response}

## Detailed Feedback Analysis
{json.dumps(feedback.get('feedback', ''), indent=2)}

## Specific Issues to Address
{chr(10).join(f"- {issue}" for issue in feedback.get('issues', []))}

## Recommendations to Implement
{chr(10).join(f"- {rec}" for rec in feedback.get('recommendations', []))}

```

Listing 4.3: Self improve

```

#SYSTEM PROMPT
You are an expert UML evaluator and software engineering reviewer with deep expertise in
system analysis and design quality assessment. Your task is to comprehensively
evaluate a UML class diagram against system requirements using rigorous academic and
industry standards.

## Evaluation Framework

Assess the class diagram across these four critical dimensions:

### 1. UML Completeness (25% weight)
**Criteria:**
- All relevant classes identified and included
- Complete set of attributes for each class with appropriate types
- Comprehensive method signatures with parameters and return types
- Proper visibility modifiers (-, +, #) applied consistently
- All necessary relationships present (associations, inheritance, dependencies)

**Scoring:**
- 0.9-1.0: All elements present, comprehensive coverage
- 0.7-0.8: Minor omissions, mostly complete
- 0.5-0.6: Several missing elements
- 0.3-0.4: Major gaps in completeness
- 0.0-0.2: Severely incomplete

### 2. UML Quality (25% weight)
**Criteria:**
- Correct UML syntax and notation
- Proper relationship types (composition vs aggregation vs association)
- Accurate multiplicity specifications
- Consistent naming conventions (PascalCase classes, camelCase attributes/methods)
- Appropriate use of abstract classes and interfaces
- Proper encapsulation and information hiding

**Scoring:**
- 0.9-1.0: Excellent quality, best practices followed

```

- 0.7-0.8: Good quality with minor issues
- 0.5-0.6: Adequate quality, some problems
- 0.3-0.4: Poor quality, multiple issues
- 0.0-0.2: Very poor quality, major problems

3. Requirement Coverage (30% weight)

Criteria:

- Every entity mentioned in requirements is modeled
- All relationships described in requirements are captured
- Business rules and constraints are represented
- Behavioral aspects are included through appropriate methods
- Domain-specific terminology is preserved
- System boundaries and scope are respected

Scoring:

- 0.9-1.0: Complete requirement coverage
- 0.7-0.8: Most requirements covered, minor gaps
- 0.5-0.6: Adequate coverage, some missing aspects
- 0.3-0.4: Poor coverage, major requirements missing
- 0.0-0.2: Very poor coverage, most requirements ignored

4. Clarity & Pragmatics (20% weight)

Criteria:

- Diagram is understandable to technical stakeholders
- Logical organization and grouping of classes
- Meaningful relationship labels and role names
- Appropriate level of abstraction
- Clear separation of concerns
- Professional presentation and layout

Scoring:

- 0.9-1.0: Exceptionally clear and well-organized
- 0.7-0.8: Clear and understandable
- 0.5-0.6: Reasonably clear, some confusion possible
- 0.3-0.4: Unclear in several areas
- 0.0-0.2: Very unclear, difficult to understand

Evaluation Instructions

1. ****Systematic Analysis****: Examine each dimension thoroughly
2. ****Evidence-Based Scoring****: Provide specific examples for scores
3. ****Detailed Issues****: List concrete problems with specific locations
4. ****Actionable Recommendations****: Provide implementable improvements
5. ****Comprehensive Assessment****: Consider the diagram as a whole system model

Required Output Format

Return ONLY a valid JSON object with this exact structure:

```
```json
```

```

{{
 "uml_completeness_score": <float 0.0-1.0>,
 "uml_quality_score": <float 0.0-1.0>,
 "requirement_coverage_score": <float 0.0-1.0>,
 "pragmatic_clarity_score": <float 0.0-1.0>,
 "overall_score": <float 0.0-1.0>,
 "detailed_analysis": {{
 "completeness_details": "<specific analysis of what's missing or present>",
 "quality_details": "<analysis of UML syntax, conventions, and design
 quality>",
 "coverage_details": "<analysis of how well requirements are captured>",
 "clarity_details": "<analysis of diagram understandability and
 organization>"
 }},
 "issues": [
 "<specific issue 1 with location/context>",
 "<specific issue 2 with location/context>",
 "<specific issue 3 with location/context>"
],
 "recommendations": [
 "<actionable recommendation 1>",
 "<actionable recommendation 2>",
 "<actionable recommendation 3>"
],
 "strengths": [
 "<identified strength 1>",
 "<identified strength 2>"
]
}}
...

```

If there is no issues or recommendations, you can return an empty array for those fields.

Calculate the overall\_score as: (uml\_completeness\_score \* 0.25) +  
 (uml\_quality\_score \* 0.25) + (requirement\_coverage\_score \* 0.30) +  
 (pragmatic\_clarity\_score \* 0.20)"""

#USER PROMPT

Evaluate the following PlantUML class diagram based on the following system  
 describing:

```

System Description
{system_description}

```

```

PlantUML class diagram
{response}

```

Base your response exclusively on the system description and in the UML principles

Listing 4.4: Self evaluation

This loop continues iteratively until either a satisfactory score is achieved or the maximum number of iterations is reached. To support transparency and replicability,



the pipeline maintains a persistent logging system that records all iterations, feedback evaluations, and diagram versions. Additionally, a structured `feedback_history` data structure is maintained, which stores for each iteration: (i) the feedback JSON object, (ii) the corresponding PlantUML diagram, and (iii) the iteration number. This facilitates post-hoc analysis and supports visual inspection of improvement trends. Overall, this experimental design allows us to rigorously test whether self-reflective generation—achieved entirely through inference-time prompting—can lead to substantial and consistent improvements in UML modeling tasks. The design aligns with emerging research advocating for *low-cost, feedback-driven refinement frameworks* (e.g., Madaan et al., 2023), which offer a viable alternative to expensive fine-tuning or supervised retraining in downstream applications.

To decide when to stop the loop we used a threshold. To know which is the best threshold that fits our goal the better we run the script with different thresholds ranging from 0.7 to 0.95. As it can be seen in the Figure 4.4, we recorded the average score, average iterations done and the standard deviation of the score. This way we can analyse the effort need to achieve a certain threshold and the stability of those scores. The thresholds 0.75 to 0.85 have high average scores and low iteration scores. The threshold 0.85 seems to be more stable. The threshold 0.9 achieves the highest scores but at the cost of the number of iterations. Also has the highest standard deviation which indicates that is less predictable in terms of performance. The last threshold has slightly worst score then the previous threshold but with a higher number of iterations. Although is more stable then 0.9 threshold.

Looking at this results we end up deciding to use 0.85 because it overs the best cost-benefit ratio.




Figure 4.4: Threshold hold test

### 4.3.2 Results and Discussion

The self-improvement pipeline was executed on the same system description used in the previous experiments. After a single iteration the score grew from **0.815** to **0.855**.

Figures 4.5 (a) and (b) show, respectively, the diagram produced in the first pass and the diagram obtained after one refinement cycle. While the initial model already contained

the eight core domain classes, their relationships and every public operation required by the ground-truth reference, the refinement step enriched the artefact in several important ways that are directly visible when the two diagrams are compared, that goes beyond what is expressed in the system description:

- **New domain concept.** A dedicated `TeamMember` class now appears, linked to `Team` through a composition (`1 Team --> 1..* TeamMember`). This makes individual contributors first-class citizens of the model.
- **Richer team management behaviour.** The `Team` class gained a `name` attribute together with membership-handling services (`addMember`, `removeMember`, `getMembers`). Complementarily, `ProjectManager` now offers `assignTeam(Project, Team)`, and `TeamMember` provides `assignToTeam`, `removeFromTeam` and `addSkill`.
- **Explicit traceability between artefacts and validation.** `WorkProduct` now maintains a collection `validations: List<Validation>` and is connected to `Validation` through an association labelled *validated by* with cardinalities `1 ↔ 0..*`. Corresponding operations (`addValidation`, `getValidations`) were also added.
- **Refined requirement compliance.** A new association *validates against* relates `System` to one or more `Requirement` instances (`1 ↔ 1..*`), turning the previously implicit link embodied in `testAgainstRequirements` into an explicit structural dependency.
- **Enhanced project coordination.** The `Project` class is now able to register requirements and the target system by means of the newly introduced operations `addRequirement` and `setSystem`.
- **Extended validation feedback.** `Validation` itself now exposes accessor methods `getValidationResult` and `getValidationDate`, providing programmatic access to the outcome and time-stamp of the validation activity.

Overall, the iteration increased the number of associations, attributes and operations, thereby improving model completeness without sacrificing correctness: no previously correct element was removed or altered erroneously. Although the quality when compared to the ground truth did not increase, there is an increase on the details which is important for following activities after modelling.

## 4.4 Summary

This chapter presents a comparative study of techniques for generating UML class diagrams from natural language system descriptions using large language models (LLMs). The experiments systematically evaluate the impact of different prompt strategies (zero-shot, few-shot, and chain-of-thought) and model choices (ChatGPT-4o, Claude Sonnet 4, Deepseek XL, Gemini 2.5 Flash, and Grok 1.5) based on structural, semantic, and lexical




Figure 4.5: Effect of the self-improvement loop on the class diagram

criteria. Results show that chain-of-thought prompting improves recall and semantic coverage, especially for low-salience elements, while few-shot prompting yields the best ROUGE scores. Among the models, Claude Sonnet 4 emerged as the most balanced in terms of structural and semantic performance. Open-source models, while tested, were excluded due to weak results and practical limitations. Additional experiments with a RAG-based tool (NotebookLM) revealed that an adapted prompt leveraging document-grounded context achieved the best alignment with the ground truth, surpassing both zero-shot and standard prompting setups.

The chapter concludes with the experiment of implementation of a self-improvement loop based on Claude and the Self-Refine framework. The system autonomously generates, critiques, and iteratively refines its UML output until a quality threshold is met. This approach increased the completeness and detail of diagrams—introducing new relevant classes and relationships—without compromising existing correctness. By testing multiple threshold values, a target score of 0.85 was found to offer the best trade-off between quality and efficiency. Overall, the combination of prompt engineering, document grounding, and self-refinement is a promising approach which provides a low-cost, effective strategy for improving the quality of UML diagram generation in resource-constrained environments.

## AN APPROACH TO AUTOMATE THE MODELING CLASS DIAGRAMS

This chapter describes and explains the decisions behind the prototype developed to automate the modeling class diagram.

### **5.1 Prompt technique and Model used**

### **5.2 Retrieval Augmented Generation System implemented**

### **5.3 Self-improve approach**

### **5.4 Agent implementation**

### **5.5 Challenges**

### **5.6 Pratical Demonstration**

### **5.7 Summary**



## EVALUATION

### **6.1 Experiment Purpose and Procedure**

### **6.2 Results**

### **6.3 Discussion**

### **6.4 Summary**



## CONCLUSIONS

### **7.1 Contributions**

### **7.2 Limitations**

### **7.3 Future Work**





## BIBLIOGRAPHY

- [1] K. Chen et al. “Automated Domain Modeling with Large Language Models: A Comparative Study”. In: *2023 ACM/IEEE 26th International Conference on Model Driven Engineering Languages and Systems (MODELS)*. Västerås, Sweden: IEEE, 2023, pp. 162–172. DOI: 10.1109/MODELS58315.2023.00037 (cit. on pp. 1, 22, 23, 56).
- [2] M. Jahan et al. “Automated Derivation of UML Sequence Diagrams from User Stories: Unleashing the Power of Generative AI vs. a Rule-Based Approach”. In: *Proceedings of the ACM/IEEE 27th International Conference on Model Driven Engineering Languages and Systems (MODELS '24)*. New York, NY, USA: Association for Computing Machinery, 2024, pp. 138–148. DOI: 10.1145/3640310.3674081. URL: <https://doi.org/10.1145/3640310.3674081> (cit. on pp. 1, 18–23, 55).
- [3] Z. Babaalla et al. “Towards an Automatic Extracting UML Class Diagram from System’s Textual Specification”. In: *Proceedings of the 7th International Conference on Networking, Intelligent Systems and Security (NISS '24)*. New York, NY, USA: Association for Computing Machinery, 2024, Article 36, 1–5. DOI: 10.1145/3659677.3659742. URL: <https://doi.org/10.1145/3659677.3659742> (cit. on pp. 1, 18, 20–23, 55).
- [4] J. W. P. Miranda et al. “Towards an In-Context LLM-Based Approach for Automating the Definition of Model Views”. In: *Proceedings of the 17th ACM SIGPLAN International Conference on Software Language Engineering (SLE '24)*. New York, NY, USA: Association for Computing Machinery, 2024, pp. 29–42. DOI: 10.1145/3687997.3695650. URL: <https://doi.org/10.1145/3687997.3695650> (cit. on p. 1).
- [5] A. Ferrari, S. Abualhaija, and C. Arora. “Model Generation with LLMs: From Requirements to UML Sequence Diagrams”. In: *2024 IEEE 32nd International Requirements Engineering Conference Workshops (REW)*. Reykjavik, Iceland: IEEE, 2024, pp. 291–300. DOI: 10.1109/REW61692.2024.00044 (cit. on pp. 1, 2, 18, 20–22, 55).
- [6] K. Ruan, X. Chen, and Z. Jin. “Requirements Modeling Aided by ChatGPT: An Experience in Embedded Systems”. In: *2023 IEEE 31st International Requirements*

- Engineering Conference Workshops (REW)*. Hannover, Germany: IEEE, 2023, pp. 170–177. DOI: 10.1109/REW57809.2023.00035 (cit. on pp. 1, 18, 20–23, 56).
- [7] M. A. Omar. “Measurement of ChatGPT Performance in Mapping Natural Language Specification into an Entity Relationship Diagram”. In: *2023 IEEE 11th International Conference on Systems and Control (ICSC)*. Sousse, Tunisia: IEEE, 2023, pp. 530–535. DOI: 10.1109/ICSC58660.2023.10449869 (cit. on pp. 2, 18, 20–22, 56).
- [8] B. Wang et al. “How LLMs Aid in UML Modeling: An Exploratory Study with Novice Analysts”. In: *2024 IEEE International Conference on Software Services Engineering (SSE)*. Shenzhen, China: IEEE, 2024, pp. 249–257. DOI: 10.1109/SSE62657.2024.00046 (cit. on pp. 2, 20–22, 55).
- [9] H. Gomma. *Software Modeling and Design: UML, Use Cases, Patterns, and Software Architectures*. Cambridge, UK: Cambridge University Press, 2011 (cit. on pp. 5–8).
- [10] G. Booch, J. Rumbaugh, and I. Jacobson. *The Unified Modeling Language Reference Manual*. 1st. Addison-Wesley, 1999. ISBN: 978-0201309983 (cit. on p. 5).
- [11] M. Sergievskiy and K. Kirpichnikova. “Optimizing UML class diagrams”. In: *ITM Web of Conferences*. Vol. 18. EDP Sciences, 2018, p. 03003 (cit. on p. 5).
- [12] Author(s). “Importance and Impact of Class Diagram in Software Development”. In: *Indian Journal of Science and Technology* (2025). Available: <https://indjst.org/articles/importance-and-impact-of-class-diagram-in-software-development> (cit. on p. 6).
- [13] M. Zapata-Barra et al. “Towards obtaining UML class diagrams from secure business processes using security patterns”. In: *Journal of Universal Computer Science* 24.10 (2018), pp. 1472–1492 (cit. on p. 6).
- [14] Microsoft Corporation. *Microsoft Visio*. Diagramming and vector graphics application. 2025. URL: <https://www.microsoft.com/en-us/microsoft-365/visio/flowchart-software> (cit. on p. 8).
- [15] MKLabs Co., Ltd. *StarUML*. UML modeling tool. 2025. URL: <http://staruml.io> (cit. on p. 8).
- [16] Arnaud Roques. *PlantUML*. Open-source tool for UML diagrams. 2025. URL: <http://plantuml.com> (cit. on pp. 8, 18).
- [17] Lucid Software Inc. *Lucidchart*. Online diagramming application. 2025. URL: <https://www.lucidchart.com> (cit. on p. 8).
- [18] T. L. S. et al. “What language model to train if you have one million GPU hours?”. In: *arXiv preprint arXiv:2210.15424* (2022) (cit. on p. 8).
- [19] J. C. et al. “The future landscape of large language models in medicine”. In: *Communications Medicine* 3.1 (2023), p. 141 (cit. on p. 8).

- 
- [20] U. P. Liyanage and N. D. Ranaweera. “Ethical Considerations and Potential Risks in the Deployment of Large Language Models in Diverse Societal Contexts”. In: *Journal of Computational Social Dynamics* 8.11 (2023), pp. 15–25 (cit. on p. 8).
  - [21] A. Vaswani et al. “Attention is all you need”. In: *Advances in Neural Information Processing Systems*. Vol. 30. 2017 (cit. on p. 8).
  - [22] T. B. Brown et al. *Language Models are Few-Shot Learners*. 2020. arXiv: 2005.14165 [cs.CL]. URL: <https://arxiv.org/abs/2005.14165> (cit. on p. 9).
  - [23] Z. Jiang et al. “How can we know what language models know?” In: *Transactions of the Association for Computational Linguistics* 8 (2020), pp. 423–438 (cit. on p. 9).
  - [24] N. Thakur et al. “BEIR: A Heterogenous Benchmark for Zero-shot Evaluation of Information Retrieval Models”. In: *arXiv preprint arXiv:2104.08663* (2021) (cit. on p. 10).
  - [25] Y. Zhang et al. “Siren’s song in the AI ocean: A survey on hallucination in large language models”. In: *arXiv preprint arXiv:2309.01219* (2023) (cit. on p. 10).
  - [26] Y. Gao et al. “Retrieval-augmented generation for large language models: A survey”. In: *arXiv preprint arXiv:2312.10997* (2023) (cit. on p. 10).
  - [27] P. Lewis et al. “Retrieval-augmented generation for knowledge-intensive NLP tasks”. In: *Proceedings of the 34th International Conference on Neural Information Processing Systems*. 2020, pp. 9459–9474 (cit. on p. 10).
  - [28] S. Robertson and H. Zaragoza. “The Probabilistic Relevance Framework: BM25 and Beyond”. In: *Foundations and Trends in Information Retrieval* 3.4 (2009), pp. 333–389 (cit. on p. 10).
  - [29] V. Karpukhin et al. “Dense Passage Retrieval for Open-Domain Question Answering”. In: *arXiv preprint arXiv:2004.04906* (2020) (cit. on p. 10).
  - [30] S. Gupta, R. Ranjan, and S. N. Singh. *A Comprehensive Survey of Retrieval-Augmented Generation (RAG): Evolution, Current Landscape and Future Directions*. 2024. arXiv: 2410.12837 [cs.CL]. URL: <https://arxiv.org/abs/2410.12837> (cit. on p. 11).
  - [31] P. Lewis et al. *Retrieval-Augmented Generation for Knowledge-Intensive NLP Tasks*. 2021. arXiv: 2005.11401 [cs.CL]. URL: <https://arxiv.org/abs/2005.11401> (cit. on p. 10).
  - [32] P. Lewis et al. “Retrieval-Augmented Generation for Knowledge-Intensive NLP Tasks”. In: *Advances in Neural Information Processing Systems*. Ed. by H. Larochelle et al. Vol. 33. Curran Associates, Inc., 2020, pp. 9459–9474. URL: [https://proceedings.neurips.cc/paper\\_files/paper/2020/file/6b493230205f780e1bc26945df7481e5-Paper.pdf](https://proceedings.neurips.cc/paper_files/paper/2020/file/6b493230205f780e1bc26945df7481e5-Paper.pdf) (cit. on p. 11).
  - [33] Y. Gao et al. *Modular RAG: Transforming RAG Systems into LEGO-like Reconfigurable Frameworks*. 2024. arXiv: 2407.21059 [cs.CL]. URL: <https://arxiv.org/abs/2407.21059> (cit. on p. 11).

- [34] J. K. *Types of RAG: An Overview*. Accessed: February 7, 2025. 2024. URL: <https://blog.jayanthk.in/types-of-rag-an-overview-0e2b3ed71b82> (cit. on p. 12).
- [35] S. K. et al. *Guidelines for performing systematic literature reviews in software engineering*. Tech. rep. Technical report, Ver. 2.3 EBSE Technical Report. EBSE, 2007 (cit. on p. 12).
- [36] K. Petersen et al. “Systematic mapping studies in software engineering”. In: *12th International Conference on Evaluation and Assessment in Software Engineering*. Vol. 17. 2008, p. 1 (cit. on pp. 12, 15).
- [37] B. Kitchenham and S. Charters. *Guidelines for performing systematic literature reviews in software engineering*. Tech. rep. 2007 (cit. on p. 13).
- [38] L. Zhao et al. “Natural Language Processing for Requirements Engineering: A Systematic Mapping Study”. In: *ACM Comput. Surv.* 54.3 (2022), Article 55, 41 pages. DOI: 10 (cit. on p. 14).
- [39] IEEE Xplore. *IEEE Xplore Digital Library*. Accessed: 2025-01-18. 2025. URL: <https://ieeexplore.ieee.org/Xplore/home.jsp> (cit. on p. 16).
- [40] ACM Digital Library. *ACM Digital Library*. Accessed: 2025-01-18. 2025. URL: <https://dl.acm.org/> (cit. on p. 16).
- [41] D. D. Bari et al. “Evaluating Large Language Models in Exercises of UML Class Diagram Modeling”. In: *Proceedings of the 18th ACM/IEEE International Symposium on Empirical Software Engineering and Measurement (ESEM '24)*. New York, NY, USA: Association for Computing Machinery, 2024, pp. 393–399. DOI: 10.1145/3674805.3690741. URL: <https://doi.org/10.1145/3674805.3690741> (cit. on pp. 18–22, 29, 55).
- [42] T. Eisenreich, S. Speth, and S. Wagner. “From Requirements to Architecture: An AI-Based Journey to Semi-Automatically Generate Software Architectures”. In: *Proceedings of the 1st International Workshop on Designing Software (Designing '24)*. New York, NY, USA: Association for Computing Machinery, 2024, pp. 52–55. DOI: 10.1145/3643660.3643942. URL: <https://doi.org/10.1145/3643660.3643942> (cit. on pp. 18–23, 55).
- [43] Y. Li et al. “LLM-Based Class Diagram Derivation from User Stories with Chain-of-Thought Promptings”. In: *2024 IEEE 48th Annual Computers, Software, and Applications Conference (COMPSAC)*. Osaka, Japan: IEEE, 2024, pp. 45–50. DOI: 10.1109/COMPSAC61105.2024.00017 (cit. on pp. 18–22, 56).
- [44] Z. Wang et al. “The Application of LLMs in the Analysis and Modeling of Software Requirements”. In: *2024 IEEE 24th International Conference on Software Quality, Reliability, and Security Companion (QRS-C)*. Cambridge, United Kingdom: IEEE, 2024, pp. 1143–1153. DOI: 10.1109/QRS-C63300.2024.00151 (cit. on pp. 18, 20–22, 55).

- 
- [45] P. Ardimento, M. L. Bernardi, and M. Cimitile. "Teaching UML using a RAG-based LLM". In: *2024 International Joint Conference on Neural Networks (IJCNN)*. Yokohama, Japan: IEEE, 2024, pp. 1–8. DOI: 10.1109/IJCNN60899.2024.10651492 (cit. on pp. 19–23, 56).
  - [46] M. B. Chaaben, L. Burgueño, and H. Sahraoui. "Towards using Few-Shot Prompt Learning for Automating Model Completion". In: *2023 IEEE/ACM 45th International Conference on Software Engineering: New Ideas and Emerging Results (ICSE-NIER)*. Melbourne, Australia: IEEE/ACM, 2023, pp. 7–12. DOI: 10.1109/ICSE-NIER58687.2023.000008 (cit. on pp. 19–23, 56).
  - [47] A. Ahmad et al. "Towards Human-Bot Collaborative Software Architecting with ChatGPT". In: *Proceedings of the 27th International Conference on Evaluation and Assessment in Software Engineering (EASE '23)*. New York, NY, USA: Association for Computing Machinery, 2023, pp. 279–285. DOI: 10.1145/3593434.3593468. URL: <https://doi.org/10.1145/3593434.3593468> (cit. on pp. 19, 21–23, 55).
  - [48] L. Naimi et al. "A new approach for automatic test case generation from use case diagram using LLMs and prompt engineering". In: *2024 International Conference on Circuit, Systems and Communication (ICCSC)*. 2024, pp. 1–5. DOI: 10.1109/ICCSC62074.2024.10616548 (cit. on pp. 21, 56).
  - [49] OpenAI. *OpenAI Models Documentation*. Accessed: January 18, 2025. 2025. URL: <https://platform.openai.com/docs/models> (cit. on p. 22).
  - [50] Llama AI. *Llama AI Platform*. Accessed: January 18, 2025. 2025. URL: <https://www.llama.com/> (cit. on p. 22).
  - [51] T. GLM et al. *ChatGLM: A Family of Large Language Models from GLM-130B to GLM-4 All Tools*. 2024. arXiv: 2406.12793 [cs.CL]. URL: <https://arxiv.org/abs/2406.12793> (cit. on p. 22).
  - [52] L. Zhao et al. "Natural Language Processing for Requirements Engineering: A Systematic Mapping Study". In: *ACM Computing Surveys* 54.3 (2021), 55:1–55:41. DOI: 10.1145/3444689 (cit. on pp. 24, 26).
  - [53] R. Dhar, K. Vaidhyanathan, and V. Varma. "Can LLMs Generate Architectural Design Decisions? An Exploratory Empirical Study". In: *Proceedings of the IEEE 21st International Conference on Software Architecture (ICSA)*. IEEE, 2024, pp. 79–89. DOI: 10.1109/ICSA59870.2024.00016 (cit. on pp. 25, 26).
  - [54] B. Chen, F. Yi, and D. Varró. "Prompting or Fine-tuning? A Comparative Study of Large Language Models for Taxonomy Construction". In: *Proceedings of the ACM/IEEE International Conference on Model Driven Engineering Languages and Systems Companion (MODELS-C)*. IEEE, 2023, pp. 588–597. DOI: 10.1109/MODELS-C59198.2023.00097 (cit. on pp. 25, 26).

- [55] S. J. Ali, V. Naganathan, and D. Bork. “Establishing Traceability between Natural Language Requirements and Software Artifacts by Combining RAG and LLMs”. In: *Proceedings of the International Conference on Conceptual Modeling (ER)*. Springer, 2024 (cit. on p. 25).
- [56] C. Arora, T. Herda, and V. Homm. “Generating Test Scenarios from NL Requirements using Retrieval-Augmented LLMs: An Industrial Study”. In: *Proceedings of the IEEE 32nd International Requirements Engineering Conference (RE)*. IEEE, 2024. DOI: 10.1109/RE59067.2024.00031 (cit. on p. 26).
- [57] S. J. Ali, I. Reinhartz-Berger, and D. Bork. “How Are LLMs Used for Conceptual Modeling? An Exploratory Study on Interaction Behavior and User Perception”. In: *Proceedings of the International Conference on Conceptual Modeling (ER)*. Springer, 2024 (cit. on pp. 26, 27).
- [58] Y. Liu et al. *G-Eval: NLG Evaluation using GPT-4 with Better Human Alignment*. 2023. arXiv: 2303.16634 [cs.CL]. URL: <https://arxiv.org/abs/2303.16634> (cit. on p. 30).
- [59] C.-Y. Lin. “ROUGE: A Package for Automatic Evaluation of Summaries”. In: *Text Summarization Branches Out*. Barcelona, Spain: Association for Computational Linguistics, 2004-07, pp. 74–81. URL: <https://aclanthology.org/W04-1013/> (cit. on p. 30).
- [60] R. Martin and S. Johnson. *Introducing NotebookLM*. Google Blog. 2023-07. URL: <https://blog.google/technology/ai/notebooklm-google-ai/> (cit. on p. 32).
- [61] A. Madaan et al. “Self-Refine: Iterative Refinement with Self-Feedback”. In: *Advances in Neural Information Processing Systems*. Ed. by A. Oh et al. Vol. 36. Curran Associates, Inc., 2023, pp. 46534–46594. URL: [https://proceedings.neurips.cc/paper\\_files/paper/2023/file/91edff07232fb1b55a505a9e9f6c0ff3-Paper-Conference.pdf](https://proceedings.neurips.cc/paper_files/paper/2023/file/91edff07232fb1b55a505a9e9f6c0ff3-Paper-Conference.pdf) (cit. on p. 34).

## PAPERS SELECTED DURING THE SYSTEMATIC MAPPING STUDY

Authors	Title	Reference
Daniele De Bari, Giacomo Garaccione, Riccardo Coppola, Marco Torchiano, Luca Ardito	Evaluating Large Language Models in Exercises of UML Class Diagram Modeling	[41]
Zakaria Babaalla, Abdeslam Jakimi, Mohamed Oualla, Rachid Saadane, Abdellah Chehri	Towards an Automatic Extracting UML Class Diagram from System's Textual Specification	[3]
Aakash Ahmad, Muhammad Waseem, Peng Liang, Mahdi Fahmideh, Mst Shamima Aktar, Tommi Mikkonen	Towards Human-Bot Collaborative Software Architecting with ChatGPT	[47]
Munima Jahan, Mohammad Mahdi Hassan, Reza Golpayegani, Golshid Ranjbaran, Chanchal Roy, Banani Roy, Kevin Schneider	Automated Derivation of UML Sequence Diagrams from User Stories: Unleashing the Power of Generative AI vs a Rule-Based Approach	[2]
A. Ferrari, S. Abualhaija, C. Arora	Model Generation with LLMs: From Requirements to UML Sequence Diagrams	[5]
B. Wang, C. Wang, P. Liang, B. Li, C. Zeng	How LLMs Aid in UML Modeling: An Exploratory Study with Novice Analysts	[8]
T. Eisenreich, S. Speth, S. Wagner	From Requirements to Architecture: An AI-Based Journey to Semi-Automatically Generate Software Architectures	[42]
Z. Wang, C. Feng, L. Liu, G. Jiao, P. Ye	The Application of LLMs in the Analysis and Modeling of Software Requirements	[44]



APPENDIX A. PAPERS SELECTED DURING THE SYSTEMATIC MAPPING STUDY

(Continued from previous page)		
Authors	Title	Reference
K. Ruan, X. Chen, Z. Jin	Requirements Modeling Aided by ChatGPT: An Experience in Embedded Systems	[6]
K. Chen, Y. Yang, B. Chen, J. A. Hernández López, G. Mussbacher, D. Varró	Automated Domain Modeling with Large Language Models: A Comparative Study	[1]
M. A. Omar	Measurement of ChatGPT Performance in Mapping Natural Language Specification into an Entity Relationship Diagram	[7]
Y. Li, J. Keung, X. Ma, C. Y. Chong, J. Zhang, Y. Liao	LLM-Based Class Diagram Derivation from User Stories with Chain-of-Thought Promptings	[43]
P. Ardimento, M. L. Bernardi, M. Cimitile	Teaching UML using a RAG-based LLM	[45]
M. B. Chaaben, L. Burgueño, H. Sahraoui	Towards using Few-Shot Prompt Learning for Automating Model Completion	[46]
L. Naimi, E. M. Bouziane, M. Manaouch, A. Jakimi	A new approach for automatic test case generation from use case diagram using LLMs and prompt engineering	[48]

Table A.1: List of selected papers

## PROMPTS USED FOR EXPIREMENTS

### B.1 Zero-shot Prompt

You are a software engineer who is creating a < project management system > who has several years of experience in created class diagram models from requirements specification.

Based on UML rules and principles, create a class diagram model for this requirements:

The project manager leads a team to execute the project within the project's start and end dates.

Once the project is created in the project management system, a manager may initiate and later terminate the project due to its completion or for some other reason.

The team executes the project.

Requirements is the input of a project.

As outputs the project shall produce a system.

Requirements and systems are work products.

Work product has a description, information of the percentage of work completed, and may be validated.

The validation is depending on the type of work product.

The requirements are validated with users in workshops.

System are validated by being tested against the requirements.

The requirements may be published using various types of media, including on an intranet or paper form.

Systems may be deployed onto specific plataforms.

The output must be presented using PlantUML code to create the class diagram model.

Relations between classes:

Type Symbol Purpose

Extension <|-- Specialization of a class in a hierarchy

Implementation <|.. Realization of an interface by a class

Composition \*-- The part cannot exist without the whole

Aggregation o-- The part can exist independently of the whole

Dependency --> The object uses another object

Dependency ..> A weaker form of dependency

Declaring element:

```
@startuml
abstract abstract
abstract class "abstract class"
annotation annotation
circle circle
() circle_short_form
class class
class class_stereo <<stereotype>>
diamond diamond
<> diamond_short_form
entity entity
enum enum
exception exception
interface interface
metaclass metaclass
protocol protocol
stereotype stereotype
struct struct
@enduml
```

Label on relations:

```
@startuml

Class01 "1" *-- "many" Class02 : contains

Class03 o-- Class04 : aggregation

Class05 --> "1" Class06

@enduml

@startuml
class Car

Driver - Car : drives >
Car *- Wheel : have 4 >
Car -- Person : < owns

@enduml
```

Listing B.1: Zero-shot prompt

## B.2 Few-shot Prompt

```
You are a software engineer who is creating a < project management system > who has
several years of experience in created class diagram models from requirements
specification.
Based on UML rules and principles, create a class diagram model for this requirements:
```

The project manager leads a team to execute the project within the project's start and end dates.

Once the project is created in the project management system, a manager may initiate and later terminate the project due to its completion or for some other reason.

The team executes the project.

Requirements is the input of a project.

As outputs the project shall produce a system.

Requirements and systems are work products.

Work product has a description, information of the percentage of work completed, and may be validated.

The validation is depending on the type of work product.

The requirements are validated with users in workshops.

System are validated by being tested against the requirements.

The requirements may be published using various types of media, including on an intranet or paper form.

Systems may be deployed onto specific plataforms.

The output must be presented using PlantUML code to create the class diagram model.

Here are some examples of how you should create the class diagram class:

Input Requirements:

Build a software application to manage filmed scenes for realizing a movie, by following the "Hollywood Approach".

Every scene shall be identified by a code and it is described by a text in natural language.

Every scene is filmed at least from one different position.

Each position is a setup.

Setup is characterized by a code (a string) and a text in natural language where the photographic parameters are noted (e.g., aperture, exposure, focal length, filters, etc.)

Each setup is related to a single scene

Every setup has at least one take filmed in.

A take has a positive natural number, a real number representing the number of meters of film that have been used for shooting the take, and the code (string) of the reel where the film is stored.

A take is associated to a single setup.

Scenes can be internals, filmed in a theater, or a externals, filmed in a location and can either be "day scene" or "night scene".

Location have a code (string), an address of the location and a text describing the location.

Output Class diagram PlantUML code:

```
@startuml
class Take{
 nbr: integer
 filmed_meters : Real
 reel : string
}
class Setup{
 code: string
```

```
 photographic_pars: Text
 }
 class Scene{
 code: string
 description: Text
 }
 class Internal{
 theater: string
 }
 class External{
 night_scene : boolean
 }
 class Location{
 name: string
 address: string
 description: text
 }
 Take "1..*" -- "1" Setup: tk_of_stp
 Setup "1..*" -- "1" Scene: stp_for_scn
 Scene <|-- Internal
 Scene <|-- External
 External "0..*" -- "1" Location : located
@enduml
```

**Input Requirements:**

A user can open a new or existing document.

Text is entered through a keyboard.

A document is made up of several pages.

Each page is made up of a header, body and footer.

Date, time and page number may be added to header or footer.

Document body is made up of sentences, which themselves made up of words, and punctuation characters.

Words are made up of letters, digits and/or special characters.

Pictures and tables may be inserted into the document body.

Tables are made up of rows and columns and every cell in a table can contain both text and pictures.

Users can save or print documents.

**Output Class diagram PlantUML code:**

```
@startuml
class Document{
 - numberOfPages
 + open()
 + save()
 + print()
 + new()
}
class Page{
 - pageNumber
 + newPage()
 + hideHeader()
}
```

```

+ hideFooter()
+ insertPicture()
+ insertTable()
}
class Trimming{
- date
- time
- pageNumber
+ display()
+ change()
+ hide()
}
class Character{
- ASCIICode
- type
+ normal()
+ italic()
+ bold()
+ underline()
}
class Table{
- rows
- columns
+ insertRow()
+ insertColumn()
+ newTable()
+ insertPicture()
}
class Picture{
- imageType
- imageSize
+ insert()
+ delete()
}
class Cell{
- cellFormat
+ edit()
}
Document "1" *-- "1..*" Page
Page "1" o-- "0..1" Trimming
Page "1" o-- "0..*" Character
Page "1" o-- "0..*" Table
Page "1" o-- "0..*" Picture
Character "0..*" --o "1" Cell
Table "1" *-- "1..*" Cell
Picture "0..*" --o "1" Cell
@enduml

```

Relations between classes:

Type Symbol Purpose

```
Extension <|-- Specialization of a class in a hierarchy
Implementation <|.. Realization of an interface by a class
Composition *-- The part cannot exist without the whole
Aggregation o-- The part can exist independently of the whole
Dependency --> The object uses another object
Dependency ..> A weaker form of dependency
```

Declaring element:

```
@startuml
abstract abstract
abstract class "abstract class"
annotation annotation
circle circle
() circle_short_form
class class
class class_stereo <<stereotype>>
diamond diamond
<> diamond_short_form
entity entity
enum enum
exception exception
interface interface
metaclass metaclass
protocol protocol
stereotype stereotype
struct struct
@enduml
```

Label on relations:

```
@startuml

Class01 "1" *-- "many" Class02 : contains

Class03 o-- Class04 : aggregation

Class05 --> "1" Class06

@enduml

@startuml
class Car

Driver - Car : drives >
Car *- Wheel : have 4 >
Car -- Person : < owns

@enduml
```

Listing B.2: Few-shot prompt

## B.3 Few-shot Chain-of-thought Prompt

You are an expert software architect and UML modeling specialist with extensive experience in transforming system requirements into precise PlantUML class diagrams that are blueprints of the system. Your task is to analyze system descriptions and create comprehensive, syntactically correct class diagrams that accurately represent the system's structure and relationships.

## Step by Step to create a class diagram

Before creating the class diagram, follow this systematic analysis:

### Step 1: Entity Identification

- **Identify Nouns**: Extract all significant nouns from the requirements (these become potential classes)
- **Classify Entities**: Categorize as concrete classes, abstract classes, or interfaces
- **Eliminate Redundancies**: Remove duplicate or overly similar concepts

### Step 2: Relationship Analysis

- **Identify Associations**: Look for "has-a", "uses", "manages", "contains" relationships
- **Determine Inheritance**: Find "is-a" relationships and generalization hierarchies
- **Establish Multiplicity**: Analyze quantitative relationships. Always specify multiplicities (e.g., `"1" *-- "1..*"`)
- **Identify Aggregation/Composition**: Determine part-whole relationships and their strength

### Step 3: Attribute and Method Extraction

- **Extract Attributes**: Identify properties, characteristics, and data each class should contain
- **Determine Methods**: Identify behaviors, operations, and responsibilities
- **Apply Encapsulation**: Consider visibility modifiers (private, protected, public)

### Step 4: UML Principles Application

- **Single Responsibility**: Ensure each class has one clear purpose
- **Cohesion**: Group related attributes and methods together
- **Coupling**: Minimize dependencies between classes
- **Abstraction**: Use abstract classes/interfaces where appropriate

### Step 5: Validate & Refine

- **No plantUML syntax errors** : Ensure that there are no syntax errors in the generated plantUML code.
- **All requirements mapped** : Guarantee that all specifications of the system present in the description are represented.

## PlantUML Syntax Guidelines



```
Class Declaration
```plantuml
class ClassName {
    - privateAttribute: Type
    # protectedAttribute: Type
    + publicAttribute: Type
    --
    - privateMethod(): ReturnType
    + publicMethod(param: Type): ReturnType
    {abstract} abstractMethod(): ReturnType
    {static} staticMethod(): Type
}

abstract class AbstractClassName
interface InterfaceName
```

Relationship Syntax
- **Association**: `ClassA -- ClassB : label`
- **Directed Association**: `ClassA --> ClassB : label`
- **Aggregation**: `ClassA o-- ClassB : label`
- **Composition**: `ClassA *-- ClassB : label`
- **Inheritance**: `ChildClass --|> ParentClass`
- **Interface Implementation**: `Class ..|> Interface`
- **Dependency**: `ClassA ..> ClassB : uses`

Multiplicity Notation
- `1` - exactly one
- `0..1` - zero or one
- `1..*` - one or more
- `0..*` - zero or more
- `n` - exactly n
- `m..n` - between m and n

Advanced PlantUML Features
- **Packages**: `package PackageName { ... }`
- **Stereotypes**: `<<stereotype>>`

Output Requirements

1. **Structure**: Begin with `@startuml` and end with `@enduml`
2. **Naming**: Use PascalCase for classes, camelCase for attributes/methods
3. **Organization**: Group related classes logically
4. **Clarity**: Include meaningful relationship labels and multiplicities
5. **Completeness**: Represent all significant entities and relationships from requirements

Examples
```

### ### Example 1: Movie Scene Management System

#### \*\*Input System Description:\*\*

We are interested in building a software application to manage filmed scenes for realizing a movie, by following the so-called "Hollywood Approach". Every scene is identified by a code (a string) and it is described by a text in natural language. Every scene is filmed from different positions (at least one), each of this is called a setup. Every setup is characterized by a code (a string) and a text in natural language where the photographic parameters are noted (e.g., aperture, exposure, focal length, filters, etc.). Note that a setup is related to a single scene. For every setup, several takes may be filmed (at least one). Every take is characterized by a (positive) natural number, a real number representing the number of meters of film that have been used for shooting the take, and the code (a string) of the reel where the film is stored. Note that a take is associated to a single setup. Scenes are divided into internals that are filmed in a theater, and externals that are filmed in a location and can either be "day scene" or "night scene". Locations are characterized by a code (a string) and the address of the location, and a text describing them in natural language.

#### \*\*Analysis Process:\*\*

1. **\*\*Entities\*\***: Scene, Setup, Take, Internal, External, Location
2. **\*\*Relationships\*\***: Scene-Setup (1:many), Setup-Take (1:many), External-Location (many:1)
3. **\*\*Inheritance\*\***: Internal and External inherit from Scene
4. **\*\*Attributes\*\***: Extracted from descriptive text

#### \*\*Output Class Diagram:\*\*

```
```plantuml
```

```
@startuml
```

```
class Scene {
    - code: string
    - description: text
    + getCode(): string
    + getDescription(): text
}

class Setup {
    - code: string
    - photographicParameters: text
    + getPhotographicParameters(): text
    + addTake(take: Take): void
}

class Take {
    - number: integer
    - filmedMeters: real
    - reelCode: string
    + getFilmedMeters(): real
    + getReelCode(): string
}
```

```
class Internal {
    - theater: string
    + getTheater(): string
}

class External {
    - isDayScene: boolean
    + isDayScene(): boolean
}

class Location {
    - code: string
    - address: string
    - description: text
    + getAddress(): string
}

Scene <|-- Internal
Scene <|-- External
Scene "1" *-- "1..*" Setup : contains
Setup "1" *-- "1..*" Take : has
External "0..*" --> "1" Location : filmed_at
@enduml
---
```

Task Execution

Now apply this framework to analyze the given system requirements and create a comprehensive PlantUML class diagram. Follow the chain of thought process, explicitly showing your analysis before presenting the final diagram.

System Description

A project manager uses the project management system to manage a project. The project manager leads a team to execute the project within the project's start and end dates. Once a project is created in the project management system, a manager may initiate and later terminate the project due to its completion or for some other reason. As input, a project uses requirements. As output, a project produces a system (or part of a system). The requirements and system are work products: things that are created, used, updated, and elaborated on throughout a project. Every work product has a description, is of some percent complete throughout the effort, and may be validated. However, validation is dependent on the type of work product. For example, the requirements are validated with users in workshops, and the system is validated by being tested against the requirements. Furthermore, requirements may be published using various types of media, including on an intranet or in paper form; and systems may be deployed onto specific platforms.

Listing B.3: Few-shot Chain-of-thought Prompt



