

Network Security - Week 3

Manuel E. Correia

DCC/FCUP

2025

Authentication Protocols - Examples

Enter the NSA

Authentication Protocols - Examples

Enter the NSA

- 1 Insert badge into reader

Enter the NSA

- 1 Insert badge into reader
- 2 Enter PIN

Authentication Protocols - Examples

Enter the NSA

- 1 Insert badge into reader
- 2 Enter PIN
- 3 Is the pin correct?

Enter the NSA

- 1 Insert badge into reader
- 2 Enter PIN
- 3 Is the pin correct?
 - **YES** - Open the door

Enter the NSA

- 1 Insert badge into reader
- 2 Enter PIN
- 3 Is the pin correct?
 - **YES** - Open the door
 - **NO** - Get immediately shot by guard

Authentication Protocols - Examples

Enter the NSA

- 1 Insert badge into reader
- 2 Enter PIN
- 3 Is the pin correct?
 - **YES** - Open the door
 - **NO** - Get immediately shot by guard

ATM Machine Protocol

- 1 Insert ATM card

Authentication Protocols - Examples

Enter the NSA

- 1 Insert badge into reader
- 2 Enter PIN
- 3 Is the pin correct?
 - **YES** - Open the door
 - **NO** - Get immediately shot by guard

ATM Machine Protocol

- 1 Insert ATM card
- 2 Enter PIN

Authentication Protocols - Examples

Enter the NSA

- 1 Insert badge into reader
- 2 Enter PIN
- 3 Is the pin correct?
 - **YES** - Open the door
 - **NO** - Get immediately shot by guard

ATM Machine Protocol

- 1 Insert ATM card
- 2 Enter PIN
- 3 Is the pin correct?

Authentication Protocols - Examples

Enter the NSA

- 1 Insert badge into reader
- 2 Enter PIN
- 3 Is the pin correct?
 - **YES** - Open the door
 - **NO** - Get immediately shot by guard

ATM Machine Protocol

- 1 Insert ATM card
- 2 Enter PIN
- 3 Is the pin correct?
 - **YES** - Perform transaction

Authentication Protocols - Examples


Enter the NSA

- 1 Insert badge into reader
- 2 Enter PIN
- 3 Is the pin correct?
 - **YES** - Open the door
 - **NO** - Get immediately shot by guard

ATM Machine Protocol


- 1 Insert ATM card
- 2 Enter PIN
- 3 Is the pin correct?
 - **YES** - Perform transaction
 - **NO** - Machine eats your card (eventually)

Authentication Protocols - For real now




- Alice must prove her identity to Bob
 - They can be humans or computers

Authentication Protocols - For real now



- Alice must prove her identity to Bob
 - They can be humans or computers
- May also require Bob to prove its identity to Alice
 - A.k.a. mutual authentication

Authentication Protocols - For real now



- Alice must prove her identity to Bob
 - They can be humans or computers
- May also require Bob to prove its identity to Alice
 - A.k.a. mutual authentication
- Often entails establishing a session key
 - For cryptographic purposes

Authentication Protocols - Challenges

Stand-alone computer

Relatively simple

Stand-alone computer

Relatively simple

- Hash a password with a salt

Stand-alone computer

Relatively simple

- Hash a password with a salt
- (relatively reduced) attack surface

Stand-alone computer

Relatively simple

- Hash a password with a salt
- (relatively reduced) attack surface
- Careful with keystroke logging!

Authentication Protocols - Challenges

Stand-alone computer

Relatively simple

- Hash a password with a salt
- (relatively reduced) attack surface
- Careful with keystroke logging!

Over the network

Much more challenging

Authentication Protocols - Challenges

Stand-alone computer

Relatively simple

- Hash a password with a salt
- (relatively reduced) attack surface
- Careful with keystroke logging!

Over the network

Much more challenging

- Adversary can passively observe messages

Authentication Protocols - Challenges

Stand-alone computer

Relatively simple

- Hash a password with a salt
- (relatively reduced) attack surface
- Careful with keystroke logging!

Over the network

Much more challenging

- Adversary can passively observe messages
- Adversary can replay messages

Authentication Protocols - Challenges

Stand-alone computer

Relatively simple


- Hash a password with a salt
- (relatively reduced) attack surface
- Careful with keystroke logging!

Over the network

Much more challenging


- Adversary can passively observe messages
- Adversary can replay messages
- Active attacks possible (insert, delete, change)

A Naive Authentication Protocol




- Simple and (perhaps) OK for a stand-alone machine

A Naive Authentication Protocol




- Simple and (perhaps) OK for a stand-alone machine

A Naive Authentication Protocol




- Simple and (perhaps) OK for a stand-alone machine

A Naive Authentication Protocol




- Simple and (perhaps) OK for a stand-alone machine
- Highly insecure for a networked system

A Naive Authentication Protocol




- Simple and (perhaps) OK for a stand-alone machine
- Highly insecure for a networked system
 - Subject to replay attacks
 - Bob must know Alice's password (explicitly)

The network is insecure!




Authentication Attack




- This is an example of a **replay** attack
 - The adversary observed the interaction
 - Used the messages to repeat a communication pattern

Authentication Attack




- This is an example of a **replay** attack
 - The adversary observed the interaction
 - Used the messages to repeat a communication pattern
- How can we prevent replay attacks?

A (still pretty) Naive Authentication Protocol




- More efficient
- But doesn't solve the replay attack problems!

Hiding the Exact Password




- This approach hides Alice's password

Hiding the Exact Password



- This approach hides Alice's password
 - From both Bob, and the adversary!

Hiding the Exact Password



- This approach hides Alice's password
 - From both Bob, and the adversary!
- But it's still subject to replay attacks...

Freshness: challenge-response

To prevent replay, we leverage a technique called **challenge-response**

Freshness: challenge-response

To prevent replay, we leverage a technique called **challenge-response**

- Suppose Bob wants to authenticate Alice (our setting)
- Bob sends a *challenge* to Alice
- Alice must respond to the *challenge* according to its password

Freshness: challenge-response

To prevent replay, we leverage a technique called **challenge-response**

- Suppose Bob wants to authenticate Alice (our setting)
- Bob sends a *challenge* to Alice
- Alice must respond to the *challenge* according to its password

Challenge

Challenge is chosen such that...

- Replay is not possible
- Only Alice can provide the correct response
- Bob can (efficiently) verify the response

Nonce: A **n**umber that is only used **once**.

Nonce: A **number** that is only used **once**.

Design choices

- How can we choose the nonce?

Nonce: A **number** that is only used **once**.

Design choices


- How can we choose the nonce?
- How should Alice work with the nonce?

Nonce: A **number** that is only used **once**.

Design choices


- How can we choose the nonce?
- How should Alice work with the nonce?
- How can Bob verify the nonce-enhanced response?

Using Nonces




- Nonce is the challenge
 - Every request for authentication must use a different nonce

Using Nonces



- Nonce is the challenge
 - Every request for authentication must use a different nonce
- The hash is the response
 - The message used for the first authentication will not work for any of the following ones
 - Collision-resistant hashes!

Using Nonces



- Nonce is the challenge
 - Every request for authentication must use a different nonce
- The hash is the response
 - The message used for the first authentication will not work for any of the following ones
 - Collision-resistant hashes!
- Bob must know Alice's pwd to verify.

Password not Necessary

An alternative design

- Alice and Bob share symmetric key k

Password not Necessary

An alternative design

- Alice and Bob share symmetric key k
- *Assumption:* k is known only to Alice and Bob

Password not Necessary

An alternative design

- Alice and Bob share symmetric key k
- *Assumption*: k is known only to Alice and Bob
- Authentication requires proving knowledge of k

Password not Necessary

An alternative design

- Alice and Bob share symmetric key k
- *Assumption*: k is known only to Alice and Bob
- Authentication requires proving knowledge of k
- How can we accomplish this?
 - Key cannot be sent over the network (obviously)
 - Replay attacks cannot be successful

Password not Necessary

An alternative design

- Alice and Bob share symmetric key k
- *Assumption*: k is known only to Alice and Bob
- Authentication requires proving knowledge of k
- How can we accomplish this?
 - Key cannot be sent over the network (obviously)
 - Replay attacks cannot be successful

Recall crypto notation!

- Protect message m , using key k to produce ciphertext c

Password not Necessary

An alternative design

- Alice and Bob share symmetric key k
- *Assumption*: k is known only to Alice and Bob
- Authentication requires proving knowledge of k
- How can we accomplish this?
 - Key cannot be sent over the network (obviously)
 - Replay attacks cannot be successful

Recall crypto notation!

- Protect message m , using key k to produce ciphertext c
- Encryption: $c = \text{Encrypt}(k, m)$

Password not Necessary


An alternative design

- Alice and Bob share symmetric key k
- *Assumption:* k is known only to Alice and Bob
- Authentication requires proving knowledge of k
- How can we accomplish this?
 - Key cannot be sent over the network (obviously)
 - Replay attacks cannot be successful

Recall crypto notation!


- Protect message m , using key k to produce ciphertext c
- Encryption: $c = \text{Encrypt}(k, m)$
- Decryption: $m = \text{Decrypt}(k, c)$

Using Symmetric Keys




- Bob can authenticate Alice using k
 - $\text{Decrypt}(k, c)$
 - *Assumption*: Knowledge of k is necessary to create a valid c
 - If c decrypts to *nonce*, then we must be talking to Alice!

Using Symmetric Keys




- Bob can authenticate Alice using k
 - $\text{Decrypt}(k, c)$
 - *Assumption*: Knowledge of k is necessary to create a valid c
 - If c decrypts to *nonce*, then we must be talking to Alice!
- Alice does not authenticate Bob...

Using Symmetric Keys




- Bob can authenticate Alice using k
 - $\text{Decrypt}(k, c)$
 - *Assumption*: Knowledge of k is necessary to create a valid c
 - If c decrypts to *nonce*, then we must be talking to Alice!
- Alice does not authenticate Bob...
- How can we get mutual authentication?

Using Symmetric Keys - Mutual Authentication



- Works... right?

Using Symmetric Keys - Mutual Authentication



- Works... right?
- Anyone can repeat c to “prove” they are Alice.

Mutual Authentication

We have a secure one-way authentication protocol!

Mutual Authentication

We have a secure one-way authentication protocol!

One-way to Mutual

So all we have to do is do the protocol twice:

- The first time is used for Bob to authenticate Alice
- The second is used for Alice to authenticate Bob

Mutual Authentication

We have a secure one-way authentication protocol!


One-way to Mutual

So all we have to do is do the protocol twice:

- The first time is used for Bob to authenticate Alice
- The second is used for Alice to authenticate Bob


What could possibly go wrong?

Mutual Authentication - Naive Protocol




- Ok, now we have mutual authentication!

Mutual Authentication - Naive Protocol



- Ok, now we have mutual authentication!
- Actually...
 - Subject to **reflection** attack

Mutual Authentication - Reflection Attack



One-way to Mutual

One-way authentication protocol is **not** secure for mutual auth

One-way to Mutual

One-way authentication protocol is **not** secure for mutual auth

- Subtle errors (told you!)
- In this case, the obvious solution is not secure

One-way to Mutual

One-way authentication protocol is **not** secure for mutual auth


- Subtle errors (told you!)
- In this case, the obvious solution is not secure
- Problem is related to the fact that the response is not bound to a specific protocol execution

One-way to Mutual

One-way authentication protocol is **not** secure for mutual auth


- Subtle errors (told you!)
- In this case, the obvious solution is not secure
- Problem is related to the fact that the response is not bound to a specific protocol execution
- How can we enforce this one-to-one relation between responses, challenges and identities?

Mutual Authentication - Reflection-proof




- Responses are bound to their respective identities

Mutual Authentication - Reflection-proof



- Responses are bound to their respective identities
- Does this help?

Mutual Authentication - Reflection-proof



- Responses are bound to their respective identities
- Does this help?
- Apparently so...
 - At least for that type of attacks!

Using Public-key Cryptography

What if we use asymmetric keys?

- Alice has secret key sk and Bob knows public key pk

Using Public-key Cryptography

What if we use asymmetric keys?

- Alice has secret key sk and Bob knows public key pk
- *Assumption:* sk is known only to Alice

Using Public-key Cryptography

What if we use asymmetric keys?

- Alice has secret key sk and Bob knows public key pk
- *Assumption*: sk is known only to Alice
- Authentication requires proving knowledge of sk

Using Public-key Cryptography

What if we use asymmetric keys?

- Alice has secret key sk and Bob knows public key pk
- *Assumption*: sk is known only to Alice
- Authentication requires proving knowledge of sk
- How can we accomplish this?
 - Decrypt something with sk
 - Sign something with sk

Using Public-key Cryptography

What if we use asymmetric keys?

- Alice has secret key sk and Bob knows public key pk
- *Assumption*: sk is known only to Alice
- Authentication requires proving knowledge of sk
- How can we accomplish this?
 - Decrypt something with sk
 - Sign something with sk

Recall crypto notation!

- Encryption: $c = \text{Encrypt}(pk, m)$
- Decryption: $m = \text{Decrypt}(sk, c)$

Using Public-key Cryptography


What if we use asymmetric keys?

- Alice has secret key sk and Bob knows public key pk
- *Assumption:* sk is known only to Alice
- Authentication requires proving knowledge of sk
- How can we accomplish this?
 - Decrypt something with sk
 - Sign something with sk

Recall crypto notation!

- Encryption: $c = \text{Encrypt}(pk, m)$
- Decryption: $m = \text{Decrypt}(sk, c)$
- Signature: $s = \text{Sign}(sk, m)$
- Verification: $T/F = \text{Verify}(pk, m, s)$

Mutual Authentication - PKC



Caution with keys...

It's (generally) a bad idea to use the same key pair for encryption and signing.

- Keys get lost
- Keys get compromised

Caution with keys...

It's (generally) a bad idea to use the same key pair for encryption and signing.

- Keys get lost
- Keys get compromised

Good practices

- Use one key pair for encryption/decryption or signing/verification
- Use another for authentication

Establish a secure channel

Session key

- A symmetric key for each session

Establish a secure channel

Session key

- A symmetric key for each session
 - Ephemeral
 - Used for confidentiality and/or integrity

Establish a secure channel

Session key

- A symmetric key for each session
 - Ephemeral
 - Used for confidentiality and/or integrity

Purpose

- Alice and Bob use session key to encrypt/authenticate data

Establish a secure channel

Session key

- A symmetric key for each session
 - Ephemeral
 - Used for confidentiality and/or integrity

Purpose

- Alice and Bob use session key to encrypt/authenticate data
- The adversary cannot determine the session key

Establish a secure channel


Session key

- A symmetric key for each session
 - Ephemeral
 - Used for confidentiality and/or integrity


Purpose

- Alice and Bob use session key to encrypt/authenticate data
- The adversary cannot determine the session key
- Limit amount of data encrypted with a given key
 - Limit damage (data loss) if one key is corrupted

PKC Mutual Authentication - Attempt #1




PKC Mutual Authentication - Attempt #1




- Session key is secure

PKC Mutual Authentication - Attempt #1




- Session key is secure
- Only Alice is authenticated...

PKC Mutual Authentication - Attempt #2




PKC Mutual Authentication - Attempt #2




- Mutual authentication is ensured

PKC Mutual Authentication - Attempt #2




- Mutual authentication is ensured
- But the key is not protected at all!

PKC Mutual Authentication - Attempt #3




PKC Mutual Authentication - Attempt #3




- Is this secure?

PKC Mutual Authentication - Attempt #3




- Is this secure?
- Vulnerable to a MitM attack!

MitM attack




MitM attack




- Carlos can get the session key in the clear
- Alice is convinced to use the same session key
- But she isn't talking to Bob!

PKC Mutual Authentication - Attempt #4




PKC Mutual Authentication - Attempt #4




- Is this secure?

PKC Mutual Authentication - Attempt #4




- Is this secure?
- All seems ok!

MitM attack?



- Carlos only has to send a valid signature to convince Alice

MitM attack?



- Carlos only has to send a valid signature to convince Alice
- ... but without knowledge of sk_b , it cannot produce it!

Network Security - Week 3

Manuel E. Correia

DCC/FCUP

2025