



FADO

Meating 1

Tiago Silva

CISUC · Data-Centric AI Lab

Department of Informatics Engineering, University of Coimbra



Outline

KANs

KAN: Kolmogorov–Arnold Networks

Ziming Liu^{1,4*} Yixuan Wang² Sachin Vaidya¹ Fabian Ruehle^{3,4}
James Halverson^{3,4} Marin Soljačić^{1,4} Thomas Y. Hou² Max Tegmark^{1,4}

¹ Massachusetts Institute of Technology

² California Institute of Technology

³ Northeastern University

⁴ The NSF Institute for Artificial Intelligence and Fundamental Interactions

Kolmogorov-Arnold Networks

Activation functions are placed on edges instead of nodes.

D^3 KAN

A denoising and data-complexity-adaptive KAN for long-term forecasting.

D^3 KAN: Dual Denoising and Data-Complexity-Adaptive Kolmogorov-Arnold Networks for Long-Term Time Series Forecasting

Minrui Wang^{1,2}, Jiwei Qin^{1,2*}, Di Wang^{3,4}, Dacheng Wang⁵,
Zhiqi Shen^{3,4}

The Fortieth AAAI Conference on Artificial Intelligence (AAAI-26)

Learning Fair Representations with Kolmogorov-Arnold Networks

Amisha Priyadarshini¹, Sergio Gago-Masague¹

¹Department of Computer Science, University of California, Irvine, USA
apriyad1@uci.edu, sgagomas@uci.edu

Learning Fair Representations with KANs

KANs applied to learning fair representations.