

# Advanced Programming in the UNIX Environment

**Week 04, Segment 5: `/etc/passwd`**

**Department of Computer Science  
Stevens Institute of Technology**

**Jan Schaumann**

jschauma@stevens.edu

<https://stevens.netmeister.org/631/>

## /etc/passwd

---

Called a *user database* by POSIX and usually found in /etc/passwd, the password file contains the following fields:

Description	struct passwd member	POSIX.1
username	char *pw_name	✓
hashed password	char *pw_passwd	
numerical UID	uid_t pw_uid	✓
numerical GID	gid_t pw_gid	✓
comment	char *pw_gecos	
initial working directory	char *pw_dir	✓
initial shell	char *pw_shell	✓

## /etc/passwd

---

```
root:*:0:0:Charlie &:/root:/bin/csh
toor:*:0:0:Bourne-again Superuser:/root:/rescue/sh
daemon:*:1:1:The devil himself:/:/sbin/nologin
operator:*:2:5:System &:/usr/guest/operator:/sbin/nologin
bin:*:3:7:Binaries Commands and Source:/:/sbin/nologin
games:*:7:13:& pseudo-user:/usr/games:/sbin/nologin
postfix:*:12:12:& pseudo-user:/var/spool/postfix:/sbin/nologin
named:*:14:14:& pseudo-user:/var/chroot/named:/sbin/nologin
ntpd:*:15:15:& pseudo-user:/var/chroot/ntpd:/sbin/nologin
sshd:*:16:16:& pseudo-user:/var/chroot/sshd:/sbin/nologin
uucp:*:66:1:UNIX-to-UNIX Copy:/nonexistent:/sbin/nologin
nobody:*:32767:39:Unprivileged user:/nonexistent:/sbin/nologin
jschauma:*:1000:100:Jan Schaumann,Lieb Building,555-1234,555-2233:/home/jschauma:/bin/sh
fred::1001:100:::/bin/sh
drwho:*:1003:100:The Doctor:/home/drwho:/bin/date
alice:*:1004:100::/home/alice:
alice:*:1002:100::/home/alice:/bin/ksh
```

```
pw_name
pw_passwd
pw_uid
pw_gid
pw_gecos
pw_dir
pw_shell
```

# /etc/passwd

root:*:0:0:Charlie &:/root:/bin/csh	pw_name
toor:*:0:0:Bourne-again Superuser:/root:/rescue/sh	pw_passwd
daemon:*:1:1:The devil himself:/:/sbin/nologin	pw_uid
operator:*:2:5:System &:/usr/guest/operator:/sbin/nologin	pw_gid
bin:*:3:7:Binaries Commands and Source:/:/sbin/nologin	pw_gecos
games:*:7:13:& pseudo-user:/usr/games:/sbin/nologin	pw_dir
postfix:*:12:12:& pseudo-user:/var/spool/postfix:/sbin/nologin	pw_shell
named:*:14:14:& pseudo-user:/var/chroot/named:/sbin/nologin	
ntpd:*:15:15:& pseudo-user:/var/chroot/ntpd:/sbin/nologin	
sshd:*:16:16:& pseudo-user:/var/chroot/sshd:/sbin/nologin	
uucp:*:66:1:UNIX-to-UNIX Copy:/nonexistent:/sbin/nologin	
nobody:*:32767:39:Unprivileged user:/nonexistent:/sbin/nologin	
jschauma:*:1000:100:Jan Schaumann,Lieb Building,555-1234,555-2233:/home/jschauma:/bin/sh	
fred::1001:100:::/bin/sh	
drwho:*:1003:100:The Doctor:/home/drwho:/bin/date	
alice:*:1004:100::/home/alice:	
alice:*:1002:100::/home/alice:/bin/ksh	



alice:\*:1004:100::/home/alice:

alice:\*:1002:100::/home/alice:/bin/ksh

alice@apue\$ pwd

/home/alice

alice@apue\$ ls -la

total 28

drwxr-xr-x	2	alice	users	512	Aug 10	22:51	.
drwxr-xr-x	6	root	wheel	512	Sep 23	21:15	..
-rw-r--r--	1	alice	users	1772	Feb 14	2020	.cshrc
-rw-r--r--	1	alice	users	431	Feb 14	2020	.login
-rw-r--r--	1	alice	users	265	Feb 14	2020	.logout
-rw-r--r--	1	alice	users	1498	Feb 14	2020	.profile
-rw-r--r--	1	alice	users	166	Feb 14	2020	.shrc

alice@apue\$ touch file

touch: file: Permission denied

alice@apue\$ whoami

alice

alice@apue\$ ls -ld

drwxr-xr-x	2	alice	users	512	Aug 10	22:51	.
------------	---	-------	-------	-----	--------	-------	---

alice@apue\$ ls -ln

drwxr-xr-x	2	1002	100	512	Aug 10	22:51	.
------------	---	------	-----	-----	--------	-------	---

alice@apue\$ id -u

1004

alice@apue\$

## /etc/passwd

---

- Most fields in the password database may be empty:
  - empty password field: anybody can log in (probably a mistake)
  - empty home directory field: use / instead
  - empty shell field: use /bin/sh instead
- Entries may be duplicated:
  - same GID: multiple users in the same primary group (normal)
  - same UID: system applies same permissions for all accounts (rarely used)
  - same username: system will pick one or the other (almost always a mistake)