



Browser Fingerprinting: Exploring Device Diversity to Augment Authentication and Build Client-Side Countermeasures

Pierre Laperdrix

Congrès SIF

Insa Rennes et IRISA

7 février 2019

Outline

- I. What is browser fingerprinting?
- II. Defending against fingerprinting: Blink and FPRandom
- III. Conclusion



I. Internet and web browsers


Pierre Laperdrix
Congrès SIF
7 février 2019

3



HTTP User agent





1995	2019
Browser: Netscape Language: Fr	Browser: Chrome v71 OS: Linux Screen: 1920x1080 Language: Fr Timezone: GMT+1 Graphic card: GTX 1080Ti ...

A bigger and richer web



- Audio
- Video
- 3D rendering
- Real-time communications
- Web payments
- Virtual reality

...

What happens when we start collecting all the information available in a web browser?

Definitions

- A **browser fingerprint** is a set of information related to a user's device from the hardware to the operating system to the browser and its configuration.
- Browser **fingerprinting** refers to the process of collecting information through a web browser to build a fingerprint of a device.



<https://amiunique.org> (Am I Unique)

The screenshot shows the Am I Unique website. On the left is a dark sidebar with a teal header 'Am I Unique?'. The sidebar contains links: Home, My fingerprint, Global statistics, FAQ, Privacy policy, Links, About, and View on GitHub. The main content area has a teal header with the same text. Below it, the text reads: 'Learn how identifiable you are on the Internet' and 'Help us investigate the diversity of web browsers'. A large dark button says 'View my browser fingerprint'. Below this button, a disclaimer states: 'By clicking on this button, only anonymous data will be collected and a cookie will be stored in your browser for four months. You can find more details in the Privacy Policy.' Further down, it says 'Spread the word! Share AmIUnique! Try it on all your devices!' followed by social media icons (email, Facebook, Twitter, Google+, Pinterest, Reddit, and a QR code). At the bottom, there is a link 'What is browser fingerprinting? Learn more' and a footer note: 'Any questions? Send us an email at contact@amiunique.org'.

- Website launched in November 2014
- Collected 980,000+ fingerprints so far
- Browser extension available to see the evolution of your own browser fingerprint

I. Example of a browser fingerprint

Attribute	Value
User agent	Mozilla/5.0 (X11; Fedora; Linux x86_64; rv:55.0) Gecko/20100101 Firefox/55.0
HTTP headers	text/html, application/xhtml+xml, application/xml;q=0.9,*/*;q=0.8 gzip, deflate, br en-US,en;q=0.5
Plugins	Plugin 0: QuickTime Plug-in 7.6.6; libtotem-narrow-space-plugin.so; Plugin 1: Shockwave Flash; Shockwave Flash 26.0 r0; libflashplayer.so.
Fonts	Century Schoolbook, Source Sans Pro Light, DejaVu Sans Mono, Bitstream Vera Serif, URW Palladio L, Bitstream Vera Sans Mono, Bitstream Vera Sans, ...
Platform	Linux x86_64
Screen resolution	1920x1080x24
Timezone	-480 (UTC+8)
OS	Linux 3.14.3-200.fc20.x86 32-bit
WebGL vendor	NVIDIA Corporation
WebGL renderer	GeForce GTX 650 Ti/PCIe/SSE2
Canvas	<div>Cwm fjordbank glyphs vext quiz, ☺</div> <div>Cwm fjordbank glyphs vext quiz, ☺</div>



Maverick
Ocean Front Villas
Mandarin tea
Regency
Sassafras & Ginger
Dollhouse
Athletics Dept.



Some user-agents

- Mozilla/5.0 (Windows NT 6.1; WOW64; rv:34.0) Gecko/20100101 Firefox/34.0
- Mozilla/5.0 (iPhone; CPU iPhone OS 8_1_2 like Mac OS X) AppleWebKit/600.1.4 (KHTML, like Gecko) Version/8.0 Mobile/12B440 Safari/600.1.4
- Mozilla/5.0 (Android; Mobile; rv:27.0) Gecko/27.0 Firefox/27.0
- Mozilla/5.0 (Macintosh; Intel Mac OS X 10_10_2) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/39.0.2171.95 Safari/537.36
- Mozilla/5.0 (X11; Ubuntu; Linux i686; rv:34.0) Gecko/20100101 Firefox/34.0

Other custom user-agents

- godzilla/5.0 (X122; BSD; rv:500.0) Gecko/20100101
- pouet
- “54. When a warlike prince attacks a powerful state, his generalship shows itself in preventing the concentration of the enemy's forces. He overawes his opponents, and their allies are prevented from joining against him.”
- Deepnet Explorer 1.5.3; Smart 2x2; Avant Browser; .NET CLR 2.0.50727; InfoPath.1)
- NSA
- Game Boy Advance
- eat it

Cwm fjordbank glyphs vext quiz, ☺

Cwm fjordbank glyphs vext quiz, ☺

What makes fingerprinting a threat to online privacy?

1. It is really easy to collect all this data. No need for extra permissions.
2. Two studies have investigated the diversity of browser fingerprints.



470,161 fingerprints
94.2% were unique

118,934 fingerprints
89.4% were unique


Tracking is possible

Am I Unique?

Outline

- I. What is browser fingerprinting?
- II. Defending against fingerprinting: Blink and FPRandom
- III. Conclusion


- Goal: to protect users against browser fingerprinting, i.e. to prevent them from being tracked online
- Challenge: finding the right balance between protection and usability
- The proposed defense solution should:
 - not break browsing.
 - not be detectable (no inconsistencies or no side-effects).
 - work automatically without requiring user interaction.




The diagram shows a table representing browser fingerprinting data. It has a 'Header' row and three data rows. The 'User agent' row contains 'Mozilla/5.0 (Windows NT 6.1; WOW64; rv:54.0) Gecko/20100101 Firefox/54.0', with 'Windows' highlighted in a red box. The 'Platform' row contains 'Linux i686', with 'Linux i686' highlighted in a red box. The 'WebGL renderer' row contains 'GeForce GTX 650 Ti/PCIe/SSE2'. The table is decorated with a pink bar on the left, an orange bar at the bottom, and a green bar at the bottom right.

Header	
User agent	Mozilla/5.0 (Windows NT 6.1; WOW64; rv:54.0) Gecko/20100101 Firefox/54.0
Platform	Linux i686
WebGL renderer	GeForce GTX 650 Ti/PCIe/SSE2


- Increase temporal diversity of fingerprints
- Browsing without Blink



- Browsing with Blink



- Reconfigure platform at runtime



- Protection against specific techniques of fingerprinting at the browser level
- Targeting “dynamic” attributes, i.e. those that are the result of a computation, by introducing noise

Canvas fingerprinting

Cwm fjordbank glyphs vext quiz, ☺

Cwm fjordbank glyphs vext quiz, ☺



Cwm fjordbank glyphs vext quiz, ☺

Cwm fjordbank glyphs vext quiz, ☺

Cwm fjordbank glyphs vext quiz, ☺

Cwm fjordbank glyphs vext quiz, ☺

Cwm fjordbank glyphs vext quiz, ☺

Cwm fjordbank glyphs vext quiz, ☺

Cwm fjordbank glyphs vext quiz, ☺

Cwm fjordbank glyphs vext quiz, ☺


Cwm fjordbank glyphs vext quiz, ☺

Cwm fjordbank glyphs vext quiz, ☺

Cwm fjordbank glyphs vext quiz, ☺

Cwm fjordbank glyphs vext quiz, ☺

AudioContext fingerprinting




Enumeration order

sendBeacon;vibrate;javaEnabled;getGamepads;mozGetUserMedia;
requestMediaKeySystemAccess;registerProtocolHandler;registerCo
ntentHandler;taintEnabled;permissions.....




plugins;oscpu;doNotTrack;getVRDisplays;mimeType;vibrate;vend
orSub;vendor;productSub;cookieEnabled;mozGetUserMedia;getBa
ttery;buildID;javaEnabled;getGamepads;permissions...

Blink
OS level



FPRandom
Browser level



Outline

- I. What is browser fingerprinting?
- II. Defending against fingerprinting: Blink and FPRandom
- III. Conclusion

Past

Present

Future

Understand
fingerprinting



Am I Unique?

Add new attributes

Cwm fjordbank glyphs vext quiz, ☺

Cwm fjordbank glyphs vext quiz, ☺

Design defense
mechanisms



Use fingerprints



Protect against it



Tracking at large scale




Increase online security?



Regulate fingerprinting



Control fingerprinting?



Thank you!

Any questions?

Contact

 plaperdrix@cs.stonybrook.edu

 @RockPartridge

Websites on fingerprinting


<https://amiunique.org>


<https://fpcentral.tbb.torproject.org/>

Additional slides

Am I Unique?

- Study performed on 118,934 in 2016
- 90% of unique fingerprints → Tracking is possible
- Validates Panoptick's findings
- Fingerprinting mobile devices is possible
 - List of plugins and fonts are strongest on desktops
 - User-agents and canvas are strongest on mobile devices
- Online privacy could be improved with simple browser modifications





- Project developed as part of the Google Summer of Code 2016
- Help Tor users to see if their fingerprint only has acceptable values
- Help Tor developers react to new fingerprinting vectors rapidly
- Will integrate the Quality Assurance process of the Tor Browser to verify the non-regression of the Tor fingerprinting protection

- In theory, all fingerprints from the Tor Browser should be identical.
- In reality, differences can still be found (screen resolution, platform...).



Tor browser on Fedora 25


Attribute	Value
User agent ⓘ	Mozilla/5.0 (Windows NT 6.1; rv:52.0) Gecko/20100101 Firefox/52.0
Accept ⓘ	text/html,application/xhtml+xml,application/xml;q=0.9;*/q=0.8
Content encoding ⓘ	gzip, deflate, br
Content language ⓘ	en-US,en;q=0.5
List of plugins ⓘ	
Platform ⓘ	Win32
Cookies enabled ⓘ	yes
Do Not Track ⓘ	NC
Timezone ⓘ	0
Screen resolution ⓘ	1000x1000x24
Use of local storage ⓘ	yes
Use of session storage ⓘ	yes
Canvas ⓘ	
WebGL Vendor ⓘ	Not supported
WebGL Renderer ⓘ	Not supported
List of fonts ⓘ	Flash not detected
Screen resolution ⓘ	Flash not detected
Language ⓘ	Flash not detected
Platform ⓘ	Flash not detected
Use of Adblock ⓘ	no



Firefox browser on Fedora 25

Attribute	Value
User agent ⓘ	Mozilla/5.0 (X11; Fedora; Linux x86_64; rv:55.0) Gecko/20100101 Firefox/55.0
Accept ⓘ	text/html,application/xhtml+xml,application/xml;q=0.9;*/q=0.8
Content encoding ⓘ	gzip, deflate, br
Content language ⓘ	en-US,en;q=0.5
List of plugins ⓘ	
Platform ⓘ	Linux x86_64
Cookies enabled ⓘ	yes
Do Not Track ⓘ	yes
Timezone ⓘ	-120
Screen resolution ⓘ	1920x1200x24
Use of local storage ⓘ	yes
Use of session storage ⓘ	yes
Canvas ⓘ	Cwm fjordbank glyphs vext quiz, ☹ Cwm fjordbank glyphs vext quiz, ☺
WebGL Vendor ⓘ	Intel Open Source Technology Center
WebGL Renderer ⓘ	Mesa DRI Intel(R) Haswell Mobile
List of fonts ⓘ	Flash not detected
Screen resolution ⓘ	Flash not detected
Language ⓘ	Flash not detected


- Plugins are considered to be a source of hangs, crashes, security incidents, and code complexity.
- HTML5 now replaces the features offered by plugins.
- Support for the plugin architecture called NPAPI was removed from Chrome in April 2015 and Firefox in March 2017.



NPAPI support

- Enabled
- Disabled
- Removed

- The global entropy of plugins is rapidly dropping.
- Their use in fingerprinting is becoming limited.



Timeline from “Battery Status Not Included: Assessing Privacy in Web Standards” by Olejnik et al.