

OUTPUT

```
mysql> create table employee
```

```
-> (  
->   emp_no int,  
->   email varchar(20),  
->   job varchar(20),  
->   salary int  
-> );
```

Query OK, 0 rows affected (0.01 sec)

```
mysql> desc employee;
```

Field	Type	Null	Key	Default	Extra
emp_no	int	YES		NULL	
email	varchar(20)	YES		NULL	
job	varchar(20)	YES		NULL	
salary	int	YES		NULL	

4 rows in set (0.02 sec)

```
mysql> alter table employee add commission int;
```

Query OK, 0 rows affected (0.05 sec)

Records: 0 Duplicates: 0 Warnings: 0

```
mysql> desc employee;
```

Field	Type	Null	Key	Default	Extra
emp_no	int	YES		NULL	
email	varchar(20)	YES		NULL	
job	varchar(20)	YES		NULL	
salary	int	YES		NULL	
commission	int	YES		NULL	

5 rows in set (0.00 sec)

```
mysql> alter table employee drop job;
```

Query OK, 0 rows affected (0.01 sec)

Records: 0 Duplicates: 0 Warnings: 0

```
mysql> desc employee;
```

Field	Type	Null	Key	Default	Extra
emp_no	int	YES		NULL	
email	varchar(20)	YES		NULL	
salary	int	YES		NULL	
commission	int	YES		NULL	

4 rows in set (0.00 sec)

```
mysql> alter table employee modify column email char(30);
```

Query OK, 0 rows affected (0.03 sec)

Records: 0 Duplicates: 0 Warnings: 0

```
mysql> desc employee;
```

Field	Type	Null	Key	Default	Extra
emp_no	int	YES		NULL	
email	char(30)	YES		NULL	
salary	int	YES		NULL	
commission	int	YES		NULL	

4 rows in set (0.00 sec)

```
mysql> alter table employee rename to employeedetails;
Query OK, 0 rows affected (0.01 sec)
```

```
mysql> show tables;
```

```
+-----+
| Tables_in_gk52 |
+-----+
| employeedetails |
+-----+
1 row in set (0.00 sec)
```

//

```
mysql> create table department
-> (
->     deptno int,
->     deptname varchar(20),
->     location varchar(20)
-> );
Query OK, 0 rows affected (0.01 sec)
```

```
mysql> desc department;
```

```
+-----+-----+-----+-----+-----+-----+
| Field | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| deptno | int           | YES  |     | NULL    |       |
| deptname | varchar(20)   | YES  |     | NULL    |       |
| location | varchar(20)   | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
3 rows in set (0.00 sec)
```

```
mysql> alter table department add designation char(20);
Query OK, 0 rows affected (0.01 sec)
Records: 0 Duplicates: 0 Warnings: 0
```

```
mysql> desc department;
```

```
+-----+-----+-----+-----+-----+-----+
| Field | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| deptno | int           | YES  |     | NULL    |       |
| deptname | varchar(20)   | YES  |     | NULL    |       |
| location | varchar(20)   | YES  |     | NULL    |       |
| designation | char(20)      | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
4 rows in set (0.00 sec)
```

```
mysql> alter table department drop location;
Query OK, 0 rows affected (0.01 sec)
Records: 0 Duplicates: 0 Warnings: 0
```

```
mysql> desc department;
```

```
+-----+-----+-----+-----+-----+-----+
| Field | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| deptno | int           | YES  |     | NULL    |       |
| deptname | varchar(20)   | YES  |     | NULL    |       |
| designation | char(20)      | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
3 rows in set (0.00 sec)
```

```
mysql> alter table department modify deptname char(50);
Query OK, 0 rows affected (0.02 sec)
Records: 0 Duplicates: 0 Warnings: 0
```

```
mysql> desc department;
```

Field	Type	Null	Key	Default	Extra
deptno	int	YES		NULL	
deptname	char(50)	YES		NULL	
designation	char(20)	YES		NULL	

3 rows in set (0.00 sec)

////////////////////////////////////

```
mysql> create table customer (
->     custname varchar(20),
->     custstreet varchar(20),
->     custcity varchar(20)
-> );
Query OK, 0 rows affected (0.01 sec)
```

```
mysql> desc customer;
```

Field	Type	Null	Key	Default	Extra
custname	varchar(20)	YES		NULL	
custstreet	varchar(20)	YES		NULL	
custcity	varchar(20)	YES		NULL	

3 rows in set (0.00 sec)

```
mysql> alter table customer add salary int;
Query OK, 0 rows affected (0.32 sec)
Records: 0 Duplicates: 0 Warnings: 0
```

```
mysql> desc customer;
```

Field	Type	Null	Key	Default	Extra
custname	varchar(20)	YES		NULL	
custstreet	varchar(20)	YES		NULL	
custcity	varchar(20)	YES		NULL	
salary	int	YES		NULL	

4 rows in set (0.00 sec)

```
mysql> alter table customer drop custstreet;
Query OK, 0 rows affected (0.01 sec)
Records: 0 Duplicates: 0 Warnings: 0
```

```
mysql> desc customer;
```

Field	Type	Null	Key	Default	Extra
custname	varchar(20)	YES		NULL	
custcity	varchar(20)	YES		NULL	
salary	int	YES		NULL	

3 rows in set (0.01 sec)

```
mysql> alter table customer modify custname char(30);
```

```
Query OK, 0 rows affected (0.03 sec)
```

```
Records: 0 Duplicates: 0 Warnings: 0
```

```
mysql> desc customer;
```

Field	Type	Null	Key	Default	Extra
custname	char(30)	YES		NULL	
custcity	varchar(20)	YES		NULL	
salary	int	YES		NULL	

```
3 rows in set (0.00 sec)
```

```
////////////////////////////////////////////////////////////////
```

```
mysql> create table branch(
```

```
->     branch_name varchar(20),
```

```
->     city varchar(20),
```

```
->     amount int
```

```
-> );
```

```
Query OK, 0 rows affected (0.01 sec)
```

```
mysql> desc branch;
```

Field	Type	Null	Key	Default	Extra
branch_name	varchar(20)	YES		NULL	
city	varchar(20)	YES		NULL	
amount	int	YES		NULL	

```
3 rows in set (0.00 sec)
```

```
mysql> alter table branch drop column branch_name, drop column city;
```

```
Query OK, 0 rows affected (1.78 sec)
```

```
Records: 0 Duplicates: 0 Warnings: 0
```

```
mysql> desc branch;
```

Field	Type	Null	Key	Default	Extra
amount	int	YES		NULL	

```
1 row in set (0.00 sec)
```

```
////////////////////////////////////////////////////////////////
```

```
mysql> create table sailor (
```

```
->     sid int,
```

```
->     sname varchar(20),
```

```
->     rating varchar(20)
```

```
-> );
```

```
Query OK, 0 rows affected (0.01 sec)
```

```
mysql> desc sailor;
```

Field	Type	Null	Key	Default	Extra
sid	int	YES		NULL	
sname	varchar(20)	YES		NULL	
rating	varchar(20)	YES		NULL	

```
3 rows in set (0.00 sec)
```

```
mysql> alter table sailor add column age int after sname;
Query OK, 0 rows affected (0.01 sec)
Records: 0 Duplicates: 0 Warnings: 0
```

```
mysql> desc sailor;
```

Field	Type	Null	Key	Default	Extra
sid	int	YES		NULL	
sname	varchar(20)	YES		NULL	
age	int	YES		NULL	
rating	varchar(20)	YES		NULL	

4 rows in set (0.00 sec)

```
mysql> alter table sailor drop column rating;
Query OK, 0 rows affected (0.01 sec)
Records: 0 Duplicates: 0 Warnings: 0
```

```
mysql> desc sailor;
```

Field	Type	Null	Key	Default	Extra
sid	int	YES		NULL	
sname	varchar(20)	YES		NULL	
age	int	YES		NULL	

3 rows in set (0.00 sec)

//