

# Two-Archive Evolutionary Algorithm for Constrained Multiobjective Optimization

Ke Li<sup>ID</sup>, *Member, IEEE*, Renzhi Chen, Guangtao Fu, and Xin Yao<sup>ID</sup>, *Fellow, IEEE*

**Abstract**—When solving constrained multiobjective optimization problems, an important issue is how to balance convergence, diversity, and feasibility simultaneously. To address this issue, this paper proposes a parameter-free constraint handling technique, a two-archive evolutionary algorithm, for constrained multiobjective optimization. It maintains two collaborative archives simultaneously: one, denoted as the convergence-oriented archive (CA), is the driving force to push the population toward the Pareto front; the other one, denoted as the diversity-oriented archive (DA), mainly tends to maintain the population diversity. In particular, to complement the behavior of the CA and provide as much diversified information as possible, the DA aims at exploring areas under-exploited by the CA including the infeasible regions. To leverage the complementary effects of both archives, we develop a restricted mating selection mechanism that adaptively chooses appropriate mating parents from them according to their evolution status. Comprehensive experiments on a series of benchmark problems and a real-world case study fully demonstrate the competitiveness of our proposed algorithm, in comparison to five state-of-the-art constrained evolutionary multiobjective optimizers.

**Index Terms**—Constraint handling, evolutionary algorithm (EA), decomposition-based technique, multiobjective optimization, two-archive strategy.

Manuscript received November 21, 2017; revised April 4, 2018; accepted June 19, 2018. Date of publication July 19, 2018; date of current version March 29, 2019. This work was supported in part by the Royal Society under Grant IEC/NSFC/170243, in part by the Ministry of Science and Technology of China under Grant 2017YFC0804003, in part by the Science and Technology Innovation Committee Foundation of Shenzhen under Grant ZDSYS201703031748284, in part by the Shenzhen Peacock Plan under Grant KQTD2016112514355531, and in part by EPSRC under Grant EP/J017515/1 and Grant EP/P005578/1. The work of G. Fu was supported by the Royal Society Industry Fellowship under Grant IF160108. (Ke Li and Renzhi Chen contributed equally to this work.) (Corresponding author: Xin Yao.)

K. Li is with the College of Computer Science and Engineering, University of Electronic Science and Technology of China, Chengdu, 611731, China, and also with the Department of Computer Science, University of Exeter, Exeter EX4 4QF, U.K. (e-mail: kli@uestc.edu.cn).

R. Chen is with the School of Computer Science, National University of Defence Technology, Changsha 410073, China (e-mail: chengrenzhi1989@gmail.com).

G. Fu is with the Department of Engineering, University of Exeter, Exeter EX4 4QF, U.K. (e-mail: g.fu@exeter.ac.uk).

X. Yao is with CERCIA, School of Computer Science, University of Birmingham, Birmingham B15 2TT, U.K., and also with the Shenzhen Key Laboratory of Computational Intelligence, Department of Computer Science and Engineering, Southern University of Science and Technology, Shenzhen 518055, China (e-mail: x.yao@cs.bham.ac.uk).

This paper has supplementary downloadable material available at <http://ieeexplore.ieee.org>, provided by the author. This supplementary document contains additional figures and tables related to the main paper. The total size of the file is 2.37 MB.

Color versions of one or more of the figures in this paper are available online at <http://ieeexplore.ieee.org>.

Digital Object Identifier 10.1109/TEVC.2018.2855411

## I. INTRODUCTION

THE CONSTRAINED multiobjective optimization problem (CMOP) considered in this paper is defined as

$$\begin{aligned} &\text{minimize } \mathbf{F}(\mathbf{x}) = (f_1(\mathbf{x}), \dots, f_m(\mathbf{x}))^T \\ &\text{subject to } g_j(\mathbf{x}) \geq a_j, \quad j = 1, \dots, q \\ &\quad h_j(\mathbf{x}) = b_j, \quad j = q + 1, \dots, \ell \\ &\quad \mathbf{x} \in \Omega \end{aligned} \quad (1)$$

where  $\mathbf{x} = (x_1, \dots, x_n)^T$  is a candidate solution, and  $\Omega = [x_i^L, x_i^U]^n \subseteq \mathbb{R}^n$  defines the search (or decision variable) space.  $\mathbf{F} : \Omega \rightarrow \mathbb{R}^m$  constitutes  $m$  conflicting objective functions, and  $\mathbb{R}^m$  is the objective space.  $g_j(\mathbf{x})$  and  $h_j(\mathbf{x})$  are the  $j$ th inequality and equality constraints, respectively. For a CMOP, the degree of constraint violation of  $\mathbf{x}$  at the  $j$ th constraint is calculated as [1]

$$c_j(\mathbf{x}) = \begin{cases} \langle g_j(\mathbf{x})/a_j - 1 \rangle, & j = 1, \dots, q \\ \langle |h_j(\mathbf{x})/b_j - 1| - \epsilon \rangle, & j = q + 1, \dots, \ell \end{cases} \quad (2)$$

where  $\epsilon$  is a sufficiently small tolerance term (e.g.,  $\epsilon = 10^{-6}$ ) for relaxing the equality constraints to the inequality constraints.  $\langle \alpha \rangle$  returns 0 if  $\alpha \geq 0$  otherwise it returns the negative of  $\alpha$ . The constraint violation value of  $\mathbf{x}$  is calculated as

$$\text{CV}(\mathbf{x}) = \sum_{j=1}^{\ell} c_j(\mathbf{x}). \quad (3)$$

$\mathbf{x}$  is feasible in case  $\text{CV}(\mathbf{x}) = 0$ ; otherwise  $\mathbf{x}$  is infeasible. Given two feasible solutions  $\mathbf{x}^1, \mathbf{x}^2 \in \Omega$ , we said that  $\mathbf{x}^1$  dominates  $\mathbf{x}^2$  (denoted as  $\mathbf{x}^1 \preceq \mathbf{x}^2$ ) in case  $\mathbf{F}(\mathbf{x}^1)$  is not worse than  $\mathbf{F}(\mathbf{x}^2)$  in any individual objective and it at least has one better objective. A solution  $\mathbf{x}^*$  is Pareto-optimal with respect to (1) in case  $\nexists \mathbf{x} \in \Omega$  such that  $\mathbf{x} \preceq \mathbf{x}^*$ . The set of all Pareto-optimal solutions is called the Pareto set (PS). Accordingly,  $\text{PF} = \{\mathbf{F}(\mathbf{x}) | \mathbf{x} \in \text{PS}\}$  is called the Pareto front (PF).

Since evolutionary algorithm (EA) is able to approximate a population of nondominated solutions, which portray the tradeoffs among conflicting objectives, in a single run, it has been recognized as a major approach for multiobjective optimization. Over the past two decades, much effort has been devoted to developing evolutionary multiobjective optimization (EMO) algorithms, e.g., elitist nondominated sorting genetic algorithm (NSGA-II) [2], indicator-based EA [3], and multiobjective EA based on decomposition [4]. Nevertheless, although most, if not all, real-life optimization scenarios have various constraints by nature,

it is surprising that the research on constraint handling is lukewarm in the EMO community [5], comparing to algorithms designed for the unconstrained scenarios.

Generally speaking, *convergence*, *diversity*, and *feasibility* are three basic issues for CMOPs. Most, if not all, current constraint handling techniques at first tend to push a population toward the feasible region as much as possible, before considering the balance between convergence and diversity within the feasible region. This might lead to the population being stuck at some locally optimal or locally feasible regions, especially when the feasible regions are narrow and/or disparately distributed in the search space.

In this paper, we propose a two-archive EA, denoted as C-TAEA, for solving CMOPs. Specifically, we simultaneously maintain two collaborative and complementary archives: one is denoted as the convergence-oriented archive (CA); while the other is denoted as the diversity-oriented archive (DA). The main characteristics of C-TAEA are delineated as follows.

- 1) As the name suggests, the CA is the driving force to maintain the convergence and feasibility of the evolution process. It provides selection pressure toward the PF.
- 2) In contrast, without considering the feasibility, the DA mainly tends to maintain the convergence and diversity of the evolution process. In particular, the DA explores the areas that have not been exploited by the CA. This not only improves the population diversity of the CA within the currently investigating feasible region but also helps to jump over the local optima or locally feasible regions.
- 3) To leverage the complementary effect and the elite information of these two collaborative archives, we develop a restricted mating selection mechanism that selects the appropriate mating parents from the CA and DA separately according to their evolution status.

The idea of using two archives in EMO has been around since 2006 [6]. For example, [6]–[8] developed several two-archive EMO algorithms that use two “conceptually” complementary populations to strike the balance between convergence and diversity of the evolutionary process. Li *et al.* [9] developed a dual-population paradigm that combines the strengths of decomposition- and Pareto-based selection mechanisms. In this paper, we would like to, for the first time, explore the potential advantages of the two-archive strategy for CMOPs.

The rest of this paper is organized as follows. Section II briefly overviews the state-of-the-art evolutionary approaches developed for CMOPs and then elicits our motivations. Section III describes the technical details of the proposed algorithm step by step. Afterward, in Sections IV and V, the effectiveness and competitiveness of the proposed algorithm are empirically investigated and compared with five state-of-the-art constrained EMO algorithms on various benchmark problems. Finally, Section VI concludes with a summary and ideas for future directions.

## II. PRELIMINARIES

In this section, we first briefly review some recent developments of constraint handling techniques in the EMO

community. A more recent empirical comparisons of the performance of various constrained EMO algorithms can be found in [10]–[12]. Afterward, we will give our motivations based on some examples.

### A. Literature Review

Generally speaking, the ideas of the existing constraint handling techniques in multiobjective optimization can be divided into the following three categories.

The first category is mainly driven by the feasibility information where feasible solutions are always granted a higher priority to survive to the next iteration. As early as the 1990s, Fonseca and Fleming [13] developed a unified framework for solving MOPs with multiple constraints. In particular, they assign a higher priority to constraints than to objective functions. This results in a prioritization of the search for feasible solutions over optimal solutions. Coello and Christiansen [14] proposed a naïve constraint handling method that simply ignores the infeasible solutions. Although this method is easy to implement, it suffers the loss of selection pressure when tackling problems with a narrow feasible region. In particular, this algorithm will have no selection pressure when the population is filled with infeasible solutions. Deb *et al.* [2] developed a constrained dominance relation for CMO. Specifically, a solution  $\mathbf{x}^1$  is said to constraint-dominate  $\mathbf{x}^2$ , if: 1)  $\mathbf{x}^1$  is feasible while  $\mathbf{x}^2$  is not; 2) both of them are infeasible and  $CV(\mathbf{x}^1) < CV(\mathbf{x}^2)$ ; or 3) both of them are feasible and  $\mathbf{x}^1 < \mathbf{x}^2$ . By simply replacing the Pareto dominance relation with this constrained dominance relation, the state-of-the-art NSGA-II and NSGA-III [15] can be readily used to tackle CMOPs. Borrowing the similar idea, several MOEA/D variants [15]–[17] use the CV as an alternative criterion in the subproblem update procedure. Different from [2], Oyama *et al.* [18] developed a modified dominance relation according to which solutions who violate fewer number of constraints are preferred. To improve the interpretability of infeasible solutions, Takahama and Sakai [19] and Martínez and Coello [20] proposed an  $\epsilon$ -constrained dominance relation where two solutions violate constraints equally in case the difference of their CVs is smaller than a threshold  $\epsilon$ . In particular, this threshold can be adaptively tuned according to the ratio of feasible solutions in the population. Asafuddoula *et al.* [21] proposed an adaptive constraint handling method that treats infeasible solutions as feasible ones in case their CVs are less than a threshold. Analogously, Fan *et al.* [22] developed an angle-based constrained dominance principle by which two infeasible solutions are regarded as nondominated from each other when their angle is larger than a threshold.

The second category aims at balancing the tradeoff between convergence and feasibility during the search process. Jiménez *et al.* [23] proposed a min–max formulation that drives feasible solutions to evolve toward optimality and drives infeasible solutions to evolve toward feasibility. Ray *et al.* [24] suggested a Ray-Tai-Seow algorithm that uses three different methods to compare and rank nondominated solutions. Specifically, the first ranking procedure is conducted by sorting

the objective values; the second one is performed according to different constraints; while the last one is based on a combination of objective values and constraints. Based on the same rigor, Young [25] proposed a constrained dominance relation that compares solutions according to the blended rank from both the objective space and the constraint space. A similar approach is developed by Angantyr *et al.* [26] that uses the weighted average rank of the ranks in both the objective space and the constraint space. By transforming each of the original objective functions of a CMOP into the sum of the distance measure and penalty function, [5] developed a new constraint handling technique for CMO. In particular, the modified objective functions are used in the nondominated sorting procedure of NSGA-II to facilitate the search of optimal solutions in both feasible and infeasible regions. To improve the population diversity, Li *et al.* [27] developed a method that preserves infeasible solutions in case they are in the isolated regions. To exploit useful information contained in infeasible solutions, Peng *et al.* [28] proposed to use a set of infeasible weights, distributed in the infeasible region, to maintain a number of well-diversified infeasible solutions. Ning *et al.* [29] proposed a constrained nondominated sorting method where each solution is assigned a constrained nondomination rank based on its Pareto rank and constraint rank. In [30], a duality evolution is proposed where infeasible particles evolve toward feasibility and feasible particles evolve toward PF.

The last category tries to repair the infeasible solutions in order to drives them toward the feasible region. For example, Harada *et al.* [31] proposed a so-called Pareto descent repair operator that explores possible feasible solutions around infeasible solutions in the constraint space. However, the gradient information is usually unavailable in practice. Singh *et al.* [32] suggested to use simulated annealing to accelerate the progress of movements from infeasible solutions toward feasible ones. Jiao *et al.* [33] developed a feasible-guiding strategy in which the feasible direction is defined as a vector starting from an infeasible solution and ending up with its nearest feasible solution. Afterward, infeasible solutions are guided toward the feasible region by leveraging the information provided by the feasible direction.

### B. Challenges to Existing Constraint Handling Techniques

From the above literature review, we find that most, if not all, constraint handling techniques in multiobjective optimization overly emphasize the importance of feasibility, whereas they rarely consider the balance among convergence, diversity, and feasibility simultaneously. This can lead to an ineffective search when encountering complex constraints.

Let us first consider a test problem C1-DTLZ3 defined in [15], where the objective functions are the same as the classic DTLZ3 problem [34] while the constraint is defined as

$$c(\mathbf{x}) = \left( \sum_{i=1}^m f_i(\mathbf{x})^2 - 16 \right) \left( \sum_{i=1}^m f_i(\mathbf{x})^2 - r^2 \right) \geq 0. \quad (4)$$

Fig. 1 shows a two-objective example where  $r$  is set to 6. From this figure, we can see that the feasible region of this test problem is intersected by an infeasible ribbon. In




Fig. 1. Comparative results on the two-objective C1-DTLZ3.




Fig. 2. Comparative results on the two-objective C2-DTLZ2.

addition, within this infeasible region, the CV of a solution increases when it moves away from the feasible boundary, and decreases otherwise. Therefore, it is not difficult to infer that a feasibility-driven strategy will be easily trapped in the outermost feasible boundary. To validate this assertion, we employ the state-of-the-art C-MOEA/D and C-NSGA-III [15] as the benchmark algorithms where the corresponding parameters are set the same as [15]. As shown in Fig. 1, solutions found by both algorithms are stuck in the outermost feasible boundary after 1000 generations.

Let us consider another test problem C2-DTLZ2 defined in [15], where the objective functions are the same as the classic DTLZ2 problem [34] while the constraint is defined as

$$c(\mathbf{x}) = \max \left\{ \max_{i=1}^m \left[ (f_i(\mathbf{x}) - 1)^2 + \sum_{j=1, j \neq i}^m f_j^2 - r^2 \right], \left[ \sum_{i=1}^m \left( f_i(\mathbf{x}) - \frac{1}{\sqrt{m}} \right)^2 - r^2 \right] \right\}. \quad (5)$$

Fig. 2 gives an example in the two-objective scenario, where the feasible region is disjointly distributed on the PF. If the size of each feasible segment is small, a feasibility-driven strategy will be easily trapped in some, not all, of the feasible segments. Furthermore, it is highly likely that none of the weight vectors used in the state-of-the-art decomposition-based EMO algorithms, e.g., C-MOEA/D and C-NSGA-III, cross these feasible segments if their sizes are sufficiently small. This results in significant difficulties for the decomposition-based EMO algorithms to find feasible solutions. The results shown in Fig. 2 fully validate our assertions, where neither C-MOEA/D nor C-NSGA-III can find Pareto-optimal solutions on all three feasible segments when we set  $r$  to be a relatively small value, say 0.1.

Based on these discussions, we find that an excessive use of the feasibility information can restrict the search ability of a constrained EMO algorithm. In Section III, we will demonstrate how to use a two-archive strategy to balance the




Fig. 3. Flow chart of C-TAEA.

convergence, diversity, and feasibility simultaneously in the entire search space. In particular, we find that an appropriate use of the infeasibility information can help to resolve the dilemma between exploration versus exploitation.

### III. PROPOSED ALGORITHM

The general flow chart of our proposed C-TAEA is given in Fig. 3. As its name suggests, C-TAEA maintains two collaborative archives, named CA and DA, each of which has the same and fixed size  $N$ . Specifically, CA, as the main force, is mainly responsible for driving the population toward the feasible region and approximating the PF; DA, as a complement, is mainly used to explore the areas under-exploited by the CA. It is worth noting that, to provide as much diversified information as possible, the update of the DA does not take the feasibility information into account. During the reproduction process, mating parents are separately selected from the CA and the DA according to their evolution status, as described in Section III-D. Afterward, the offspring are used to update the CA and the DA according to the mechanisms described in Sections III-B and III-C separately.

#### A. Density Estimation Method

Before explaining the update mechanisms of the CA and the DA in C-TAEA, we first introduce the density estimation method that is useful for both cases. To facilitate the density estimation, we borrow the idea from MOEA/D-M2M [35] to divide the objective space into  $N$  subregions, each of which is represented by a unique weight vector on the canonical simplex. In particular, we employ our previously developed weight vector generation method [27], which is scalable to the many-objective scenarios, to sample a set of uniformly distributed weight vectors, i.e.,  $W = \{\mathbf{w}^1, \dots, \mathbf{w}^N\}$ . Specifically, a subregion  $\Delta^i$ , where  $i \in \{1, \dots, N\}$ , is defined as

$$\Delta^i = \{\mathbf{F}(\mathbf{x}) \in \mathbb{R}^m | \langle \mathbf{F}(\mathbf{x}), \mathbf{w}^i \rangle \leq \langle \mathbf{F}(\mathbf{x}), \mathbf{w}^j \rangle\} \quad (6)$$

where  $j \in \{1, \dots, N\}$  and  $\langle \mathbf{F}(\mathbf{x}), \mathbf{w} \rangle$  is the acute angle between  $\mathbf{F}(\mathbf{x})$  and  $\mathbf{w}$ . After the setup of subregions, each solution  $\mathbf{x}$  of a population is associated with a unique subregion whose index is determined as

$$k = \underset{i \in \{1, \dots, N\}}{\operatorname{argmin}} \langle \bar{\mathbf{F}}(\mathbf{x}), \mathbf{w}^i \rangle \quad (7)$$

where  $\bar{\mathbf{F}}(\mathbf{x}, t)$  is the normalized objective vector of  $\mathbf{x}$ , and its  $i$ th objective function is calculated as

$$\bar{f}_i(\mathbf{x}) = \frac{f_i(\mathbf{x}) - z_i^*}{z_i^{\text{nad}} - z_i^*} \quad (8)$$

#### Algorithm 1: Association Procedure

**Input:** Solution set  $S$ , weight vector set  $W$

**Output:** Subregions  $\Delta^1, \dots, \Delta^N$

```

1  $\Delta^1 \leftarrow \emptyset, \dots, \Delta^N \leftarrow \emptyset;$ 
2 foreach  $\mathbf{x} \in S$  do
3   foreach  $\mathbf{w} \in W$  do
4     Compute  $d^\perp(\mathbf{x}, \mathbf{w}) = \mathbf{x} - \mathbf{w}^T \mathbf{x} / \|\mathbf{w}\|;$ 
5    $k \leftarrow \underset{\mathbf{w} \in W}{\operatorname{argmin}} d^\perp(\mathbf{x}, \mathbf{w});$ 
6    $\Delta^k \leftarrow \Delta^k \cup \{\mathbf{x}\};$ 
7 return  $\Delta^1, \dots, \Delta^N$ 
  
```

where  $i \in \{1, \dots, m\}$ ,  $\mathbf{z}^*$ , and  $\mathbf{z}^{\text{nad}}$  are, respectively, the estimated ideal and nadir points, where  $z_i^* = \min_{\mathbf{x} \in S} f_i(\mathbf{x})$  and  $z_i^{\text{nad}} = \max_{\mathbf{x} \in S} f_i(\mathbf{x})$  and  $S$  is the current solution set. Algorithm 1 gives the pseudo-code of this association procedure. After associating solutions with subregions, the density of a subregion is counted as the number of its associated solutions.

#### B. Update Mechanism of the CA

The effect of the CA is similar to the other constrained EMO algorithms in the literature. It first pushes the population toward the feasible region as much as possible, then it tries to balance the convergence and diversity within the feasible region. The pseudo-code of the update mechanism of the CA is given in Algorithm 2. Specifically, we first form a hybrid population  $H_c$ , a combination of the CA and the offspring population  $Q$ . Feasible solutions in  $H_c$  are chosen into a temporary archive  $S_c$  (lines 3–5 of Algorithm 2). Afterward, the follow-up procedure depends on the size of  $S_c$ .

- 1) If the size of  $S_c$  equals  $N$  (i.e., the predefined size of the CA), it is directly used as the new CA and this update procedure terminates (lines 6 and 7 of Algorithm 2).
- 2) If  $|S_c| > N$ , we use the fast nondominated sorting method [2] to divide  $S_c$  into several nondomination levels, i.e.,  $F_1, F_2$ , and so on. Starting from  $F_1$ , each nondomination level is sequentially chosen to construct a temporary archive  $S$  until its size equals or for the first time exceeds  $N$  (lines 9–11 of Algorithm 2). If we denote the last acceptable nondomination level as  $F_l$ , solutions belonging to  $F_{l+1}$  onward are exempt from further consideration. Note that  $S$  can be used as the new CA if its size equals  $N$ ; otherwise we associate each solution in  $S$  with its corresponding subregion and calculate  $S$ 's



**Algorithm 2:** Update Mechanism of CA

---

**Input:** CA, offspring population  $Q$ , weight vector set  $W$   
**Output:** Updated CA

```

1  $S \leftarrow \emptyset, S_c \leftarrow \emptyset, i \leftarrow 1, H_c \leftarrow CA \cup Q;$ 
2 foreach  $\mathbf{x} \in H_c$  do
3   if  $CV(\mathbf{x}) = 0$  then
4      $S_c \leftarrow S_c \cup \{\mathbf{x}\};$ 
5 if  $|S_c| = N$  then
6    $CA \leftarrow S_c;$ 
7 else if  $|S_c| > N$  then
8   Use nondominated sorting to divide  $S_c$  into
    $\{F_1, F_2, \dots\}$  based on the MOP defined in (1);
9   while  $|S| < N$  do
10     $S \leftarrow S \cup F_i, i \leftarrow i + 1;$ 
11 if  $|S| > N$  then
12   foreach  $\mathbf{x} \in S$  do
13      $\bar{\mathbf{F}}_k(\mathbf{x}) = \frac{\mathbf{F}(\mathbf{x}) - \mathbf{z}^*}{\mathbf{z}^{nad} - \mathbf{z}^*};$ 
14      $\{\Delta^1, \dots, \Delta^N\} \leftarrow \text{Association}(S, W);$ 
15     while  $|S| > N$  do
16       Find the most crowded subregion  $\Delta^i;$ 
17       foreach  $\mathbf{x} \in \Delta^i$  do
18          $dist(\mathbf{x}) \leftarrow \min_{\mathbf{x}' \in \Delta^i, \mathbf{x} \neq \mathbf{x}'} \|\mathbf{x} - \mathbf{x}'\|;$ 
19        $S_t \leftarrow \underset{\mathbf{x} \in \Delta^i}{\text{argmin}}\{dist(\mathbf{x})\};$ 
20        $\mathbf{x}^w \leftarrow \underset{\mathbf{x} \in S_t}{\text{argmax}}\{g^{tch}(\mathbf{x}|\mathbf{w}^i, \mathbf{z}^*)\};$ 
21        $S \leftarrow S \setminus \{\mathbf{x}^w\};$ 
22    $CA \leftarrow S;$ 
23 else
24    $S_t \leftarrow H_c \setminus S_c;$ 
25   Use nondominated sorting to divide  $S_t$  into
    $\{F_1, F_2, \dots\}$  based on the MOP defined in (12);
26   while  $|S_c| < N$  do
27      $S \leftarrow S \cup F_i, i \leftarrow i + 1;$ 
28   while  $|S| > N$  do
29      $\mathbf{x}^w \leftarrow \underset{\mathbf{x} \in F_{i-1}}{\text{argmax}}\{CV(\mathbf{x})\}, S \leftarrow S \setminus \{\mathbf{x}^w\};$ 
30    $CA \leftarrow S;$ 
31 return CA

```

---

density information afterward. Iteratively, a worst solution from the most crowded subregion (tie is broken randomly) is trimmed one at a time until  $S$ 's size equals  $N$  (lines 11–21 of Algorithm 2). Note that, to improve the population diversity within a subregion, we propose the following process to identify the worst solution  $\mathbf{x}^w$ . First, we calculate the distance between each solution  $\mathbf{x}$  in  $\Delta^i$  and its nearest neighbor

$$dist(\mathbf{x}) = \min_{\mathbf{x}' \in \Delta^i, \mathbf{x} \neq \mathbf{x}'} \|\mathbf{x} - \mathbf{x}'\| \quad (9)$$

where  $\|\cdot\|$  indicates the  $\ell_2$ -norm. Afterward, the solutions having the smallest distance are stored in a temporary

archive  $S_t$ , while  $\mathbf{x}^w$  is defined as

$$\mathbf{x}^w = \underset{\mathbf{x} \in S_t}{\text{argmax}} \left\{ g^{tch}(\mathbf{x}|\mathbf{w}^i, \mathbf{z}^*) \right\} \quad (10)$$

where

$$g^{tch}(\mathbf{x}|\mathbf{w}^i, \mathbf{z}^*) = \max_{1 \leq j \leq m} \left\{ |f_j(\mathbf{x}) - z_j^*|/w_j^i \right\}. \quad (11)$$

- 3) Otherwise, if the feasible solutions in  $H_c$  do not fill the new CA ( $|S_c| < N$ ), we formulate a new bi-objective optimization problem as follows:

$$\begin{aligned} &\text{minimize } \mathbf{F}(\mathbf{x}) = (f_1(\mathbf{x}), f_2(\mathbf{x}))^T \\ &\text{where } \begin{cases} f_1(\mathbf{x}) = CV(\mathbf{x}) \\ f_2(\mathbf{x}) = g^{tch}(\mathbf{x}|\mathbf{w}^i, \mathbf{z}^*). \end{cases} \end{aligned} \quad (12)$$

Based on (12), we use the fast nondominated sorting method to divide the infeasible solutions in  $H_c$  into several nondomination levels (lines 24 and 25 of Algorithm 2). Solutions in the first several levels have a higher priority to survive into the new CA. Exceeded solutions are trimmed according to their CVs, i.e., the solution having a larger CV is trimmed at first (lines 28 and 29 of Algorithm 2). These operations tend to further balance the convergence, diversity, and feasibility.

### C. Update Mechanism of the DA

Different from the CA, the DA aims at providing as much diversified solutions as possible. In particular, its update mechanism has two characteristics: 1) it does not take the constraint violation into consideration and 2) it takes the up to date CA as a reference set so that it complements the behavior of the CA by exploring its under-exploited areas. The pseudo-code of this update procedure is presented in Algorithm 3. Specifically, similar to Section III-B, we at first combine the DA with the offspring population  $Q$  to form a hybrid population  $H_d$ . Then, we separately associate each solution in  $H_d$  and the up to date CA with its corresponding subregion according to the method introduced in Section III-A (lines 1–3 of Algorithm 3). Afterward, we iteratively investigate each subregion and decide the survival of solutions in  $H_d$  to the new DA. In particular, at the  $itr$ th iteration, at most  $itr$  solutions, including those in the CA and  $H_d$ , can survive in each subregion. In other words, for the currently investigating subregion, say  $\Delta^i, i \in \{1, \dots, N\}$ , if there already exists  $itr$  solutions in CA at  $\Delta^i$ , no solution in  $H_d$  will be considered to survive at  $\Delta^i$  during this iteration. Otherwise, the best nondominated solutions in  $H_d$  associated with  $\Delta^i$ , denoted as  $\mathbf{O}^i$ , will be chosen to survive to the new DA (lines 10–12 of Algorithm 3). Here, the best solution  $\mathbf{x}^b$  is identified as

$$\mathbf{x}^b = \underset{\mathbf{x} \in \mathbf{O}^i}{\text{argmin}} \left\{ g^{tch}(\mathbf{x}|\mathbf{w}^i, \mathbf{z}^*) \right\}. \quad (13)$$

This iterative investigation continues till the DA is filled.

### D. Offspring Reproduction

The interaction and collaboration between two archives is a vital step in C-TAEA. Apart from the complementary behavior of the update mechanisms of the CA and the DA, the

**Algorithm 3: Update Mechanism of the DA**


---

**Input:** CA, DA, offspring population  $Q$ , weight vector set  $W$   
**Output:** Updated DA

```

1  $S \leftarrow \emptyset, i \leftarrow 1, H_d \leftarrow DA \cup Q;$ 
2  $\{\Delta_d^1, \dots, \Delta_d^N\} \leftarrow \text{Association}(H_d, W);$ 
3  $\{\Delta_c^1, \dots, \Delta_c^N\} \leftarrow \text{Association}(CA, W);$ 
4  $\text{itr} \leftarrow 1;$ 
5 while  $|S| \leq N$  do
6   for  $i \leftarrow 1$  to  $N$  do
7     if  $|\Delta_c^i| < \text{itr}$  then
8       for  $i \leftarrow 1$  to  $\text{itr} - |\Delta_c^i|$  do
9         if  $\Delta_d^i \neq \emptyset$  then
10           $O^i \leftarrow \text{nondominated solutions in } \Delta_d^i;$ 
11           $\mathbf{x}^b \leftarrow \text{argmin}_{\mathbf{x} \in O^i} \{g^{tch}(\mathbf{x} | \mathbf{w}^c, \mathbf{z}^*)\};$ 
12           $\Delta_d^i \leftarrow \Delta_d^i \setminus \{\mathbf{x}^b\}, S \leftarrow S \cup \{\mathbf{x}^b\};$ 
13        else
14          break;
15    $\text{itr} \leftarrow \text{itr} + 1;$ 
16  $DA \leftarrow S;$ 
17 return DA

```

---

**Algorithm 4: Restricted Mating Selection**


---

**Input:** CA, DA  
**Output:** Mating parents  $\mathbf{p}_1, \mathbf{p}_2$

```

1  $H_m \leftarrow CA \cup DA;$ 
2  $\rho_c \leftarrow \text{proportion of nondominated solution of CA in } H_m;$ 
3  $\rho_d \leftarrow \text{proportion of nondominated solution of DA in } H_m;$ 
4 if  $\rho_c > \rho_d$  then
5    $\mathbf{p}_1 \leftarrow \text{TournamentSelection}(CA);$ 
6 else
7    $\mathbf{p}_1 \leftarrow \text{TournamentSelection}(DA);$ 
8 if  $\text{rand} < \rho_c$  then
9    $\mathbf{p}_2 \leftarrow \text{TournamentSelection}(CA);$ 
10 else
11    $\mathbf{p}_2 \leftarrow \text{TournamentSelection}(DA);$ 
12 return  $\mathbf{p}_1, \mathbf{p}_2$ 

```

---

other contributing factor for this collaboration is the restricted mating selection. Generally speaking, its major purpose is to leverage the elite information from both archives for offspring reproduction. Algorithm 4 provides the pseudo code of this restricted mating selection procedure. Specifically, we first combine the CA and the DA into a composite set  $H_m$ . Afterward, we separately evaluate the proportion of nondominated solutions of the CA and the DA in  $H_m$  (lines 2 and 3 of Algorithm 4). If  $\rho_c > \rho_d$ , it means that the convergence status of the CA is better than that of the DA. Accordingly, the first mating parent is chosen from the CA; otherwise, it comes from the DA (lines 4–7 of Algorithm 4). As for the other mating parent, whether it is chosen from the CA or the DA depends on the proportion of nondominated solutions in

**Algorithm 5: Tournament Selection**


---

**Input:** Solution set  $S$   
**Output:** Mating parent  $\bar{\mathbf{x}}$

```

1 Randomly pick two solutions  $\mathbf{x}^1$  and  $\mathbf{x}^2$  from  $S$ ;
2 if  $\mathbf{x}^1$  and  $\mathbf{x}^2$  are feasible then
3   if  $\mathbf{x}^1 \preceq \mathbf{x}^2$  then
4      $\bar{\mathbf{x}} \leftarrow \mathbf{x}^1;$ 
5   else if  $\mathbf{x}^2 \preceq \mathbf{x}^1$  then
6      $\bar{\mathbf{x}} \leftarrow \mathbf{x}^2;$ 
7   else
8      $\bar{\mathbf{x}} \leftarrow \text{Randomly pick one from } \mathbf{x}^1 \text{ and } \mathbf{x}^2;$ 
9 else if Only one solution is feasible then
10   $\bar{\mathbf{x}} \leftarrow \text{feasible one from } \mathbf{x}^1 \text{ and } \mathbf{x}^2;$ 
11 else
12   $\bar{\mathbf{x}} \leftarrow \text{Randomly pick one from } \mathbf{x}^1 \text{ and } \mathbf{x}^2;$ 
13 return  $\bar{\mathbf{x}}$ 

```

---

the CA (lines 8–11 of Algorithm 4). The more nondominated solutions CA has, the larger chance it has to be chosen as the mating pool. As shown in lines 5–11 of Algorithm 4, we use a binary tournament selection to choose a mating parent. As shown in Algorithm 5, the same as the one proposed in [2], this tournament selection procedure is feasibility-driven. Specifically, if the randomly selected candidates are all feasible, they are chosen based on the Pareto dominance; if only one of them is feasible, the feasible one will be chosen; otherwise, the mating parent is chosen in a random manner. Once the mating parents are chosen, we use the popular simulated binary crossover [36] and the polynomial mutation [37] for offspring reproduction. In principle, any other reproduction operator can be readily applied with a minor modification.

## IV. EXPERIMENTAL SETUP

Before discussing the empirical results, this section briefly introduces the benchmark problems, performance metrics, and the state-of-the-art constrained EMO algorithms used for peer comparisons in our empirical studies.

## A. Benchmark Suite

Five constrained test problems (i.e., C1-DTLZ1/DTLZ3, C2-DTLZ2, and C3-DTLZ1/DTLZ4) from [15] and six newly proposed test problems (DC1-DTLZ1/DTLZ3, DC2-DTLZ2/DTLZ4, and DC3-DTLZ1/DTLZ4) are chosen to form the benchmark suite. All these test problems are scalable to any number of objectives, where we set  $m \in \{3, 5, 8, 10, 15\}$  here. Detailed descriptions, including the mathematical definitions and properties, of these test problems are given in Section I in the supplementary material.

## B. Performance Metrics

Two widely used metrics are chosen to assess the performance of different algorithms.

- 1) *Inverted Generational Distance (IGD)* [38]: Given  $P^*$  as a set of points uniformly sampled along the PF and  $P$  as

the set of solutions obtained from an EMO algorithm. The IGD value of  $P$  is calculated as

$$\text{IGD}(P, P^*) = \frac{\sum_{z \in P^*} \text{dist}(z, P)}{|P^*|} \quad (14)$$

where  $\text{dist}(z, P)$  is the Euclidean distance between  $z$  and its nearest neighbor in  $P$ .

- 2) *Hypervolume (HV)* [39]: Let  $\mathbf{z}^r = (z_1^r, \dots, z_m^r)^T$  be a worst point dominated by all the Pareto optimal objective vectors. The HV of  $P$  is defined as the volume of the objective space dominated by solutions in  $P$  and bounded by  $\mathbf{z}^r$

$$\text{HV}(P) = \text{VOL} \left( \bigcup_{z \in P} [z_1, z_1^r] \times \dots \times [z_m, z_m^r] \right) \quad (15)$$

where VOL indicates the Lebesgue measure.

To calculate the IGD, we need to sample sufficient amount of points from the PF to form  $P^*$ . For C-DTLZ benchmark problems, we use the method developed in [27] to fulfill this purpose. Before calculating the HV, we remove the solutions dominated by the  $\mathbf{z}^r$ , which is set as  $\underbrace{(1.1, \dots, 1.1)}_m^T$

in our empirical studies, except for C3-DTLZ4 where  $\mathbf{z}^r = \underbrace{(2.1, \dots, 2.1)}_m^T$ . Note that only feasible solutions are used for performance metric calculation. Both IGD and HV can evaluate the convergence and diversity simultaneously. A smaller IGD or a larger HV value indicates a better approximation to the PF. Each algorithm is independently run 51 times. The median and the interquartile range (IQR) of the IGD and HV values are presented in the corresponding tables. In particular, the best results are highlighted in boldface with a gray background. To have a statistically sound conclusion, we use the Wilcoxon's rank sum test at a significant level of 5% to validate the significance of the better performance achieved by the proposed C-TAEA with respect to the other peer algorithms.

### C. EMO Algorithms Used for Comparisons

Five state-of-the-art constrained EMO algorithms, i.e., C-MOEA/D, C-NSGA-III, C-MOEA/DD [27], I-DBEA [21], and CMOEA [5], are chosen for peer comparisons. Due to the page limit, the description of these algorithms and their corresponding parameter settings can be found in Section II in the supplementary material.

## V. EMPIRICAL STUDIES

In this section, we discuss the empirical results on different benchmark problems separately.

### A. C-DTLZ Benchmark Suite

The comparison results of IGD values are given in Table I while the results on HV values are given in Tables VI and VII in the supplementary material. Generally speaking, our proposed C-TAEA produces superior IGD and HV values on most test instances.

Let us first look at the Type-1 constrained problem. Although the feasible region of C1-DTLZ1 is only a narrow

region above the PF, it actually does not pose any difficulty to all algorithms. In particular, all algorithms, especially those purely feasibility-driven ones, just simply push solutions toward the feasible boundary. As for C1-DTLZ3, C-TAEA shows the best performance on all 3- to 15-objective problem instances. In particular, it obtains around 50 times smaller IGD values than the other peer algorithms on average; only C-TAEA obtains effective HV values while the HV values obtained by the other peer algorithms are always 0, which means that the obtained nondominated solutions are all dominated by  $\mathbf{z}^r$ . As shown in Fig. 2 in the supplementary material, C1-DTLZ3 places an infeasible barrier in the attainable objective space, which obstructs the population for converging to the true PF. As discussed in Section II-B, due to their feasibility-driven selection strategy, the other peer algorithms cannot provide any further selection pressure to push the population forward when it approaches the outer boundary of this infeasible barrier, as shown in Fig. 4.<sup>1</sup> In contrast, since the selection mechanism of the DA does not take the feasibility information into account, it can constantly push the solutions of the DA toward the PF without considering the existence of this infeasible barrier. In the meanwhile, the CA can at the end overcome this infeasible barrier via the restricted mating selection between the CA and the DA. We also notice that C-TAEA cannot push solutions to fully converge on the PF in high-dimensional cases as shown in Fig. 17–20 in the supplementary material. This is because the size of the infeasible barrier increases with the dimensionality. It makes C1-DTLZ3 even more difficult in a many-objective scenario. Nevertheless, the solutions obtained by C-TAEA are much closer to the PF than the other peer algorithms.

The feasible region of the Type-2 constrained problem, i.e., C2-DTLZ2, is disjointedly distributed along the PF. All algorithms do not have any difficulty in finding at least one feasible PF segment, whereas only C-TAEA can find all disparately distributed small feasible PF segments as shown in Fig. 5. The reason that leads to this phenomenon is similar to C1-DTLZ3. Specifically, each feasible segment is small when setting a small  $r$  in C2-DTLZ2, thus different feasible segments are separated by large infeasible barriers. In this case, if an algorithm finds one of the feasible PF segments, it hardly has any sufficient selection pressure to jump over this locally feasible PF segment. However, due to the existence of the DA in C-TAEA, it complements the coverage of the CA. As shown in Fig. 6, solutions in the CA and the DA perfectly complements each other in terms of the coverage over the PF. Thus, the DA helps the CA to explore new feasible segments.

As for the Type-3 constrained problems, i.e., C3-DTLZ1 and C3-DTLZ4, the original PF of the baseline problem becomes infeasible when considering the constraints while the new PF is formed by the feasible boundaries. In terms of the constraint handling, this type of problems does not provide too much difficulty. From the comparison results shown in Tables I and VI in the supplementary material, we

<sup>1</sup>We only show the 3-objective scatter plots in this paper, while the high-dimensional plots, which are not as intuitive as the 3-objective scenarios, are put in the supplementary material.

TABLE I  
COMPARISON RESULTS ON IGD METRIC (MEDIAN AND IQR) FOR C-TAEA AND THE OTHER PEER ALGORITHMS ON C-DTLZ BENCHMARK SUITE

	$m$	C-TAEA	C-NSGA-III	C-MOEA/D	C-MOEA/DD	I-DBEA	CMOEA
C1-DTLZ1	3	2.069E-2(1.33E-5)	<b>2.037E-2(7.06E-5)<sup>‡</sup></b>	2.110E-2(3.17E-4) <sup>†</sup>	2.116E-2(4.75E-4) <sup>†</sup>	2.180E-2(6.03E-6) <sup>†</sup>	2.140E-2(5.45E-4) <sup>†</sup>
	5	<b>5.278E-2(1.16E-3)</b>	5.427E-2(1.62E-3) <sup>†</sup>	5.294E-2(7.79E-5) <sup>†</sup>	5.287E-2(1.81E-5)	5.285E-2(6.62E-5)	5.284E-2(1.97E-5)
	8	<b>9.912E-2(1.60E-3)</b>	1.009E-1(1.59E-3)	1.006E-1(6.93E-4)	1.024E-1(1.86E-3) <sup>†</sup>	1.009E-1(5.30E-4)	1.008E-1(5.76E-4)
	10	1.061E-1(3.82E-3)	<b>1.038E-1(8.86E-3)<sup>‡</sup></b>	1.074E-1(7.81E-2)	1.065E-1(9.08E-2)	1.072E-1(7.87E-3)	1.072E-1(3.39E-3)
	15	<b>2.233E-1(8.02E-4)</b>	2.351E-1(3.40E-3) <sup>†</sup>	2.608E-1(7.62E-3) <sup>†</sup>	2.490E-1(6.53E-3) <sup>†</sup>	2.506E-1(4.47E-3) <sup>†</sup>	2.611E-1(7.25E-3) <sup>†</sup>
C1-DTLZ3	3	<b>5.661E-2(8.49E-3)</b>	8.020E+0(4.22E-3) <sup>†</sup>	8.007E+0(1.72E-3) <sup>†</sup>	8.012E+0(1.08E-3) <sup>†</sup>	8.013E+0(7.59E-3) <sup>†</sup>	8.007E+0(2.07E-3) <sup>†</sup>
	5	<b>5.364E-1(9.03E-1)</b>	1.162E+1(3.96E-2) <sup>†</sup>	1.154E+1(4.41E-3) <sup>†</sup>	1.155E+1(1.12E+1) <sup>†</sup>	1.153E+1(4.79E-3) <sup>†</sup>	1.154E+1(9.23E-3) <sup>†</sup>
	8	<b>4.115E-1(1.31E-2)</b>	1.180E+1(8.59E-2) <sup>†</sup>	1.160E+1(2.64E-3) <sup>†</sup>	1.161E+1(4.47E-4) <sup>†</sup>	1.160E+1(6.98E-3) <sup>†</sup>	1.159E+1(1.84E-2) <sup>†</sup>
	10	<b>3.896E-1(8.75E-2)</b>	1.430E+1(3.30E-2) <sup>†</sup>	1.414E+1(1.93E-2) <sup>†</sup>	1.414E+1(7.36E-3) <sup>†</sup>	1.416E+1(6.11E-3) <sup>†</sup>	1.412E+1(2.90E-2) <sup>†</sup>
	15	<b>8.749E-1(3.16E-2)</b>	1.470E+1(5.33E-2) <sup>†</sup>	1.466E+1(8.22E-2) <sup>†</sup>	1.461E+1(4.30E-2) <sup>†</sup>	1.463E+1(1.26E-2) <sup>†</sup>	1.461E+1(6.31E-2) <sup>†</sup>
C2-DTLZ2	3	<b>1.594E-2(2.95E-3)</b>	9.043E-1(1.25E-4) <sup>†</sup>	9.069E-1(3.74E-1) <sup>†</sup>	5.648E-1(3.67E-1) <sup>†</sup>	9.069E-1(1.76E-3) <sup>†</sup>	9.069E-1(1.05E-2) <sup>†</sup>
	5	<b>3.386E-1(1.46E-1)</b>	1.068E+0(2.59E-5) <sup>†</sup>	4.863E-1(5.93E-1) <sup>†</sup>	1.069E+0(3.97E-2) <sup>†</sup>	1.070E+0(1.54E-3) <sup>†</sup>	1.074E+0(4.35E-3) <sup>†</sup>
	8	<b>1.310E-4(8.22E-4)</b>	1.206E+0(1.25E-5) <sup>†</sup>	1.220E+0(7.64E-3) <sup>†</sup>	1.237E+0(2.27E-6) <sup>†</sup>	1.051E+0(1.84E-1) <sup>†</sup>	1.223E+0(6.64E-4) <sup>†</sup>
	10	<b>2.600E-5(1.03E-6)</b>	1.241E+0(7.00E-6) <sup>†</sup>	1.254E+0(5.57E-3) <sup>†</sup>	1.273E+0(1.28E-5) <sup>†</sup>	1.263E+0(1.46E-1) <sup>†</sup>	1.257E+0(4.48E-3) <sup>†</sup>
	15	<b>5.658E-1(2.38E-3)</b>	1.287E+0(3.34E-4) <sup>†</sup>	1.317E+0(6.43E-2) <sup>†</sup>	1.320E+0(7.21E-1) <sup>†</sup>	1.315E+0(3.64E-2) <sup>†</sup>	1.316E+0(3.79E-2) <sup>†</sup>
C3-DTLZ1	3	<b>4.311E-2(1.22E-4)</b>	7.653E-2(1.40E-3) <sup>†</sup>	4.344E-2(2.86E-2) <sup>†</sup>	9.344E-2(1.98E-4) <sup>†</sup>	4.435E-2(4.79E-3) <sup>†</sup>	4.435E-2(1.22E-3) <sup>†</sup>
	5	1.073E-1(3.06E-5)	1.124E-1(2.76E-3) <sup>†</sup>	<b>1.073E-1(5.84E-5)</b>	1.438E-1(5.19E-4) <sup>†</sup>	1.074E-1(6.95E-6)	1.077E-1(3.30E-4)
	8	<b>1.993E-1(8.34E-3)</b>	2.052E-1(4.98E-3)	2.009E-1(4.97E-3)	2.460E-1(1.11E-4) <sup>†</sup>	2.031E-1(2.07E-3)	2.011E-1(8.72E-4)
	10	<b>2.104E-1(2.27E-4)</b>	2.310E-1(2.52E-2) <sup>†</sup>	2.151E-1(2.72E-3) <sup>†</sup>	2.655E-1(7.16E-3) <sup>†</sup>	2.154E-1(5.21E-3) <sup>†</sup>	2.163E-1(3.30E-3) <sup>†</sup>
	15	<b>3.463E-1(4.76E-3)</b>	3.686E-1(1.41E-2) <sup>†</sup>	3.989E-1(8.25E-3) <sup>†</sup>	3.688E-1(2.49E-2) <sup>†</sup>	3.680E-1(8.14E-2) <sup>†</sup>	3.909E-1(5.29E-2) <sup>†</sup>
C3-DTLZ4	3	<b>4.789E-1(2.00E-6)</b>	4.838E-1(1.03E-4) <sup>†</sup>	4.841E-1(4.21E-3) <sup>†</sup>	4.848E-1(2.57E-4) <sup>†</sup>	4.824E-1(3.57E-4) <sup>†</sup>	4.813E-1(8.11E-4) <sup>†</sup>
	5	<b>4.170E-1(5.51E-4)</b>	4.358E-1(5.65E-3) <sup>†</sup>	4.484E-1(4.89E-3) <sup>†</sup>	4.249E-1(5.17E-3) <sup>†</sup>	4.430E-1(5.07E-3) <sup>†</sup>	4.389E-1(1.36E-2) <sup>†</sup>
	8	5.049E-1(4.77E-4)	<b>5.020E-1(5.33E-4)</b>	5.268E-1(7.46E-3) <sup>†</sup>	6.481E-1(1.35E-4) <sup>†</sup>	5.234E-1(6.96E-3) <sup>†</sup>	5.236E-1(3.33E-4) <sup>†</sup>
	10	5.604E-1(3.19E-3)	<b>5.571E-1(5.34E-3)</b>	5.651E-1(1.18E-3) <sup>†</sup>	5.735E-1(4.11E-3) <sup>†</sup>	5.643E-1(2.22E-2)	5.645E-1(8.09E-2)
	15	7.587E-1(5.23E-3)	7.627E-1(3.79E-2) <sup>†</sup>	7.589E-1(4.40E-2) <sup>†</sup>	<b>7.587E-1(3.78E-2)</b>	7.590E-1(8.28E-2) <sup>†</sup>	7.589E-1(2.25E-2) <sup>†</sup>

<sup>†</sup> denotes the performance of C-TAEA is significantly better than the other peers according to the Wilcoxon's rank sum test at a 0.05 significance level;  
<sup>‡</sup> denotes the corresponding algorithm significantly outperforms C-TAEA.




Fig. 4. Scatter plots of the population obtained by C-TAEA and the peer algorithms on C1-DTLZ3 (median IGD value).




Fig. 5. Scatter plots of the population obtained by C-TAEA and the peer algorithms on C2-DTLZ2 (median IGD value).

find that all algorithms obtain comparable IGD and HV values on all C3-DTLZ1 and C3-DTLZ4 problem instances. In particular, C-TAEA is outperformed by C-MOEA/D on the 5-objective C3-DTLZ1 problem instance; and it is outperformed by C-NSGA-II on the 8- and 10-objective C3-DTLZ4 problem instances. In general, due to the advanced selection mechanisms of the CA and the DA for balancing convergence and diversity, C-TAEA obtains better IGD and HV values on most cases.

### B. DC-DTLZ Benchmark Suite

The comparison results of IGD and HV values on the DC-DTLZ benchmark suite are given in Tables III and VII in the supplementary material, respectively. From these results, it is obvious to see the overwhelmingly superior performance of




Fig. 6. Comparison of the solutions finally obtained in CA and DA on C2-DTLZ2 (median IGD value).

C-TAEA over the other peer algorithms, given the observation that C-TAEA obtains the best IGD and HV values in all comparisons. The following paragraphs try to decipher the potential reasons that lead to the ineffectiveness of the other peer algorithms.

Let us start from the Type-1 constrained problem. As described in Section I-B1 in the supplementary material, the






Fig. 7. Scatter plots of the population obtained by C-TAEA and the peer algorithms on DC1-DTLZ1 (median IGD value).




Fig. 8. Scatter plots of the population obtained by C-TAEA and the peer algorithms on DC1-DTLZ3 (median IGD value).

constraints restrict the feasible region to a couple of narrow cone-shaped strips. Similar to C2-DTLZ2, the other peer algorithms have a risk of being trapped in one feasible region thus fail to find all feasible PF segments. However, DC1-DTLZ1 and DC1-DTLZ3 seem to be less challenging than C2-DTLZ2 with a small  $r$  setting, given the observation that some peer algorithms are able to find a good number of solutions in different feasible PF segments as shown in Figs. 7 and 8. This might be attributed to the  $g(\mathbf{x})$  function of the baseline test problems, i.e., DTLZ1 and DTLZ3, which can make the crossover and mutation generate offspring far apart from their parents. Therefore, we can expect that solutions have opportunities to jump over the locally feasible region. Nevertheless, as shown in Tables III and VII in the supplementary material, the IGD and HV values obtained by our proposed C-TAEA constantly outperform the other peer algorithms and the better results are with a statistical significance.

The Type-2 constrained problem seems to be similar to C1-DTLZ1, at first glance, as shown in Figs. 8 and 9 in the supplementary material, where the constraints make the feasible region be reduced to a thin ribbon zone above the PF. However, it is more challenging due to the fluctuation in the CV of an infeasible solution when it approaches the PF, as shown in Fig. 10 in the supplementary material. Table II shows the number of runs, out of 51 runs in total, where feasible solutions were found. From this table, we clearly see that all algorithms, except C-TAEA, can hardly find feasible




Fig. 9. Scatter plots of the population obtained by C-TAEA and the peer algorithms on DC2-DTLZ1 (median IGD value).

TABLE II  
NUMBER OF RUNS WHEN FINDING FEASIBLE SOLUTIONS

	$m$	C-TAEA	C-NSGA-III	C-MOE/D	C-MOE/DD	I-DBEA	CMOEA
DC2-DTLZ1	3	46	4	3	2	2	0
	5	43	5	1	2	1	2
	8	33	1	0	2	0	2
	10	39	0	0	1	1	0
	15	31	1	1	1	2	0
DC2-DTLZ3	3	51	5	2	1	1	2
	5	51	6	3	2	2	1
	8	29	2	0	1	2	2
	10	37	1	2	0	1	2
	15	35	2	1	0	2	2

solutions in most cases. This is also demonstrated from Figs. 9 and 10, where we can clearly see that all other peer algorithms are trapped in a region far away from the PF. As the problem definitions of DC2-DTLZ1 and DC2-DTLZ3 shown in the supplementary material, all solutions obtained by the other peer algorithms are infeasible. Their failures on this type of constrained problems can be attributed to their feasibility-driven selection mechanisms, which drive the population to fluctuate between the CV's local optima. As for our proposed C-TAEA, its success can be owed to the use of the DA. In particular, the selection mechanism of the DA does not take the CV into account so that it has sufficient selection pressure to move toward the PF. As shown in Figs. 9 and 10, only C-TAEA finally find solutions on the PF. However, from Table II, we also find that C-TAEA can end up with infeasible solutions while the other algorithms have a chance to obtain feasible solutions. This is because the crossover and mutation can generate some significantly different offspring when working on the  $g(\mathbf{x})$  function of DC2-DTLZ1 and DC2-DTLZ3. And such offspring solutions have a chance to bring infeasible solutions to the feasible region.

As for the Type-3 constrained problem, its constraints are a combination of the previous two. In particular, the feasible region is restricted to a couple of segmented cone stripes. In addition, there exists the same fluctuation, as the Type-2 constrained problem, in the CV of an infeasible solution when it approaches the PF. In this case, the other peer algorithms are not only struggling on jumping over a particular locally feasible segment, but also have a significant trouble with the fluctuation (back and forth) of the population. Again, the success of our proposed C-TAEA is also attributed to the collaborative and complementary effects of two archives. As shown in Figs. 11 and 12, only C-TAEA finds all feasible PF

TABLE III  
COMPARISON RESULTS ON IGD METRIC (MEDIAN AND IQR) FOR C-TAEA AND THE OTHER PEER ALGORITHMS ON DC-DTLZ BENCHMARK SUITE

	$m$	C-TAEA	C-NSGA-III	C-MOEA/D	C-MOEA/DD	I-DBEA	CMOEA
DC1-DTLZ1	3	<b>5.638E-2(8.10E-5)</b>	5.990E-2(1.59E-5) <sup>†</sup>	1.835E-1(1.26E-1) <sup>†</sup>	1.042E-1(2.03E-3) <sup>†</sup>	5.843E-2(3.38E-3) <sup>†</sup>	5.843E-2(3.65E-3) <sup>†</sup>
	5	<b>7.301E-2(3.76E-3)</b>	7.655E-2(1.41E-2) <sup>†</sup>	7.327E-2(1.71E-4) <sup>†</sup>	8.705E-2(3.75E-3) <sup>†</sup>	7.344E-2(3.91E-4) <sup>†</sup>	7.640E-2(3.38E-3) <sup>†</sup>
	8	<b>1.086E-1(6.44E-4)</b>	1.104E-1(9.78E-4) <sup>†</sup>	1.414E-1(1.51E-2) <sup>†</sup>	1.175E-1(7.30E-2) <sup>†</sup>	1.290E-1(8.13E-2) <sup>†</sup>	1.291E-1(5.20E-3) <sup>†</sup>
	10	<b>1.189E-1(2.84E-3)</b>	1.206E-1(3.34E-3) <sup>†</sup>	1.524E-1(5.84E-3) <sup>†</sup>	1.278E-1(4.24E-2) <sup>†</sup>	1.545E-1(6.27E-2) <sup>†</sup>	1.529E-1(8.16E-3) <sup>†</sup>
	15	<b>1.753E-1(1.83E-2)</b>	1.984E-1(4.11E-3) <sup>†</sup>	2.017E-1(6.17E-2) <sup>†</sup>	1.772E-1(5.25E-3) <sup>†</sup>	2.070E-1(7.79E-2) <sup>†</sup>	1.986E-1(2.06E-2) <sup>†</sup>
DC1-DTLZ3	3	<b>1.466E-1(7.62E-4)</b>	2.720E-1(1.31E-1) <sup>†</sup>	1.349E-1(3.77E-1) <sup>†</sup>	2.908E-1(1.18E-1) <sup>†</sup>	5.140E-1(3.75E-1) <sup>†</sup>	5.140E-1(3.77E-1) <sup>†</sup>
	5	<b>2.083E-1(2.54E-3)</b>	2.040E-1(1.01E-2) <sup>†</sup>	3.947E-1(1.18E-4) <sup>†</sup>	2.318E-1(7.15E-4) <sup>†</sup>	3.948E-1(8.69E-4) <sup>†</sup>	3.947E-1(2.47E-4) <sup>†</sup>
	8	<b>3.405E-1(8.35E-5)</b>	4.062E-1(3.03E-2) <sup>†</sup>	4.330E-1(1.68E-3) <sup>†</sup>	3.639E-1(5.28E-2) <sup>†</sup>	4.344E-1(8.13E-3) <sup>†</sup>	3.422E-1(4.01E-2) <sup>†</sup>
	10	<b>3.886E-1(3.18E-3)</b>	4.586E-1(4.89E-2) <sup>†</sup>	4.596E-1(4.06E-3) <sup>†</sup>	4.154E-1(9.14E-3) <sup>†</sup>	4.456E-1(2.23E-3) <sup>†</sup>	4.235E-1(5.23E-3) <sup>†</sup>
	15	<b>8.009E-1(5.10E-3)</b>	8.287E-1(6.23E-3) <sup>†</sup>	8.456E-1(6.28E-2) <sup>†</sup>	8.034E-1(5.80E-3) <sup>†</sup>	8.150E-1(1.26E-2) <sup>†</sup>	8.144E-1(7.20E-3) <sup>†</sup>
DC2-DTLZ1	3	<b>2.199E-2(8.44E-3)</b>	/	/	/	/	/
	5	<b>5.371E-2(3.07E-2)</b>	/	/	/	/	/
	8	<b>9.937E-2(—)</b>	/	/	/	/	/
	10	<b>1.048E-1(8.65E-3)</b>	/	/	/	/	/
	15	<b>2.308E-1(—)</b>	/	/	/	/	/
DC2-DTLZ3	3	<b>5.498E-2(6.78E-2)</b>	/	/	/	/	/
	5	<b>1.667E-1(9.36E-3)</b>	/	/	/	/	/
	8	<b>5.674E+1(—)</b>	/	/	/	/	/
	10	<b>3.836E-1(—)</b>	/	/	/	/	/
	15	<b>7.959E-1(—)</b>	/	/	/	/	/
DC3-DTLZ1	3	<b>5.034E-2(1.72E-4)</b>	9.745E+0(5.64E-3) <sup>†</sup>	9.746E+0(7.80E-3) <sup>†</sup>	9.789E+0(8.76E-4) <sup>†</sup>	9.745E+0(2.02E-3) <sup>†</sup>	9.755E+0(1.29E-2) <sup>†</sup>
	5	<b>8.554E-1(1.29E-3)</b>	7.702E+0(2.60E-2) <sup>†</sup>	8.165E+0(1.78E-1) <sup>†</sup>	8.467E+0(1.21E-1) <sup>†</sup>	1.847E+1(1.03E+1) <sup>†</sup>	8.408E+0(1.71E-3) <sup>†</sup>
	8	<b>1.250E-1(6.01E-1)</b>	6.450E+0(2.30E+0) <sup>†</sup>	9.729E+0(2.03E+0) <sup>†</sup>	6.988E+0(3.74E-3) <sup>†</sup>	8.409E+0(1.30E-2) <sup>†</sup>	5.938E+0(2.83E+0) <sup>†</sup>
	10	<b>2.332E-1(5.29E-3)</b>	5.598E+0(8.71E-2) <sup>†</sup>	2.120E+1(7.29E-3) <sup>†</sup>	6.004E+0(8.26E-3) <sup>†</sup>	8.432E+0(5.9E-2) <sup>†</sup>	7.166E+0(1.93E-3) <sup>†</sup>
	15	<b>1.837E-1(3.43E-5)</b>	5.431E+0(4.38E-1) <sup>†</sup>	2.567E+1(1.10E+1) <sup>†</sup>	2.346E-1(7.51E+0) <sup>†</sup>	7.204E+0(1.76E+1) <sup>†</sup>	2.584E+1(1.66E+1) <sup>†</sup>
DC3-DTLZ3	3	<b>1.250E-1(8.04E-4)</b>	3.334E+1(7.20E-2) <sup>†</sup>	3.335E+1(6.20E-2) <sup>†</sup>	3.337E+1(2.54E-2) <sup>†</sup>	7.335E+1(8.46E-2) <sup>†</sup>	7.335E+1(4.52E-2) <sup>†</sup>
	5	<b>2.219E-1(9.16E-3)</b>	3.349E+1(5.57E-3) <sup>†</sup>	3.340E+1(3.75E-3) <sup>†</sup>	3.341E+1(4.86E-4) <sup>†</sup>	3.340E+1(7.59E-1) <sup>†</sup>	3.339E+1(2.28E-2) <sup>†</sup>
	8	<b>3.429E-1(8.37E-2)</b>	3.360E+1(3.52E-3) <sup>†</sup>	3.350E+1(1.88E-2) <sup>†</sup>	3.343E+1(5.02E-3) <sup>†</sup>	3.369E+1(3.39E-3) <sup>†</sup>	3.359E+1(7.59E-3) <sup>†</sup>
	10	<b>3.835E-1(1.16E-3)</b>	3.362E+1(9.10E-2) <sup>†</sup>	7.377E+1(9.92E-3) <sup>†</sup>	7.346E+1(8.57E-3) <sup>†</sup>	7.376E+1(7.36E-2) <sup>†</sup>	7.377E+1(4.91E-2) <sup>†</sup>
	15	<b>7.872E-1(2.33E-2)</b>	7.411E+1(3.62E-3) <sup>†</sup>	1.541E+2(8.61E-3) <sup>†</sup>	7.407E+1(9.35E-2) <sup>†</sup>	7.416E+1(4.29E-2) <sup>†</sup>	7.407E+1(5.49E-2) <sup>†</sup>

<sup>†</sup> denotes the performance of C-TAEA is significantly better than the other peers according to the Wilcoxon's rank sum test at a 0.05 significance level; <sup>‡</sup> denotes the corresponding algorithm significantly outperforms C-TAEA. / denotes the median metric value is not available, while — denotes the IQR is not available.




Fig. 10. Scatter plots of the population obtained by C-TAEA and the peer algorithms on DC2-DTLZ3 (median IGD value).




Fig. 11. Scatter plots of the population obtained by C-TAEA and the peer algorithms on DC3-DTLZ1 (median IGD value).

segments while the other peer algorithms are stuck at some locally feasible segments away from the PF.

### C. Further Analysis

From the experimental results shown in Sections V-A and V-B, we have witnessed the superior performance of C-TAEA for solving various constrained multiobjective benchmark problems. To have a better understanding of its design principles, this section will investigate some important algorithmic components of C-TAEA by comparing it with the following two variants.

- 1) *Variant-I*: As shown in lines 15–21 of Algorithm 2, we iteratively remove the worst solution from the most

crowded region when updating the CA. In particular, the worst solution is determined in terms of both its local crowdedness and its fitness value as defined in (11). This operation mainly aims to further improve the population diversity. To validate its effectiveness, we develop a variant in which the worst solution is simply defined as the one having the worst fitness value within the currently identified most crowded region.

- 2) *Variant-II*: We claimed that the collaboration between the CA and the DA is partially implemented by the restricted mating selection that automatically chooses the appropriate mating parents for offspring reproduction according to their evolution status. To validate the effectiveness of this operation, we develop another variant




Fig. 12. Scatter plots of the population obtained by C-TAEA and the peer algorithms on DC3-DTLZ3 (median IGD value).




Fig. 13. Comparative results on the two-objective C2-DTLZ2.

that randomly chooses mating parents from the CA and the DA with an equal probability.

In the empirical studies, we use the same parameter settings as Sections V-A and V-B and compare the performance of C-TAEA with these two variants on C-DTLZ and DC-DTLZ benchmark problems. From the comparison results, i.e., the IGD and HV values, respectively, shown in Tables VIII and IX in the supplementary material, we can see that the performance of C-TAEA and its two variants are comparable when the constraints are not difficult to solve, e.g., C1-DTLZ1 and C3-DTLZ1/DTLZ4; whereas the superiority of C-TAEA becomes evident otherwise. More specifically, we find that Variant-I fails to maintain a good diversity when the feasible region is a small segment, e.g., C2-DTLZ2, DC1-DTLZ1/DTLZ3, and DC3-DTLZ1/DTLZ3. Fig. 13 shows a comparison of the solutions found by C-TAEA and Variant-I on C2-DTLZ2 with  $r = 0.1$ . From this figure, we can see that the solutions found by Variant-I are sparsely distributed within the feasible region. This is because the purely fitness-based selection strategy tends to drive solutions toward the corresponding weight vector within the feasible region as much as possible.

As for Variant-II, its random mating selection mechanism does not take enough advantage of the complementary effect of the CA and the DA, thus it fails to help the algorithm overcome the locally infeasible barrier, e.g., C1-DTLZ3, DC2-DTLZ1/DTLZ3, and DC3-DTLZ1/DTLZ3.

#### D. Case Study: Water Distribution Network Optimization

Having tested C-TAEA's ability in solving various kinds of constrained benchmark problems, this section tends to




Fig. 14. Layout of the Anytown WDN.

investigate the performance of C-TAEA and the other peer algorithms on a real-world case study about optimal design of the water distribution network (WDN). In the past decade, multiobjective optimal design and rehabilitation of a WDN has attracted an increasing attention [40]. The shift from the least-cost design to a multiobjective performance-based design advances decision makers' understanding of tradeoff relationship between conflicting design objectives [41].

This paper uses the Anytown WDN, one of the most popular benchmark networks, as the case study. Anytown WDN has many typical features and challenges that can be found in real-world networks, e.g., pump scheduling, tank storage provision, and fire-fighting capacity provision. The network layout is shown in Fig. 14, where it has 35 pipes, 2 storage tanks, and 3 identical pumps delivering water from the treatment plant into the system. To meet the city expansion and increasing demands, 77 decision variables are considered, including 35 variables related to the existing pipes (with options of cleaning and lining or duplication with a parallel pipe), six new pipe diameters, 12 variables for two potential tanks, and 24 variables for the number of pumps in operation during 24 h of a day. In this paper, the WDN design problem is formulated as a four-objective optimization problem with two constraints. In particular, we consider costs, resilience index, statistical flow entropy, and water age as the objective functions. Descriptions of the problem formulation can be found in Section IV in the supplementary material.

In the experiment, C-TAEA and the other five peer algorithms use the solution encoding scheme as suggested in [42]. The population size is set to  $N = 100$ , and the number of function evaluations used for each algorithm is set to  $10\,000 \times N$ . The reproduction operators and their corresponding parameters are still set the same as before. Since the true PF is unknown for this real-world WDN model, we only use the HV as the performance metric where  $\mathbf{z}^* = (1.1, \dots, 1.1)^T$ . In particular, we normalize the objective functions before calculating






Fig. 15. Box plots of HV obtained by different algorithms.

the HV metric. From the box plots (with respect to 51 independent runs) shown in Fig. 15, we can clearly see that our proposed C-TAEA shows better performance than the other five peer algorithms.

## VI. CONCLUSION

In this paper, we have suggested a parameter-free constraint handling technique, C-TAEA, for constrained multiobjective optimization. In C-TAEA, we simultaneously maintain two collaborative archives. Specifically, one, denoted as CA, mainly focuses on driving the population toward the PF; while the other one, denoted as DA, mainly tends to explore the areas under-exploited by the CA (even those infeasible regions) thus provide more diversified information. In this case, the CA and the DA have different behaviors and complementary effects. In particular, they complement each other via a restricted mating selection mechanism which selects complementary mating parents for offspring reproduction. The performance of C-TAEA has been investigated on a series of benchmark problems with various types of constraints and up to 15 objectives. The empirical results fully demonstrate its competitiveness on CMOPs, in comparison to five state-of-the-art constrained EMO algorithms. In addition to artificial benchmark problems, the effectiveness of C-TAEA has also been validated on a real-world case study of the WDN design optimization.

Constrained multiobjective optimization is ubiquitous in real-world applications. The CMOPs considered in this paper do not embrace all types of constraints in the real-world. We hope this paper can inspire more research on constrained multiobjective optimization, including investigations of other constrained formulations and applications in real-world optimization scenarios. As previously demonstrated in [6]–[8], we believe that C-TAEA is more than a specific algorithm. Instead, its basic idea, i.e., simultaneously maintaining multiple complementary and collaborative archives, can be widely used in the general EMO algorithm design. In future, it is worth further investigating its underlying mechanisms from both algorithm design and theoretical foundation perspectives. Furthermore, we plan to investigate the effectiveness of this two-archive collaborative framework on a wider range of problems, such as unconstrained MOP including those with complex properties (e.g., problems with complicated PSs [43] and imbalanced convergence and diversity [44]), dynamic optimization (e.g., problems with a changing number of objectives or constraints [45]).

## REFERENCES

- [1] K. Deb, *Multi-Objective Optimization Using Evolutionary Algorithms*. New York, NY, USA: Wiley, 2001.
- [2] K. Deb, S. Agrawal, A. Pratap, and T. Meyarivan, "A fast and elitist multiobjective genetic algorithm: NSGA-II," *IEEE Trans. Evol. Comput.*, vol. 6, no. 2, pp. 182–197, Apr. 2002.
- [3] E. Zitzler and S. Künzli, "Indicator-based selection in multiobjective search," in *Proc. PPSN 8th Int. Conf. Parallel Problem Solving Nat. (PPSN VIII)*, 2004, pp. 832–842.
- [4] Q. Zhang and H. Li, "MOEA/D: A multiobjective evolutionary algorithm based on decomposition," *IEEE Trans. Evol. Comput.*, vol. 11, no. 6, pp. 712–731, Dec. 2007.
- [5] Y. G. Woldesenbet, G. G. Yen, and B. G. Tessema, "Constraint handling in multiobjective evolutionary optimization," *IEEE Trans. Evol. Comput.*, vol. 13, no. 3, pp. 514–525, Jun. 2009.
- [6] K. Praditwong and X. Yao, "A new multi-objective evolutionary optimisation algorithm: The two-archive algorithm," in *Proc. Int. Conf. Comput. Intell. Security (CIS)*, 2006, pp. 95–104.
- [7] B. Li, J. Li, K. Tang, and X. Yao, "An improved two archive algorithm for many-objective optimization," in *Proc. IEEE Congr. Evol. Comput. (CEC)*, 2014, pp. 2869–2876.
- [8] H. Wang, L. Jiao, and X. Yao, "Two\_Arch2: An improved two-archive algorithm for many-objective optimization," *IEEE Trans. Evol. Comput.*, vol. 19, no. 4, pp. 524–541, Aug. 2015.
- [9] K. Li, S. Kwong, and K. Deb, "A dual-population paradigm for evolutionary multiobjective optimization," *Inf. Sci.*, vol. 309, pp. 50–72, Jul. 2015.
- [10] Z. Fan *et al.*, "A comparative study of constrained multi-objective evolutionary algorithms on constrained multi-objective optimization problems," in *Proc. IEEE Congr. Evol. Comput. (CEC)*, 2017, pp. 209–216.
- [11] R. Tanabe and A. Oyama, "A note on constrained multi-objective optimization benchmark problems," in *Proc. IEEE Congr. Evol. Comput. (CEC)*, 2017, pp. 1127–1134.
- [12] F. Snyman and M. Helbig, "Solving constrained multi-objective optimization problems with evolutionary algorithms," in *Proc. 8th Int. Conf. Adv. Swarm Intell. (ICSI)*, 2017, pp. 57–66.
- [13] C. M. Fonseca and P. J. Fleming, "Multiobjective optimization and multiple constraint handling with evolutionary algorithms. I. A unified formulation," *IEEE Trans. Syst., Man, Cybern. A, Syst., Humans*, vol. 28, no. 1, pp. 26–37, Jan. 1998.
- [14] C. A. C. Coello and A. D. Christiansen, "MOSES: A multiobjective optimization tool for engineering design," *Eng. Optim.*, vol. 31, no. 3, pp. 337–368, 1999.
- [15] H. Jain and K. Deb, "An evolutionary many-objective optimization algorithm using reference-point based nondominated sorting approach, part II: Handling constraints and extending to an adaptive approach," *IEEE Trans. Evol. Comput.*, vol. 18, no. 4, pp. 602–622, Aug. 2014.
- [16] M. A. Jan and Q. Zhang, "MOEA/D for constrained multiobjective optimization: Some preliminary experimental results," in *Proc. U.K. Workshop Comput. Intell. (UKCI)*, 2010, pp. 1–6.
- [17] R. Cheng, Y. Jin, M. Olhofer, and B. Sendhoff, "A reference vector guided evolutionary algorithm for many-objective optimization," *IEEE Trans. Evol. Comput.*, vol. 20, no. 5, pp. 773–791, Oct. 2016.
- [18] A. Oyama, K. Shimoyama, and K. Fujii, "New constraint-handling method for multi-objective and multi-constraint evolutionary optimization," *Jpn. Soc. Aeronaut. Space Sci. Trans.*, vol. 50, no. 167, pp. 56–62, 2007.
- [19] T. Takahama and S. Sakai, "Efficient constrained optimization by the  $\epsilon$  constrained rank-based differential evolution," in *Proc. IEEE Congr. Evol. Comput. (CEC)*, 2012, pp. 1–8.
- [20] S. Z. Martínez and C. A. C. Coello, "A multi-objective evolutionary algorithm based on decomposition for constrained multi-objective optimization," in *Proc. IEEE Congr. Evol. Comput. (CEC)*, 2014, pp. 429–436.
- [21] M. Asafuddoula, T. Ray, and R. A. Sarker, "A decomposition-based evolutionary algorithm for many objective optimization," *IEEE Trans. Evol. Comput.*, vol. 19, no. 3, pp. 445–460, Jun. 2015.
- [22] Z. Fan *et al.*, "Angle-based constrained dominance principle in MOEA/D for constrained multi-objective optimization problems," in *Proc. IEEE Congr. Evol. Comput. (CEC)*, 2016, pp. 460–467.
- [23] F. Jiménez, A. F. Gómez-Skarmeta, G. Sánchez, and K. Deb, "An evolutionary algorithm for constrained multi-objective optimization," in *Proc. IEEE Congr. Evol. Comput. (CEC)*, 2002, pp. 1133–1138.




- [24] T. Ray, K. Tai, and K.-C. Seow, "Multiobjective design optimization by an evolutionary algorithm," *Eng. Optim.*, vol. 33, no. 4, pp. 399–424, 2001.
- [25] N. Young, "Blended ranking to cross infeasible regions in constrained multiobjective problems," in *Proc. Int. Conf. Comput. Intell. Model. Control Autom. (CIMCA)*, 2005, pp. 191–196.
- [26] A. Angantyr, J. Andersson, and J.-O. Aidanpaa, "Constrained optimization based on a multiobjective evolutionary algorithm," in *Proc. IEEE Congr. Evol. Comput. (CEC)*, 2003, pp. 1560–1567.
- [27] K. Li, K. Deb, Q. Zhang, and S. Kwong, "An evolutionary many-objective optimization algorithm based on dominance and decomposition," *IEEE Trans. Evol. Comput.*, vol. 19, no. 5, pp. 694–716, Oct. 2015.
- [28] C. Peng, H.-L. Liu, and F. Gu, "An evolutionary algorithm with directed weights for constrained multi-objective optimization," *Appl. Soft Comput.*, vol. 60, pp. 613–622, Nov. 2017.
- [29] W. Ning *et al.*, "Constrained multi-objective optimization using constrained non-dominated sorting combined with an improved hybrid multi-objective evolutionary algorithm," *Eng. Optim.*, vol. 49, no. 10, pp. 1645–1664, 2017.
- [30] A. E. Sorkhabi, M. D. Amiri, and A. R. Khantemoori, "Duality evolution: An efficient approach to constraint handling in multi-objective particle swarm optimization," *Soft Comput.*, vol. 21, no. 24, pp. 7251–7267, 2017.
- [31] K. Harada, J. Sakuma, I. Ono, and S. Kobayashi, "Constraint-handling method for multi-objective function optimization: Pareto descent repair operator," in *Proc. 4th Int. Conf. Evol. Multi Criterion Optim. (EMO)*, 2006, pp. 156–170.
- [32] H. K. Singh, T. Ray, and W. Smith, "C-PSA: Constrained Pareto simulated annealing for constrained multi-objective optimization," *Inf. Sci.*, vol. 180, no. 13, pp. 2499–2513, 2010.
- [33] L. Jiao, J. Luo, R. Shang, and F. Liu, "A modified objective function method with feasible-guiding strategy to solve constrained multi-objective optimization problems," *Appl. Soft Comput.*, vol. 14, pp. 363–380, Jan. 2014.
- [34] K. Deb, L. Thiele, M. Laumanns, and E. Zitzler, *Scalable Test Problems for Evolutionary Multiobjective Optimization*. London, U.K.: Springer, 2005, pp. 105–145.
- [35] H. Liu, F. Gu, and Q. Zhang, "Decomposition of a multiobjective optimization problem into a number of simple multiobjective sub-problems," *IEEE Trans. Evol. Comput.*, vol. 18, no. 3, pp. 450–455, Jun. 2014.
- [36] K. Deb and R. B. Agrawal, "Simulated binary crossover for continuous search space," *Complex Syst.*, vol. 9, no. 2, pp. 115–148, 1994.
- [37] K. Deb and M. Goyal, "A combined genetic adaptive search (GeneAS) for engineering design," *Comput. Sci. Inform.*, vol. 26, no. 4, pp. 30–45, 1996.
- [38] P. A. N. Bosman and D. Thierens, "The balance between proximity and diversity in multiobjective evolutionary algorithms," *IEEE Trans. Evol. Comput.*, vol. 7, no. 2, pp. 174–188, Apr. 2003.
- [39] E. Zitzler and L. Thiele, "Multiobjective evolutionary algorithms: A comparative case study and the strength Pareto approach," *IEEE Trans. Evol. Comput.*, vol. 3, no. 4, pp. 257–271, Nov. 1999.
- [40] H. Mala-Jetmarova, N. Sultanova, and D. A. Savić, "Lost in optimisation of water distribution systems? A literature review of system operation," *Environ. Model. Softw.*, vol. 93, pp. 209–254, Jul. 2017.
- [41] T. M. Walski, "The wrong paradigm—Why water distribution optimization doesn't work," *J. Water Resour. Plan. Manag.*, vol. 127, no. 4, pp. 203–205, 2001.
- [42] G. Fu, Z. Kapelan, J. R. Kasprzyk, and P. Reed, "Optimal design of water distribution systems using many-objective visual analytics," *J. Water Resour. Plan. Manag.*, vol. 139, no. 6, pp. 624–633, 2013.
- [43] Q. Zhang *et al.*, "Multiobjective optimization test instances for the CEC 2009 special session and competition," *School Comput. Sci. Elect. Eng., Univ. Essex, Colchester, U.K., Nanyang Technol. Univ., Singapore, Rep. CSE-487*, 2008.
- [44] H.-L. Liu, L. Chen, K. Deb, and E. D. Goodman, "Investigating the effect of imbalance between convergence and diversity in evolutionary multiobjective algorithms," *IEEE Trans. Evol. Comput.*, vol. 21, no. 3, pp. 408–425, Jun. 2017.
- [45] R. Chen, K. Li, and X. Yao, "Dynamic multi-objectives optimization with a changing number of objectives," *IEEE Trans. Evol. Comput.*, vol. 22, no. 1, pp. 157–171, Feb. 2018, doi: [10.1109/TEVC.2017.2669638](https://doi.org/10.1109/TEVC.2017.2669638).



**Ke Li** (M'17) received the B.Sc. and M.Sc. degrees in computer science and technology from Xiangtan University, Xiangtan, China, in 2007 and 2010, respectively, and the Ph.D. degree in computer science from the City University of Hong Kong, Hong Kong, in 2014.


He was a postdoctoral research associate at Michigan State University, a research fellow at University of Birmingham and a Lecturer (Assistant Professor) in Data Analytics at the Department of Computer Science of the University of Exeter. He is currently a Professor with the University of Electronic Science and Technology of China, Chengdu, China. His current research interests include the evolutionary multiobjective optimization, large scale optimization, and machine learning and applications in water engineering and software engineering.

Dr. Li was the Founding Chair of IEEE Computational Intelligence Society Task Force on Decomposition-based Techniques in EC with the EC Technical Committee. He has served as a regular reviewer and has published several research papers in renowned journals such as the IEEE TRANSACTIONS ON EVOLUTIONARY COMPUTATION and the IEEE TRANSACTIONS ON CYBERNETICS.



**Renzhi Chen** received the B.Sc. degree in computer science from the National University of Defence Technology, Hunan, China, in 2012 and the Ph.D. degree in computer science from the University of Birmingham, Birmingham, U.K., in 2018.

His current research interest includes evolutionary algorithms for solving dynamic multiobjective optimization problems.



**Guangtao Fu** received the B.Eng. and M.Eng. degrees in hydraulic engineering from Shandong University, Jinan, China, in 1997 and 2000, respectively, and the Ph.D. degree in water resources engineering from the Dalian University of Technology, Dalian, China, in 2003.

He is currently a Royal Society Industry Fellow and an Associate Professor of water infrastructure systems with the Centre for Water Systems, University of Exeter, Exeter, U.K. His current research interests include developing and applying

new computer models, data analytics, and artificial intelligence tools to tackle urban water infrastructure challenges.



**Xin Yao** (M'91–SM'96–F'03) received the B.Sc. and Ph.D. degrees from the University of Science and Technology of China, Hefei, China, in 1982 and 1990, respectively.

He is a Chair Professor of computer science with the Southern University of Science and Technology, Shenzhen, China, and a Professor of computer science with the University of Birmingham, Birmingham, U.K. He has been researching on multiobjective optimization since 2003, when he published a well-cited EMO'03 paper on many

objective optimization. His current research interests include evolutionary computation and ensemble learning and their applications in software engineering.

Prof. Yao was a recipient of the 2001 IEEE Donald G. Fink Prize Paper Award for his research, the 2010, 2016, and 2017 IEEE TRANSACTIONS ON EVOLUTIONARY COMPUTATION Outstanding Paper Awards, the 2010 BT Gordon Radley Award for Best Author of Innovation (Finalist), the 2011 IEEE TRANSACTIONS ON NEURAL NETWORKS Outstanding Paper Award, the Prestigious Royal Society Wolfson Research Merit Award in 2012 and the IEEE CIS Evolutionary Computation Pioneer Award in 2013, and many other best paper awards. He was the President of IEEE CIS from 2014 to 2015 and the Editor-in-Chief of the IEEE TRANSACTIONS ON EVOLUTIONARY COMPUTATION from 2003 to 2008. He is a Distinguished Lecturer of IEEE Computational Intelligence Society.