
CNN-Based Jigsaw Puzzles Solver

Tianbao

Department of Computer Science
University of Toronto
Toronto, ON M5S 1A1
tianbao@cs.toronto.edu

Abstract

This paper presents an innovative way to solve jigsaw puzzle with the help of deep convolutional neural networks. For a simpler procedure, we turn the puzzle to a prediction that whether two arbitrary pieces should be adjacent. Compared with traditional solutions, using the feature maps generated from CNN can give a deeper intuition on the correlation between edges, which can improve the puzzle solution.

1 Introduction

Jigsaw puzzles were first introduced around 1760 for map research and then became a popular intelligence entertainment [4]. The origin image is divided into $N \times M$. People usually take advantage of image information at edges, such as color, texture, instance, etc., to reconstruct the origin image. However, this problem has been proven to be a NP-complete one [1, 2].

1.1 Problem Definition

Jigsaw puzzles aims to reshape the $N \times M$ non-overlapping, equal-sized pieces from the origin image to the correct arrangement. For the worst case, it takes the complicity of $O((N \times M)!)$.

1.2 Related Work

Jigsaw has been researched on for many years. One most basic idea is to evaluate the compatibility of the adjacent pieces and take a strategy, such as greedy search, to arrange the pieces. One famous work is the Genetic Algorithm (GA) [8]. Given initial candidate solutions, it applies operations like selection, reproduction and mutation based on the color-distance fitness function. Similarly but innovatively, [9] first introduces deep neural network to jigsaw solver and transforms the puzzle to the piece pair adjacency prediction. It samples piece edges to learn the adjacent likelihood through DNN based on the color distance. For these two solvers, they only use color information to judge whether two pieces should be together. However, human use some others like texture to solve. So, there is still some further steps on it.

Recently, with the prosper of convolutional neural networks in computer vision area, CNN also becomes a good tool to solve jigsaw puzzles. CNN can extract regional features in many perspectives, such as color, texture, pattern, instance. These can be good inference for judging adjacent pieces. So, [3, 7] choose to use feature maps from pre-trained CFN [7] (siamese-enned AlexNet [6]), VGG [5] or Resnet [10] and predict the location. However, the main problem for these approach is that they hold a siamese structure with shared weights for each location, which means they can only solve a limited number for pieces (3×3 in [7], 2×2 and 2×3 in [3]). With the piece amount increasing, the network becomes extremely heavy to train.

1.3 Expected Contribution

During this project, the main idea is to combine these two approach and solve their disadvantages. Main expected contribution is as follows:

- extract features from existing CNN architecture and enhance the adjacency prediction in [9]. There should be improvement on the accuracy.
- apply the adjacency likelihood to current algorithm like GA as the compatibility measure to improve the performance on large-scaled and obscured images.
- try to find a reinforcement learning way using the adjacency likelihood as a form of reward function. Then the location could be found via policy search.

References

- [1] Tom Altman. Solving the jigsaw puzzle problem in linear time. *Applied Artificial Intelligence an International Journal*, 3(4):453–462, 1989.
- [2] Erik D Demaine and Martin L Demaine. Jigsaw puzzles, edge matching, and polyomino packing: Connections and complexity. *Graphs and Combinatorics*, 23(1):195–208, 2007.
- [3] Lucio Dery, Robel Mengistu, and Oluwasanya Awe. Neural combinatorial optimization for solving jigsaw puzzles: A step towards unsupervised pre-training.
- [4] Herbert Freeman and L Garder. Apictorial jigsaw puzzles: The computer solution of a problem in pattern recognition. *IEEE Transactions on Electronic Computers*, (2):118–127, 1964.
- [5] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.
- [6] Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. In *Advances in neural information processing systems*, pages 1097–1105, 2012.
- [7] Mehdi Noroozi and Paolo Favaro. Unsupervised learning of visual representations by solving jigsaw puzzles. In *European Conference on Computer Vision*, pages 69–84. Springer, 2016.
- [8] Dror Sholomon, Omid David, and Nathan S Netanyahu. A genetic algorithm-based solver for very large jigsaw puzzles. In *Computer Vision and Pattern Recognition (CVPR), 2013 IEEE Conference on*, pages 1767–1774. IEEE, 2013.
- [9] Dror Sholomon, Omid E David, and Nathan S Netanyahu. Dnn-buddies: a deep neural network-based estimation metric for the jigsaw puzzle problem. In *International Conference on Artificial Neural Networks*, pages 170–178. Springer, 2016.
- [10] Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *arXiv preprint arXiv:1409.1556*, 2014.