

---

# CNN Assistance in Jigsaw Puzzle Solution

---

**Tianbao Li**

Department of Computer Science  
University of Toronto  
Toronto, ON M5S 1A1  
tianbao@cs.toronto.edu

## Abstract

This paper presents an innovative way to assist solving jigsaw puzzle with the help of deep convolutional neural networks. The main goal of this project is to predict whether two pieces from the jigsaw puzzle should be neighbors in the origin image. Proceeding from traditional methods of using color (like RGB) distance, here, we introduce the low level features in the image which are extracted by convolutional neural networks. Compared with color-based solutions, using the feature maps generated can help with a deeper intuition on the correlation between edges. The proposed algorithm can achieve considerable accuracy on adjacency prediction.

## 1 Introduction

Jigsaw puzzles were first introduced around 1760 for map research and then became a popular intelligence entertainment [4] in the last few centuries. The origin image is divided into  $N \times M$ . To solve this, people need to cluster similar tiles, find the neighbors and then reconstruct the origin image. However, due to the possible locations and relationship behind pieces, there are quite a huge number of solutions even for a small jigsaw puzzle, for example,  $(8 * 8)! = 1.2688693 * 10^{89}$  solutions for an  $8 * 8$  puzzle. Indeed, this problem has been proven to be a NP-complete one [1, 2]. Though tough, actually, jigsaw puzzle solving is quite meaningful beyond the intelligence challenge. It helps a lot in combining shredded documents [9, 10] and even recovering artifacts debris [7].

Recently year, there have been a lot of researchers working on this problem and achieved much progress. However, one of the most important sub-problems in this procedure, determining adjacency between pieces, seems to keep in the same track for long. When people solve the puzzle manually, they need image information at edges, such as color, texture, instance, etc. to make the judgement whether two pieces are neighbors. However, most of previous research only eyes on the color features such as RGB distance. This makes such solutions quite bad for simple-colored images, especially in reconstructing printed documents or ancient artifacts.

Here, we want to mimic how people really solve jigsaw puzzles and work on finding features capable to help make adjacency prediction. Recently, Convolution Neural Networks (CNN) leads the research area of computer vision with its capability of extracting inside features underneath the images and solve hard problems such as detection [13] and segmentation [5, 18]. Based on the existing tremendous structures, people start to apply transfer learning and use extracted features to solve related computer vision problems [12].

In this paper, we contribute in providing neural networks to predict whether two tiles from a jigsaw puzzle are adjacent in the origin image. The neural networks judge the jigsaw piece pair by extracted low level image features from pre-trained CNN together with color information at edges, and outputs whether these two tiles are neighbors. This model achieves outstanding prediction accuracy in images from ILSVRC2012 dataset [14].

## 2 Related Work

Jigsaw has been researched on for many years. One most basic idea is to evaluate the compatibility of the adjacent pieces and take a strategy, such as greedy search, to arrange the pieces. One famous work is the Genetic Algorithm (GA) [15]. Given initial candidate solutions, it applies operations like selection, reproduction and mutation based on the color-distance fitness function. Similarly but innovatively, [16] first introduces deep neural network to jigsaw solver and transforms the puzzle to the piece pair adjacency prediction. It samples piece edges to learn the adjacent likelihood through DNN based on the color distance. For these two solvers, they only use color information to judge whether two pieces should be together. However, human use some others like texture to solve. So, there is still some further steps on it.

Recently, with the prosper of convolutional neural networks in computer vision area, CNN also becomes a good tool to solve jigsaw puzzles. CNN can extract regional features in many perspectives, such as color, texture, pattern, instance. These can be good inference for judging adjacent pieces. So, [3, 11] choose to use feature maps from pre-trained CFN [11] (siamese-enned AlexNet [8]), VGG [6] or Resnet [17] and predict the location. However, the main problem for these approach is that they hold a siamese structure with shared weights for each location, which means they can only solve a limited number for pieces ( $3 \times 3$  in [11],  $2 \times 2$  and  $2 \times 3$  in [3]). With the piece amount increasing, the network becomes extremely heavy to train.

## 3 Problem Definition

Jigsaw puzzles aims to reshape the  $N \times M$  non-overlapping, equal-sized pieces from the origin image to the correct arrangement. For the worst case, it takes the complicity of  $O((N \times M)!)$ .

## References

- [1] Tom Altman. Solving the jigsaw puzzle problem in linear time. *Applied Artificial Intelligence an International Journal*, 3(4):453–462, 1989.
- [2] Erik D Demaine and Martin L Demaine. Jigsaw puzzles, edge matching, and polyomino packing: Connections and complexity. *Graphs and Combinatorics*, 23(1):195–208, 2007.
- [3] Lucio Dery, Robel Mengistu, and Oluwasanya Awe. Neural combinatorial optimization for solving jigsaw puzzles: A step towards unsupervised pre-training. 20167.
- [4] Herbert Freeman and L Garder. Apictorial jigsaw puzzles: The computer solution of a problem in pattern recognition. *IEEE Transactions on Electronic Computers*, (2):118–127, 1964.
- [5] Kaiming He, Georgia Gkioxari, Piotr Dollár, and Ross Girshick. Mask r-cnn. In *Computer Vision (ICCV), 2017 IEEE International Conference on*, pages 2980–2988. IEEE, 2017.
- [6] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.
- [7] David Koller and Marc Levoy. Computer-aided reconstruction and new matches in the forma urbis romae. *Bullettino Della Commissione Archeologica Comunale di Roma*, 2:103–125, 2006.
- [8] Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. In *Advances in neural information processing systems*, pages 1097–1105, 2012.
- [9] Samuel R Levin. The computer and literary studies, 1975.
- [10] Marlos AO Marques and Cinthia OA Freitas. Reconstructing strip-shredded documents using color as feature matching. In *Proceedings of the 2009 ACM symposium on Applied Computing*, pages 893–894. ACM, 2009.
- [11] Mehdi Noroozi and Paolo Favaro. Unsupervised learning of visual representations by solving jigsaw puzzles. In *European Conference on Computer Vision*, pages 69–84. Springer, 2016.

- [12] Ali Sharif Razavian, Hossein Azizpour, Josephine Sullivan, and Stefan Carlsson. Cnn features off-the-shelf: an astounding baseline for recognition. In *Computer Vision and Pattern Recognition Workshops (CVPRW), 2014 IEEE Conference on*, pages 512–519. IEEE, 2014.
- [13] Joseph Redmon and Ali Farhadi. Yolo9000: better, faster, stronger. *arXiv preprint*, 2017.
- [14] Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, Alexander C. Berg, and Li Fei-Fei. ImageNet Large Scale Visual Recognition Challenge. *International Journal of Computer Vision (IJCV)*, 115(3):211–252, 2015.
- [15] Dror Sholomon, Omid David, and Nathan S Netanyahu. A genetic algorithm-based solver for very large jigsaw puzzles. In *Computer Vision and Pattern Recognition (CVPR), 2013 IEEE Conference on*, pages 1767–1774. IEEE, 2013.
- [16] Dror Sholomon, Omid E David, and Nathan S Netanyahu. Dnn-buddies: a deep neural network-based estimation metric for the jigsaw puzzle problem. In *International Conference on Artificial Neural Networks*, pages 170–178. Springer, 2016.
- [17] Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *arXiv preprint arXiv:1409.1556*, 2014.
- [18] Fisher Yu and Vladlen Koltun. Multi-scale context aggregation by dilated convolutions. *arXiv preprint arXiv:1511.07122*, 2015.