VIETNAM NATIONAL UNIVERSITY HO CHI MINH CITY
HO CHI MINH CITY UNIVERSITY OF TECHNOLOGY

Multidisciplinary Project

H.E.R.A

(Home Environment & Response Assistant)

Instructor: Dr. Võ Thị Ngọc Châu

Student's Name	Student ID
Nguyễn Tiến Hưng	2352441
Hồ Lâm Khánh Vy	2353353
Trần Anh Đức	2352271
Nguyễn Khánh Hưng	2352435

Ho Chi Minh City, January 2026.

Member list & Workload

Group Leader: Nguyễn Tiến Hưng - hung.nguyenk23cse@hcmut.edu.vn

No.	Full name	Contribution	Percentage
1.	Nguyễn Tiến Hưng		100%
2.	Hồ Lâm Khánh Vy		100%
3.	Trần Anh Đức		100%
4.	Nguyễn Khánh Hưng		100%

Lecturer's Assessment

No.	Full name	Evaluation	Notes
1.	Nguyễn Tiến Hưng		
2.	Hồ Lâm Khánh Vy		
3.	Trần Anh Đức		
4.	Nguyễn Khánh Hưng		

Contents

1 Introduction

1.1 Problem Statement

Context and Target Environment

The evolution of the "Smart Home" has transitioned from simple connectivity to the demand for intelligent automation. While the general market is saturated with fragmented IoT solutions, this project specifically targets modern urban households—such as mid-sized apartments or townhouses—occupied by busy families, elderly members, or pets. In these environments, standard smart platforms function merely as centralized remote controls. They enable manual actuation via smartphone applications but fail to deliver a cohesive, autonomous living experience tailored to the specific safety, convenience, and energy needs of an active urban family.

Key Challenges

Despite the ubiquity of connected hardware, several critical architectural and functional deficiencies persist in residential deployments:

- **Data Silos & Fragmentation:** Devices from different manufacturers often operate on proprietary protocols. This fragmentation prevents the aggregation of data into a single Unified Source of Truth, making holistic analytics and cross-device correlation impossible.[**?**]
- **Deterministic vs. Probabilistic Limitations:** Current systems rely on rigid, rule-based automation (e.g., "turn on lights at 6 PM"). They lack the probabilistic reasoning needed to adapt to dynamic human routines or distinguish between a human and a pet triggering a motion sensor.
- **Data Rich, Information Poor (DRIP):** IoT devices generate high-velocity telemetry daily. Without robust Data Engineering pipelines (ETL processes) to filter noise, users are overwhelmed with raw notifications rather than actionable insights regarding energy anomalies.
- **Reactive Operation & Energy Inefficiency:** Systems operate reactively (e.g., cooling a room only after it gets hot). This lag degrades user comfort and leads to significant energy waste, as the system cannot pre-emptively optimize resources.

Operational Assumptions & Constraints

To effectively address these challenges, the H.E.R.A system is designed with the following bounded parameters:

- **Physical Scope:** The system is optimized for a single enclosed residential room (approximately 15–30 square meters), such as a bedroom or living room. The spatial model focuses on localized environmental monitoring and occupant interaction within this bounded area to ensure precise sensor calibration, accurate spatial tracking, and simplified Digital Twin representation.
- **Infrastructure Compatibility:** The architecture assumes the presence of a stable Wi-Fi network for cloud-based AI processing (such as NLP and heavy predictive modeling). However, it requires local Edge processing capabilities (e.g., via ESP32) to maintain critical deterministic operations and sensor readings if internet connectivity drops.

- **Privacy & Security:** Given the continuous ingestion of environmental telemetry and voice commands, the system is constrained by strict data privacy requirements, ensuring that behavioral data and audio inputs are securely processed and shielded from unauthorized access.

The Need for a Solution and Scope of Intelligence

There is an urgent need for a comprehensive AIoT (AI + IoT) platform that bridges the gap between physical control and cognitive processing for urban homes. A truly intelligent system must transcend basic command execution to act as a proactive agent. H.E.R.A addresses this by narrowing its "smart" focus onto three prioritized pillars:

1. **AI-Enhanced Security:** Utilizing machine learning to differentiate between genuine human presence and pets, thereby eliminating false alarms and providing reliable monitoring.
2. **Proactive Energy Management:** Deploying predictive analytics to optimize power consumption based on historical usage patterns and environmental forecasts.
3. **Frictionless Interaction:** Leveraging Natural Language Processing (NLP) to allow residents to control their environment intuitively, effectively shifting the paradigm from manual "Smart Control" to autonomous "Smart Living."

1.2 Project Overview

H.E.R.A (Home Environment & Response Assistant) is a comprehensive AI-powered virtual assistant system designed to revolutionize residential living. Unlike traditional passive smart homes, H.E.R.A integrates a robust IoT infrastructure with advanced Natural Language Processing (NLP) and Data Analytics. This fusion allows the system to not only continuously monitor environmental conditions but also understand and execute complex user commands via voice or text. By bridging the gap between raw telemetry and human intent, H.E.R.A delivers a living environment that is proactively energy-efficient, secure, and deeply personalized.

System Workflow

The system operates on a dual-stream data pipeline, integrating both automated environmental monitoring and user-centric interaction into a unified architecture:

1. **Multi-modal Data Acquisition:** The system continuously ingests data from two primary sources:
   - Telemetry: Sensors monitor physical parameters (temperature, humidity, motion) and device states, transmitting data via MQTT.
   - User Interaction: A dedicated interface captures voice commands or text inputs from the user, serving as the direct communication bridge.
2. **Processing & Verification:** A centralized backend processes these incoming streams. For telemetry, it filters noise and verifies if data exceeds safety thresholds. Simultaneously, for user inputs, it initiates a Speech-to-Text (STT) process (if applicable) to convert audio signals into processable query strings.
3. **Intelligence Layer (NLP & Analytics):** This is the decision-making core:

- Natural Language Understanding (NLU): AI models analyze user queries to extract intents (e.g., "turn on") and entities (e.g., "living room light").
- Predictive Analytics: Machine learning algorithms analyze historical logs to forecast trends or detect anomalies, enriching the decision context.

4. **Action, Control & Feedback:** Based on either AI interpretation or threshold triggers, the system executes commands:
   - Device Control: Sending signals to microcontrollers (ESP32/YoLo) to adjust physical devices.
   - User Response: Generating a natural language response (Text-to-Speech) to confirm actions or report status back to the user.
5. **Activity Logging:** Every interaction—whether a sensor reading, a voice command, or a system automated response—is recorded in an activity log. This maintains a single source of truth for debugging, dashboard visualization, and future model training.

By combining reactive automation with interactive AI capabilities, this workflow fulfills the dual purpose of a robust monitoring system and an intelligent virtual assistant.

Architectural Hierarchy

To ensure scalability, maintainability, and a clear separation of concerns, the H.E.R.A system architecture is bifurcated into two distinct layers. This two-tier design decouples the physical hardware constraints from the high-level computational logic:

- **Layer 1: The Physical Perception & IoT Control Layer**
  This foundational layer serves as the direct interface with the physical environment. It is responsible for Data Acquisition and Device Actuation.
  - **Sensing & Ingestion:** A network of distributed sensors captures raw environmental telemetry (temperature, humidity, motion) and converts physical phenomena into digital signals. These signals are transmitted via lightweight protocols (MQTT) to ensure low-latency communication.
  - **Execution:** This layer receives operational commands from the upper layer and executes them through actuators (relays, IR blasters, dimmers) to physically alter the state of the home environment.
  - **Edge Responsibility:** It handles immediate hardware interactions and ensures connection stability, acting as the reliable "hands and eyes" of the system.
- **Layer 2: The Cognitive Intelligence & Orchestration Layer**
  Hosted on a central server, this high-level layer abstracts the complexity of decision-making. It focuses on Language Processing, Data Analysis, and Command Dispatching.
  - **Natural Language Understanding (NLU):** This module processes user inputs (text or voice), parsing unstructured language to extract intents and entities (e.g., converting "I'm cold" into a specific "increase temperature" command).
  - **Decision Engine:** Utilizing historical data and pre-trained AI models, this engine analyzes patterns to make autonomous decisions (e.g., anomaly detection for security or predictive energy saving).

- **Orchestration:** acting as the central coordinator, it translates high-level decisions into specific, protocol-compliant commands and dispatches them down to the IoT layer for execution.

The interaction between these two layers creates a seamless feedback loop: the Lower Layer provides the context (data), while the Upper Layer provides the intelligence (actionable decisions).

1.3 Stakeholders of the Project

1.3.1 Residents (Family Members)

Residents are the end-users who interact with the smart home environment daily. Their primary concern is comfort, convenience, and health.

- **Pain Point:** They are tired of manually adjusting multiple apps for different devices and want a system that "just understands" their preferences.
- **Benefit:** They gain a hands-free experience where the home adjusts temperature and lighting based on their presence and habits, along with health monitoring through air quality sensors.

1.3.2 System's Administrator

The System's Administrator is the decision-maker responsible for the property's maintenance, security, and operational costs.

- **Pain Point:** They struggle with rising electricity bills and the anxiety of potential security breaches or fire hazards when away from home.
- **Benefit:** They receive detailed analytics on energy consumption to identify waste, along with real-time, AI-filtered security alerts that distinguish between false alarms (e.g., a pet) and genuine threats.

1.4 Goal of the Project

Primary Objectives:

- Develop a Scalable IoT Architecture: Build a system capable of handling concurrent connections from multiple sensor nodes with low latency.
- Implement Data-Driven Automation: Move beyond simple timers to behavior-based automation using machine learning algorithms.
- Optimize Energy Consumption: Provide visualization and forecasting tools that empower users to reduce their carbon footprint and electricity costs.
- Enhance Security with AI: Utilize computer vision and anomaly detection techniques to provide superior security coverage compared to traditional motion sensors.

Scope of the Project:

- IoT Core Infrastructure: Implementation of essential smart home management features including device provisioning (registration), state synchronization (on/off status), real-time command dispatching via MQTT, and role-based access control (RBAC) for family members.

- Data Pipeline Integration: Development of automated ETL (Extract, Transform, Load) pipelines to ingest high-frequency sensor telemetry, clean noise, and structure data for analytical processing.
- AI-Driven Insights: Leveraging machine learning models to transform raw data into intelligence:
  - Regression Models: Forecasting energy consumption trends for the upcoming month.
  - Classification Models: Distinguishing between human presence and pets to filter false security alarms.
  - Clustering Algorithms: Grouping similar user activity patterns to recommend personalized automation schedules.
- Visualization & Reporting: Deployment of interactive dashboards featuring heatmaps (for room occupancy) and time-series charts to visualize historical environmental data and real-time system states.
- Digital Twin Integration & Simulation-to-Reality (Sim2Real):
  - Virtual Environment Replication: Development of a 3D digital twin of the home environment to synchronize and visualize the real-time status of IoT devices and environmental sensors.
  - Scenario Simulation: Creating "What-if" scenarios, such as fire outbreaks, gas leaks, or security breaches, to validate the responsiveness and accuracy of the system's emergency protocols without risking physical assets.
  - Sim2Real Framework: Ensuring that the control logic and AI models developed in the simulation can be seamlessly transitioned to physical hardware with minimal reconfiguration, facilitating robust testing and reducing the risk of equipment failure during deployment.

References

[1] R. Martino, "It's a matter of interoperability: The new standard makes smart homes just work," Dec. 2021.