

Introduction to Quantum Computing

Module 2 — Part III

Ugo Dal Lago



ALMA MATER STUDIORUM
UNIVERSITÀ DI BOLOGNA



Academic Year 2024/2025

Part I

Error Correction

Errors in Classical Computation and Communication

- The possibility of observing **errors** is present both in realm of computation and communication devices, already in classical computing.

Errors in Classical Computation and Communication

- ▶ The possibility of observing **errors** is present both in realm of computation and communication devices, already in classical computing.
 - ▶ Logical *gates* can indeed behave in a way which is different from their specification, but the possibility that this happens is so low that it can be taken to be 0.
 - ▶ It can well be, instead, that long-distance *communication channels* are subject to errors.

Errors in Classical Computation and Communication

- ▶ The possibility of observing **errors** is present both in realm of computation and communication devices, already in classical computing.
 - ▶ Logical *gates* can indeed behave in a way which is different from their specification, but the possibility that this happens is so low that it can be taken to be 0.
 - ▶ It can well be, instead, that long-distance *communication channels* are subject to errors.
- ▶ One can deal with errors occurring along communication channels in a variety of ways, as studied in **information theory**

- ▶ For example, one can encode every logical bit to be sent as three instances of *the same* bit:

$$0 \longrightarrow 000 \qquad 1 \longrightarrow 111$$

- ▶ This way, if errors affect either 0 or 1 of the bits in the triple, errors can be not only recognized, but also corrected.
 - ▶ This is the so-called **repetition code**.

Errors in Quantum Computing

- ▶ When we switch from *classical* to *quantum* communication/computation, a number of additional problems show up:
 - ▶ Already at the level of quantum **computation**, error correction is absolutely crucial, because qubits are implemented by individual atomic-scale physical systems.
 - ▶ Quantum error correction is problematic, given the very nature of quantum computing, because the typical way of *detecting* an error in any piece of data consists in *observing it*, but doing this would **disturb** the underlying quantum state.
 - ▶ The kind of errors one can observe are more general: not only the state of a qubit can be flipped, but there could be, e.g. *phase errors*.
- ▶ Despite all these additional problem, quantum error correction is indeed possible, and there is a whole research field whose objective is precisely that of designing **quantum error correcting codes** (QECCs for short).

Part II


QECC in a Simplified Setting

Quantum Repetition Code?

- ▶ One could try to replicate the idea behind classical repetition codes, and effectively replicate the value of a qubit to two other qubits, by way of controlled-not gates.
- ▶ For simplicity, we can assume that the only kind of errors we are interested in correcting are **single qubit flipping errors**.


Quantum Repetition Code?

- ▶ One could try to replicate the idea behind classical repetition codes, and effectively replicate the value of a qubit to two other qubits, by way of controlled-not gates.
- ▶ For simplicity, we can assume that the only kind of errors we are interested in correcting are **single qubit flipping errors**.
- ▶ In other words, we are in the following situation:



Quantum Repetition Code?

- ▶ One could try to replicate the idea behind classical repetition codes, and effectively replicate the value of a qubit to two other qubits, by way of controlled-not gates.
- ▶ For simplicity, we can assume that the only kind of errors we are interested in correcting are **single qubit flipping errors**.
- ▶ In other words, we are in the following situation:



- ▶ How can we **detect** and **correct** errors, then?

A Simple QECC

