

No	Class Name	References to Objects	Property and method name	Script Call	Detailed explanation
1	Game_Temp	\$gameTemp	isPlaytest()	\$gameTemp.isPlaytest()	Determine if the game is in test play or not
2	Game_Temp	\$gameTemp	isDestinationValid()	\$gameTemp.isDestinationValid()	Determine if the destination is specified
3	Game_Temp	\$gameTemp	destinationX()	\$gameTemp.destinationX()	X-coordinate of the destination
4	Game_Temp	\$gameTemp	destinationY()	\$gameTemp.destinationY()	Y-coordinate of the destination
5	Game_Temp	\$gameTemp	touchTarget()	\$gameTemp.touchTarget()	Retrieve the target game object most recently touched
6	Game_Temp	\$gameTemp	touchState()	\$gameTemp.touchState()	Acquire the touch status of the most recent touch operation
7	Game_Temp	\$gameTemp	isBattleRefreshRequested()	\$gameTemp.isBattleRefreshRequested()	Retrieve information on whether Refresh Flag is requested. (Used to determine whether to redraw the window)
8	Game_Temp	\$gameTemp	reserveCommonEvent(id)	\$gameTemp.reserveCommonEvent(id)	Scheduled execution of common events of the specified ID (stored in a queue)
9	Game_Temp	\$gameTemp	isCommonEventReserved()	\$gameTemp.isCommonEventReserved()	Determine if a common event has been reserved.
10	Game_Temp	\$gameTemp	requestAnimation(targets, animationId, mirror)	\$gameTemp.requestAnimation(targets, animationId, mirror)	Request to play the animation with the target, ID and reversal flag (stored in the queue)
11	Game_Temp	\$gameTemp	requestBalloon(target, balloonId)	\$gameTemp.requestBalloon(target, balloonId)	Request the display of balloon icon by specifying a target and balloon icon ID (stored in a queue)
12	Game_Temp	\$gameTemp	lastActionData(type)	\$gameTemp.lastActionData(type)	Retrieve a variety of behavioral data by specifying the type (as shown below) 0: The last skill someone used 1: Last item used by someone 2: The last actor to act 3: Last enemy character to act 4: The last targeted actor 5: The last enemy character targeted
13	Game_System	\$gameSystem	isJapanese()	\$gameSystem.isJapanese()	Whether the language setting of the database is set to Japanese or not
14	Game_System	\$gameSystem	isChinese()	\$gameSystem.isChinese()	Whether the language setting of the database is set to Chinese or not
15	Game_System	\$gameSystem	isKorean()	\$gameSystem.isKorean()	Whether the database language is set to Korean or not
16	Game_System	\$gameSystem	isCJK()	\$gameSystem.isCJK()	Whether the database language setting is set to CJK (Chinese, Japanese, Korean) or not
17	Game_System	\$gameSystem	isRussian()	\$gameSystem.isRussian()	Whether the database language is set to Russian or not
18	Game_System	\$gameSystem	isSideView()	\$gameSystem.isSideView()	Whether the combat setting is set to side-view or not
19	Game_System	\$gameSystem	isAutosaveEnabled()	\$gameSystem.isAutosaveEnabled()	Whether auto-save is enabled or not
20	Game_System	\$gameSystem	isSaveEnabled()	\$gameSystem.isSaveEnabled()	Whether saving from the menu screen is allowed or not
21	Game_System	\$gameSystem	disableSave()	\$gameSystem.disableSave()	Disable saving from the menu screen
22	Game_System	\$gameSystem	enableSave()	\$gameSystem.enableSave()	Enable saving from the menu screen
23	Game_System	\$gameSystem	isMenuEnabled()	\$gameSystem.isMenuEnabled()	Whether or not the menu screen can be opened or not
24	Game_System	\$gameSystem	disableMenu()	\$gameSystem.disableMenu()	Disable opening the menu screen
25	Game_System	\$gameSystem	enableMenu()	\$gameSystem.enableMenu()	Enable opening the menu screen
26	Game_System	\$gameSystem	isEncounterEnabled()	\$gameSystem.isEncounterEnabled()	Whether encounters are enabled or not
27	Game_System	\$gameSystem	disableEncounter()	\$gameSystem.disableEncounter()	Disable encounters
28	Game_System	\$gameSystem	enableEncounter()	\$gameSystem.enableEncounter()	Enable encounters
29	Game_System	\$gameSystem	isFormationEnabled()	\$gameSystem.isFormationEnabled()	Whether the formation of the party can be changed or not.
30	Game_System	\$gameSystem	disableFormation()	\$gameSystem.disableFormation()	Disable formation changes
31	Game_System	\$gameSystem	enableFormation()	\$gameSystem.enableFormation()	Enable formation changes
32	Game_System	\$gameSystem	battleCount()	\$gameSystem.battleCount()	Total number of encounters
33	Game_System	\$gameSystem	winCount()	\$gameSystem.winCount()	Total number of wins
34	Game_System	\$gameSystem	escapeCount()	\$gameSystem.escapeCount()	Total number of successful escapes
35	Game_System	\$gameSystem	saveCount()	\$gameSystem.saveCount()	Total number of saves
36	Game_System	\$gameSystem	versionId()	\$gameSystem.versionId()	Version ID (which is changed to a different value each time the project is saved)
37	Game_System	\$gameSystem	savefileId()	\$gameSystem.savefileId()	Save file ID
38	Game_System	\$gameSystem	windowTone()	\$gameSystem.windowTone()	Current color tone of Window graphic.
39	Game_System	\$gameSystem	setWindowTone(value)	\$gameSystem.setWindowTone(value)	Set the color tone of Window graphic to 'value'
40	Game_System	\$gameSystem	battleBgm()	\$gameSystem.battleBgm()	Currently set battle BGM
41	Game_System	\$gameSystem	setBattleBgm(audio)	\$gameSystem.setBattleBgm(audio)	Set the battle BGM (Specify Audio Object)
42	Game_System	\$gameSystem	victoryMe()	\$gameSystem.victoryMe()	Currently set Victory ME
43	Game_System	\$gameSystem	setVictoryMe(audio)	\$gameSystem.setVictoryMe(audio)	Set the Victory ME
44	Game_System	\$gameSystem	defeatMe()	\$gameSystem.defeatMe()	Currently set Defeat ME
45	Game_System	\$gameSystem	setDefeatMe(audio)	\$gameSystem.setDefeatMe(audio)	Set the Defeat ME
46	Game_System	\$gameSystem	playtime()	\$gameSystem.playtime()	Total time played (in seconds)
47	Game_System	\$gameSystem	playtimeText()	\$gameSystem.playtimeText()	Total play time as a string in (hh:mm:ss) format
48	Game_System	\$gameSystem	saveBgm()	\$gameSystem.saveBgm()	Save the currently playing BGM
49	Game_System	\$gameSystem	replayBgm()	\$gameSystem.replayBgm()	Play the BGM stored if "save BGM" has been used
50	Game_System	\$gameSystem	mainFontFace()	\$gameSystem.mainFontFace()	The name of the main font used
51	Game_System	\$gameSystem	numberFontFace()	\$gameSystem.numberFontFace()	The name of the font used for numbers. Used in timers, damage displays, etc
52	Game_System	\$gameSystem	mainFontSize()	\$gameSystem.mainFontSize()	The font size of the main font used.
53	Game_System	\$gameSystem	windowPadding()	\$gameSystem.windowPadding()	The size of the window padding/margins.
54	Game_Timer	\$gameTimer	start(count)	\$gameTimer.start(count)	Start the timer. Specifies the number of frames (1/60th of a second)
55	Game_Timer	\$gameTimer	stop()	\$gameTimer.stop()	Deactivate the timer
56	Game_Timer	\$gameTimer	isWorking()	\$gameTimer.isWorking()	Determine whether the timer is operating or not
57	Game_Timer	\$gameTimer	seconds()	\$gameTimer.seconds()	The number of seconds left on the timer

No	Class Name	References to Objects	Property and method name	Script Call	Detailed explanation
58	Game_Message	\$gameMessage	choices()	\$gameMessage.choices()	Event command/ Choices array in "Show Choices"
59	Game_Message	\$gameMessage	speakerName()	\$gameMessage.speakerName()	Event command/ The name in "Show Message"
60	Game_Message	\$gameMessage	faceName()	\$gameMessage.faceName()	Event command/ Face file name for "Show Message"
61	Game_Message	\$gameMessage	faceIndex()	\$gameMessage.faceIndex()	Event command/ Face index of "Show Message"
62	Game_Message	\$gameMessage	background()	\$gameMessage.background()	Event command/ Background type of "Show Message"
63	Game_Message	\$gameMessage	positionType()	\$gameMessage.positionType()	Event command/ The position of the "Show Message" window
64	Game_Message	\$gameMessage	choiceDefaultType()	\$gameMessage.choiceDefaultType()	Event command/ Default choice for "Show Choices"
65	Game_Message	\$gameMessage	choiceCancelType()	\$gameMessage.choiceCancelType()	Event command/ Cancel choice for "Show choices"
66	Game_Message	\$gameMessage	choiceBackground()	\$gameMessage.choiceBackground()	Event command/ Background on "Show Choices"
67	Game_Message	\$gameMessage	choicePositionType()	\$gameMessage.choicePositionType()	Event command/ The position of the "Show Choices" window
68	Game_Message	\$gameMessage	numInputVariableId()	\$gameMessage.numInputVariableId()	Event command/ The variable number of "Input Number"
69	Game_Message	\$gameMessage	numInputMaxDigits()	\$gameMessage.numInputMaxDigits()	Event command/ Number of digits in "Input Number"
70	Game_Message	\$gameMessage	itemChoiceVariableId()	\$gameMessage.itemChoiceVariableId()	Event command/ The variable number of "Select Item"
71	Game_Message	\$gameMessage	itemChoiceTypeId()	\$gameMessage.itemChoiceTypeId()	Event command/ The item type in "Item Select"
72	Game_Message	\$gameMessage	scrollMode()	\$gameMessage.scrollMode()	Whether or not to scroll through the text when displaying it
73	Game_Message	\$gameMessage	scrollSpeed()	\$gameMessage.scrollSpeed()	Speed of the event command "Show Scrolling Text"
74	Game_Message	\$gameMessage	scrollNoFast()	\$gameMessage.scrollNoFast()	Prevent fast-forwarding of the event command "Show Scrolling Text"
75	Game_Message	\$gameMessage	hasText()	\$gameMessage.hasText()	Whether the text to be displayed in the message window exists or not
76	Game_Message	\$gameMessage	isChoice()	\$gameMessage.isChoice()	Whether "Show Choices" is used or not
77	Game_Message	\$gameMessage	isNumberInput()	\$gameMessage.isNumberInput()	Whether "Input Number" is used or not
78	Game_Message	\$gameMessage	isItemChoice()	\$gameMessage.isItemChoice()	Whether "Select Item" is used or not
79	Game_Message	\$gameMessage	isBusy()	\$gameMessage.isBusy()	Whether any of the message displays, choices, etc. are present
80	Game_Message	\$gameMessage	allText()	\$gameMessage.allText()	All text to be displayed in the message (including newline characters)
81	Game_Message	\$gameMessage	isRTL()	\$gameMessage.isRTL()	Whether the message to be displayed is in the right-to-left language
82	Game_Switches	\$gameSwitches	value(n)	\$gameSwitches.value(n)	Get the value of nth switch
83	Game_Switches	\$gameSwitches	setValue(n, value)	\$gameSwitches.setValue(n, value)	Set the n-th switch to value
84	Game_Variables	\$gameVariables	value(n)	\$gameVariables.value(n)	Get the value of nth variable
85	Game_Variables	\$gameVariables	setValue(n, value)	\$gameVariables.setValue(n, value)	Set the value of n-th variable
86	Game_SelfSwitches	\$gameSelfSwitches	value(key)	\$gameSelfSwitches.value(key)	Get the self-switch value of the specified key ([Map ID, Event ID, Type])
87	Game_SelfSwitches	\$gameSelfSwitches	setValue(key, value)	\$gameSelfSwitches.setValue(key, value)	Set the self-switch value of the specified key
88	Game_Screen	\$gameScreen	brightness()	\$gameScreen.brightness()	Value of screen brightness (used in fade in and fade out)
89	Game_Screen	\$gameScreen	tone()	\$gameScreen.tone()	Value of color tone of the screen
90	Game_Screen	\$gameScreen	flashColor()	\$gameScreen.flashColor()	Value of flash color of the screen
91	Game_Screen	\$gameScreen	shake()	\$gameScreen.shake()	Value of screen shake state
92	Game_Screen	\$gameScreen	zoomX()	\$gameScreen.zoomX()	Value of horizontal focal coordinates of the screen
93	Game_Screen	\$gameScreen	zoomY()	\$gameScreen.zoomY()	Value of vertical focal point of the screen
94	Game_Screen	\$gameScreen	zoomScale()	\$gameScreen.zoomScale()	Value of screen magnification
95	Game_Screen	\$gameScreen	weatherType()	\$gameScreen.weatherType()	Get the weather type
96	Game_Screen	\$gameScreen	weatherPower()	\$gameScreen.weatherPower()	Get the weather strength
97	Game_Screen	\$gameScreen	picture(id)	\$gameScreen.picture(id)	Obtain picture information of the specified ID
98	Game_Screen	\$gameScreen	clearFade()	\$gameScreen.clearFade()	Clear screen fade out
99	Game_Screen	\$gameScreen	clearTone()	\$gameScreen.clearTone()	Clear screen color tone
100	Game_Screen	\$gameScreen	clearFlash()	\$gameScreen.clearFlash()	Clear screen flash
101	Game_Screen	\$gameScreen	clearShake()	\$gameScreen.clearShake()	Clear screen shake
102	Game_Screen	\$gameScreen	clearZoom()	\$gameScreen.clearZoom()	Clear screen zoom
103	Game_Screen	\$gameScreen	clearWeather()	\$gameScreen.clearWeather()	Clear weather effects
104	Game_Screen	\$gameScreen	clearPictures()	\$gameScreen.clearPictures()	Clear all pictures
105	Game_Screen	\$gameScreen	maxPictures()	\$gameScreen.maxPictures()	Maximum number of pictures that can be displayed on the screen (default 100)
106	Game_Screen	\$gameScreen	startFadeOut(d)	\$gameScreen.startFadeOut(d)	Start fading out by specifying a frame
107	Game_Screen	\$gameScreen	startFadeIn(d)	\$gameScreen.startFadeIn(d)	Start fading in by specifying a frame
108	Game_Screen	\$gameScreen	startTint(tone, d)	\$gameScreen.startTint(tone, d)	Change the screen color by specifying the color tone and frame
109	Game_Screen	\$gameScreen	startFlash(color, d)	\$gameScreen.startFlash(color, d)	Flash the screen by specifying a color and frame
110	Game_Screen	\$gameScreen	startShake(p, s, d)	\$gameScreen.startShake(p, s, d)	Shake the screen by specifying strength, speed and frame
111	Game_Screen	\$gameScreen	startZoom(x, y, scale, d)	\$gameScreen.startZoom(x, y, scale, d)	Zoom into the screen by specifying the focal coordinates, magnification, and frame
112	Game_Screen	\$gameScreen	setZoom(x, y, scale,)	\$gameScreen.setZoom(x, y, scale,)	Instantly zoom in by specifying the focal coordinates and magnification
113	Game_Screen	\$gameScreen	changeWeather(type, p, d)	\$gameScreen.changeWeather(type, p, d)	Change the weather by specifying type, strength and frame
114	Game_Screen	\$gameScreen	showPicture()	\$gameScreen.showPicture()	Display a picture
115	Game_Screen	\$gameScreen	movePicture()	\$gameScreen.movePicture()	Move a picture
116	Game_Screen	\$gameScreen	rotatePicture(id, s)	\$gameScreen.rotatePicture(id, s)	Rotate a picture by specifying the picture ID and speed
117	Game_Screen	\$gameScreen	tintPicture(id, tone, d)	\$gameScreen.tintPicture(id, tone, d)	Change the color tone of a picture by specifying the picture ID, color tone and frame
118	Game_Screen	\$gameScreen	erasePicture(id)	\$gameScreen.erasePicture(id)	Erase a picture by specifying the picture ID
119	Game_Picture	\$gameScreen.picture(n)	name()	\$gameScreen.picture(n).name()	Get the name of the nth picture
120	Game_Picture	\$gameScreen.picture(n)	origin()	\$gameScreen.picture(n).origin()	Get the origin of the n-th picture

No	Class Name	References to Objects	Property and method name	Script Call	Detailed explanation
121	Game_Picture	\$gameScreen.picture(n)	x()	\$gameScreen.picture(n).x()	Get the x-coordinate of the n-th picture
122	Game_Picture	\$gameScreen.picture(n)	y()	\$gameScreen.picture(n).y()	Get the y-coordinate of the n-th picture
123	Game_Picture	\$gameScreen.picture(n)	scaleX()	\$gameScreen.picture(n).scaleX()	Get the magnification (width) of the n-th picture
124	Game_Picture	\$gameScreen.picture(n)	scaleY()	\$gameScreen.picture(n).scaleY()	Get the magnification (height) of the n-th picture
125	Game_Picture	\$gameScreen.picture(n)	opacity()	\$gameScreen.picture(n).opacity()	Get the opacity of the nth picture
126	Game_Picture	\$gameScreen.picture(n)	blendMode()	\$gameScreen.picture(n).blendMode()	Get the nth picture's blend mode.
127	Game_Picture	\$gameScreen.picture(n)	tone()	\$gameScreen.picture(n).tone()	Get the color tone of the n-th picture
128	Game_Picture	\$gameScreen.picture(n)	angle()	\$gameScreen.picture(n).angle()	Get the rotation angle of the n-th picture
129	Game_BattlerBase	\$gameActors.actor(n)	isStateAffected(id)	\$gameActors.actor(n).isStateAffected(id)	Whether actor ID (n) is affected by state ID or not
130	Game_BattlerBase	a	isStateAffected(id)	a.isStateAffected(id)	Whether or not the user is affected by state (ID) in the combat formula
131	Game_BattlerBase	b	isStateAffected(id)	b.isStateAffected(id)	Whether or not the target is affected by state (ID) in the combat formula
132	Game_BattlerBase	\$gameTroop.members()[n]	isStateAffected(id)	\$gameTroop.members()[n].isStateAffected(id)	Whether or not the nth enemy character is affected by state (ID)
133	Game_BattlerBase	\$gameParty.members()[n]	isStateAffected(id)	\$gameParty.members()[n].isStateAffected(id)	Whether or not the nth party member is affected by state (ID)
134	Game_BattlerBase	\$gameParty.members()[n]	isDeathStateAffected()	\$gameParty.members()[n].isDeathStateAffected()	Whether or not an actor is in a no combat state
135	Game_BattlerBase	\$gameParty.members()[n]	isBuffAffected(id)	\$gameParty.members()[n].isBuffAffected(id)	Whether the parameter id is buffed or not
136	Game_BattlerBase	\$gameParty.members()[n]	isDebuffAffected(id)	\$gameParty.members()[n].isDebuffAffected(id)	Whether the parameter id is debuffed or not
137	Game_BattlerBase	\$gameParty.members()[n]	isBuffOrDebuffAffected(id)	\$gameParty.members()[n].isBuffOrDebuffAffected(id)	Whether the parameter id is buffed or debuffed
138	Game_BattlerBase	\$gameParty.members()[n]	isMaxBuffAffected(id)	\$gameParty.members()[n].isMaxBuffAffected(id)	Whether the parameter id is buffed to the maximum
139	Game_BattlerBase	\$gameParty.members()[n]	isMaxDebuffAffected(id)	\$gameParty.members()[n].isMaxDebuffAffected(id)	Whether the debuff of parameter id is maxed out or not
140	Game_BattlerBase	\$gameParty.members()[n]	states()	\$gameParty.members()[n].states()	Get an array of enabled states
141	Game_BattlerBase	\$gameParty.members()[n]	stateIcons()	\$gameParty.members()[n].stateIcons()	Get an array of enabled state icons
142	Game_BattlerBase	\$gameParty.members()[n]	buffIcons()	\$gameParty.members()[n].buffIcons()	Get an array of enabled buff icons
143	Game_BattlerBase	\$gameParty.members()[n]	allIcons()	\$gameParty.members()[n].allIcons()	Get an array of enabled states and buffing icons
144	Game_BattlerBase	\$gameParty.members()[n]	allTraits()	\$gameParty.members()[n].allTraits()	Get an array of enabled traits
145	Game_BattlerBase	\$gameParty.members()[n]	traits(code)	\$gameParty.members()[n].traits(code)	Get any traits of the specified code
146	Game_BattlerBase	\$gameParty.members()[n]	traitsWithId(code, id)	\$gameParty.members()[n].traitsWithId(code, id)	Retrieve any traits of the specified code or data ID
147	Game_BattlerBase	\$gameParty.members()[n]	traitsPi(code, id)	\$gameParty.members()[n].traitsPi(code, id)	Get the result of multiplying all the values of the specified code and data ID traits
148	Game_BattlerBase	\$gameParty.members()[n]	traitsSum(code, id)	\$gameParty.members()[n].traitsSum(code, id)	Get the result of adding all the values of the specified code and data ID traits
149	Game_BattlerBase	\$gameParty.members()[n]	traitsSumAll(code)	\$gameParty.members()[n].traitsSumAll(code)	Get the result of adding all the values of the specified code traits
150	Game_BattlerBase	\$gameParty.members()[n]	traitsSet(code)	\$gameParty.members()[n].traitsSet(code)	Retrieve an array of code values for the specified code traits
151	Game_BattlerBase	\$gameParty.members()[n]	param(id)	\$gameParty.members()[n].param(id)	Get the normal ability value of the specified parameter ID
152	Game_BattlerBase	\$gameParty.members()[n]	xparam(id)	\$gameParty.members()[n].xparam(id)	Get the additional capability value of the specified parameter ID
153	Game_BattlerBase	\$gameParty.members()[n]	sparam(id)	\$gameParty.members()[n].sparam(id)	Get the special ability value of the specified parameter ID
154	Game_BattlerBase	\$gameParty.members()[n]	elementRate(id)	\$gameParty.members()[n].elementRate(id)	Retrieve the attribute validity of the specified attribute ID
155	Game_BattlerBase	\$gameParty.members()[n]	debuffRate(id)	\$gameParty.members()[n].debuffRate(id)	Get the weakness effectiveness of the specified parameter ID
156	Game_BattlerBase	\$gameParty.members()[n]	stateRate(id)	\$gameParty.members()[n].stateRate(id)	Get the weakness effectiveness of the specified state ID
157	Game_BattlerBase	\$gameParty.members()[n]	isStateResist(id)	\$gameParty.members()[n].isStateResist(id)	Returns whether the specified state ID can be disabled
158	Game_BattlerBase	\$gameParty.members()[n]	attackElements()	\$gameParty.members()[n].attackElements()	Get attributes for Attack
159	Game_BattlerBase	\$gameParty.members()[n]	attackStates()	\$gameParty.members()[n].attackStates()	Get states for attack
160	Game_BattlerBase	\$gameParty.members()[n]	attackStatesRate()	\$gameParty.members()[n].attackStatesRate()	Get the percentage of state granted on attack
161	Game_BattlerBase	\$gameParty.members()[n]	attackSpeed()	\$gameParty.members()[n].attackSpeed()	Get attack speed
162	Game_BattlerBase	\$gameParty.members()[n]	attackTimesAdd()	\$gameParty.members()[n].attackTimesAdd()	Get the number of additional attacks
163	Game_BattlerBase	\$gameParty.members()[n]	attackSkillId()	\$gameParty.members()[n].attackSkillId()	Get a skill ID for a normal attack
164	Game_BattlerBase	\$gameParty.members()[n]	addedSkillTypes()	\$gameParty.members()[n].addedSkillTypes()	Get additional skill types
165	Game_BattlerBase	\$gameParty.members()[n]	isSkillTypeSealed(id)	\$gameParty.members()[n].isSkillTypeSealed(id)	Whether the specified skill type ID is sealed
166	Game_BattlerBase	\$gameParty.members()[n]	addedSkills()	\$gameParty.members()[n].addedSkills()	Get additional skills
167	Game_BattlerBase	\$gameParty.members()[n]	isSkillSealed(id)	\$gameParty.members()[n].isSkillSealed(id)	Check if the skill of the specified ID sealed
168	Game_BattlerBase	\$gameParty.members()[n]	isEquipWtypeOk(id)	\$gameParty.members()[n].isEquipWtypeOk(id)	Check if an actor can equip the weapon type of the specified ID
169	Game_BattlerBase	\$gameParty.members()[n]	isEquipAtypeOk(id)	\$gameParty.members()[n].isEquipAtypeOk(id)	Check if an actor can equip the armor type of the specified ID
170	Game_BattlerBase	\$gameParty.members()[n]	isEquipTypeLocked(id)	\$gameParty.members()[n].isEquipTypeLocked(id)	Check if the equipment type of the specified ID is locked
171	Game_BattlerBase	\$gameParty.members()[n]	isEquipTypeSealed(id)	\$gameParty.members()[n].isEquipTypeSealed(id)	Check if the equipment type of the specified ID is sealed
172	Game_BattlerBase	\$gameParty.members()[n]	isDualWield()	\$gameParty.members()[n].isDualWield()	Check if the equipment type of the specified ID can be dual wielded
173	Game_BattlerBase	\$gameParty.members()[n]	collapseType()	\$gameParty.members()[n].collapseType()	Collapse type of an enemy
174	Game_BattlerBase	\$gameParty.members()[n]	partyAbility(id)	\$gameParty.members()[n].partyAbility(id)	Whether or not you have a party ability of the specified type
175	Game_BattlerBase	\$gameParty.members()[n]	isAutoBattle()	\$gameParty.members()[n].isAutoBattle()	Check if autobattle is enabled or not
176	Game_BattlerBase	\$gameParty.members()[n]	isGuard()	\$gameParty.members()[n].isGuard()	Check if guard is enabled or not
177	Game_BattlerBase	\$gameParty.members()[n]	isSubstitute()	\$gameParty.members()[n].isSubstitute()	Check if substitute is enabled or not
178	Game_BattlerBase	\$gameParty.members()[n]	isPreserveTp()	\$gameParty.members()[n].isPreserveTp()	Check if preserve TP is enabled or not
179	Game_BattlerBase	\$gameParty.members()[n]	addParam(id, value)	\$gameParty.members()[n].addParam(id, value)	Increases the value of the specified parameter ID by value
180	Game_BattlerBase	\$gameParty.members()[n]	setHp(value)	\$gameParty.members()[n].setHp(value)	Set HP value
181	Game_BattlerBase	\$gameParty.members()[n]	setMp(value)	\$gameParty.members()[n].setMp(value)	Set MP value
182	Game_BattlerBase	\$gameParty.members()[n]	setTp(value)	\$gameParty.members()[n].setTp(value)	Set TP value
183	Game_BattlerBase	\$gameParty.members()[n]	maxTp()	\$gameParty.members()[n].maxTp()	Get the maximum value of TP

No	Class Name	References to Objects	Property and method name	Script Call	Detailed explanation
184	Game_BattlerBase	\$gameParty.members()[n]	recoverAll()	\$gameParty.members()[n].recoverAll()	Full recovery
185	Game_BattlerBase	\$gameParty.members()[n]	hpRate()	\$gameParty.members()[n].hpRate()	Get the percentage of remaining HP
186	Game_BattlerBase	\$gameParty.members()[n]	mpRate()	\$gameParty.members()[n].mpRate()	Get the percentage of remaining MP
187	Game_BattlerBase	\$gameParty.members()[n]	tpRate()	\$gameParty.members()[n].tpRate()	Get the percentage of remaining TP
188	Game_BattlerBase	\$gameParty.members()[n]	isHidden()	\$gameParty.members()[n].isHidden()	Check if a battler is hidden or not.
189	Game_BattlerBase	\$gameParty.members()[n]	isAppeared()	\$gameParty.members()[n].isAppeared()	Check if a battler has appeared or not.
190	Game_BattlerBase	\$gameParty.members()[n]	isDead()	\$gameParty.members()[n].isDead()	Check if a battler is dead.
191	Game_BattlerBase	\$gameParty.members()[n]	isAlive()	\$gameParty.members()[n].isAlive()	Check if a battler is alive.
192	Game_BattlerBase	\$gameParty.members()[n]	isDying()	\$gameParty.members()[n].isDying()	Check if a battler is on very low HP.
193	Game_BattlerBase	\$gameParty.members()[n]	isRestricted()	\$gameParty.members()[n].isRestricted()	Check if a battler is restricted or not.
194	Game_BattlerBase	\$gameParty.members()[n]	canInput()	\$gameParty.members()[n].canInput()	Check if a battler can input moves or not.
195	Game_BattlerBase	\$gameParty.members()[n]	canMove()	\$gameParty.members()[n].canMove()	Check if a battler can move.
196	Game_BattlerBase	\$gameParty.members()[n]	isConfused()	\$gameParty.members()[n].isConfused()	Check if a battler is confused.
197	Game_BattlerBase	\$gameParty.members()[n]	isActor()	\$gameParty.members()[n].isActor()	Check if a battler is an actor or not.
198	Game_BattlerBase	\$gameParty.members()[n]	isEnemy()	\$gameParty.members()[n].isEnemy()	Check if a battler is an enemy or not.
199	Game_BattlerBase	\$gameParty.members()[n]	canUse(skill)	\$gameParty.members()[n].canUse(skill)	Whether a given skill or item can be used.
200	Game_BattlerBase	\$gameParty.members()[n]	canEquip(item)	\$gameParty.members()[n].canEquip(item)	Whether or not an actor can equip the specified equipment
201	Game_BattlerBase	\$gameParty.members()[n]	guardSkillId()	\$gameParty.members()[n].guardSkillId()	Get the skill ID for Guard
202	Game_BattlerBase	\$gameParty.members()[n]	canAttack()	\$gameParty.members()[n].canAttack()	Whether or not it's possible to attack
203	Game_BattlerBase	\$gameParty.members()[n]	canGuard()	\$gameParty.members()[n].canGuard()	Whether a battler can use Guard or not
204	Game_Battler	\$gameParty.members()[n]	addState(id)	\$gameParty.members()[n].addState(id)	Apply the specified state ID to a battler
205	Game_Battler	\$gameParty.members()[n]	removeState()	\$gameParty.members()[n].removeState()	Remove the specified state ID from a battler
206	Game_Battler	\$gameParty.members()[n]	addBuff(id, turns)	\$gameParty.members()[n].addBuff(id, turns)	Apply a buff of the specified parameter ID for the duration of the turns
207	Game_Battler	\$gameParty.members()[n]	addDebuff(id, turns)	\$gameParty.members()[n].addDebuff(id, turns)	Apply a debuff of the specified parameter ID for the duration of the turns
208	Game_Battler	\$gameParty.members()[n]	removeBuff(id)	\$gameParty.members()[n].removeBuff(id)	Removes the buff and debuff of the specified parameter ID
209	Game_Battler	\$gameParty.members()[n]	removeBattleStates()	\$gameParty.members()[n].removeBattleStates()	Remove battle states
210	Game_Battler	\$gameParty.members()[n]	removeAllBuffs()	\$gameParty.members()[n].removeAllBuffs()	Remove all buffs and debuffs
211	Game_Battler	\$gameParty.members()[n]	useItem(item)	\$gameParty.members()[n].useItem(item)	Use the specified item
212	Game_Battler	\$gameParty.members()[n]	gainHp(value)	\$gameParty.members()[n].gainHp(value)	Increase or decrease HP by value
213	Game_Battler	\$gameParty.members()[n]	gainMp(value)	\$gameParty.members()[n].gainMp(value)	Increase or decrease MP by value
214	Game_Battler	\$gameParty.members()[n]	gainTp(value)	\$gameParty.members()[n].gainTp(value)	Increase or decrease TP by value
215	Game_Battler	\$gameParty.members()[n]	gainSilentTp(value)	\$gameParty.members()[n].gainSilentTp(value)	Increase or decrease TP without displaying a message
216	Game_Actor	\$gameParty.members()[n]	actorId()	\$gameParty.members()[n].actorId()	Get an actor's ID
217	Game_Actor	\$gameParty.members()[n]	actor()	\$gameParty.members()[n].actor()	Gets the position of an actor in the party.
218	Game_Actor	\$gameParty.members()[n]	name()	\$gameParty.members()[n].name()	Get an actor's name.
219	Game_Actor	\$gameParty.members()[n]	setName(value)	\$gameParty.members()[n].setName(value)	Set an actor's name.
220	Game_Actor	\$gameParty.members()[n]	nickname()	\$gameParty.members()[n].nickname()	Get an actor's nickname.
221	Game_Actor	\$gameParty.members()[n]	setNickname(value)	\$gameParty.members()[n].setNickname(value)	Set an actor's nickname.
222	Game_Actor	\$gameParty.members()[n]	profile()	\$gameParty.members()[n].profile()	Get an actor's profile.
223	Game_Actor	\$gameParty.members()[n]	setProfile(value)	\$gameParty.members()[n].setProfile(value)	Set an actor's profile.
224	Game_Actor	\$gameParty.members()[n]	characterName()	\$gameParty.members()[n].characterName()	Get an actor's file name
225	Game_Actor	\$gameParty.members()[n]	characterIndex()	\$gameParty.members()[n].characterIndex()	Get an actor's sprite index
226	Game_Actor	\$gameParty.members()[n]	faceName()	\$gameParty.members()[n].faceName()	Get an actor's face file name
227	Game_Actor	\$gameParty.members()[n]	faceIndex()	\$gameParty.members()[n].faceIndex()	Get an actor's face file index
228	Game_Actor	\$gameParty.members()[n]	battlerName()	\$gameParty.members()[n].battlerName()	Get an actor's battler file name
229	Game_Actor	\$gameParty.members()[n]	currentExp()	\$gameParty.members()[n].currentExp()	Get an actor's current EXP
230	Game_Actor	\$gameParty.members()[n]	nextRequiredExp()	\$gameParty.members()[n].nextRequiredExp()	Get the value of an actor's needed EXP to get to the next level
231	Game_Actor	\$gameParty.members()[n]	maxLevel()	\$gameParty.members()[n].maxLevel()	Get an actor's maximum level
232	Game_Actor	\$gameParty.members()[n]	isMaxLevel()	\$gameParty.members()[n].isMaxLevel()	Whether or not the maximum level is reached
233	Game_Actor	\$gameParty.members()[n]	equips()	\$gameParty.members()[n].equips()	Get the actor's equipment as an array
234	Game_Actor	\$gameParty.members()[n]	weapons()	\$gameParty.members()[n].weapons()	Get the actor's weapons as an array
235	Game_Actor	\$gameParty.members()[n]	armors()	\$gameParty.members()[n].armors()	Get the actor's armor as an array
236	Game_Actor	\$gameParty.members()[n]	hasWeapon(weapon)	\$gameParty.members()[n].hasWeapon(weapon)	Checks whether an actor is equipped with the specified weapon
237	Game_Actor	\$gameParty.members()[n]	hasArmor(armor)	\$gameParty.members()[n].hasArmor(armor)	Checks whether an actor is equipped with the specified armor
238	Game_Actor	\$gameParty.members()[n]	isEquipChangeOk(id)	\$gameParty.members()[n].isEquipChangeOk(id)	Checks whether the equipment in the specified slot ID can be changed
239	Game_Actor	\$gameParty.members()[n]	changeEquip(id, item)	\$gameParty.members()[n].changeEquip(id, item)	Change the equipment of the specified slot ID to item
240	Game_Actor	\$gameParty.members()[n]	forceChangeEquip()	\$gameParty.members()[n].forceChangeEquip()	Forces the equipment of a specified slot ID to be changed to item
241	Game_Actor	\$gameParty.members()[n]	changeEquipById(id, itemId)	\$gameParty.members()[n].changeEquipById(id, itemId)	Changes the equipment of the specified equipment ID to itemId
242	Game_Actor	\$gameParty.members()[n]	isEquipped(item)	\$gameParty.members()[n].isEquipped(item)	Checks whether the item is equipped
243	Game_Actor	\$gameParty.members()[n]	discardEquip(item)	\$gameParty.members()[n].discardEquip(item)	Unequips an item
244	Game_Actor	\$gameParty.members()[n]	clearEquipments()	\$gameParty.members()[n].clearEquipments()	Unequips all items
245	Game_Actor	\$gameParty.members()[n]	optimizeEquipments()	\$gameParty.members()[n].optimizeEquipments()	Optimizes an actor to the best equipment
246	Game_Actor	\$gameParty.members()[n]	friendsUnit()	\$gameParty.members()[n].friendsUnit()	Get a unit (party or enemy group)

No	Class Name	References to Objects	Property and method name	Script Call	Detailed explanation
247	Game_Actor	\$gameParty.members()[n]	opponentsUnit()	\$gameParty.members()[n].opponentsUnit()	Get an enemy unit (party or enemy group)
248	Game_Actor	\$gameParty.members()[n]	index()	\$gameParty.members()[n].index()	Gets the party order
249	Game_Actor	\$gameParty.members()[n]	isBattleMember()	\$gameParty.members()[n].isBattleMember()	Checks if an actor is a battle member
250	Game_Actor	\$gameParty.members()[n]	isFormationChangeOk()	\$gameParty.members()[n].isFormationChangeOk()	Checks whether the formation can be changed or not
251	Game_Actor	\$gameParty.members()[n]	currentClass()	\$gameParty.members()[n].currentClass()	Gets an actor's class
252	Game_Actor	\$gameParty.members()[n]	isClass(gameClass)	\$gameParty.members()[n].isClass(gameClass)	Checks if a class is the same as the specified gameClass
253	Game_Actor	\$gameParty.members()[n]	skillTypes()	\$gameParty.members()[n].skillTypes()	Get an array of acquired skill types
254	Game_Actor	\$gameParty.members()[n]	skills()	\$gameParty.members()[n].skills()	Get an array of acquired skills
255	Game_Actor	\$gameParty.members()[n]	usableSkills()	\$gameParty.members()[n].usableSkills()	Get an array of skills that can be used
256	Game_Actor	\$gameParty.members()[n]	hasNoWeapons()	\$gameParty.members()[n].hasNoWeapons()	Checks if an actor has a weapon equipped
257	Game_Actor	\$gameParty.members()[n]	bareHandsElementId()	\$gameParty.members()[n].bareHandsElementId()	Get the attribute ID of an unequipped weapon slot
258	Game_Actor	\$gameParty.members()[n]	attackAnimationId1()	\$gameParty.members()[n].attackAnimationId1()	Get the animation ID of a normal attack
259	Game_Actor	\$gameParty.members()[n]	attackAnimationId2()	\$gameParty.members()[n].attackAnimationId2()	Get two normal attack animation IDs in the case of a two-pronged attack
260	Game_Actor	\$gameParty.members()[n]	bareHandsAnimationId()	\$gameParty.members()[n].bareHandsAnimationId()	Get the animation ID of a barehanded attack
261	Game_Actor	\$gameParty.members()[n]	gainExp(exp)	\$gameParty.members()[n].gainExp(exp)	Increase experience by exp
262	Game_Actor	\$gameParty.members()[n]	finalExpRate()	\$gameParty.members()[n].finalExpRate()	Get experience gain rate
263	Game_Actor	\$gameParty.members()[n]	benchMembersExpRate()	\$gameParty.members()[n].benchMembersExpRate()	Get the experience gain rate for non-combat members
264	Game_Actor	\$gameParty.members()[n]	shouldDisplayLevelUp()	\$gameParty.members()[n].shouldDisplayLevelUp()	Checks whether to display the level-up message
265	Game_Actor	\$gameParty.members()[n]	changeLevel(level, show)	\$gameParty.members()[n].changeLevel(level, show)	Change the level to level, or display a message if show is true
266	Game_Actor	\$gameParty.members()[n]	learnSkill(id)	\$gameParty.members()[n].learnSkill(id)	Learn the skill of the specified skill ID
267	Game_Actor	\$gameParty.members()[n]	forgetSkill(id)	\$gameParty.members()[n].forgetSkill(id)	Forget the skill of the specified skill ID
268	Game_Actor	\$gameParty.members()[n]	isLearnedSkill(id)	\$gameParty.members()[n].isLearnedSkill(id)	Checks whether an actor has learned the skill of the specified skill ID (not including additional skills by trait)
269	Game_Actor	\$gameParty.members()[n]	hasSkill(id)	\$gameParty.members()[n].hasSkill(id)	Checks whether an actor has learned the skill of the specified skill id (including additional skills by trait)
270	Game_Actor	\$gameParty.members()[n]	changeClass(id, keep)	\$gameParty.members()[n].changeClass(id, keep)	Change to the class of the specified class id, keeping the experience if keep is true
271	Game_Actor	\$gameParty.members()[n]	setCharacterImage(file, index)	\$gameParty.members()[n].setCharacterImage(file, index)	Change the character image to a specified file and index
272	Game_Actor	\$gameParty.members()[n]	setFacelImage(file, index)	\$gameParty.members()[n].setFacelImage(file, index)	Change the face image to a specified file and index
273	Game_Actor	\$gameParty.members()[n]	setBattlerImage(file)	\$gameParty.members()[n].setBattlerImage(file)	Change the battler image to a specified file
274	Game_Actor	\$gameParty.members()[n]	lastSkill()	\$gameParty.members()[n].lastSkill()	Last skill used
275	Game_Actor	\$gameParty.members()[n]	lastMenuSkill()	\$gameParty.members()[n].lastMenuSkill()	The last menu skill used
276	Game_Actor	\$gameParty.members()[n]	lastBattleSkill()	\$gameParty.members()[n].lastBattleSkill()	The last combat skill used
277	Game_Enemy	\$gameParty.members()[n]	name()	\$gameParty.members()[n].name()	Gets enemy character names (with suffixes)
278	Game_Enemy	\$gameParty.members()[n]	enemyId()	\$gameParty.members()[n].enemyId()	Gets an enemy character ID
279	Game_Enemy	\$gameParty.members()[n]	enemy()	\$gameParty.members()[n].enemy()	Gets the enemy character object
280	Game_Enemy	\$gameParty.members()[n]	friendsUnit()	\$gameParty.members()[n].friendsUnit()	Gets a unit (party or enemy group)
281	Game_Enemy	\$gameParty.members()[n]	opponentsUnit()	\$gameParty.members()[n].opponentsUnit()	Gets an enemy unit (party or enemy group)
282	Game_Enemy	\$gameParty.members()[n]	screenX()	\$gameParty.members()[n].screenX()	Gets the display X coordinate
283	Game_Enemy	\$gameParty.members()[n]	screenY()	\$gameParty.members()[n].screenY()	Gets the display Y coordinate
284	Game_Enemy	\$gameParty.members()[n]	index()	\$gameParty.members()[n].index()	Gets the formation
285	Game_Enemy	\$gameParty.members()[n]	exp()	\$gameParty.members()[n].exp()	Gets experience gained
286	Game_Enemy	\$gameParty.members()[n]	gold()	\$gameParty.members()[n].gold()	Gets gold gained
287	Game_Enemy	\$gameParty.members()[n]	battlerName()	\$gameParty.members()[n].battlerName()	Get the battler file name
288	Game_Enemy	\$gameParty.members()[n]	battlerHue()	\$gameParty.members()[n].battlerHue()	Get the battler hue
289	Game_Enemy	\$gameParty.members()[n]	originalName()	\$gameParty.members()[n].originalName()	Get the enemy's name
290	Game_Unit	\$gameParty	inBattle()	\$gameParty.inBattle()	Checks if the party is in a battle or not.
291	Game_Unit	\$gameParty	members()	\$gameParty.members()	Gets an array of party members
292	Game_Unit	\$gameTroop	members()	\$gameTroop.members()	Gets an array of enemy character members
293	Game_Unit	\$gameParty	aliveMembers()	\$gameParty.aliveMembers()	Gets an array of party members who are alive
294	Game_Unit	\$gameParty	deadMembers()	\$gameParty.deadMembers()	Gets an array of party members who are dead
295	Game_Unit	\$gameParty	movableMembers()	\$gameParty.movableMembers()	Get an array of party members who can move
296	Game_Unit	\$gameParty	isAllDead()	\$gameParty.isAllDead()	Checks whether all members of the party are dead or not
297	Game_Party	\$gameParty	exists()	\$gameParty.exists()	Checks whether or not there is one actor in every position
298	Game_Party	\$gameParty	size()	\$gameParty.size()	Gets the number of members
299	Game_Party	\$gameParty	isEmpty()	\$gameParty.isEmpty()	Checks whether the party is empty
300	Game_Party	\$gameParty	allMembers()	\$gameParty.allMembers()	Gets an array of all members
301	Game_Party	\$gameParty	battleMembers()	\$gameParty.battleMembers()	Gets an array of battle participants
302	Game_Party	\$gameParty	maxBattleMembers()	\$gameParty.maxBattleMembers()	Gets the number of battle members participating
303	Game_Party	\$gameParty	leader()	\$gameParty.leader()	Gets the party leader
304	Game_Party	\$gameParty	reviveBattleMembers()	\$gameParty.reviveBattleMembers()	Revives dead party members (for a defeat event)
305	Game_Party	\$gameParty	items()	\$gameParty.items()	Gets an array of items in the party's possession
306	Game_Party	\$gameParty	weapons()	\$gameParty.weapons()	Gets an array of weapons in the party's possession
307	Game_Party	\$gameParty	armors()	\$gameParty.armors()	Gets an array of armor in the party's possession

No	Class Name	References to Objects	Property and method name	Script Call	Detailed explanation
308	Game_Party	\$gameParty	equipItems()	\$gameParty.equipItems()	Gets an array of equipment (weapons and armor) in the party's possession
309	Game_Party	\$gameParty	allItems()	\$gameParty.allItems()	Gets an array of all possessions (items + weapons + armor)
310	Game_Party	\$gameParty	name()	\$gameParty.name()	Gets the party name (leader's name + 'they')
311	Game_Party	\$gameParty	setupBattleTest()	\$gameParty.setupBattleTest()	Sets up members and items for combat testing
312	Game_Party	\$gameParty	setupBattleTestMembers()	\$gameParty.setupBattleTestMembers()	Sets up members for battle testing
313	Game_Party	\$gameParty	setupBattleTestItems()	\$gameParty.setupBattleTestItems()	Set up items for battle testing (get the maximum number of all items)
314	Game_Party	\$gameParty	highestLevel()	\$gameParty.highestLevel()	Gets the party's maximum level
315	Game_Party	\$gameParty	addActor(id)	\$gameParty.addActor(id)	Adds the specified actor ID to the party
316	Game_Party	\$gameParty	removeActor(id)	\$gameParty.removeActor(id)	Removes the specified actor ID from the party
317	Game_Party	\$gameParty	gold()	\$gameParty.gold()	Gets the party's gold
318	Game_Party	\$gameParty	gainGold(value)	\$gameParty.gainGold(value)	Increases the party's gold
319	Game_Party	\$gameParty	loseGold(value)	\$gameParty.loseGold(value)	Decreases the party's gold
320	Game_Party	\$gameParty	maxGold()	\$gameParty.maxGold()	Gets the maximum amount of gold
321	Game_Party	\$gameParty	steps()	\$gameParty.steps()	Gets the step count
322	Game_Party	\$gameParty	increaseSteps()	\$gameParty.increaseSteps()	Increases the step count
323	Game_Party	\$gameParty	numItems(item)	\$gameParty.numItems(item)	Gets the number of specified items in the party's possession
324	Game_Party	\$gameParty	maxItems(item)	\$gameParty.maxItems(item)	Gets the maximum number of possession of the specified item
325	Game_Party	\$gameParty	hasMaxItems()	\$gameParty.hasMaxItems()	Checks whether the party has the maximum possible number of items
326	Game_Party	\$gameParty	hasItem(item, includeEquip)	\$gameParty.hasItem(item, includeEquip)	Checks whether the party has the specified item or not / If includeEquip is true, then the equipment is included
327	Game_Party	\$gameParty	isAnyMemberEquipped(item)	\$gameParty.isAnyMemberEquipped(item)	Checks whether one of the members is equipped with the specified item or not
328	Game_Party	\$gameParty	gainItem(item, amount, includeEquip)	\$gameParty.gainItem(item, amount, includeEquip)	Retrieves the specified number of items for amount / If includeEquip is true, it is also reduced from equipment (if amount is negative)
329	Game_Party	\$gameParty	loseItem(item, amount, includeEquip)	\$gameParty.loseItem(item, amount, includeEquip)	Reduces the specified item by the number of amount
330	Game_Party	\$gameParty	consumeItem(item)	\$gameParty.consumeItem(item)	Consumes the specified item
331	Game_Party	\$gameParty	canUse(item)	\$gameParty.canUse(item)	Checks whether the specified item can be used or not
332	Game_Party	\$gameParty	canInput()	\$gameParty.canInput()	Checks whether command is input enabled or not
333	Game_Party	\$gameParty	menuActor()	\$gameParty.menuActor()	Retrieves the selected actor from the main menu screen
334	Game_Party	\$gameParty	targetActor()	\$gameParty.targetActor()	Checks which actor is selected in the Actor Selection Window
335	Game_Party	\$gameParty	lastItem()	\$gameParty.lastItem()	Gets the last item used
336	Game_Party	\$gameParty	swapOrder(index1, index2)	\$gameParty.swapOrder(index1, index2)	Swaps two party members by specifying the index
337	Game_Party	\$gameParty	hasEncounterHalf()	\$gameParty.hasEncounterHalf()	Checks whether or not the encounter rate is halved
338	Game_Party	\$gameParty	hasEncounterNone()	\$gameParty.hasEncounterNone()	Checks if encounters are disabled or not.
339	Game_Party	\$gameParty	hasCancelSurprise()	\$gameParty.hasCancelSurprise()	Checks if surprise encounter is cancelled
340	Game_Party	\$gameParty	hasRaisePreemptive()	\$gameParty.hasRaisePreemptive()	Checks for increased chance of preemptive strike
341	Game_Party	\$gameParty	hasGoldDouble()	\$gameParty.hasGoldDouble()	Checks if double gold is enabled
342	Game_Party	\$gameParty	hasDropItemDouble()	\$gameParty.hasDropItemDouble()	Checks if double item drop rate is enabled
343	Game_Party	\$gameParty	ratePreemptive()	\$gameParty.ratePreemptive()	Checks the rate of preemptive strikes
344	Game_Party	\$gameParty	rateSurprise()	\$gameParty.rateSurprise()	Checks the rate of surprise attacks
345	Game_Troop	\$gameTroop	isEventRunning()	\$gameTroop.isEventRunning()	Checks whether a battle event is running or not
346	Game_Troop	\$gameTroop	turnCount()	\$gameTroop.turnCount()	Gets the number of turns
347	Game_Troop	\$gameTroop	troop()	\$gameTroop.troop()	Gets a database object from an enemy group
348	Game_Troop	\$gameTroop	enemyNames()	\$gameTroop.enemyNames()	Gets an array of enemy names
349	Game_Troop	\$gameTroop	increaseTurn()	\$gameTroop.increaseTurn()	Add to the number of turns
350	Game_Troop	\$gameTroop	expTotal()	\$gameTroop.expTotal()	Gets the total experience gained
351	Game_Troop	\$gameTroop	goldTotal()	\$gameTroop.goldTotal()	Gets the total amount of gold earned
352	Game_Map	\$gameMap	isEventRunning()	\$gameMap.isEventRunning()	Checks whether map events (excluding parallel processing) are being executed or not
353	Game_Map	\$gameMap	tileWidth()	\$gameMap.tileWidth()	Gets the number of pixels per tile width
354	Game_Map	\$gameMap	tileHeight()	\$gameMap.tileHeight()	Gets the number of pixels per tile height
355	Game_Map	\$gameMap	mapId()	\$gameMap.mapId()	Gets the current map ID
356	Game_Map	\$gameMap	tilesetId()	\$gameMap.tilesetId()	Gets a tile set ID
357	Game_Map	\$gameMap	displayX()	\$gameMap.displayX()	Gets the X coordinates (pixels) on the screen
358	Game_Map	\$gameMap	displayY()	\$gameMap.displayY()	Gets the Y coordinate (pixels) on the screen
359	Game_Map	\$gameMap	parallaxName()	\$gameMap.parallaxName()	Gets the parallax file name
360	Game_Map	\$gameMap	battleback1Name()	\$gameMap.battleback1Name()	Gets the file name of battle background 1
361	Game_Map	\$gameMap	battleback2Name()	\$gameMap.battleback2Name()	Gets the file name of battle background 2
362	Game_Map	\$gameMap	isNameDisplayEnabled()	\$gameMap.isNameDisplayEnabled()	Checks whether map name display is enabled or not
363	Game_Map	\$gameMap	disableNameDisplay()	\$gameMap.disableNameDisplay()	Disables map name display
364	Game_Map	\$gameMap	enableNameDisplay()	\$gameMap.enableNameDisplay()	Enables map name display
365	Game_Map	\$gameMap	vehicles()	\$gameMap.vehicles()	Gets an array of vehicles
366	Game_Map	\$gameMap	boat()	\$gameMap.boat()	Summons the boat vehicle
367	Game_Map	\$gameMap	ship()	\$gameMap.ship()	Summons the ship vehicle
368	Game_Map	\$gameMap	airship()	\$gameMap.airship()	Summons the airship vehicle

No	Class Name	References to Objects	Property and method name	Script Call	Detailed explanation
369	Game_Map	\$gameMap	events()	\$gameMap.events()	Gets an array of map events
370	Game_Map	\$gameMap	event(id)	\$gameMap.event(id)	Retrieves an event with a specified event ID
371	Game_Map	\$gameMap	eraseEvent(id)	\$gameMap.eraseEvent(id)	Clears the event of the specified event ID
372	Game_Map	\$gameMap	autorunCommonEvents()	\$gameMap.autorunCommonEvents()	Gets an array of autorun events
373	Game_Map	\$gameMap	parallelCommonEvents()	\$gameMap.parallelCommonEvents()	Gets an array of parallel process events
374	Game_Map	\$gameMap	parallaxOx()	\$gameMap.parallaxOx()	Gets the X coordinate of the parallax position
375	Game_Map	\$gameMap	parallaxOy()	\$gameMap.parallaxOy()	Gets the Y coordinate of the parallax position
376	Game_Map	\$gameMap	tileset()	\$gameMap.tileset()	Retrieves a tile set database object
377	Game_Map	\$gameMap	width()	\$gameMap.width()	Gets the width of the map (number of tiles)
378	Game_Map	\$gameMap	height()	\$gameMap.height()	Gets the height of the map (number of tiles)
379	Game_Map	\$gameMap	isLoopHorizontal()	\$gameMap.isLoopHorizontal()	Checks if the parallax loops horizontally
380	Game_Map	\$gameMap	isLoopVertical()	\$gameMap.isLoopVertical()	Checks if the parallax loops vertically
381	Game_Map	\$gameMap	isDashDisabled()	\$gameMap.isDashDisabled()	Checks if dash is disabled
382	Game_Map	\$gameMap	encounterList()	\$gameMap.encounterList()	Gets the list of encounters
383	Game_Map	\$gameMap	encounterStep()	\$gameMap.encounterStep()	Gets the encounter steps
384	Game_Map	\$gameMap	isOverworld()	\$gameMap.isOverworld()	Checks whether the tileset is set to Overworld or not
385	Game_Map	\$gameMap	screenTileX()	\$gameMap.screenTileX()	Gets the number of horizontal tiles displayed on a screen
386	Game_Map	\$gameMap	screenTileY()	\$gameMap.screenTileY()	Gets the number of vertical tiles displayed on a screen
387	Game_Map	\$gameMap	distance(x1, y1, x2, y2)	\$gameMap.distance(x1, y1, x2, y2)	Calculates the distance between the coordinates (taking into account the loops in the map)
388	Game_Map	\$gameMap	eventsXy(x, y)	\$gameMap.eventsXy(x, y)	Retrieves an array of events that exist at a given coordinate
389	Game_Map	\$gameMap	eventsXyNt()	\$gameMap.eventsXyNt()	Obtains an array of events that exist at the specified coordinates (excluding slip events)
390	Game_Map	\$gameMap	tileEventsXy()	\$gameMap.tileEventsXy()	Gets an array of tile events at the specified coordinates
391	Game_Map	\$gameMap	eventIdXy()	\$gameMap.eventIdXy()	Gets the ID of an event that exists in the specified coordinates
392	Game_Map	\$gameMap	isValid(x, y)	\$gameMap.isValid(x, y)	Checks whether the coordinates are within the map's range
393	Game_Map	\$gameMap	tileId(x, y, z)	\$gameMap.tileId(x, y, z)	Gets the tile ID of the specified coordinates.
394	Game_Map	\$gameMap	layeredTiles(x, y)	\$gameMap.layeredTiles(x, y)	Gets an array of tile IDs for all layers at the specified coordinates
395	Game_Map	\$gameMap	allTiles(x, y)	\$gameMap.allTiles(x, y)	Gets an array of all layers at the specified coordinates, including tile events
396	Game_Map	\$gameMap	isPassable(x, y, d)	\$gameMap.isPassable(x, y, d)	Checks whether it is possible to move in the specified direction from the specified coordinates
397	Game_Map	\$gameMap	isBoatPassable(x, y, d)	\$gameMap.isBoatPassable(x, y, d)	Checks whether the boat vehicle can move in a specified direction from a specified coordinate
398	Game_Map	\$gameMap	isShipPassable(x, y, d)	\$gameMap.isShipPassable(x, y, d)	Checks whether the ship vehicle can move in a specified direction from a specified coordinate
399	Game_Map	\$gameMap	isAirshipLandOk(x, y)	\$gameMap.isAirshipLandOk(x, y)	Checks whether the airship vehicle can land at the specified coordinates
400	Game_Map	\$gameMap	isLadder(x, y)	\$gameMap.isLadder(x, y)	Checks whether the specified coordinates are ladders or not
401	Game_Map	\$gameMap	isBush(x, y)	\$gameMap.isBush(x, y)	Checks whether the specified coordinates are bushes or not
402	Game_Map	\$gameMap	isCounter(x, y)	\$gameMap.isCounter(x, y)	Checks whether the specified coordinates are counters or not
403	Game_Map	\$gameMap	isDamageFloor(x, y)	\$gameMap.isDamageFloor(x, y)	Checks whether the specified coordinates are damage floor or not
404	Game_Map	\$gameMap	terrainTag(x, y)	\$gameMap.terrainTag(x, y)	Gets a terrain tag for the given coordinate
405	Game_Map	\$gameMap	regionId(x, y)	\$gameMap.regionId(x, y)	Gets a region for the given coordinate
406	Game_Map	\$gameMap	changeTileset(id)	\$gameMap.changeTileset(id)	Changes the tileset to the specified ID
407	Game_Map	\$gameMap	changeBattleback(name1, name2)	\$gameMap.changeBattleback(name1, name2)	Changes the battle background to the specified files
408	Game_Map	\$gameMap	changeParallax(name, loopX, loopY, sx, sy)	\$gameMap.changeParallax(name, loopX, loopY, sx, sy)	Changes the parallax to the specified data
409	Game_Map	\$gameMap	unlockEvent(id)	\$gameMap.unlockEvent(id)	Unlocks the event for the specified ID
410	Game_CharacterBase	\$gamePlayer	x	\$gamePlayer.x	Gets the player's X coordinates
411	Game_CharacterBase	\$gameMap.boat()	x	\$gameMap.boat().x	Gets the X-coordinates of the boat vehicle
412	Game_CharacterBase	\$gameMap.event(id)	x	\$gameMap.event(id).x	Gets the X-coordinate of the ID event
413	Game_CharacterBase	\$gamePlayer.followers().follower(i)	x	\$gamePlayer.followers().follower(i).x	Gets the X-coordinate of the i-th follower
414	Game_CharacterBase	\$gamePlayer	y	\$gamePlayer.y	Gets the player's Y coordinate
415	Game_CharacterBase	\$gameMap.boat()	y	\$gameMap.boat().y	Gets the Y-coordinates of the boat vehicle
416	Game_CharacterBase	\$gameMap.event(id)	y	\$gameMap.event(id).y	Gets the Y-coordinate of the ID event.
417	Game_CharacterBase	\$gamePlayer.followers().follower(i)	y	\$gamePlayer.followers().follower(i).y	Gets the Y coordinate of the i-th follower.
418	Game_CharacterBase	\$gameMap.event(id)	pos(x, y)	\$gameMap.event(id).pos(x, y)	Checks whether or not the character's coordinates match the x and y coordinates specified
419	Game_CharacterBase	\$gameMap.event(id)	posNt(x, y)	\$gameMap.event(id).posNt(x, y)	Checks whether or not the character's coordinates match the specified x, y (Don't match in case of a skipping setting).
420	Game_CharacterBase	\$gameMap.event(id)	moveSpeed()	\$gameMap.event(id).moveSpeed()	Gets the event's movement speed
421	Game_CharacterBase	\$gameMap.event(id)	setMoveSpeed(value)	\$gameMap.event(id).setMoveSpeed(value)	Sets the event's movement speed
422	Game_CharacterBase	\$gameMap.event(id)	moveFrequency()	\$gameMap.event(id).moveFrequency()	Gets the event's movement frequency
423	Game_CharacterBase	\$gameMap.event(id)	setMoveFrequency(value)	\$gameMap.event(id).setMoveFrequency(value)	Sets the event's the movement frequency
424	Game_CharacterBase	\$gameMap.event(id)	opacity()	\$gameMap.event(id).opacity()	Gets the event's the opacity
425	Game_CharacterBase	\$gameMap.event(id)	setOpacity(value)	\$gameMap.event(id).setOpacity(value)	Sets the event's opacity
426	Game_CharacterBase	\$gameMap.event(id)	blendMode()	\$gameMap.event(id).blendMode()	Gets the event's blend mode
427	Game_CharacterBase	\$gameMap.event(id)	setBlendMode(value)	\$gameMap.event(id).setBlendMode(value)	Sets the event's blend mode
428	Game_CharacterBase	\$gameMap.event(id)	isNormalPriority()	\$gameMap.event(id).isNormalPriority()	Checks whether the priority is the same as a 'normal character'
429	Game_CharacterBase	\$gameMap.event(id)	setPriorityType()	\$gameMap.event(id).setPriorityType()	Sets the event's priority
430	Game_CharacterBase	\$gameMap.event(id)	isMoving()	\$gameMap.event(id).isMoving()	Checks whether an event is moving or not.

No	Class Name	References to Objects	Property and method name	Script Call	Detailed explanation
431	Game_CharacterBase	\$gameMap.event(id)	isJumping()	\$gameMap.event(id).isJumping()	Checks whether an event is jumping or not
432	Game_CharacterBase	\$gameMap.event(id)	jumpHeight()	\$gameMap.event(id).jumpHeight()	Gets an event's jump altitude
433	Game_CharacterBase	\$gameMap.event(id)	isStopping()	\$gameMap.event(id).isStopping()	Checks if an event is moving or jumping
434	Game_CharacterBase	\$gameMap.event(id)	resetStopCount()	\$gameMap.event(id).resetStopCount()	Resets the step count
435	Game_CharacterBase	\$gameMap.event(id)	realMoveSpeed()	\$gameMap.event(id).realMoveSpeed()	Gets the actual movement speed (taking into account whether an event is dashing or not)
436	Game_CharacterBase	\$gameMap.event(id)	isDashing()	\$gameMap.event(id).isDashing()	Checks whether the character is dashing
437	Game_CharacterBase	\$gameMap.event(id)	isDebugThrough()	\$gameMap.event(id).isDebugThrough()	Checks whether or not the debugging mode wall breaker is effective
438	Game_CharacterBase	\$gameMap.event(id)	straighten()	\$gameMap.event(id).straighten()	Resets the footsteps animation
439	Game_CharacterBase	\$gameMap.event(id)	canPass(x, y, d)	\$gameMap.event(id).canPass(x, y, d)	Checks whether it is possible to move in the specified direction from the specified coordinates
440	Game_CharacterBase	\$gameMap.event(id)	copyPosition(character)	\$gameMap.event(id).copyPosition(character)	Copies the position of the specified character.
441	Game_CharacterBase	\$gameMap.event(id)	locate(x, y)	\$gameMap.event(id).locate(x, y)	Moves the character to the specified coordinates.
442	Game_CharacterBase	\$gameMap.event(id)	direction()	\$gameMap.event(id).direction()	Gets the direction an event is facing
443	Game_CharacterBase	\$gameMap.event(id)	setDirection(value)	\$gameMap.event(id).setDirection(value)	Sets the direction an event is facing
444	Game_CharacterBase	\$gameMap.event(id)	isTile()	\$gameMap.event(id).isTile()	Checks whether the graphics are tiled or not
445	Game_CharacterBase	\$gameMap.event(id)	screenX()	\$gameMap.event(id).screenX()	Gets the X coordinate on the screen.
446	Game_CharacterBase	\$gameMap.event(id)	screenY()	\$gameMap.event(id).screenY()	Gets the Y coordinate on the screen.
447	Game_CharacterBase	\$gameMap.event(id)	screenZ()	\$gameMap.event(id).screenZ()	Gets the Z coordinate
448	Game_CharacterBase	\$gameMap.event(id)	isNearTheScreen()	\$gameMap.event(id).isNearTheScreen()	Checks whether an event is near the screen (used to determine autonomous movement)
449	Game_CharacterBase	\$gameMap.event(id)	maxPattern()	\$gameMap.event(id).maxPattern()	Gets the number of footstep animation patterns.
450	Game_CharacterBase	\$gameMap.event(id)	pattern()	\$gameMap.event(id).pattern()	Gets the animation pattern
451	Game_CharacterBase	\$gameMap.event(id)	setPattern(value)	\$gameMap.event(id).setPattern(value)	Sets the animation pattern
452	Game_CharacterBase	\$gameMap.event(id)	isOriginalPattern()	\$gameMap.event(id).isOriginalPattern()	Checks whether the current pattern is original or not
453	Game_CharacterBase	\$gameMap.event(id)	resetPattern()	\$gameMap.event(id).resetPattern()	Resets the animation pattern
454	Game_CharacterBase	\$gameMap.event(id)	isOnLadder()	\$gameMap.event(id).isOnLadder()	Checks whether or not the event is on a ladder.
455	Game_CharacterBase	\$gameMap.event(id)	isOnBush()	\$gameMap.event(id).isOnBush()	Checks whether or not the event is in a bush
456	Game_CharacterBase	\$gameMap.event(id)	terrainTag()	\$gameMap.event(id).terrainTag()	Gets a terrain tag
457	Game_CharacterBase	\$gameMap.event(id)	regionId()	\$gameMap.event(id).regionId()	Gets a region
458	Game_CharacterBase	\$gameMap.event(id)	tileId()	\$gameMap.event(id).tileId()	Gets a tile ID for a tile event
459	Game_CharacterBase	\$gameMap.event(id)	characterName()	\$gameMap.event(id).characterName()	Gets an event's character graphic file name.
460	Game_CharacterBase	\$gameMap.event(id)	characterIndex()	\$gameMap.event(id).characterIndex()	Gets an event's character graphic index
461	Game_CharacterBase	\$gameMap.event(id)	setImage(name, index)	\$gameMap.event(id).setImage(name, index)	Sets an event's character graphic file name and index
462	Game_CharacterBase	\$gameMap.event(id)	setTileImage(id)	\$gameMap.event(id).setTileImage(id)	Sets an event's tile ID.
463	Game_CharacterBase	\$gameMap.event(id)	moveStraight(d)	\$gameMap.event(id).moveStraight(d)	Moves an event to the specified coordinates in straight lines
464	Game_CharacterBase	\$gameMap.event(id)	moveDiagonally(h, v)	\$gameMap.event(id).moveDiagonally(h, v)	Moves an event to the specified coordinates in straight lines and diagonal lines
465	Game_CharacterBase	\$gameMap.event(id)	jump()	\$gameMap.event(id).jump()	Makes an event jump
466	Game_CharacterBase	\$gameMap.event(id)	hasWalkAnime()	\$gameMap.event(id).hasWalkAnime()	Checks whether an event has walking animations set or not
467	Game_CharacterBase	\$gameMap.event(id)	setWalkAnime(walkAnime)	\$gameMap.event(id).setWalkAnime(walkAnime)	Sets an event to have walking animations (true/false)
468	Game_CharacterBase	\$gameMap.event(id)	hasStepAnime()	\$gameMap.event(id).hasStepAnime()	Checks whether an event has stepping animations set or not
469	Game_CharacterBase	\$gameMap.event(id)	setStepAnime(stepAnime)	\$gameMap.event(id).setStepAnime(stepAnime)	Sets an event to have stepping animations (true/false)
470	Game_CharacterBase	\$gameMap.event(id)	isDirectionFixed()	\$gameMap.event(id).isDirectionFixed()	Checks whether an event has direction fix set or not
471	Game_CharacterBase	\$gameMap.event(id)	setDirectionFix(directionFix)	\$gameMap.event(id).setDirectionFix(directionFix)	Sets an event to have direction fix (true/false)
472	Game_CharacterBase	\$gameMap.event(id)	isThrough()	\$gameMap.event(id).isThrough()	Checks whether an event is set to through or not
473	Game_CharacterBase	\$gameMap.event(id)	setThrough(through)	\$gameMap.event(id).setThrough(through)	Sets an event to through (true/false)
474	Game_CharacterBase	\$gameMap.event(id)	isTransparent()	\$gameMap.event(id).isTransparent()	Checks whether an event is transparent or not
475	Game_CharacterBase	\$gameMap.event(id)	setTransparent(transparent)	\$gameMap.event(id).setTransparent(transparent)	Sets an event to transparent (true/false)
476	Game_CharacterBase	\$gameMap.event(id)	isAnimationPlaying()	\$gameMap.event(id).isAnimationPlaying()	Checks whether an animation is playing
477	Game_CharacterBase	\$gameMap.event(id)	isBalloonPlaying()	\$gameMap.event(id).isBalloonPlaying()	Checks whether a balloon icon is playing
478	Game_CharacterBase	\$gameMap.event(id)	endAnimation()	\$gameMap.event(id).endAnimation()	Stops the animation
479	Game_CharacterBase	\$gameMap.event(id)	endBalloon()	\$gameMap.event(id).endBalloon()	Stop the balloon icon
480	Game_Character	\$gameMap.event(id)	isMoveRouteForcing()	\$gameMap.event(id).isMoveRouteForcing()	Checks whether or not a travel route is being forced.
481	Game_Character	\$gameMap.event(id)	moveRandom()	\$gameMap.event(id).moveRandom()	Sets an event to move at random
482	Game_Character	\$gameMap.event(id)	moveTowardCharacter(character)	\$gameMap.event(id).moveTowardCharacter(character)	Sets an event to move towards the character
483	Game_Character	\$gameMap.event(id)	moveAwayFromCharacter(character)	\$gameMap.event(id).moveAwayFromCharacter(character)	Sets an event to move away from the character
484	Game_Character	\$gameMap.event(id)	turnTowardCharacter(character)	\$gameMap.event(id).turnTowardCharacter(character)	Sets an event to turn towards the character
485	Game_Character	\$gameMap.event(id)	turnAwayFromCharacter(character)	\$gameMap.event(id).turnAwayFromCharacter(character)	Sets an event to turn away from the character
486	Game_Character	\$gameMap.event(id)	turnTowardPlayer()	\$gameMap.event(id).turnTowardPlayer()	Sets an event to turn towards the player
487	Game_Character	\$gameMap.event(id)	turnAwayFromPlayer()	\$gameMap.event(id).turnAwayFromPlayer()	Sets an even to turn away from the player
488	Game_Character	\$gameMap.event(id)	moveTowardPlayer()	\$gameMap.event(id).moveTowardPlayer()	Sets an event to move towards the player
489	Game_Character	\$gameMap.event(id)	moveAwayFromPlayer()	\$gameMap.event(id).moveAwayFromPlayer()	Sets an event to move away from the player
490	Game_Character	\$gameMap.event(id)	moveForward()	\$gameMap.event(id).moveForward()	Sets an event to take one step forward
491	Game_Character	\$gameMap.event(id)	moveBackward()	\$gameMap.event(id).moveBackward()	Sets an event to take one step backward
492	Game_Character	\$gameMap.event(id)	turnRight90()	\$gameMap.event(id).turnRight90()	Sets an event to rotate 90 degrees to the right.
493	Game_Character	\$gameMap.event(id)	turnLeft90()	\$gameMap.event(id).turnLeft90()	Sets an event to rotate 90 degrees to the left.

No	Class Name	References to Objects	Property and method name	Script Call	Detailed explanation
494	Game_Character	\$gameMap.event(id)	turn180()	\$gameMap.event(id).turn180()	Sets an event to rotate 180 degrees.
495	Game_Character	\$gameMap.event(id)	turnRightOrLeft90()	\$gameMap.event(id).turnRightOrLeft90()	Sets an event to rotate 90 degrees to the right or left.
496	Game_Character	\$gameMap.event(id)	turnRandom()	\$gameMap.event(id).turnRandom()	Sets an event to randomly change direction
497	Game_Character	\$gameMap.event(id)	swap(character)	\$gameMap.event(id).swap(character)	Sets an event to swap positions with a specified character.
498	Game_Character	\$gameMap.event(id)	findDirectionTo(x, y)	\$gameMap.event(id).findDirectionTo(x, y)	Obtains the direction of travel at a specified location
499	Game_Character	\$gameMap.event(id)	searchLimit()	\$gameMap.event(id).searchLimit()	Obtains route search limits
500	Game_Player	\$gamePlayer	followers()	\$gamePlayer.followers()	Gets a list of followers
501	Game_Player	\$gamePlayer	isInBoat()	\$gamePlayer.isInBoat()	Checks whether the player is in the boat vehicle or not
502	Game_Player	\$gamePlayer	isInShip()	\$gamePlayer.isInShip()	Checks whether the player is in the ship vehicle or not
503	Game_Player	\$gamePlayer	isInAirship()	\$gamePlayer.isInAirship()	Checks whether the player is in the airship vehicle or not
504	Game_Player	\$gamePlayer	isInVehicle()	\$gamePlayer.isInVehicle()	Checks whether the player is in a vehicle or not
505	Game_Player	\$gamePlayer	isOnDamageFloor()	\$gamePlayer.isOnDamageFloor()	Checks whether the player is on damage floor or not
506	Game_Player	\$gamePlayer	showFollowers()	\$gamePlayer.showFollowers()	Views the party's followers
507	Game_Player	\$gamePlayer	hideFollowers()	\$gamePlayer.hideFollowers()	Clears the party's followers
508	Game_Player	\$gamePlayer	gatherFollowers()	\$gamePlayer.gatherFollowers()	Gathers the party's followers.
509	Game_Follower	\$gamePlayer.followers().follower(i)	actor()	\$gamePlayer.followers().follower(i).actor()	Gets the actor object
510	Game_Follower	\$gamePlayer.followers().follower(i)	isVisible()	\$gamePlayer.followers().follower(i).isVisible()	Gets the display status
511	Game_Follower	\$gamePlayer.followers().follower(i)	chaseCharacter(character)	\$gamePlayer.followers().follower(i).chaseCharacter(character)	Sets a follower to follow the specified character.
512	Game_Vehicle	\$gameMap.boat()	isBoat()	\$gameMap.boat().isBoat()	Checks whether a vehicle is the boat
513	Game_Vehicle	\$gameMap.boat()	isShip()	\$gameMap.boat().isShip()	Checks whether a vehicle is the ship
514	Game_Vehicle	\$gameMap.boat()	isAirship()	\$gameMap.boat().isAirship()	Checks whether a vehicle is the airship
515	Game_Vehicle	\$gameMap.boat()	vehicle()	\$gameMap.boat().vehicle()	Gets a vehicle's database object
516	Game_Vehicle	\$gameMap.boat()	shadowX()	\$gameMap.boat().shadowX()	Gets the X coordinates of a vehicle's shadow image.
517	Game_Vehicle	\$gameMap.boat()	shadowY()	\$gameMap.boat().shadowY()	Gets the Y coordinate of a vehicle's shadow image.
518	Game_Vehicle	\$gameMap.boat()	shadowOpacity()	\$gameMap.boat().shadowOpacity()	Gets the opacity of a vehicle's shadow image.
519	Game_Vehicle	\$gameMap.boat()	maxAltitude()	\$gameMap.boat().maxAltitude()	Gets a vehicle's maximum altitude.
520	Game_Vehicle	\$gameMap.boat()	isLandOk(x, y, d)	\$gameMap.boat().isLandOk(x, y, d)	Checks whether it is possible to descend from the specified coordinates to the specified direction
521	Game_Event	\$gameMap.event(id)	eventId()	\$gameMap.event(id).eventId()	Gets an event ID
522	Game_Event	\$gameMap.event(id)	event()	\$gameMap.event(id).event()	Gets an event's database object
523	Game_Event	\$gameMap.event(id)	page()	\$gameMap.event(id).page()	Gets an event's current page