



MATERIAL SAFETY DATA SHEET

Sikadur Injection Gel FS / Anchor Fix 3 - Part A

HMIS

HEALTH	2
FLAMMABILITY	1
REACTIVITY	0
PERSONAL PROTECTION	C

1. Product And Company Identification

Supplier

Sika Corporation
201 Polito Ave
Lyndhurst, NJ 07071

Company Contact: EHS Department
Telephone Number: 201-933-8800
FAX Number: 201-933-9379
Web Site: www.sikausa.com

Manufacturer

Sika Corporation
201 Polito Ave
Lyndhurst, NJ 07071

Company Contact: EHS Department
Telephone Number: 201-933-8800
FAX Number: 201-933-9379
Web Site: www.sikausa.com

Supplier Emergency Contacts & Phone Number

CHEMTREC: 800-424-9300
INTERNATIONAL: 703-527-3887

Manufacturer Emergency Contacts & Phone Number

CHEMTREC: 800-424-9300
INTERNATIONAL: 703-527-3887

Issue Date: 04/19/2006

Product Name: Sikadur Injection Gel FS / Anchor Fix 3 - Part A

CAS Number: Not Established

Chemical Family: Epoxy Compound

Chemical Formula: RMF-2945

MSDS Number: 3880

Product Code: 0786130

2. Composition/Information On Ingredients

Ingredient Name	CAS Number	Percent Of Total Weight
BENZYL ALCOHOL	100-51-6	
CALCIUM CARBONATE	471-34-1	
PROPRIETARY MODIFIED EPOXY RESIN	Mixture	
TALC	14807-96-6	

Note: Exposure to Calcium Carbonate and Talc is applicable only if cured with Part "B" and sanded.

3. Hazards Identification

Eye Hazards

May cause eye irritation.

Skin Hazards

May cause skin irritation. May cause skin sensitization.

MATERIAL SAFETY DATA SHEET

Sikadur Injection Gel FS / Anchor Fix 3 - Part A

3. Hazards Identification - Continued

Ingestion Hazards

May be harmful if swallowed.

Inhalation Hazards

May cause nose, throat, and lung irritation.

4. First Aid Measures

Eye

In case of contact, immediately flush eyes with plenty of water. Get medical attention immediately if irritation develops and persists.

Skin

In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately if irritation (redness, rash, blistering) develops and persists.

Ingestion

If swallowed, do not induce vomiting unless directed to do so by medical personnel.

Inhalation

Remove to fresh air. If not breathing, give artificial respiration.

5. Fire Fighting Measures

Flash Point: >200 °F

Autoignition Point: N/AV °F

Fire And Explosion Hazards

None Known

Extinguishing Media

In case of fire, use water spray (fog) foam, dry chemical, or CO2.

Fire Fighting Instructions

Firefighters should wear self-contained breathing apparatus and full protective gear.

6. Accidental Release Measures

Avoid release to the environment. Use appropriate personal protective equipment (PPE). Contain spill and collect with absorbent material and transfer into suitable containers. Ventilate enclosed area.

7. Handling And Storage

Handling And Storage Precautions

Keep containers tightly closed. Keep out of reach of children.

Work/Hygienic Practices

Wash thoroughly with soap and water after handling.

8. Exposure Controls/Personal Protection

Engineering Controls

Use with adequate general and local exhaust ventilation.

Eye/Face Protection

Safety glasses with side shields or goggles.

Skin Protection

Chemical-resistant gloves. Lab coat or other work clothing. Launder before reuse.

M A T E R I A L S A F E T Y D A T A S H E E T

Sikadur Injection Gel FS / Anchor Fix 3 - Part A

8. Exposure Controls/Personal Protection - Continued

Respiratory Protection

A respirator protection program that meets 29 CFR 1910.134 requirement must be followed whenever workplace conditions warrant a respirator's use. In areas where the Permissible Exposure Limits are exceeded, use a properly fitted NIOSH-approved respirator.

Other/General Protection

Wash thoroughly after handling.

Ingredient(s) - Exposure Limits

CALCIUM CARBONATE

ACGIH TLV-TWA 10 mg/m³

OSHA PEL-TWA 15 mg/m³

OSHA PEL-TWA 5 mg/m³

TALC

ACGIH TLV-TWA 2 mg/m³

OSHA PEL-TWA 20 mppcf

9. Physical And Chemical Properties

Appearance

White Paste

Odor

Mild Aromatic Odor

Chemical Type: Mixture

Physical State: Solid

Melting Point: N/AV °F

Boiling Point: N/AV °F

Specific Gravity: 1.54

Percent Volatiles: N/AV

Percent VOCs: 2.17 (A+B)

Packing Density: 12.88 pounds/gallon

Vapor Pressure: N/AV

Vapor Density: > AIR

Solubility: N/AV

Evaporation Rate: Slower than ether

VOC Content (A+B): 33 grams/liter

10. Stability And Reactivity

Stability: Stable

Hazardous Polymerization: Will Not Occur

Conditions To Avoid (Stability)

None Known

Incompatible Materials

Strong oxidizing materials, acids, and bases.

Hazardous Decomposition Products

CO, CO₂, Aldehydes and other Organics

Conditions To Avoid (Polymerization)

Fired/Exotherm when curing in mass.

M A T E R I A L S A F E T Y D A T A S H E E T

Sikadur Injection Gel FS / Anchor Fix 3 - Part A

11. Toxicological Information
<u>Ingredient(s) - Carginogenicity</u> TALC Listed In The IARC Monographs
12. Ecological Information
No Data Available...
13. Disposal Considerations
Dispose in accordance with applicable federal, state and local government regulations.
14. Transport Information
<u>Proper Shipping Name</u> Not Regulated - USDOT.
15. Regulatory Information
<u>U.S. Regulatory Information</u> All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory. <u>SARA Hazard Classes</u> Acute Health Hazard Chronic Health Hazard <u>SARA Section 313 Notification</u> This product does not contain any ingredients regulated under Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 or 40 CFR 372. <u>State Regulations</u> This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm (Proposition 65). <u>Ingredient(s) - State Regulations</u> BENZYL ALCOHOL New Jersey - Workplace Hazard Pennsylvania - Workplace Hazard Massachusetts - Hazardous Substance CALCIUM CARBONATE Pennsylvania - Workplace Hazard TALC New Jersey - Workplace Hazard Pennsylvania - Workplace Hazard Massachusetts - Hazardous Substance
16. Other Information
<u>HMIS Rating</u> Health: 2 Fire: 1 Reactivity: 0 PPE: C

M A T E R I A L S A F E T Y D A T A S H E E T

Sikadur Injection Gel FS / Anchor Fix 3 - Part A

16. Other Information - Continued

Revision/Preparer Information

MSDS Preparer: EHS Department

This MSDS Supersedes A Previous MSDS Dated: 04/14/2005

Disclaimer

The information contained in this Material Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Technical Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this MSDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikacorp.com or 201-933-8800.

SIKA CORPORATION

Printed Using MSDS Generator™ 2000