



MATERIAL SAFETY DATA SHEET

Sikadur Injection Gel / Anchor Fix 4 - Part B

HMIS

HEALTH	3
FLAMMABILITY	1
REACTIVITY	0
PERSONAL PROTECTION	C

1. Product And Company Identification

Supplier

Sika Corporation
201 Polito Ave
Lyndhurst, NJ 07071

Company Contact: EHS Department
Telephone Number: 201-933-8800
FAX Number: 201-933-9379
Web Site: www.sikausa.com

Manufacturer

Sika Corporation
201 Polito Ave
Lyndhurst, NJ 07071

Company Contact: EHS Department
Telephone Number: 201-933-8800
FAX Number: 201-933-9379
Web Site: www.sikausa.com

Supplier Emergency Contacts & Phone Number

CHEMTREC: 800-424-9300
INTERNATIONAL: 703-527-3887

Manufacturer Emergency Contacts & Phone Number

CHEMTREC: 800-424-9300
INTERNATIONAL: 703-527-3887

Issue Date: 04/16/2003

Product Name: Sikadur Injection Gel / Anchor Fix 4 - Part B

CAS Number: Not Established

Chemical Family: Amine Compound

Chemical Formula: RMF-2945

MSDS Number: 2652

Product Code: 0786140

2. Composition/Information On Ingredients

Ingredient Name	CAS Number	Percent Of Total Weight
AROMATIC HYDROCARBON BLEND	68477-31-6	
BENZYL ALCOHOL	100-51-6	
CALCIUM CARBONATE	471-34-1	
PROPRIETARY BLEND OF ALIPHATIC AND CYCLOALIPHATIC AMINES	Trade Secret	
TALC	14807-96-6	

Note: Exposure to Calcium Carbonate and Talc is applicable only if cured with Part "A" and sanded.

3. Hazards Identification

Eye Hazards

Causes eye irritation. Causes irreversible eye damage.

M A T E R I A L S A F E T Y D A T A S H E E T

Sikadur Injection Gel / Anchor Fix 4 - Part B

3. Hazards Identification - Continued

Skin Hazards

Causes skin irritation. Causes irreversible skin damage.

Ingestion Hazards

May be harmful if swallowed.

Inhalation Hazards

May cause nose, throat, and lung irritation. May cause respiratory tract irritation.

4. First Aid Measures

Eye

In case of contact, immediately flush eyes with plenty of water. Get medical attention immediately if irritation develops and persists.

Skin

In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately if irritation (redness, rash, blistering) develops and persists.

Ingestion

If swallowed, do not induce vomiting unless directed to do so by medical personnel.

Inhalation

Remove to fresh air. If not breathing, give artificial respiration.

5. Fire Fighting Measures

Flash Point: >200 °F

Autoignition Point: N/AV °F

Fire And Explosion Hazards

None known

Extinguishing Media

In case of fire, use water spray (fog) foam, dry chemical, or CO2.

Fire Fighting Instructions

Firefighters should wear self-contained breathing apparatus and full protective gear.

6. Accidental Release Measures

Avoid release to the environment. Use appropriate personal protective equipment (PPE). Contain spill and collect with absorbent material and transfer into suitable containers. Ventilate enclosed area.

7. Handling And Storage

Handling And Storage Precautions

Keep containers tightly closed. Keep out of reach of children.

Work/Hygienic Practices

Wash thoroughly with soap and water after handling.

8. Exposure Controls/Personal Protection

Engineering Controls

Use with adequate general and local exhaust ventilation.

Eye/Face Protection

Safety glasses with side shields or goggles.

MATERIAL SAFETY DATA SHEET

Sikadur Injection Gel / Anchor Fix 4 - Part B

8. Exposure Controls/Personal Protection - Continued

Skin Protection

Chemical-resistant gloves. Lab coat or other work clothing. Launder before reuse.

Respiratory Protection

A respirator protection program that meets 29 CFR 1910.134 requirement must be followed whenever workplace conditions warrant a respirator's use. In areas where the Permissible Exposure Limits are exceeded, use a properly fitted NIOSH-approved respirator.

Other/General Protection

Wash thoroughly after handling.

Ingredient(s) - Exposure Limits

CALCIUM CARBONATE

ACGIH TLV-TWA 10 mg/m³

OSHA PEL-TWA 15 mg/m³

OSHA PEL-TWA 5 mg/m³

TALC

ACGIH TLV-TWA 2 mg/m³

OSHA PEL-TWA 20 mppcf

9. Physical And Chemical Properties

Appearance

Grey Paste

Odor

Amine Odor

Chemical Type: Mixture

Physical State: Solid

Melting Point: N/AV °F

Boiling Point: N/AV °F

Specific Gravity: 1.65

Percent Volatiles: N/AV

Packing Density: 13.81 pounds/gallon

Vapor Pressure: N/AV

Vapor Density: >AIR

Solubility: N/AV

10. Stability And Reactivity

Stability: Stable

Hazardous Polymerization: Will Not Occur

Conditions To Avoid (Stability)

None Known

Incompatible Materials

Strong Oxidizers, Acids

Hazardous Decomposition Products

CO, CO₂, Oxides of Nitrogen, Ammonia

11. Toxicological Information

No Data Available...

M A T E R I A L S A F E T Y D A T A S H E E T

Sikadur Injection Gel / Anchor Fix 4 - Part B

11. Toxicological Information - Continued

Ingredient(s) - Carginogenicity

TALC

Listed In The IARC Monographs

12. Ecological Information

No Data Available...

13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations.

14. Transport Information

Proper Shipping Name

Not Regulated by the USDOT.

15. Regulatory Information

U.S. Regulatory Information

All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

SARA Hazard Classes

Acute Health Hazard

Chronic Health Hazard

SARA Section 313 Notification

This product does not contain any ingredients regulated under Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 or 40 CFR 372.

Ingredient(s) - State Regulations

BENZYL ALCOHOL

New Jersey - Workplace Hazard

Pennsylvania - Workplace Hazard

Massachusetts - Hazardous Substance

CALCIUM CARBONATE

Pennsylvania - Workplace Hazard

TALC

New Jersey - Workplace Hazard

Pennsylvania - Workplace Hazard

Massachusetts - Hazardous Substance

16. Other Information

HMIS Rating

Health: 3

Fire: 1

Reactivity: 0

PPE: C

Revision/Preparer Information

MSDS Preparer: EHS Department

This MSDS Supersedes A Previous MSDS Dated: 05/21/2002

M A T E R I A L S A F E T Y D A T A S H E E T

Sikadur Injection Gel / Anchor Fix 4 - Part B

Disclaimer

The data in this Material Safety Data Sheet relates only to the specific material herein and does not relate to use in combination with any other material or in any process. The information set forth herein is based on technical data that Sika believes to be reliable as of the date hereof. Since conditions of use are outside our control, we make no warranties, express or implied and assume no liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under or a recommendation to infringe any patents.

SIKA CORPORATION

Printed Using MSDS Generator™ 2000