

Student Name	Tilak Kumar Kushwaha [241102] Aashish [240021]
Project ID	LE1
Title	Empirical Distribution of Intervener Complexity in Natural Language Dependencies
Research Question: What kind of nodes intervene a dependency in natural human languages? Hypothesis: Intervening nodes are short, low-arity, and mostly nouns and adverbs. Motivation: • Structural Geometry of Language: A sentence is an array of nodes, connected by dependency arcs, where a head node, governs the role of a dependent node. In languages these pairs of dependencies are not adjacent and are present at a distance (called dependency length) with words in between called intervening nodes. • Cognitive Efficiency and Memory Constraints: Human languages are designed to reduce memory load and processing effort by simplifying the nodes between dependencies. Since holding a head node in working memory is cognitively taxing, these interveners are supposed to be structurally simple in nature. • Inspiration from DLM Theorem: Parallel to the DLM theorem, which suggests languages prefer shorter dependencies, this project investigates if languages also optimize the internal complexity of the gap. We focus on whether interveners are optimized for low arity and minimal subtree length to facilitate easier parsing. • Categorical Bias in Interveners: We have also investigated the general kind of interveners in terms of their UPOS tags (Universal Part of Speech) to prove their distributions across UPOS is not homogenous, but biased. Apart from this, structural relationship of an intervener with its respective Head and Dependent pair. • Universal Architecture of Human Languages: To ensure results are part of a universal architecture of human communication rather than a property of specific grammars, we have tested these hypotheses across 20 languages- 10 per student.	

Objectives	Outcome
Quantitative POS Analysis	Interveners cluster in specific categories- Nouns, Adpositions, Determiners and are not homogenous among UPOS tags.
Arity Distribution	Low-Arity Constraints: Proved minimal structural complexity where intervener tend to have mostly zero arity.
Structural Relational Mapping	Subtree Simplicity: Confirmed that the majority of intervening nodes have a subtree length of 1.
Intervener Subtree Analysis	Intervener Independence: Determined that most intervening nodes are structurally independent from head and dependent nodes.

Theoretical Implications of the outcomes:

- Human languages are designed to reduce human memory load by simplifying interveners.
- Parallel to Dependency Length Minimization, languages prefer shorter dependencies.
- Most interveners are structurally independent of pair, so they cause little parsing interference.
- Human Languages tend to have a universal inclination for simplification.
- Only some specific types of words of some certain UPOS are preferred to be interveners.

Language Codes for Project: (10 Languages for each student.)


en: English	it: Italian	ar: Arabic	pl: Polish
hi: Hindi	ru: Russian	tr: Turkish	da: Danish
de: German	zh: Chinese	fi: Finnish	nl: Dutch
es: Spanish	ja: Japanese	el: Greek	pt: Portuguese
fr: French	ko: Korean	sv: Swedish	bg: Bulgarian

Methods and Tools:

- Entire analysis is done by python.
- Python libraries like conllu, seaborn, matplotlib, pandas and statmodels have been used.
- Universal Dependencies Treebanks have been used, specifically only conllu files have been utilized.
- No specific mathematical model has been used; concepts of hypothesis testing is used for doing tests.
- Entire analysis is saved on a public Google Drive folder given here.
- **Links** [Google Drive [Folder](#), Google_Colab [Notebook](#), [GitHub Repo](#)]

Objective 1 Arity Distribution: To prove interveners have low arity.

Arity refers to the number of immediate children or dependent nodes a head has in a sentence.



Here we have presented a heatmap for empirical evidence to show that most of the interveners have almost zero arity.

Now to prove human efficiency we have used a Poisson GLM.

$$\ln(\lambda) = \beta_0 + \beta_1(\text{Condition}) + \beta_2(\text{Dependency-Length})$$

λ : Average arity of interveners

β_1 : Change in log count of arity from random to real.

β_2 : Dependency Length of head-child pair.

So here we take a sentence, take its (length, average-arity) data, shuffle its words randomly and take (length, average-arity) data and form the regression.

We've done this shuffling to establish human efficiency.


Language	Beta_1	Z_Statistic	Result
ar	-1.6584	-1096.0117	Reject H0
bg	-1.0633	-313.1289	Reject H0
da	-1.1266	-311.9581	Reject H0
de	-0.9493	-523.9140	Reject H0
el	-1.3048	-280.6767	Reject H0
en	-1.3587	-590.5879	Reject H0
es	-1.4392	-938.0254	Reject H0
fi	-1.3257	-481.0656	Reject H0
fr	-1.7829	-1082.2753	Reject H0
hi	-1.0298	-582.1650	Reject H0
it	-1.6911	-916.0463	Reject H0
ja	-1.7701	-603.2262	Reject H0
ko	-1.0391	-225.4686	Reject H0
nl	-0.8258	-353.9928	Reject H0
pl	-1.0850	-528.7421	Reject H0
pt	-1.3458	-708.3096	Reject H0
ru	-1.2124	-327.5100	Reject H0
sv	-1.2551	-296.0357	Reject H0
tr	-0.9109	-137.9050	Reject H0
zh	-0.9966	-363.6454	Reject H0

Null Hypothesis: $\beta_1 = 0$, This assumes that human languages are no better than random word order

Alternative Hypothesis: $\beta_1 < 0$, This assumes that real languages are optimized for low arity.


Test Statistic: $Z = \frac{\beta_1}{SE(\beta_1)}$; One Tailed Test.

For 95% one tailed test our significance is -1.645, if $Z < -1.645$ we reject null hypothesis. Also $IRR = e^{\beta_1}$ represents the multiplicative change as we go from random to real, say its 20% then we say the arity of real nodes is only 20% than that from random word order.



The following presents a comprehensive overview of our finding here. The Z-Statistics are significantly lower here indicating the difference between random word order and our languages is huge in terms of Arity simplification. For the regression we have included 'distance', because as distance increases the arity of interveners will increase as well, hence the regression we find average arity with fixed dependency distance.

For forming the random baselines, we have retained the dependency arcs of a sentence while shuffling the linear distance and the word order of the nodes of a real sentence.



Evidently, the value of coefficient β_1

are negative, indicating a reduction in average arity as we switch from random baseline sentences to their corresponding real versions, suggesting human languages are more inclined towards lower arity.


Here is a KDE plot, basically it's the probability density graph of arity of each language, expressing the probability of finding an intervener with a certain arity. We have also included dependency distance in the regression because as it increases the probability of interveners having more children nodes increases as well.

Outcome: Interveners have zero arity in general for all 20 human languages.

Theoretical Implication: This implicates a universal pressure to minimize structural complexity of languages by adopting low-arity interveners.

Objective 2 Subtree Weight Analysis: Subtree is a mapping of a head node and its dependent nodes.

Now to analyse complexity we need to find the 'Subtree Weight' i.e. the total constituents of a subtree. For an intervener with no immediate children subtree weight is one. Here only immediate children nodes are considered.



Again, a heatmap for empirical standing depicting the proportion of interveners having weights across languages, since the proportion is negligible after 3, we have just limited it to three.

We have again used a Poisson GLM because this essentially a categorical data

$$\ln(\lambda) = \beta_0 + \beta_{weight}(\text{SubtreeLength}) + \ln(\text{DependencyDistance})$$

λ : Expected count of interveners

β_0 : Intercept baseline intervention rate.

β_{weight} : The log rate decreases when we increase our subtree length by one unit.

Similar to arity analysis we have random baseline words to establish that human languages are efficient but in order to make the regression light we have formed completely two different regressions for it altogether, to check (β_{weight_Real}) and

(β_{weight_Random}) Separately.

We have formed two separate regressions for real and random sentences. Random Shuffling is done maintaining dependency arcs and changing the order and linear distances between nodes of the sentences. Also, we included dependency distance in the regression because as it increases its dependent nodes for intervener will increase as well.

We have used to two tests:

- **Null Hypothesis:** $\beta_{weight} = 0$, Structural weight has no impact on the probability of a node appearing as an intervener.
- **Alternative Hypothesis:** $\beta_{weight} < 0$, As the weight of a subtree increases, its likelihood of appearing in a dependency gap decreases (Negative Decay).

Test Statistic: $Z = \beta_{weight} / SE(\beta_{weight})$: A Wald Z statistic (One- Tailed Test), for $\alpha = 0.05$ we reject Null if, $Z < -1.645$.

This checks the optimality of Intervener Subtree in real languages only.

- **Null Hypothesis:** $\beta_{weight_Real} = \beta_{weight_Random}$, the observed decay in real language is simply a by-product of the general rarity of large subtrees in the dataset.
- **Alternative Hypothesis:** $\beta_{weight_Real} < \beta_{weight_Random}$, natural language neglects heavy interveners significantly more than would be expected by chance.

Test Statistic: $Z_{Diff} = \frac{\beta_{Real} - \beta_{Random}}{\sqrt{SE_{Real}^2 + SE_{Random}^2}}$ again for $\alpha = 0.05$ we reject null for $Z < -1.645$ (One-tailed test).

Do take note of the fact that a language is 'Efficient' if satisfies both of the test presented here.


- **Internal Validity:** The weight filter is active (Wald: $Z < -1.645$).
- **Optimized Selection:** The suppression is stronger than the random baseline ($Z_{Diff} < -1.645$).

Lang	Beta_R	Wald_Z	Z_Diff	Conclusion
en	-0.956	-639.92	-263.95	Efficient
hi	-0.847	-774.01	-211.3	Efficient
de	-0.888	-791.09	-244.69	Efficient
es	-0.74	-857.81	-319.51	Efficient
ru	-0.794	-378.14	-152.73	Efficient
zh	-0.854	-504.98	-139.71	Efficient
ja	-1.002	-516.23	-218.16	Efficient
ko	-0.846	-303.0	-87.56	Efficient
tr	-0.947	-220.0	-64.33	Efficient
el	-0.805	-295.85	-121.77	Efficient
sv	-0.954	-351.28	-133.57	Efficient
pl	-0.836	-710.93	-283.45	Efficient
da	-0.901	-412.42	-158.74	Efficient
nl	-0.944	-641.81	-200.68	Efficient
pt	-0.798	-717.57	-301.51	Efficient
bg	-0.962	-443.54	-176.32	Efficient


Here β_{weight} is labelled as β_R it shows log intervention in lambda by an increase in Subtree Length by 1 for real languages, it being -ve implies as its subtree length gets heavier its probability of appearing in the same dependency length falls exponentially.

The greater the negative value greater the suppression of heavy interveners.

For the test statistics say for Spanish the Wald_Z is -857.81, so its -857.81 standard deviations away from null hypothesis, establishing this outcome to be a universal law for human languages, since the test statistics of all languages are negative and huge in value.



Here are the coefficients distributions: β_{weight_Real} for the first regression. They denote the decay, as in what is the effect when we increase the subtree weight for constant dependency length in human languages. Its negative signifying the count of interveners would reduce as we increase the subtree weight by one. This is a sort of 'Negative Decay', where the arity falls when we jump to relatively complex interveners.




But do note that even $\beta_{\text{weight_Random}}$ is -ve, because even when nodes are shuffled the heavier structure are still rare overall, since the dependencies are just scrambled here. The observation is ,is that for every language the corresponding $\beta_{\text{weight_Random}}$ is less negative than their real counterpart, indicating the real human languages are even more averse to heavier interveners.

Outcome: Majority of interveners are simple, with Subtree length 1, i.e. they lack immediate children nodes.

Theoretical Implication: Human languages are designed to minimize memory load by avoiding complex interruptions between head and dependent words, the ‘Negative Decay’ ensures lesser load in working memory.

Objective 3 Structural Relational Mapping: To prove that interveners don’t modify the head and dependent node of the dependency pair they are part of.



We have presented a heatmap for the substantial understanding here, clearly interveners generally appear independent in a sentence across all these languages. For tests we have used a Poisson GLM here given as:

$$\ln(\lambda) = \beta_0 + \beta_1(\text{Modifies} - \text{Head}) + \beta_2(\text{Modifies} - \text{Dependent}) + \ln(\text{DependencyDistance})$$

λ : Expected Count of Interveniers

β_1 : Change in rate of intervention when an intervener modifies head.

β_2 : Change in rate of intervention when a intervener modifies dependent word.

We haven’t used random word order here because this sort of dependency is human-language property only.

Hypothesis Testing: We have conducted two tests here both have same Test Statistic and same confidence level of 95%. For Wald_Z statistic (one tailed-test) test here, we reject null hypothesis at, $Z < -1.645$.

Test Statistic: $Z = \frac{\beta - \beta_{H_0}}{SE(\beta)}$ where β is the log rate for head or dependent, β_{H_0} is zero, and is log rate of independent intervener. $SE(\beta)$ is standard error for β .

Language	Z _H	Result _H	Z _D	Result _D
zh	-200.918661	Reject Null	-256.302130	Reject Null
tr	-54.995115	Reject Null	-99.323031	Reject Null
sv	-64.844438	Reject Null	-130.377472	Reject Null
ru	-141.517212	Reject Null	-165.789371	Reject Null
pt	-279.478532	Reject Null	-304.998045	Reject Null
pl	-217.219260	Reject Null	-286.005040	Reject Null
nl	-159.156779	Reject Null	-283.992764	Reject Null
ko	-101.259257	Reject Null	-145.612776	Reject Null
ja	-68.947630	Reject Null	-161.653866	Reject Null
it	-251.042492	Reject Null	-309.905705	Reject Null
hi	-280.107197	Reject Null	-382.777533	Reject Null
fr	-273.173833	Reject Null	-328.104294	Reject Null
fi	-118.442614	Reject Null	-220.197021	Reject Null
es	-349.704324	Reject Null	-376.341552	Reject Null
en	-149.902814	Reject Null	-232.752903	Reject Null
el	-115.176256	Reject Null	-123.167804	Reject Null
de	-255.730630	Reject Null	-381.976693	Reject Null
da	-94.807401	Reject Null	-159.793931	Reject Null
bg	-105.734438	Reject Null	-141.969907	Reject Null
ar	-456.035333	Reject Null	-487.905966	Reject Null

Test 1: Head vs. Independent (Z_H)

- **Null Hypothesis:** $\beta_{Head} = \beta_{Independent}$
- **Alternative Hypothesis:** $\beta_{Head} < \beta_{Independent}$


Test 2: Dependent vs. Independent (Z_D)

- **Null Hypothesis:** $\beta_{Dependent} = \beta_{Independent}$
- **Alternative Hypothesis:** $\beta_{Dependent} < \beta_{Independent}$

Given all of the Test-Statistics are negative, it implies the proportion of interveners reduces significantly when they modify either the head or dependent word of its respective pair. Given the property of β for each category we state that for any intervener its probability of being independent of its head and dependent node is substantially high across the given 20 languages.

For a more comprehensive view of the independent nature of interveners we have updated the regression.

$$\ln(\lambda) = \beta_0 + \beta_1(\text{Modifies} - \text{Head}) + \beta_2(\text{Modifies} - \text{Dependent}) + \beta_3(\text{Independent}) + \ln(\text{DependencyDistance})$$



IRR ($e^{\beta_{category}}$): represents the multiplicative change in the intervention rate for a node based on its structural relationship, given the graph independent interveners are dominant.

Outcome: Majority of intervening nodes are structurally independent of both the head and the dependent nodes.

Theoretical Implication: By being independent, interveners reduce parsing interference and reduce ‘noise’, simplifying human processing.

Objective 4 Quantitative POS Analysis: To prove that interveners are spread among UPOS in a heterogenous manner and Nouns, Determiners and Adpositions tend to be most prominent UPOS.

We have used a Poisson regression here;

$$\ln(\lambda) = \beta_0 + \beta_1(\text{Distance}) + \beta_j(\text{UPOS Tag})$$




λ : Expected count of interveners.

β_0 : The log-expected count when the distance is at its minimum.

β_1 : Coefficient for Dependency Distance.

β_j : Tag specific Coefficient for all tags except VERB. UPOS tag (VERB) is the baseline category here.

We have provided a heatmap for a comprehensive understanding of distribution of interveners among UPOS Tags.



IRR ($e^{\beta_{UPOS_Category}}$): indicates the multiplicative change in the intervention rate or the appearance of interveners as we go from one UPOS Category to another w.r.t the VERB Tag baseline. Parallel to the heatmap, Noun and Adposition Tags dominate the intervener traffic in real human languages.

To prove heterogeneity in UPOS distribution in human languages, we have shuffled sentences across languages, while retaining a word's UPOS identity and dependency arcs.

The Noun UPOS is still dominant because in general, nodes with Noun as UPOS Tags are dominant across real languages, which is similar for Adpositions as well. From this we infer even if we remove the natural inclinations of human languages towards certain UPOS, these UPOS category still dominant because they are huge in numbers.

We observe the IRR value has reduced for prominent categories. It's because of the random shuffling the distribution has become less biased for these categories but is still big because of their majority.

--- Final Hypothesis Test Summary ---

Language	LRT_Stat	LRT_Reject_H0	NOUN_Beta	NOUN_Wald_Z	\	NOUN_Dominant	ADP_Beta	ADP_Wald_Z	ADP_Dominant
0 Arabic	861095.143101	Yes	1.985156	111.889397	0	Yes	1.415940	49.088473	Yes
1 BG	161232.503616	Yes	1.643999	13.213230	1	Yes	1.768360	20.142664	Yes
2 Danish	115851.801791	Yes	1.275444	27.837564	2	Yes	1.125004	19.292360	Yes
3 German	640199.092431	Yes	2.371103	-7.673784	3	No	2.193963	-19.765742	No
4 Greek	77360.294119	Yes	1.384200	-17.459817	4	No	0.890758	-36.511045	No
5 English	266351.849427	Yes	1.103768	30.361516	5	Yes	0.759040	-1.122276	No
6 Spanish	833958.495033	Yes	1.346517	-40.895921	6	No	1.751602	4.857247	Yes
7 Finnish	253756.399931	Yes	1.373639	87.680874	7	Yes	-1.396367	-99.227771	No
8 French	725563.084223	Yes	1.541831	-41.544043	8	No	1.894711	-6.099602	No
9 Hindi	782679.816777	Yes	1.608224	71.146377	9	Yes	1.806539	93.668370	Yes
10 Italian	680705.358280	Yes	1.527191	-36.561606	10	No	1.749254	-15.846993	No
11 Japanese	442714.010294	Yes	1.444970	48.413624	11	Yes	1.541349	56.630335	Yes
12 Korean	209438.279059	Yes	1.432980	72.476907	12	Yes	-1.263467	-66.852884	No
13 Dutch	334540.922236	Yes	1.290319	-1.306378	13	No	1.337558	2.802687	Yes
14 Polish	468754.431570	Yes	1.683590	54.582856	14	Yes	1.254940	13.501201	Yes
15 Portuguese	605095.235582	Yes	1.431373	-38.023983	15	No	1.834168	-2.340029	No
16 Russian	160081.569078	Yes	1.885958	11.302143	16	Yes	1.359359	-13.395844	No
17 Swedish	87679.997850	Yes	1.740352	22.370193	17	Yes	1.399290	7.052435	Yes
18 Turkish	46394.739289	Yes	0.885015	40.181517	18	Yes	-0.597020	-22.189399	No
19 Chinese	253535.962576	Yes	0.993231	93.914102	19	Yes	-0.831582	-62.307915	No

Test1: To prove heterogeneity

- **Null Hypothesis:** $\beta_{UPOS} = 0$ the part-of-speech category has no effect on the likelihood of a word being an intervener; the distribution is uniform.
- **Alternative Hypothesis:** At least one $\beta_{UPOS} \neq 0$ the distribution of interveners is heterogeneous, meaning specific categories occur more or less frequently than others.
- Test Statistic: $\Delta = 2 * (LL_{H_1} - LL_{H_0})$: an omnibus likelihood ratio test is used here, that uses χ^2 Distribution with degree of freedom equal to number of UPOS tags minus one.

Test2: To prove Nouns and Adpositions dominate the most:

- **Null Hypothesis:** $\beta_{Target} \leq \beta_{Next_Highest}$ the target tag (NOUN or ADP) is not significantly more frequent than the most common "non-target" tag in the language.
- **Alternative Hypothesis:** $\beta_{Target} > \beta_{Next_Highest}$ the target tag is an abnormally high intervener that dominates the distribution. [One-Tailed Test]
- A Wald_Z statistic is used here with $Z = \frac{\beta_{Target} - \beta_{Next}}{\sqrt{SE_{Target}^2 + SE_{Next}^2}}$

For both of them Confidence level is 95%, for Test1 we reject null for [p<0.05] and Test2 we reject null for [Z>1.645]

A "No" result indicates that NOUN and ADP form a statistically indistinguishable "top-tier cluster" rather than a single outlier. This proves that in certain languages, intervention is shared across a functional-lexical complex rather than being dominated by one specific category.

Outcome: Intervenors primarily belong to Nouns and Adpositions UPOS Category.

Theoretical Implications: By biasing intervenors towards some specific predictable tags, human languages reduce overall effort to identify and skip intervening nodes during parsing.

Conclusion: From our analysis, we can infer that intervening nodes are of low arity, simple (subtree length=1), and are mainly independent of the head-dependent pair they are part of. But we have analyzed that they are mostly Nouns and Adpositions, unlike our original hypothesis which claimed them to be Nouns and Adverbs. **Hence, we partially reject our original hypothesis** and establish the result that **Intervening nodes are low arity words of simple structure that are independent of the head and dependent pair they are part of and are mostly Nouns and Adpositions.**

Note:

- After sir's approval we have extended the main document (by 2 pages) for the theoretical understanding for each objective, in the order of its occurrence. These are extensions for better understanding for every analysis done.
- This report was made in MS Word where the images of our analysis is put adjacent to its explanation in text boxes, found in MS Word. So, it's basically a collage-like summary of our findings.

Appendix

This Appendix is divided into the objectives that were given in the project, all the code for a specific kind of analysis is found within its objective block.

For performing the analysis, just change the path below given here, make the folder public and create four sub-folders inside namely, ‘Arity_Analysis’, ‘Dependency_Analysis’, ‘Subtree_Weight_Analysis’ and ‘UPOS_Analysis’

Appendix 0 :

For initialization:

```
drive_path = "/content/drive/MyDrive/Course_Project"
!pip install conllu
```

For downloading ‘conllu’ data:

```
from google.colab import drive
import os, requests
drive.mount('/content/drive')
os.makedirs(drive_path, exist_ok=True)

files = {
    "en_train": "https://raw.githubusercontent.com/UniversalDependencies/UD_English-EWT/master/en_ewt-ud-train.conllu",
    "hi_train": "https://raw.githubusercontent.com/UniversalDependencies/UD_Hindi-HDTB/master/hi_hdtb-ud-train.conllu",
    "de_train": "https://raw.githubusercontent.com/UniversalDependencies/UD_German-GSD/master/de_gsd-ud-train.conllu",
    "es_train": "https://raw.githubusercontent.com/UniversalDependencies/UD_Spanish-GSD/master/es_gsd-ud-train.conllu",
    "fr_train": "https://raw.githubusercontent.com/UniversalDependencies/UD_French-GSD/master/fr_gsd-ud-train.conllu",
    "it_train": "https://raw.githubusercontent.com/UniversalDependencies/UD_Italian-ISDT/master/it_isdt-ud-train.conllu",
    "ru_train": "https://raw.githubusercontent.com/UniversalDependencies/UD_Russian-GSD/master/ru_gsd-ud-train.conllu",
    "zh_train": "https://raw.githubusercontent.com/UniversalDependencies/UD_Chinese-GSD/master/zh_gsd-ud-train.conllu",
    "ja_train": "https://raw.githubusercontent.com/UniversalDependencies/UD_Japanese-GSD/master/ja_gsd-ud-train.conllu",
    "ko_train": "https://raw.githubusercontent.com/UniversalDependencies/UD_Korean-GSD/master/ko_gsd-ud-train.conllu",
    "ar_train": "https://raw.githubusercontent.com/UniversalDependencies/UD_Arabic-PADT/master/ar_padt-ud-train.conllu",
    "tr_train": "https://raw.githubusercontent.com/UniversalDependencies/UD_Turkish-IMST/master/tr_imst-ud-train.conllu",
    "fi_train": "https://raw.githubusercontent.com/UniversalDependencies/UD_Finnish-TDT/master/fi_idt-ud-train.conllu",
    "el_train": "https://raw.githubusercontent.com/UniversalDependencies/UD_Greek-GDT/master/el_gdt-ud-train.conllu",
    "sv_train": "https://raw.githubusercontent.com/UniversalDependencies/UD_Swedish-Talbanken/master/sv_talbanken-ud-train.conllu",
    "pl_train": "https://raw.githubusercontent.com/UniversalDependencies/UD_Polish-PDB/master/pl_pdb-ud-train.conllu",
    "da_train": "https://raw.githubusercontent.com/UniversalDependencies/UD_Danish-DDT/master/da_ddt-ud-train.conllu",
    "nl_train": "https://raw.githubusercontent.com/UniversalDependencies/UD_Dutch-Alpino/master/nl_alpino-ud-train.conllu",
    "pt_train": "https://raw.githubusercontent.com/UniversalDependencies/UD_Portuguese-GSD/master/pt_gsd-ud-train.conllu",
    "bg_train": "https://raw.githubusercontent.com/UniversalDependencies/UD_Bulgarian-BTB/master/bg_btb-ud-train.conllu"
}

for name, url in files.items():
    print(f"Downloading {name}...")
    r = requests.get(url)
    if r.status_code == 200:
        with open(os.path.join(drive_path, name + ".conllu"), "wb") as f:
            f.write(r.content)
    else:
        print(f"Failed: {name} ({r.status_code})")

print("All downloads complete.")
```

Appendix 1: For Arity Analysis

Heatmap and Kernel Density Plot for Arity

```
import os
import pandas as pd
import seaborn as sns
import matplotlib.pyplot as plt
from conllu import parse_incr
from google.colab import drive

drive_root = "/content/drive/MyDrive/Course_Project"
save_dir = os.path.join(drive_root, "Arity_Analysis")

if not os.path.exists(save_dir):
    os.makedirs(save_dir)

if not os.path.exists("/content/drive"):
    drive.mount("/content/drive")

def analyze_language_arity(path):
    all_nodes = []
    intervener_nodes = []

    with open(path, "r", encoding="utf-8") as f:
        for sentence in parse_incr(f):
            out_degrees = {}
            for word in sentence:
                parent = word['head']
                if parent is not None and parent != 0:
                    out_degrees[parent] = out_degrees.get(parent, 0) + 1

            for word in sentence:
                all_nodes.append((out_degrees.get(word['id'], 0)))

            for word in sentence:
                h_id = word['head']
                d_id = word['id']

                if h_id == 0 or h_id is None:
                    continue

                left, right = min(h_id, d_id), max(h_id, d_id)
                for i in range(left + 1, right):
                    intervener_nodes.append(out_degrees.get(i, 0))

    return all_nodes, intervener_nodes
```

```

kde_records = []
heatmap_records = []

conllu_files = [f for f in os.listdir(drive_root) if f.endswith('.conllu')]

for file_name in conllu_files:
    lang_name = file_name.split('_')[0]
    full_path = os.path.join(drive_root, file_name)

    node_data, intv_data = analyze_language_arity(full_path)

    kde_records.append(pd.DataFrame({'Ariety': node_data, 'Language': lang_name}))

    distribution = pd.Series(intv_data).value_counts(normalize=True).sort_index()
    distribution.name = lang_name
    heatmap_records.append(distribution)

combined_kde_df = pd.concat(kde_records)
plt.figure(figsize=(14, 8))
sns.kdeplot(data=combined_kde_df, x='Ariety', hue='Language', common_norm=False, bw_adjust=2)
plt.title("Ariety Distribution across Languages")
plt.xlim(0, 8)
plt.savefig(os.path.join(save_dir, "arity_kde.png"))
plt.show()

matrix_df = pd.concat(heatmap_records, axis=1).fillna(0).T
matrix_df = matrix_df.iloc[:, :6]

plt.figure(figsize=(12, 10))
sns.heatmap(matrix_df, annot=True, cmap="YlGnBu", fmt=".2f")
plt.title("Intervener Ariety Proportions")
plt.xlabel("Ariety")
plt.ylabel("Language")
plt.savefig(os.path.join(save_dir, "intervener_heatmap.png"))
plt.show()

```

For Hypothesis Testing:

```

import os
import random
import pandas as pd
import statsmodels.api as sm
import statsmodels.formula.api as smf
from conllu import parse_incr
from google.colab import drive

drive_root = "/content/drive/MyDrive/Course_Project"
save_dir = os.path.join(drive_root, "Ariety_Analysis")

if not os.path.exists(save_dir):
    os.makedirs(save_dir)

if not os.path.exists("/content/drive"):
    drive.mount("/content/drive")

def process_language(path, lang):
    observations = []

    with open(path, "r", encoding="utf-8") as f:
        for sentence in parse_incr(f):
            nodes = [t for t in sentence if isinstance(t['id'], int)]
            if not nodes:
                continue

            out_degrees = {}
            for t in nodes:
                h = t['head']
                if h is not None and h != 0:
                    out_degrees[h] = out_degrees.get(h, 0) + 1

            dependencies = []
            for t in nodes:
                if t['head'] is not None and t['head'] != 0:
                    dependencies.append((t['head'], t['id']))

            for h_id, d_id in dependencies:
                real_dist = abs(h_id - d_id)
                real_arity_sum = 0
                for i in range(min(h_id, d_id) + 1, max(h_id, d_id)):
                    real_arity_sum += out_degrees.get(i, 0)

            observations.append({
                'arity': real_arity_sum,
                'condition': 1,
                'length': real_dist
            })

            positions = [t['id'] for t in nodes]
            shuffled_positions = positions[:]
            random.shuffle(shuffled_positions)
            pos_map = dict(zip(positions, shuffled_positions))

            for h_id, d_id in dependencies:
                rand_h_pos = pos_map[h_id]
                rand_d_pos = pos_map[d_id]
                rand_dist = abs(rand_h_pos - rand_d_pos)

                rand_arity_sum = 0
                low, high = min(rand_h_pos, rand_d_pos), max(rand_h_pos, rand_d_pos)

                for orig_id, new_pos in pos_map.items():
                    if low < new_pos < high:
                        rand_arity_sum += out_degrees.get(orig_id, 0)

            observations.append({
                'arity': rand_arity_sum,
                'condition': 0,
                'length': rand_dist
            })

    return pd.DataFrame(observations)

summary_rows = []
all_results = []

conllu_files = sorted([f for f in os.listdir(drive_root) if f.endswith('.conllu')])

```

```

for file_name in conllu_files:
    lang_code = file_name.split('_')[0]
    file_path = os.path.join(drive_root, file_name)

    df = process_language(file_path, lang_code)

    model = smf.glm(formula="arity ~ condition + length",
                    data=df,
                    family=sm.families.Poisson()).fit()

    beta_1 = model.params['condition']
    beta_2 = model.params['length']
    z_score = model.tvalues['condition']
    p_value = model.pvalues['condition']

    is_rejected = "Reject H0" if (beta_1 < 0 and (p_value / 2) < 0.05) else "Fail to Reject"

    summary_rows.append({
        'Language': lang_code,
        'Beta_1': round(beta_1, 4),
        'Z_Statistic': round(z_score, 4),
        'Result': is_rejected
    })

    all_results.append({
        'language': lang_code,
        'beta_0': model.params['Intercept'],
        'beta_1': beta_1,
        'beta_2': beta_2,
        'z_stat': z_score,
        'p_value_one_tailed': p_value / 2,
        'url': os.path.exp(beta_1) if hasattr(os, 'exp') else 2.71828**beta_1,
        'decision': is_rejected
    })

pd.DataFrame(all_results).to_csv(os.path.join(save_dir, "poisson_regression_summary.csv"), index=False)

output_table = pd.DataFrame(summary_rows)
print(output_table.to_string(index=False))

```

For statistical strength and Optimization effect graph:

```

import os
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns
import numpy as np

drive_root = "/content/drive/MyDrive/Course_Project"
save_dir = os.path.join(drive_root, "Arity_Analysis")
data_path = os.path.join(save_dir, "poisson_regression_summary.csv")

df = pd.read_csv(data_path)
df = df.sort_values(beta_1)

plt.figure(figsize=(12, 8))
sns.pointplot(data=df, x=beta_1, y='language', join=False, color='darkblue')
plt.axvline(0, color='red', linestyle='--')
plt.title("Optimization Effect Size (Beta 1) by Language")
plt.xlabel("Coefficient Value (Negative = Higher Efficiency)")
plt.ylabel("Language")
plt.tight_layout()
plt.savefig(os.path.join(save_dir, "coefficient_forest_plot.png"))
plt.show()

df = df.sort_values(z_stat)
plt.figure(figsize=(12, 8))
colors = ['green' if z < -1.645 else 'grey' for z in df['z_stat']]
sns.barplot(data=df, x=z_stat, y='language', palette=colors)
plt.axvline(-1.645, color='red', linestyle='--', label='95% Significance Threshold')
plt.title("Statistical Strength (Z-Statistic) by Language")
plt.xlabel("Z-Statistic")
plt.ylabel("Language")
plt.legend()
plt.tight_layout()
plt.savefig(os.path.join(save_dir, "z_statistic_bars.png"))
plt.show()

```

Appendix 2 : Structural Relational Mapping

For Empirical Heatmap:

```

import os
import pandas as pd
import seaborn as sns
import matplotlib.pyplot as plt
from google.colab import drive

drive.mount('/content/drive')

drive_path = "/content/drive/MyDrive/Course_Project"
output_dir = os.path.join(drive_path, "Dependency_Analysis")
os.makedirs(output_dir, exist_ok=True)

languages = [
    'zh', 'tr', 'sv', 'ru', 'pt', 'pl', 'nl', 'ko', 'ja', 'it',
    'hi', 'fr', 'fi', 'es', 'en', 'el', 'de', 'da', 'bg', 'ar'
]

dataset = []

def parse_conllu(file_path):
    sentences = []
    current_sent = []
    with open(file_path, 'r', encoding='utf-8') as f:
        for line in f:
            if line.startswith('#'):
                continue
            if line.strip() == "":
                if current_sent:
                    sentences.append(current_sent)
                    current_sent = []

```

```

        else:
            current_sent.append(line.strip().split("\t"))
    return sentences

for lang in languages:
    path = os.path.join(drive_path, f"{lang}_train.conllu")
    if not os.path.exists(path):
        continue

    sentences = parse_conllu(path)
    for sent in sentences:
        tree = {int(node[0]): int(node[6]) for node in sent if node[0].isdigit()}

        for dep, head in tree.items():
            if head == 0:
                continue

            left, right = min(dep, head), max(dep, head)
            if right - left <= 1:
                continue

            for i in range(left + 1, right):
                if i not in tree:
                    continue

                i_head = tree[i]
                if i_head == head:
                    role = 'Head-Modifier (H)'
                elif i_head == dep:
                    role = 'Dependent-Modifier (D)'
                else:
                    role = 'Independent (I)'

            dataset.append({'Language': lang, 'Category': role})

analysis_df = pd.DataFrame(dataset)

plt.figure(figsize=(12, 6))
sns.kdeplot(data=analysis_df, x=analysis_df.index, hue='Category', fill=True, common_norm=False)
plt.title('Distribution of Intervener Categories')
plt.xlabel('Observation Index')
plt.ylabel('Density')
plt.savefig(os.path.join(output_dir, 'intervener_kernel_density.png'))
plt.close()

counts = analysis_df.groupby(['Language', 'Category']).size().unstack(fill_value=0)
proportions = counts.div(counts.sum(axis=1), axis=0)

plt.figure(figsize=(14, 10))
sns.heatmap(proportions, annot=True, cmap='YlGnBu', fmt='.2f')
plt.title('Relative Frequency of Intervener Roles Across Languages')
plt.savefig(os.path.join(output_dir, 'intervener_role_heatmap.png'))
plt.close()

```

Hypothesis Testing:

```

import os
import numpy as np
import pandas as pd
import statsmodels.api as sm
import statsmodels.formula.api as smf
from google.colab import drive
import patsy.contrasts as sx

drive.mount('/content/drive')

base_path = "/content/drive/MyDrive/Course_Project"
output_path = os.path.join(base_path, "Dependency_Analysis")
os.makedirs(output_path, exist_ok=True)

languages = [
    'zh', 'tr', 'sv', 'ru', 'pt', 'pl', 'nl', 'ko', 'ja', 'it',
    'hi', 'fr', 'fr', 'es', 'en', 'el', 'de', 'da', 'bg', 'ar'
]

results = []

for lang in languages:
    file_path = os.path.join(base_path, f"{lang}_train.conllu")
    if not os.path.exists(file_path):
        continue

    records = []
    with open(file_path, 'r', encoding='utf-8') as f:
        sentence = []
        for line in f:
            if line.startswith("#"):
                continue
            if line.strip() == "":
                if sentence:
                    nodes = {int(n[0]): int(n[6]) for n in sentence if n[0].isdigit()}
                    for dep, head in nodes.items():
                        if head == 0: continue

                    start, end = min(dep, head), max(dep, head)
                    dist = end - start
                    if dist <= 1: continue

                    counts = {'H': 0, 'D': 0, 'I': 0}
                    for i in range(start + 1, end):
                        if i not in nodes: continue
                        if nodes[i] == head:
                            counts['H'] += 1
                        elif nodes[i] == dep:
                            counts['D'] += 1
                        else:
                            counts['I'] += 1

                    for cat in ['H', 'D', 'I']:
                        records.append({
                            'count': counts[cat],
                            'category': cat,
                            'log_dist': np.log(dist)
                        })
                    sentence = []
            else:
                sentence.append(line.strip().split("\t"))

```

```

if records:
    df = pd.DataFrame(records)

    model = smf.glm(
        formula="count ~ C(category, sx.Treatment(reference='I'))",
        data=df,
        family=sm.families.Poisson(),
        offset=df['log_dist']
    ).fit()

    b_h = model.params["C(category, sx.Treatment(reference='I'))(T.H)"]
    z_h = model.values["C(category, sx.Treatment(reference='I'))(T.H)"]
    p_h = model.pvalues["C(category, sx.Treatment(reference='I'))(T.H)"] / 2 if z_h < 0 else 1 - (model.pvalues["C(category, sx.Treatment(reference='I'))(T.H)"] / 2)

    b_d = model.params["C(category, sx.Treatment(reference='I'))(T.D)"]
    z_d = model.values["C(category, sx.Treatment(reference='I'))(T.D)"]
    p_d = model.pvalues["C(category, sx.Treatment(reference='I'))(T.D)"] / 2 if z_d < 0 else 1 - (model.pvalues["C(category, sx.Treatment(reference='I'))(T.D)"] / 2)

    results.append({
        'Language': lang,
        'Beta_H_vs_I': b_h,
        'Z_H': z_h,
        'P_H_OneTailed': p_h,
        'Result_H': 'Reject Null' if p_h < 0.05 and b_h < 0 else 'Fail to Reject',
        'Beta_D_vs_I': b_d,
        'Z_D': z_d,
        'P_D_OneTailed': p_d,
        'Result_D': 'Reject Null' if p_d < 0.05 and b_d < 0 else 'Fail to Reject'
    })

summary_df = pd.DataFrame(results)
summary_df.to_csv(os.path.join(output_path, "language_hypothesis_testing.csv"), index=False)

print(summary_df[["Language", 'Z_H', 'Result_H', 'Z_D', 'Result_D']].to_string(index=False))

```

For plots of Forest Plot: Log-Rate Coefficients (Beta) across 20 Language, Incidence Rate Ratio (IRR) by Structural Role’ and ‘The Gatekeeper Hierarchy: Universal Suppression Ranking’:

```

import os
import numpy as np
import pandas as pd
import seaborn as sns
import matplotlib.pyplot as plt
import statsmodels.api as sm
import statsmodels.formula.api as smf
from google.colab import drive

drive.mount('/content/drive')
drive_path = "/content/drive/MyDrive/Course_Project"
output_dir = os.path.join(drive_path, "Dependency_Analysis")
os.makedirs(output_dir, exist_ok=True)

languages = ['zh', 'tr', 'sv', 'ru', 'pt', 'pl', 'nl', 'ko', 'ja', 'it',
            'hi', 'fr', 'es', 'en', 'el', 'de', 'da', 'bg', 'ar']

plot_data = []

for lang in languages:
    file_path = os.path.join(drive_path, f'{lang}_train.conllu')
    if not os.path.exists(file_path): continue

    observations = []
    with open(file_path, 'r', encoding='utf-8') as f:
        sentence = []
        for line in f:
            if line.strip() == "" and sentence:
                nodes = {int(n[0]): int(n[6]) for n in sentence if n[0].isdigit()}
                for dep, head in nodes.items():
                    if head == 0: continue
                    start, end = min(dep, head), max(dep, head)
                    dist = end - start
                    if dist <= 1: continue

                counts = {'H': 0, 'D': 0, 'I': 0}
                for i in range(start + 1, end):
                    if i in nodes:
                        if nodes[i] == head: counts['H'] += 1
                        elif nodes[i] == dep: counts['D'] += 1
                        else: counts['I'] += 1

                for cat in ['H', 'D', 'I']:
                    observations.append({'count': counts[cat], 'category': cat, 'log_dist': np.log(dist)})
                sentence = []
            elif not line.startswith("#"):
                sentence.append(line.strip().split(" "))

    if observations:
        df_lang = pd.DataFrame(observations)
        model = smf.glm(formula="count ~ category - 1",
            data=df_lang, family=sm.families.Poisson(),
            offset=df_lang['log_dist']).fit()

        conf = model.conf_int()
        for cat in ['H', 'D', 'I']:
            p_name = f'category{cat}'
            plot_data.append({
                'Language': lang, 'Category': cat,
                'Beta': model.params[p_name],
                'Lower': conf.loc[p_name, 0], 'Upper': conf.loc[p_name, 1],
                'IRR': np.exp(model.params[p_name])
            })

df_plot = pd.DataFrame(plot_data)

plt.figure(figsize=(10, 14))
sns.set_theme(style="whitegrid")
colors = {'H': '#1f77b4', 'D': '#2ca02c', 'I': '#d62728'}
for cat in ['H', 'D', 'I']:
    sub = df_plot[df_plot['Category'] == cat]
    plt.errorbar(sub['Beta'], sub['Language'],
        xerr=[sub['Beta'] - sub['Lower'], sub['Upper'] - sub['Beta']],
        fmt='o', label=f'Category {cat}', color=colors[cat], alpha=0.8, capsizes=3)

plt.axvline(0, color='black', linestyle='--', alpha=0.6)
plt.title('Forest Plot: Log-Rate Coefficients (Beta) across 20 Languages', fontsize=14)
plt.xlabel('Log-Rate Coefficient (Beta)')
plt.legend(title='Intervener Role')

```



```

plt.tight_layout()
plt.savefig(os.path.join(output_dir, 'forest_plot_betas.png'))

plt.figure(figsize=(16, 7))
sns.barplot(data=df_plot, x='Language', y='IRR', hue='Category', palette='muted')
plt.axhline(1, color='red', linestyle='--', label='Neutral Baseline')
plt.title('Incidence Rate Ratio (IRR) by Structural Role', fontsize=14)
plt.ylabel('IRR (Exp(Beta))')
plt.xticks(rotations=45)
plt.legend(title='Role')
plt.tight_layout()
plt.savefig(os.path.join(output_dir, 'irr_grouped_barplot.png'))

pivot_slope = df_plot.pivot(index='Language', columns='Category', values='Beta')
plt.figure(figsize=(10, 10))
cat_order = ['I', 'D', 'H']
cat_labels = ['Independent', 'Dependent', 'Head']
for lang in pivot_slope.index:
    y_vals = [pivot_slope.loc[lang, c] for c in cat_order]
    plt.plot(cat_labels, y_vals, marker='o', alpha=0.4, linewidth=1.5)
    plt.text(2.05, y_vals[2], lang, fontsize=9, alpha=0.8)

plt.title('The Gatekeeper Hierarchy: Universal Suppression Ranking', fontsize=14)
plt.ylabel('Beta (Log-Rate of Intervention)')
plt.grid(True, linestyle=':', alpha=0.6)
plt.tight_layout()
plt.savefig(os.path.join(output_dir, 'structural_ranking_slopegraph.png'))

```

Appendix 3 : Subtree_Weight_Analysis:

Heatmap

```

import os
import pandas as pd
import seaborn as sns
import matplotlib.pyplot as plt
from conllu import parse_incr
from google.colab import drive
import io

drive_root = "/content/drive/MyDrive/Course_Project"
save_dir = os.path.join(drive_root, "Subtree_Weight_Analysis")

if not os.path.exists(save_dir):
    os.makedirs(save_dir)

if not os.path.exists("/content/drive"):
    drive.mount('/content/drive')

def get_subtree_weights(sentence):
    weights = {}
    for word in sentence:
        if isinstance(word['id'], int):
            weights[word['id']] = 1
        else:
            continue

    heads = {word['id']: word['head'] for word in sentence if isinstance(word['id'], int)}

    ids = sorted(weights.keys(), reverse=True)

    for i in ids:
        h = heads.get(i)
        if h is not None and h in weights:
            weights[h] += weights[i]
    return weights

def analyze_weight_filter(path):
    intervener_weights = []

    with io.open(path, "r", encoding="utf-8") as f:
        for sentence in parse_incr(f):
            sent_weights = get_subtree_weights(sentence)

            for word in sentence:
                if not isinstance(word['id'], int) or not isinstance(word['head'], int):
                    continue

                h_id = word['head']
                d_id = word['id']

                if h_id == 0 or h_id is None:
                    continue

                left, right = min(h_id, d_id), max(h_id, d_id)
                for i in range(left + 1, right):
                    if i in sent_weights:
                        intervener_weights.append(sent_weights[i])

    return intervener_weights

heatmap_records = []
conllu_files = [f for f in os.listdir(drive_root) if f.endswith('.conllu')]

for file_name in conllu_files:
    lang_name = file_name.split('_')[0]
    full_path = os.path.join(drive_root, file_name)

    print("Processing Weight Filter for: " + lang_name)
    intv_data = analyze_weight_filter(full_path)

    if not intv_data:
        continue

    dist = pd.Series(intv_data).value_counts(normalize=True).sort_index()
    dist.name = lang_name
    heatmap_records.append(dist)

matrix_df = pd.concat(heatmap_records, axis=1).fillna(0).T
matrix_df = matrix_df.iloc[:, :3]
matrix_df.columns = ["Weight 1", "Weight 2", "Weight 3"]

plt.figure(figsize=(12, 10))
sns.heatmap(matrix_df, annot=True, cmap="YlGnBu", fmt=".2f")

```

```
plt.title("Proportion of Intervener Weights by Language")
plt.xlabel("Subtree Weight (Nodes)")
plt.ylabel("Language")
plt.savefig(os.path.join(save_dir, "weight_filter_heatmap.png"))
plt.show()
```

Hypothesis Testing:

```
import os
import pandas as pd
import numpy as np
import statsmodels.api as sm
import random
import io
import math
import warnings
from conllu import parse_incr
from google.colab import drive
from scipy.stats import norm

warnings.filterwarnings('ignore')

drive_root = "/content/drive/MyDrive/Course_Project"
save_dir = os.path.join(drive_root, "Subtree_Weight_Analysis")

if not os.path.exists(save_dir):
    os.makedirs(save_dir)

if not os.path.exists("/content/drive"):
    drive.mount('/content/drive')

def get_subtree_weights(sentence):
    weights = {}
    for word in sentence:
        if isinstance(word['id'], int):
            weights[word['id']] = 1
        else:
            continue

    heads = {}
    for word in sentence:
        if isinstance(word['id'], int):
            head_val = word['head']
            if isinstance(head_val, int):
                heads[word['id']] = head_val
            elif head_val is None:
                heads[word['id']] = 0
        else:
            try:
                heads[word['id']] = int(head_val)
            except (ValueError, TypeError):
                heads[word['id']] = 0

    ids = sorted(weights.keys(), reverse=True)

    for i in ids:
        h = heads.get(i)
        if isinstance(h, int) and h in weights:
            weights[h] += weights[i]
    return weights

def extract_obs(sentence, weights, shuffle=False):
    nodes = [word['id'] for word in sentence if isinstance(word['id'], int)]
    if shuffle:
        shf = list(nodes)
        random.shuffle(shf)
        pos = {node: i for i, node in enumerate(shf)}
    else:
        pos = {node: i for i, node in enumerate(nodes)}

    obs = []
    for word in sentence:
        if not isinstance(word['id'], int) or not isinstance(word['head'], int):
            continue

        h_id, d_id = word['head'], word['id']
        if h_id == 0 or h_id is None: continue

        if h_id not in pos or d_id not in pos: continue

        p1, p2 = pos[h_id], pos[d_id]
        l, r = min(p1, p2), max(p1, p2)
        dist = r - l
        if dist > 1:
            for n_id, p_val in pos.items():
                if l < p_val < r:
                    obs.append({'dist': dist, 'weight': weights[n_id]})
    return obs

def run_model(data):
    if not data: return None, None, None
    df = pd.DataFrame(data)
    counts = df.groupby(['dist', 'weight']).size().reset_index(name='y')
    counts['log_dist'] = np.log(counts['dist'])
    X = sm.add_constant(counts[['weight']])
    try:
        res = sm.GLM(counts['y'], X, family=sm.families.Poisson(), offset=counts['log_dist']).fit()
        return res.params['weight'], res.bse['weight'], res.tvalues['weight']
    except:
        return None, None, None

conllu_files = [f for f in os.listdir(drive_root) if f.endswith('.conllu')]
all_results = []

header = "{<6} | {<8} | {<8} | {<8} | {<12}"
print(header.format("Lang", "Beta_R", "Wald_Z", "Z_Diff", "Conclusion"))
print("-" * 55)

for f_name in conllu_files:
    lang = f_name.split('.')[0]
    path = os.path.join(drive_root, f_name)
    r_obs, s_obs = [], []
    with io.open(path, "r", encoding="utf-8") as f:
        for sent in parse_incr(f):
            w = get_subtree_weights(sent)
            r_obs.extend(extract_obs(sent, w, False))
            s_obs.extend(extract_obs(sent, w, True))
```

```

r_b, r_se, r_z = run_model(r_obs)
s_b, s_se, s_z = run_model(s_obs)

if r_b is not None and s_b is not None:
    z_diff = (r_b - s_b) / math.sqrt(r_se**2 + s_se**2)

    test1 = r_z < -1.645
    test2 = z_diff < -1.645

    conc = "Efficient" if (test1 and test2) else "Insignificant"

    all_results.append({
        'Language': lang,
        'Real_Beta': r_b,
        'Real_Wald_Z': r_z,
        'Rand_Beta': s_b,
        'Rand_Wald_Z': s_z,
        'Z_Diff': z_diff,
        'Conclusion': conc
    })
    print(header.format(lang, round(r_b, 3), round(r_z, 2), round(z_diff, 2), conc))

pd.DataFrame(all_results).to_csv(os.path.join(save_dir, "dual_test_results.csv"), index=False)

```

Bar Plot for Real Beta Coefficients:

```

import os
import pandas as pd
import numpy as np
import statsmodels.api as sm
import random
import io
import math
import warnings
import matplotlib.pyplot as plt
import seaborn as sns
from conllu import parse_incr
from google.colab import drive
from scipy.stats import norm

warnings.filterwarnings('ignore')

drive_root = "/content/drive/MyDrive/Course_Project"
save_dir = os.path.join(drive_root, "Subtree_Weight_Analysis")

if not os.path.exists(save_dir):
    os.makedirs(save_dir)

if not os.path.exists("/content/drive"):
    drive.mount("/content/drive")

def get_subtree_weights(sentence):
    weights = {}
    for word in sentence:
        if isinstance(word['id'], int):
            weights[word['id']] = 1
        else:
            continue

    heads = {}
    for word in sentence:
        if isinstance(word['id'], int):
            head_val = word['head']
            if isinstance(head_val, int):
                heads[word['id']] = head_val
            elif head_val is None:
                heads[word['id']] = 0
            else:
                try:
                    heads[word['id']] = int(head_val)
                except (ValueError, TypeError):
                    heads[word['id']] = 0

    ids = sorted(weights.keys(), reverse=True)

    for i in ids:
        h = heads.get(i)
        if isinstance(h, int) and h in weights:
            weights[h] += weights[i]
    return weights

def extract_obs(sentence, weights, shuffle=False):
    nodes = [word['id'] for word in sentence if isinstance(word['id'], int)]
    if shuffle:
        shf = list(nodes)
        random.shuffle(shf)
        pos = {node: i for i, node in enumerate(shf)}
    else:
        pos = {node: i for i, node in enumerate(nodes)}

    obs = []
    for word in sentence:
        if not isinstance(word['id'], int) or not isinstance(word['head'], int):
            continue

        h_id, d_id = word['head'], word['id']
        if h_id == 0 or h_id is None: continue

        if h_id not in pos or d_id not in pos: continue

        p1, p2 = pos[h_id], pos[d_id]
        l, r = min(p1, p2), max(p1, p2)
        dist = r - l
        if dist > 1:
            for n_id, p_val in pos.items():
                if l < p_val < r:
                    obs.append({'dist': dist, 'weight': weights[n_id]})
    return obs

def run_model(data):
    if not data: return None, None, None
    df = pd.DataFrame(data)
    counts = df.groupby(['dist', 'weight']).size().reset_index(name='y')
    counts['log_dist'] = np.log(counts['dist'])
    X = sm.add_constant(counts[['weight']])
    try:
        res = sm.GLM(counts['y'], X, family=sm.families.Poisson(), offset=counts['log_dist']).fit()
        return res.params['weight'], res.bse['weight'], res.tvalues['weight']
    except:
        return None, None, None

```

```

except:
    return None, None, None

conllu_files = [f for f in os.listdir(drive_root) if f.endswith('.conllu')]
all_results = []

header = "{<6} | {<8} | {<8} | {<8} | {<12}"
print(header.format("Lang", "Beta_R", "Wald_Z", "Z_Diff", "Conclusion"))
print("." * 55)

for f_name in conllu_files:
    lang = f_name.split('.')[0]
    path = os.path.join(drive_root, f_name)
    r_obs, s_obs = [], []
    with io.open(path, "r", encoding="utf-8") as f:
        for sent in parse_incr(f):
            w = get_subtree_weights(sent)
            r_obs.extend(extract_obs(sent, w, False))
            s_obs.extend(extract_obs(sent, w, True))

    r_b, r_se, r_z = run_model(r_obs)
    s_b, s_se, s_z = run_model(s_obs)

    if r_b is not None and s_b is not None:
        z_diff = (r_b - s_b) / math.sqrt(r_se**2 + s_se**2)

        test1 = r_z < -1.645
        test2 = z_diff < -1.645

        conc = "Efficient" if (test1 and test2) else "Insignificant"

    all_results.append({
        'Language': lang,
        'Real_Beta': r_b,
        'Real_Wald_Z': r_z,
        'Rand_Beta': s_b,
        'Rand_Wald_Z': s_z,
        'Z_Diff': z_diff,
        'Conclusion': conc
    })
    print(header.format(lang, round(r_b, 3), round(r_z, 2), round(z_diff, 2), conc))

df_final = pd.DataFrame(all_results)
df_final.to_csv(os.path.join(save_dir, "dual_test_results.csv"), index=False)

plt.figure(figsize=(14, 7))
sns.set(style="whitegrid")
plot_data = df_final.sort_values("Real_Beta")
sns.barplot(x="Language", y="Real_Beta", data=plot_data, palette="coolwarm")
plt.title("Comparison of Structural Weight Decay (Beta_R) across Languages")
plt.ylabel("Real Beta Coefficient")
plt.xlabel("Language Code")
plt.xticks(rotation=45)

plot_save_path = os.path.join(save_dir, "beta_r_distribution.png")
plt.savefig(plot_save_path, bbox_inches='tight', dpi=300)
plt.show()

```

Comparison of Randomized Structural Weight Decay (Beta_Random) across Languages:

```

import os
import pandas as pd
import numpy as np
import statsmodels.api as sm
import random
import io
import math
import warnings
import matplotlib.pyplot as plt
import seaborn as sns
from pathlib import Path
from conllu import parse_incr
from google.colab import drive
from scipy.stats import norm

warnings.filterwarnings('ignore')

def setup_environment(root_path):
    base_path = Path(root_path)
    output_path = base_path / "Subtree_Weight_Analysis"
    output_path.mkdir(parents=True, exist_ok=True)

    if not Path("/content/drive").exists():
        drive.mount('/content/drive')

    return base_path, output_path

def get_subtree_weights(sentence):
    weights = {word['id']: 1 for word in sentence if isinstance(word['id'], int)}
    heads = {word['id']: (int(word['head']) if isinstance(word['head'], (int, float)) else 0)
              for word in sentence if isinstance(word['id'], int)}

    for i in sorted(weights.keys(), reverse=True):
        h = heads.get(i, 0)
        if h in weights:
            weights[h] += weights[i]
    return weights

def extract_obs(sentence, weights, shuffle=False):
    nodes = [word['id'] for word in sentence if isinstance(word['id'], int)]
    if shuffle:
        shuffled = random.sample(nodes, len(nodes))
        pos = {node: i for i, node in enumerate(shuffled)}
    else:
        pos = {node: i for i, node in enumerate(nodes)}

    observations = []
    for word in sentence:
        if not isinstance(word['id'], int) or not isinstance(word['head'], int):
            continue

```

```

h_id, d_id = word['head'], word['id']
if h_id == 0 or h_id not in pos or d_id not in pos:
    continue

p1, p2 = pos[h_id], pos[d_id]
l, r = min(p1, p2), max(p1, p2)
dist = r - l

if dist > 1:
    observations.extend([{'dist': dist, 'weight': weights[n_id]}
                        for n_id, p_val in pos.items() if l < p_val < r])
return observations

def run_model(data):
    if not data:
        return None, None, None

    df = pd.DataFrame(data)
    counts = df.groupby(['dist', 'weight']).size().reset_index(name='y')
    counts['log_dist'] = np.log(counts['dist'])

    X = sm.add_constant(counts[['weight']])
    try:
        model = sm.GLM(counts['y'], X, family=sm.families.Poisson(), offset=counts['log_dist']).fit()
        return model.params['weight'], model.bse['weight'], model.tvalues['weight']
    except Exception:
        return None, None, None

def main():
    drive_root, save_dir = setup_environment("/content/drive/MyDrive/Course_Project")
    conllu_files = list(drive_root.glob(*.conllu))

    results = []
    print(f"{'Lang':<6} | {'Beta_S':<8} | {'Wald_Z':<8} | {'Z_Diff':<8} | {'Conclusion':<12}")
    print("-" * 55)

    for file_path in conllu_files:
        lang = file_path.stem.split('_')[0]
        real_obs, rand_obs = [], []

        with open(file_path, "r", encoding="utf-8") as f:
            for sent in parse_incr(f):
                w = get_subtree_weights(sent)
                real_obs.extend(extract_obs(sent, w, False))
                rand_obs.extend(extract_obs(sent, w, True))

        r_b, r_se, r_z = run_model(real_obs)
        s_b, s_se, s_z = run_model(rand_obs)

        if r_b is not None and s_b is not None:
            z_diff = (r_b - s_b) / math.sqrt(r_se**2 + s_se**2)
            is_efficient = r_z < -1.645 and z_diff < -1.645
            conclusion = "Efficient" if is_efficient else "Insignificant"

            results.append({
                'Language': lang, 'Real_Beta': r_b, 'Real_Wald_Z': r_z,
                'Rand_Beta': s_b, 'Rand_Wald_Z': s_z, 'Z_Diff': z_diff,
                'Conclusion': conclusion
            })
        print(f"{'lang':<6} | {'s_b':>8.3f} | {'s_z':>8.2f} | {'z_diff':>8.2f} | {'conclusion':<12}")

    if not results:
        return

    df_final = pd.DataFrame(results)
    df_final.to_csv(save_dir / "dual_test_results.csv", index=False)

    plt.figure(figsize=(14, 7))
    sns.set_theme(style="whitegrid")
    plot_data = df_final.sort_values("Rand_Beta")

    sns.barplot(data=plot_data, x="Language", y="Rand_Beta", hue="Language", palette="viridis", legend=False)

    plt.title("Comparison of Randomized Structural Weight Decay (Beta_Random) across Languages", fontsize=14)
    plt.ylabel("Random Beta Coefficient", fontsize=12)
    plt.xlabel("Language Code", fontsize=12)
    plt.xticks(rotation=45)

    plt.savefig(save_dir / "beta_random_distribution.png", bbox_inches='tight', dpi=300)
    plt.show()

if __name__ == "__main__":
    main()

```

Appendix 4 : UPOS Quantitative Analysis:

Heatmap:

```

import os
import networkx as nx
import conllu
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns
from google.colab import drive
import shutil

if os.path.ismount("/content/drive"):
    try:
        drive.flush_and_unmount()

```

```

except:
    pass

if os.path.isdir('/content/drive') and os.listdir('/content/drive'):
    for item in os.listdir('/content/drive'):
        item_path = os.path.join('/content/drive', item)
        try:
            if os.path.isfile(item_path) or os.path.islink(item_path):
                os.unlink(item_path)
            elif os.path.isdir(item_path):
                shutil.rmtree(item_path)
        except:
            pass

drive.mount('/content/drive', force_remount=True)

drive_path = "/content/drive/MyDrive/Course_Project"
data_path = drive_path
output_path = os.path.join(drive_path, "UPOS_Analysis")

os.makedirs(output_path, exist_ok=True)

lang_map = {
    'EN': 'English', 'HI': 'Hindi', 'DE': 'German', 'FR': 'French', 'ES': 'Spanish',
    'IT': 'Italian', 'RU': 'Russian', 'ZH': 'Chinese', 'JA': 'Japanese', 'KO': 'Korean',
    'AR': 'Arabic', 'TR': 'Turkish', 'FI': 'Finnish', 'EL': 'Greek', 'SV': 'Swedish',
    'PL': 'Polish', 'DA': 'Danish', 'NL': 'Dutch', 'PT': 'Portuguese', 'RO': 'Romanian'
}

with open("Measures_rand.py", "w") as f:
    f.write("""
import networkx as nx

class Compute_measures_rand(object):
    def __init__(self, tree, root):
        self.tree = tree
        self.root = root

    def get_intervenors(self, edge):
        nodes = sorted([n for n in self.tree.nodes if n != self.root])
        h, d = edge
        if h > d:
            return [n for n in nodes if d < n < h]
        return [n for n in nodes if h < n < d]
""")

from Measures_rand import Compute_measures_rand

def conduct_pos_analysis(directory):
    files = sorted([f for f in os.listdir(directory) if f.endswith('.conllu')])
    master_data = []

    for file in files:
        lang_code = file.split('.')[0].upper()
        file_path = os.path.join(directory, file)
        full_name = lang_map.get(lang_code, lang_code)

        try:
            with open(file_path, "r", encoding="utf-8") as f:
                for sent in conllu.parse_incr(f):
                    G = nx.DiGraph()
                    G.add_node(0, upos="ROOT")

                    for t in sent:
                        if isinstance(t['id'], int):
                            G.add_node(t['id'], upos=t['upostag'])

                    for t in sent:
                        if isinstance(t['id'], int):
                            G.add_edge(t['head'], t['id'])

                    measurer = Compute_measures_rand(G, 0)

                    for h, d in G.edges():
                        if h == 0:
                            continue

                        intervener_ids = measurer.get_intervenors((h, d))

                        for int_id in intervener_ids:
                            tag = G.nodes[int_id].get('upos', 'UNKNOWN')
                            master_data.append({'Language': full_name, "UPOS": tag})

        except:
            pass

    return pd.DataFrame(master_data)

df_pos = conduct_pos_analysis(data_path)

heatmap_data = df_pos.groupby(['Language', 'UPOS']).size().unstack(fill_value=0)
heatmap_normalized = heatmap_data.div(heatmap_data.sum(axis=1), axis=0).round(2)

plt.figure(figsize=(20, 12))

sns.heatmap(
    heatmap_normalized,
    cmap="YlOrRd",
    annot=True,
    fmt=".2f",
    linewidths=0.5,
    linecolor='gray',
    annot_kws={"size": 8}
)

plt.title("Intervener Distribution Across UPOS Tags (All Languages)", fontsize=18)
plt.xlabel("UPOS Tags", fontsize=14)
plt.ylabel("Languages", fontsize=14)

plt.xticks(rotation=45, ha='right')
plt.yticks(rotation=0)

heatmap_path = os.path.join(output_path, "upos_heatmap_annotated.png")
plt.savefig(heatmap_path, dpi=300, bbox_inches='tight')

plt.show()

heatmap_data.to_csv(os.path.join(output_path, "upos_heatmap_raw.csv"))
heatmap_normalized.to_csv(os.path.join(output_path, "upos_heatmap_normalized.csv"))

```

UPOS GLM Summary:

```
import os
import pandas as pd
import statsmodels.api as sm
import statsmodels.formula.api as smf
import numpy as np
import io

drive_path = "/content/drive/MyDrive/Course_Project"
output_path = os.path.join(drive_path, "UPOS_Analysis")

lang_map = {
    'EN': 'English', 'HI': 'Hindi', 'DE': 'German', 'FR': 'French', 'ES': 'Spanish',
    'IT': 'Italian', 'RU': 'Russian', 'ZH': 'Chinese', 'JA': 'Japanese', 'KO': 'Korean',
    'AR': 'Arabic', 'TR': 'Turkish', 'FI': 'Finnish', 'EL': 'Greek', 'SV': 'Swedish',
    'PL': 'Polish', 'DA': 'Danish', 'NL': 'Dutch', 'PT': 'Portuguese', 'RO': 'Romanian'
}

def get_counts(file_path):
    obs = []
    with io.open(file_path, 'r', encoding='utf-8') as f:
        sent = []
        for line in f:
            line = line.strip()
            if not line:
                if sent:
                    tag_map = {w['id']: w['upos'] for w in sent}
                    for w in sent:
                        h, d = w['head'], w['id']
                        if h == 0: continue
                        dist = abs(h - d)
                        start, end = min(h, d), max(h, d)
                        for i in range(start + 1, end):
                            tag = tag_map.get(i)
                            if tag:
                                obs.append({'Distance': dist, 'Tag': tag})
                    sent = []
                continue
            if line.startswith('#'): continue
            p = line.split('\t')
            if '.' in p[0] or '.' in p[0]: continue
            sent.append({'id': int(p[0]), 'upos': p[3], 'head': int(p[6])})

    df = pd.DataFrame(obs)
    return df.groupby(['Distance', 'Tag']).size().reset_index(name='Count')

files = sorted([f for f in os.listdir(drive_path) if f.endswith('.conllu')])
all_lang_results = []

for f_name in files:
    lang_code = f_name.split('.')[0].upper()
    lang_name = lang_map.get(lang_code, lang_code)

    try:
        data = get_counts(os.path.join(drive_path, f_name))
        model = smf.glm("Count ~ Distance + C(Tag, Treatment(reference='VERB'))",
                        data=data,
                        family=sm.families.Poisson()).fit()

        row = {'Language': lang_name, 'Beta_Nough': model.params['Intercept']}

        for param_name, value in model.params.items():
            if 'T.' in param_name:
                tag = param_name.split('.')[1][:-1]
                row['IRR_ ' + tag] = np.exp(value)

        row['IRR_VERB'] = 1.0
        all_lang_results.append(row)
        print("Processed: {}".format(lang_name))

    except Exception as e:
        print("Failed {}: {}".format(lang_name, str(e)))

final_df = pd.DataFrame(all_lang_results)
cols = ['Language', 'Beta_Nough'] + [c for c in final_df.columns if c.startswith('IRR_')]
final_df = final_df[cols].fillna(0)

final_df.to_csv(os.path.join(output_path, "upos_glm_summary_table.csv"), index=False)

print("\n--- Final Summary Table (First 10 Rows) ---")
print(final_df.head(10))
```

Plot For Global Incident Rate Ratios of UPOS tags for all languages combined:

```
import os
import pandas as pd
import statsmodels.api as sm
import statsmodels.formula.api as smf
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns
import io

drive_path = "/content/drive/MyDrive/Course_Project"
output_path = os.path.join(drive_path, "UPOS_Analysis")

def extract_global_data(directory):
    all_obs = []
    files = [f for f in os.listdir(directory) if f.endswith('.conllu')]
    print("Parsing {} files...".format(len(files)))

    for filename in files:
        with io.open(os.path.join(directory, filename), 'r', encoding='utf-8') as f:
            sent = []
            for line in f:
                line = line.strip()
                if not line:
                    if sent:
                        tag_map = {w['id']: w['upos'] for w in sent}
                        for w in sent:
                            h, d = w['head'], w['id']
                            if h == 0: continue
                            dist = abs(h - d)
                            start, end = min(h, d), max(h, d)
                            for i in range(start + 1, end):
                                if i in tag_map:
                                    all_obs.append({'Distance': dist, 'Tag': tag_map[i]})
                    sent = []
```



```

        sent = []
        continue
        if line.startswith("#"): continue
        p = line.split('t')
        if ':' in p[0] or ':' in p[0]: continue
        sent.append({'id': int(p[0]), 'upos': p[3], 'head': int(p[6])})

df = pd.DataFrame(all_obs)
return df.groupby(['Distance', 'Tag']).size().reset_index(name='Count')

global_counts = extract_global_data(drive_path)

model = smf.glm("Count ~ Distance + C(Tag, Treatment(reference='VERB'))",
               data=global_counts,
               family=sm.families.Poisson()).fit()

results = pd.DataFrame({'Beta': model.params})
results['IRR'] = np.exp(results['Beta'])

results = results.reset_index()
results['UPOS'] = results['index'].apply(lambda x: x.split(':')[1][:-1] if 'T' in x else ('VERB' if 'Intercept' in x else x))
results = results[results['index'] != 'Distance']
results.at[results[results['UPOS'] == 'VERB'].index[0], 'IRR'] = 1.0

results = results.sort_values(by='IRR', ascending=False)

plt.figure(figsize=(14, 10))
sns.set_style("whitegrid")
palette = sns.color_palette("YlOrRd_r", len(results))

ax = sns.barplot(x='IRR', y='UPOS', data=results, hue='UPOS', palette=palette, legend=False)
plt.axvline(x=1, color='black', linestyle='--', linewidth=2, label=Baseline (VERB))

for i, p in enumerate(ax.patches):
    ax.annotate("%2f" % p.get_width(), (p.get_width(), p.get_y() + p.get_height() / 2),
               xytext=(5, 0), textcoords='offset points', ha='left', va='center', fontweight='bold')

plt.title("Global Incident Rate Ratios (IRRs) of Intervening UPOS Tags\n(Pooled Analysis of All Languages)", fontsize=18)
plt.xlabel("Incident Rate Ratio (Likelihood relative to VERB)", fontsize=14)
plt.ylabel("UPOS Tag", fontsize=14)
plt.legend(loc='lower right')

plt.savefig(os.path.join(output_path, "global_upos_dominance.png"), dpi=300, bbox_inches='tight')
results.to_csv(os.path.join(output_path, "global_upos_results.csv"), index=False)

print("Global Analysis Complete. Beta_0 (Intercept): {:.4f}".format(model.params['Intercept']))

```

Hypothesis Testing:

```

import os
import pandas as pd
import statsmodels.api as sm
import statsmodels.formula.api as smf
import numpy as np
import io
from scipy.stats import chi2
from google.colab import drive

drive.mount('/content/drive', force_remount=True)

drive_path = "/content/drive/MyDrive/Course_Project"
output_path = os.path.join(drive_path, "UPOS_Analysis")
if not os.path.exists(output_path):
    os.makedirs(output_path)

lang_map = {
    'EN': 'English', 'HI': 'Hindi', 'DE': 'German', 'FR': 'French', 'ES': 'Spanish',
    'IT': 'Italian', 'RU': 'Russian', 'ZH': 'Chinese', 'JA': 'Japanese', 'KO': 'Korean',
    'AR': 'Arabic', 'TR': 'Turkish', 'FI': 'Finnish', 'EL': 'Greek', 'SV': 'Swedish',
    'PL': 'Polish', 'DA': 'Danish', 'NL': 'Dutch', 'PT': 'Portuguese', 'RO': 'Romanian'
}

def analyze_language(file_path):
    obs = []
    with io.open(file_path, 'r', encoding='utf-8') as f:
        sent = []
        for line in f:
            line = line.strip()
            if not line:
                if sent:
                    id_map = {w['id']: w['upos'] for w in sent}
                    for w in sent:
                        h, d = w['head'], w['id']
                        if h == 0: continue
                        dist, start, end = abs(h - d), min(h, d), max(h, d)
                        for i in range(start + 1, end):
                            if i in id_map:
                                obs.append({'Distance': dist, 'Tag': id_map[i]})
                    sent = []
                continue
            if line.startswith("#"): continue
            p = line.split('t')
            if ':' in p[0] or ':' in p[0]: continue
            sent.append({'id': int(p[0]), 'upos': p[3], 'head': int(p[6])})

df = pd.DataFrame(obs)
counts = df.groupby(['Distance', 'Tag']).size().reset_index(name='Count')
return counts

files = sorted([f for f in os.listdir(drive_path) if f.endswith('.conllu')])
final_results = []

for filename in files:
    lang_code = filename.split('.')[0].upper()
    lang_name = lang_map.get(lang_code, lang_code)
    print("Testing: {}".format(lang_name))

    try:
        data = analyze_language(os.path.join(drive_path, filename))

        m0 = smf.glm("Count ~ Distance", data=data, family=sm.families.Poisson()).fit()
        m1 = smf.glm("Count ~ Distance + C(Tag, Treatment(reference='VERB'))",
                    data=data, family=sm.families.Poisson()).fit()

        lrt_stat = 2 * (m1.llf - m0.llf)
        p_lrt = chi2.sf(lrt_stat, df=len(m1.params) - len(m0.params))
        reject_lrt = "Yes" if p_lrt < 0.05 else "No"
    
```

UPOS Distribution for Random Distribution of Words while retaining the UPOS identity for each node:

```

        if w['head'] != 0 and w['head'] in id_map:
            w['head'] = id_map[w['head']]

tag_map = {w['id']: w['upos'] for w in sent}
for w in sent:
    h, d = w['head'], w['id']
    if h == 0: continue

    dist = abs(h - d)
    start, end = min(h, d), max(h, d)

    for i in range(start + 1, end):
        if i in tag_map:
            all_obs.append({'Distance': dist, 'Tag': tag_map[i]})
    sent = []
    continue

    if line.startswith('#'): continue
    p = line.split(' ')
    if ':' in p[0] or ':' in p[0]: continue
    sent.append({'id': int(p[0]), 'upos': p[3], 'head': int(p[6])})

df = pd.DataFrame(all_obs)
if df.empty:
    return df
return df.groupby(['Distance', 'Tag']).size().reset_index(name='Count')

global_counts = extract_global_data(drive_path, shuffle_words=True)

if not global_counts.empty:
    model = smf.glm("Count ~ Distance + C(Tag, Treatment(reference='VERB'))",
                    data=global_counts,
                    family=sm.families.Poisson()).fit()

results = pd.DataFrame({'Beta': model.params})
results['IRR'] = np.exp(results['Beta'])

results = results.reset_index()
results['UPOS'] = results['index'].apply(lambda x: x.split(' ')[-1] if 'T' in x else ('VERB' if 'Intercept' in x else x))
results[results['index'] != 'Distance']

verb_idx = results[results['UPOS'] == 'VERB'].index
if not verb_idx.empty:
    results.at[verb_idx[0], 'IRR'] = 1.0

results = results.sort_values(by='IRR', ascending=False)

plt.figure(figsize=(14, 10))
sns.set_style("whitegrid")
palette = sns.color_palette("YlOrRd_r", len(results))

ax = sns.barplot(x='IRR', y='UPOS', data=results, hue='UPOS', palette=palette, legend=False)
plt.axvline(x=1, color='black', linestyle='--', linewidth=2, label='Baseline (VERB)')

for i, p in enumerate(ax.patches):
    width = p.get_width()
    ax.annotate("%2f" % width, (width, p.get_y() + p.get_height() / 2),
                xytext=(5, 0), textcoords='offset points', ha='left', va='center', fontweight='bold')

plt.title("Shuffled Global Incident Rate Ratios (IRRs) of Intervening UPOS Tags", fontsize=18)
plt.xlabel("Incident Rate Ratio (Likelihood relative to VERB)", fontsize=14)
plt.ylabel("UPOS Tag", fontsize=14)
plt.legend(loc='lower right')

plt.savefig(os.path.join(output_path, "shuffled_upos_dominance.png"), dpi=300, bbox_inches='tight')
results.to_csv(os.path.join(output_path, "shuffled_upos_results.csv"), index=False)

print(f"Analysis Complete. Results saved to: {output_path}")
print("Beta_0 (Intercept): {:.4f}".format(model.params['Intercept']))
else:
    print("Failed-Execution.")

```