

Primary census: 404 execution blocks, 1651 windows

402 Class A (fine channel, the carrier search) + 1249 Class B (coarse channel)

Trigger → crossings

$T_{\star} \geq 5$ at the stellar position, in a
searched channel $\times$ drift cell

56

52 Class A, 4 Class B

— The line flag is a FLAG, not a disposal: 21 of the 56 crossings
coincide with a catalogued transition, and all 56 go on.

Attribution → unattributed crossings

more than 50 km s^{-1} in the star's own frame
from every catalogued transition

35

— Diagnostics, deciding nothing: 1 of the 35 outranks all 512 control
positions; the visibility fit localises but cannot discriminate
at the trigger.

Recurrence → confirmed signals

present again above the trigger at the predicted
stellar-frame channel, or anywhere within
 $\pm 833 \text{ km s}^{-1}$ of it at any drift, in another block

0

largest $T_{\star}$ 4.71; carriers
above 0.43 of the discovery
amplitude excluded

35 of the 35 unattributed crossings tested, against 425 covering repeat windows: 30
exclusions, 4 withheld on data quality, 1 with no retained flux.

Reserved hold-out, searched with the frozen pipeline

77 blocks reserved before the search, 315 windows: 8 crossings, none outranking
all 512 controls, none confirmed.