Primary census: 407 execution blocks, 1663 windows

405 Class A (fine channel, the carrier search) + 1258 Class B (coarse channel)

Trigger → crossings

$T_\star \geq 5$ at the stellar position, in a searched channel × drift cell

56

52 Class A, 4 Class B

The line flag is a FLAG, not a disposal: 18 of the 56 crossings coincide with a masked transition, and all 56 go on.

Attribution → unattributed crossings

more than 50 km s^{-1} in the star's own frame from every transition of the line mask

38

Diagnostics, deciding nothing: 2 of the 38 outrank all 512 control positions; the visibility fit localises but cannot discriminate at the trigger.

Recurrence → confirmed signals

present again above the trigger at the predicted stellar-frame cell in another block; over the ±833 km s^{-1} searched about it, one trajectory per pair where resolved (7 of 13 pairs) and a count against chance where not

0

largest $T_\star$ 4.71 at any drift

37 of the 38 unattributed crossings tested against 444 repeat-block readings: 33 exclusions and 4 withheld on data quality; 1 retains no flux to transport. The repeat coverage rules out a carrier above a median 0.43 of the discovery amplitude, individually 0.02–1.00; on 7 of them the criterion has under 90 per cent power.

Reserved hold-out, searched with the frozen pipeline

77 blocks held out by a rule fixed before any of them was searched, 315 windows: 8 crossings, none outranking all 512 controls, none confirmed.