Primary census: 407 execution blocks, 1663 windows

405 Class A (fine channel, the carrier search) + 1258 Class B (coarse channel)

Trigger → crossings

$T_\star \geq 5$ at the stellar position, in a searched channel × drift cell

56

52 Class A, 4 Class B

The line flag is a FLAG, not a disposal: 18 of the 56 crossings coincide with a masked transition, 18 attributed, and all 56 go on.

Attribution → unattributed crossings

more than 50 km s^{-1} in the star's own frame from every transition of the line mask

38

Diagnostics, deciding nothing: 2 of the 38 outrank all 512 control positions; the visibility fit localises but cannot discriminate at the trigger.

Recurrence → confirmed signals

present again above the trigger in a separated block: over the ±833 km s^{-1} searched about the crossing, one trajectory per pair where resolved (7 of 13 pairs) and a count against chance where not; and at the one cell the discovery predicts, which tests a carrier whose stellar-frame frequency is unchanged

0

largest $T_\star$ 4.71 at any drift

29 of the 328 covering windows hold a reading above the trigger, against the 28.3 chance predicts; of 13 testable pairs the searched grid separates 1 and leaves 12 unresolved (10 open, 2 edge-limited). At the predicted cell, 37 of the 38 unattributed crossings carry a repeat reading over 444 repeat-block readings: 25 excluded, 8 too shallow to test and 4 withheld on data quality; the 38th retains no flux to transport. The repeat coverage rules out a carrier above a median 0.43 of the discovery amplitude, individually 0.017–0.997, and the criterion has under 90 per cent power on the 8 it leaves untested.

Reserved hold-out, searched with the same pipeline

77 blocks held out by an identifier rule, 315 windows: 8 crossings, none outranking all 512 controls, none confirmed.