

Primary census: 404 execution blocks, 1651 windows

402 Class A (fine channel, the carrier search) + 1249 Class B (coarse channel)

Trigger → crossings

$T_{\star} \geq 5$ at the stellar position, in a
searched channel $\times$ drift cell

56

52 Class A, 4 Class B



The line flag is a FLAG, not a disposal: 18 of the 56 crossings
coincide with a catalogued transition, and all 56 go on.

Attribution → unattributed crossings

more than 50 km s^{-1} in the star's own frame
from every catalogued transition

38



Diagnostics, deciding nothing: 2 of the 38 outrank all 512 control
positions; the visibility fit localises but cannot discriminate
at the trigger.

Recurrence → confirmed signals

present again above the trigger at the predicted
stellar-frame cell in another block; over the
 $\pm 833 \text{ km s}^{-1}$ searched about it, one trajectory
per pair where resolved (7 of 13 pairs) and a
count against chance where not

0

largest $T_{\star}$ 4.71
at any drift

38 of the 38 unattributed crossings tested against 444 repeat-block readings: 33 exclusions, 4 withheld
on data quality, 1 with no retained flux. The repeat coverage rules out a carrier above a median
0.43 of the discovery amplitude, individually 0.02–1.00; on 4 of them the criterion has under 90 per cent power.

Reserved hold-out, searched with the frozen pipeline

77 blocks reserved before the search, 315 windows: 8 crossings, none outranking
all 512 controls, none confirmed.