

Improving AFB

*Note: Sub-titles are not captured in Xplore and should not be used

1st Given Name Surname
dept. name of organization (of Aff.)
name of organization (of Aff.)
City, Country
email address or ORCID

2nd Given Name Surname
dept. name of organization (of Aff.)
name of organization (of Aff.)
City, Country
email address or ORCID

3rd Given Name Surname
dept. name of organization (of Aff.)
name of organization (of Aff.)
City, Country
email address or ORCID

4th Given Name Surname
dept. name of organization (of Aff.)
name of organization (of Aff.)
City, Country
email address or ORCID

5th Given Name Surname
dept. name of organization (of Aff.)
name of organization (of Aff.)
City, Country
email address or ORCID

6th Given Name Surname
dept. name of organization (of Aff.)
name of organization (of Aff.)
City, Country
email address or ORCID

Abstract—This document is a model and instructions for \LaTeX . This and the `IEEEtran.cls` file define the components of your paper [title, text, heads, etc.]. ***CRITICAL: Do Not Use Symbols, Special Characters, Footnotes, or Math in Paper Title or Abstract.**

Index Terms—component, formatting, style, styling, insert

I. INTRODUCTION

This document is a model and instructions for \LaTeX . Please observe the conference page limits.

II. BASIC AFB ALGORITHM

III. METHODOLOGY

IV. IMPROVEMENTS

A. Considerations about number of birds

If we study the effects of how different number of birds change the solution of different tours, we learn that less birds seem to yield better solutions. At first this may seem counterintuitive, but there is an intuitive explanation to this:

The basic algorithm defines one iteration as the calculation for the cost of one tour. Now, let a phase of the algorithm denote each bird performing one move. So, in each phase each bird performs one move. If we now use more birds the number of phases the algorithm will run through will decrease, as in each phase the length of more tours will be calculated, which will use up more iterations. Therefore, the more birds we have, the more iterations we will use up per phase, which means the algorithm will run through less phases until it stops. Because in one phase each bird can perform one move, less phases mean each bird can perform less moves. Less moves in turn leads to a less pronounced search of possible solutions, which will make the algorithm worse. This is why the less birds we have, the better the results will be.

Consequently, we aim to improve the bird behaviour, so that each bird needs fewer overall steps to achieve a good solution.

Identify applicable funding agency here. If none, delete this.

B. Swarm behaviour

Currently, if one big bird made the decision to join another bird, he picks one randomly. This means joining any bird without considering how good the position of that bird might be. This contradicts the original idea of the authors that big birds tend to join others that have found a good food source (current solution seems promising). Therefore, we propose that a big will only be able to join the top- b percent of birds that have the lowest current cost. If one chooses the right ratio, we assume that it will automatically nudge the swarm in the direction of the global minimum.

We implement this by storing the indices i of the birds in an ordered integer array ord and introducing a new hyperparameter call b , denoting which of the top- b percent to join. When we select the bird to join to, we draw a random uniform number j between 1 and $b \cdot n$ (n denotes the number of birds) and get the index of the bird to join from the ordered array ($ord[j]$).

The main disadvantage this approach has is that at we need to continuously update ord so that we only join the actual top- b percent at the moment of the move. We decide to update the list after each bird has performed one move, so after each phase.

We test numerous values for b and decide to build on $b = 0.01$ for future improvement, as this strategy yields the best results. For intuitions on why such a low value performs this good, please refer to section "NOCH HINZUFÜGEN".

C. 3-opt Walk

For the walk move the Algorithm uses a modified version of the 2-opt heuristic as a local search. Instead of using 2-opt, we test a 3-opt variant, as this often yields the best solutions under consideration of computational complexity [1]. At the same time we decide to remove the estimation of local similarity from the algorithm, as the authors did not provide any intuitions why this may be beneficial [2].

With this variant, each bird selects the tour with the lowest cost out of the 7 different tours possible in 3-opt. At which 3 points a tour is opened is determined by a random uniform draw of 3 integers, denoting the indices of the tour. Because we need to calculate the length of each of the possible 7 tours, and this happens in just one move of one bird, this move still only costs one iteration.




Fig. 1. [3]

The results can be seen in

D. Delegating Responsibility

Because we are not implementing the 3-opt algorithms by itself, but rather in a swarm algorithm, in which each bird (or agent respectively) can perform this action, the computational complexity will rise by a margin, as seen in Table 1. This is why we test the case where only big birds are able to perform a 3-opt walk, while smaller birds are only capable of the usual 2-opt walk as specified in the paper. This should not only reduce the computational complexity but also pairs well with the assumption that big birds are superior, as only they can join other birds and therefore profit from them.

Furthermore, we also test the inverse approach: Only small birds can perform 3-opt. Based on the results we decide to use 3-opt for big birds from, as this provides the best average improvement in performance with a reasonable increase in computation time.

E. Nearest-Neighbor Initialization

F. Intuitions on Improvements

V. ANALYSIS

A. Metabirds

B. Algorithm Stability

Every swarm algorithm there is usually includes action of agents which can either be classified as exploitation or exploration. Exploitation means an agent uses its current result and tries to improve it, i.e. the agent continues to go into the direction he previously went in the search tree/space. For AFB this can be achieved using the walk move, so a local search. Exploration means an agent tries to find a better solution in the search space that is not necessarily dependent on its current solution, as is the case with exploitation. Therefore, it can be seen as a global search. For AFB, this can be achieved using the fly move.

For a swarm algorithm to deliver a solution which is as close as possible to the global minimum it needs a good balance between exploitation and exploration: It needs to be able to improve a good solution and search for different solutions if the current one does not seem promising.

If exploitation is too dominant, then the algorithm might get stuck in a local minimum, as other solutions (for TSP other, vastly different tours) will not be explored enough, and vice versa.

Because in AFB the balance is mostly specified by the probability of moves walk and fly, and the authors already tuned the algorithm to probabilities that work well in practice, we did not focus on changing this balance. Instead, our focus was mainly on exploitation: Improving a good solution, which is mainly done by the introduction of 3-opt and that big birds can only join successful birds. Even though the latter cannot be seen directly as a local search, it does lead to more (big) birds performing exploitation of the solutions of other birds.

We explicitly do not modify the fly-move, selecting a random tour, as this provides us with a rich selection of other possible solution, which at the same time is completely independent of the current solution (of an agent).

The prior is crucial for the success of our algorithm, because the extreme join-behaviour modeled by the algorithm has a high danger of getting stuck in a local minimum: For our experiments we used just 200 birds, a top-b join of 0.01 therefore means big birds will only join the 2 birds with the best current tour.

Therefore, we get an algorithm that has an empirically tested balance between exploitation and exploration. At the same time, it exploits good solutions in a harsh manner while also being able to switch to completely new solutions if they prove to be better. This process will be repeated until a solution is reached that will be close to the optimum (the algorithm converges).

C. Exploitators and Explorators

The base algorithm consists of two types of agents, small and big birds. With our improvements it may have been noticeable that we separated the roles of both agent types more and more from each other: While small birds can perform the usual 2-opt local search when they are walking, big birds can perform a more powerful 3-opt walk; while small birds will be able to fly, big birds can only perform a walk; and big birds can join other birds. We do this in order to make the components contained in each swarm algorithm, exploration and exploitation, an explicit part of the algorithm by delegating small birds to the role of explorators, and big birds to the role of exploitators:

Small birds are able to access vastly different areas of the search space for possible better solutions than their current one using the fly-move, big birds are able to profit from those that have found the best current solution by joining them and improving that solution using 3-opt (walk).

The circumstance that small birds can also perform exploitation using their own version of the walk-move is owed to

the fact that they otherwise would just jump between random solutions, which wouldn't be a good foundation for the join behaviour of big birds. At the same time, since big birds can also join other big birds and the solutions for small birds would be rather poor, the probability that big birds will exclusively join other big birds would be very high, making small birds essentially useless.

REFERENCES

REFERENCES

- [1] Lin, S. (1965), Computer Solutions of the Traveling Salesman Problem. Bell System Technical Journal, 44: 2245-2269. <https://doi.org/10.1002/j.1538-7305.1965.tb04146.x>
- [2] Jean-Baptiste Lamy. Artificial Feeding Birds (AFB): a new metaheuristic inspired by the behavior of pigeons. Advances in nature-inspired computing and applications, 2019, 10.1007/978-3-319-96451-5_3 . hal-02264232
- [3] Jingyan Sui, Shizhe Ding, Ruizhi Liu, Liming Xu, Dongbo Bu Proceedings of The 13th Asian Conference on Machine Learning, PMLR 157:1301-1316, 2021.