

Activity 1 — Firefox DevTools (10 min)



DELEGATE INSTRUCTIONS:

Open Firefox. Navigate to <http://localhost:3001> (Juice Shop).

Press F12 to open Developer Tools.

Click the Network tab. Reload the page with Ctrl+Shift+R (hard reload).

Look at the list of requests that appeared. Click the first request (the main HTML document).

In the right panel, click Headers. Find and note down: the Server header, the Content-Type, and any security headers like X-Content-Type-Options.

Now click the Response tab. This is the raw HTML your browser received.

Switch to the Sources tab. Find the main JavaScript file. Look for any strings starting with `/api/` — these are internal API endpoints.

Activity 2 — ZAP Proxy HTTP Interception (10 min)



DELEGATE INSTRUCTIONS:

ZAP is already open and Firefox is already configured to use it.

If ZAP is not open, click the ZAP desktop shortcut.

In Firefox, browse to <http://localhost:3000>. You will see ZAP capturing the traffic in the History tab.

Log in to Juice Shop with: email = `admin@juice-sh.op` / password = `admin123`

In ZAP, find the POST request to `/rest/user/login` in the History panel.

Right-click it → Open in Requester. Look at the request body. What credentials did you send?

Look at the response body. Find the token field. This is a JWT (JSON Web Token) — note its format: three base64 parts separated by dots.

Paste the token into <https://jwt.io> (open in a new tab) and decode it. What information is stored in the token payload?