

Question		Marks
06	0	The ant checks if there is a neighbour with a “strongest pheromone” (if the index returned is not -1); If no pheromone is detected (index is -1), the ant selects a random neighbour from the available list; If a pheromone is detected, the ant selects the neighbour cell associated with that strongest pheromone index;

Question		Marks
07	1	$O(n)$ / Linear / $O(\text{Nests.Count})$;
07	2	Because the algorithm is iterating through the collection; Removing an item could cause unintended consequences // skip Pheromones;

Question		Marks
08	1	<code>WorkerAnt // QueenAnt;</code>
08	2	<code>Grid // Ants // Pheromones // Nests //</code> <code>NumberOfRows // NumberOfColumns // StartingFoodInNest //</code> <code>StartingNumberOfFoodCells // StartingNumberOfNests;</code>
08	3	<code>GetCellDetails;</code>
08	4	<code>(2, 4);</code>
08	5	Joining two (or more) strings to form a single (longer) string;

Question		Marks
09	0	Max 2 No calculations would be needed to access Cells at a given coordinate; It makes the data structure closer represent the simulation; It (may) result in faster lookups; It would prevent cells outside of the grid being indexed; (A. reference to wrap-around issues)

Question		Marks
10	0	So that the parent/base class’s variables are initialised correctly;