

Ansible Workshop - Exercises

Automation Platform

Learn to manage and run your Ansible
content in AAP.



3 - Projects & Job Templates

Objective

An Ansible automation controller **Project** is a logical collection of Ansible playbooks. You can manage your playbooks by placing them into a source code management (SCM) system supported by automation controller such as Git or Subversion.

This exercise covers:

- Understanding and using an Ansible automation controller Project
- Using Ansible playbooks kept in a Git repository.
- Creating and using an Ansible Job Template

Guide

Setup Git Repository

For this demonstration we will use playbooks stored in a Git repository:

<https://github.com/ansible/workshop-examples>

A playbook to install the Apache web server has already been committed to the directory **rhel/apache**,
`apache_install.yml`:

```

---  

- name: Apache server installed  

  hosts: web  
  

  tasks:  

  - name: latest Apache version installed  

    yum:  

      name: httpd  

      state: latest  
  

  - name: latest firewalld version installed  

    yum:  

      name: firewalld  

      state: latest  
  

  - name: firewalld enabled and running  

    service:  

      name: firewalld  

      enabled: true  

      state: started  
  

  - name: firewalld permits http service  

    firewalld:  

      service: http  

      permanent: true  

      state: enabled  

      immediate: yes  
  

  - name: Apache enabled and running  

    service:  

      name: httpd  

      enabled: true  

      state: started

```

Tip

Note the difference to other playbooks you might have written! Most importantly there is no `become` set, this has to be done later in the Job template!

To configure and use this repository as a **Source Control Management (SCM)** system in automation controller you have to create a **Project** that uses the repository

Create the Project

- Automation Execution → Projects, click the **Create Project** button. Fill in the form:

Parameter	Value
Name	Workshop Project
Organization	Default
Default Execution Environment	Default Execution Environment

Source Control Type	Git
---------------------	-----

Enter the URL into the Project configuration:

Parameter	Value
Source Control URL	https://github.com/ansible/workshop-examples.git
Options	Select Clean , Delete and Update Revision on Launch to request a fresh copy of the repository and to update the repository when launching a job.

- Click **Create project**

The new project will be synced automatically after creation. But you can also do this manually: Sync the Project again with the Git repository by going to the **Projects** view and clicking the circular arrow **Sync Project** icon in the top right corner.

The screenshot shows the 'Workshop Project' details page in the Red Hat Ansible Automation Platform. The left sidebar is collapsed. The main content area shows the following details for the 'Workshop Project':

Name	Organization	Last job status
Workshop Project	Default	Success
Source control type	Source control revision	Source control URL
Git	fef099af84ce0f8a93eb5b16fb2c8b5b6dc6...	https://github.com/ansible/workshop-examples.git
Cache timeout	Execution environment	Project base path
0 seconds	Default execution environment	/home/ec2-user/aap/controller/data/projects
Playbook directory	Created	Last modified
_8__workshop_project	1/20/2024, 8:35:09 PM by admin	1/20/2024, 8:35:09 PM by admin
Enabled options		
Discard local changes before syncing Delete the project before syncing Update revision on job launch		

After starting the sync job, go to the **Jobs** view: there is a new job for the update of the Git repository.

Create a Job Template and Run a Job

A job template is a definition and set of parameters for running an Ansible job. Job templates are useful to execute the same job many times. So before running an Ansible **Job** from automation controller you must create a **Job Template** that pulls together:

- Inventory:** On what hosts should the job run?
- Credentials** What credentials are needed to log into the hosts?
- Project:** Where is the playbook?
- What** playbook to use?

Okay, let's just do that: To create a Job Template, go to the **Automation Execution -> Templates** view, click the **Create template** button and choose **Create job template**.

Tip

Remember that you can often click on the question mark with a circle to get more details about the field.

Parameter	Value
Name	Install Apache
Job Type	Run
Inventory	Workshop Inventory
Project	Workshop Project
Execution Environment	Default execution environment
Playbook	rhel/apache/apache_install.yml
Credentials	Workshop Credential
Limit	web
Options	<input checked="" type="checkbox"/> Privilege Escalation

- Click **Create job template**

You can start the job by directly clicking the blue **Launch template** button, or by clicking on the rocket in the Job Templates overview. After launching the Job Template, you are automatically brought to the job overview where you can follow the playbook execution in real time.

Job Details

The screenshot shows the 'Install Apache' template details page. The left sidebar has 'Templates' selected. The top right has a red box around the 'Launch template' button. The main area shows the template configuration:

- Name:** Install Apache
- Job type:** run
- Organization:** Default
- Inventory:** Workshop Inventory
- Project:** Workshop Project
- Execution environment:** Default execution environment
- Playbook:** rhel/apache/apache_install.yml
- Credentials:** SSH: Workshop Credentials
- Limit:** web
- Verbosity:** 0 (Normal)
- Forks:** 0
- Timeout:** 0
- Show changes:** Off
- Job slicing:** 1
- Created:** 11/20/2024, 8:47:50 PM by admin
- Last modified:** 11/20/2024, 8:47:50 PM by admin
- Extra variables:** (YAML, JSON)
- Enabled options:** Privilege Escalation

Job Run

The screenshot shows the 'Output' tab for the 'Install Apache' job run. The top right has a red box around the 'Relaunch job' button. The main area shows the job log:

Install Apache Success

Plays 1 Elapsed 00:00:03

Search output Filter by keyword

```
0 Identity added: /runner/artifacts/13/ssh_key_data (/runner/artifacts/13/ssh_key_data)
7
8 PLAY [Apache server installed] **** 1:52:20 PM
9
10 TASK [Gathering Facts] **** 1:52:20 PM
11 ok: [node1]
12 ok: [node2]
13 ok: [node3]
14
15 TASK [latest Apache version installed] **** 1:52:45 PM
16 ok: [node1]
17 ok: [node2]
18 changed: [node3]
19
20 PLAY RECAP ****
```

Since this might take some time, have a closer look at all the details provided:

- All details of the job template like inventory, project, credentials and playbook are shown.
- Additionally, the actual revision of the playbook is recorded here - this makes it easier to analyse job runs later on.
- Also the time of execution with start and end time is recorded, giving you an idea of how long a job execution actually was.
- Selecting **Output** shows the output of the running playbook. Click on a node underneath a task and see that detailed information are provided for each task of each node.

After the Job has finished go to the main **Jobs** view: All jobs are listed here, you should see directly before the Playbook run an Source Control Update was started. This is the Git update we configured for the **Project** on launch!

Challenge Lab: Check the Result

Time for a little challenge:

- Use the playbook `check_httpd_service.yml` from the Github Repository
<https://github.com/TimGrt/workshop-demo.git> to check the state of the webserver on all `web` hosts.

You have already been through all the steps needed, so try this for yourself.

Solution

Go to **Automation Execution → Projects**, click the **Create Project** button. Fill in the form:

Parameter	Value
Name	Workshop Demo Project
Organization	Default
Default Execution Environment	Default Execution Environment
Source Control Type	Git

Enter the URL into the Project configuration:

Parameter	Value
Source Control URL	https://github.com/TimGrt/workshop-demo.git
Options	Select Clean , Delete and Update Revision on Launch to request a fresh copy of the repository and to update the repository when launching a job.

Click **Create project**.

Go to **Automation Execution -> Templates**, click the **Create template** button and choose **Create job template**.

Parameter	Value
Name	Check webserver service
Job Type	Run
Inventory	Workshop Inventory
Project	Workshop Project
Execution Environment	Default execution environment
Playbook	check_httpd_service.yml
Credentials	Workshop Credential

▼ Details

Limit	web
Options	<input checked="" type="checkbox"/> Privilege Escalation

To check the state with an *ad-hoc* command, do the following:

- Go to **Automation Execution** → **Infrastructure** → **Inventories** → **Workshop Inventory**
- In the **Automation Execution** → **Infrastructure** → **Inventories** → **Workshop Inventory**, select the **Hosts** tab and select `node1` , `node2` , `node3` and click **Run Command**
- Within the **Details** window, select **Module** `command` , in **Arguments** type `systemctl status httpd` and click **Next**.
- Within the **Execution Environment** window, select **Default execution environment** and click **Next**.
- Within the **Credential** window, select **Workshop Credentials** and click **Next**.
- Review your inputs and click **Finish**.

 **Info**

The output of the results is displayed once the command has completed.

© Tim Grützmacher 2025