

Ansible Workshop - Exercises

# Automation Platform

Learn to manage and run your Ansible  
content in AAP.



# 7 - AAP Wrap up

## Objective

This is the final challenge where we try to put most of what you have learned together.

## Guide

### Let's set the stage

Your operations team and your application development team likes what they see in Ansible automation controller. To really use it in their environment they put together these requirements:

- All webserver hosts ( `node1` , `node2` and `node3` ) should go in one group
- As the webserver hosts can be used for development purposes or in production, there has to be a way to flag them accordingly as "stage dev" or "stage prod".
  - Currently `node1` and `node3` are used as a development system and `node2` is in production.
- Of course the content of the world famous application "index.html" will be different between dev and prod stages.
  - There should be a title on the page stating the environment
  - There should be a content field
- The content writer `wwweb` should have access to a survey to change the content for dev and prod servers.

### The Git Repository

All code is already in place - this is a automation controller lab after all. Check out the **Workshop Project** git repository at <https://github.com/ansible/workshop-examples>. There you will find the playbook `webcontent.yml`, which calls the role `role_webcontent`.

Compared to the previous Apache installation role there is a major difference: there are now multiple versions of an `index.html` template, and a task deploying the template file, which has a variable as part of the source file name.

For the development servers the file is named `dev_index.html.j2` with the following content:

```
<body>
<h1>This is a development webserver, have fun!</h1>
{{ dev_content }}
</body>
```

For the production servers the file is named `prod_index.html.j2` with the following content:

```
<body>
<h1>This is a production webserver, take care!</h1>
{{ prod_content }}
</body>
```

The playbook `main.yml` deploys the template:

```
[...]
- name: Deploy index.html from template
  template:
    src: "{{ stage }}_index.html.j2"
    dest: /var/www/html/index.html
  notify: apache-restart
```

## Prepare Inventory

There is of course more than one way to accomplish this, but for the purposes of this lab, we will use Ansible automation controller.

Navigate to **Automation Execution** → **Infrastructure** → **Inventories**. Select 'Workshop Inventory' and complete the following:

- Go to the Groups tab, click **Create group**, and create a new group labeled Webserver. Click **Create group**.
- In the Webserver group, click **Edit group** and define the following variable:


```
---
stage: dev
```

Within the **Details** tab of the `Webserver` inventory, click the **Hosts** tab, click the **Add existing host** button. Select `node1`, `node2`, `node3` as the hosts to be part of the `Webserver` inventory.

Within **Automation Execution** → **Infrastructure** → **Inventories**, select the `Workshop Inventory`. Click on the `Hosts` tab and click on `node2`. Click on `Edit` and add the `stage: prod` variable in the **Variables** window. This overrides the inventory variable due to order of operations of how the variables are accessed during playbook execution.

Within the **Variables** textbox define a variable labeled `stage` with the value of `prod` and click **Save host**.

```
ansible_host: node2.example.com
stage: prod
```



# Create the Template

Within **Automation Execution** → **Templates**, select the **Create template** button and **Create job template** as follows:

Parameter	Value
Name	Create Web Content
Job Type	Run
Inventory	Workshop Inventory
Project	Workshop Project
Execution Environment	Default execution environment
Playbook	rhel/apache/webcontent.yml
Credentials	Workshop Credential
Limit	web
Variables	dev_content: "default dev content", prod_content: "default prod content"
Options	<input checked="" type="checkbox"/> Privilege Escalation

Click **Create job template**.

Red Hat Ansible Automation Platform

Overview

Automation Execution

Jobs

Templates

Schedules

Projects

Infrastructure

Topology View

Inventories

Hosts

Instance Groups

Instances

Execution Environments

Credentials

Credential Types

Administration

Automation Decisions

Event-Driven Ansible

Automation Content

Automation Hub

Automation Analytics

Access Management

Authentication Methods

Organizations

Teams

Users

Roles

OAuth Applications

Templates > Create job template

### Create job template

**Name \*** Create Web Content **Description** Enter description **Job type \*** Run ☐ Prompt on launch

**Inventory \*** Workshop Inventory ☐ Prompt on launch **Project \*** Workshop Project **Playbook \*** rhel/apache/webcontent.yml

**Execution environment** Default execution environment ☐ Prompt on launch **Credentials** Workshop Credentials... ☐ Prompt on launch **Labels** Select or create labels ☐ Prompt on launch

**Forks** 0 ☐ Prompt on launch **Limit** Enter limit to reduce number of hosts ☐ Prompt on launch **Verbosity** 0 ☐ Prompt on launch

**Job slicing** 1 ☐ Prompt on launch **Timeout** 0 ☐ Prompt on launch **Show changes** ☐ Prompt on launch

**Instance groups** Select instance groups ☐ Prompt on launch **Job tags** Select or create job tags ☐ Prompt on launch **Skip tags** Select or create skip tags ☐ Prompt on launch

**Extra variables** ☐ Prompt on launch **YAML** **JSON**

```
dev_content: "default dev content"
prod_content: "default prod content"
```

☒ Privilege escalation ☐ Provisioning callback ☐ Enable webhook

☐ Concurrent jobs ☐ Enable fact storage ☐ Prevent instance group fallback

**Create job template** **Cancel**

Run the template by clicking the **Launch** button.

## Check the Results

This time we use the power of Ansible to check the results: execute uri to get the web content from each node, orchestrated by an Ansible playbook labeled `check_url.yml`



### Tip

We are using the `ansible_host` variable in the URL to access every node in the inventory group.

```
---
- name: Check URL results
  hosts: web
  tasks:
    - name: Check that you can connect (GET) to a page and it returns a status 200
      ansible.builtin.uri:
        url: "http://{{ ansible_host }}"
        return_content: true
        register: uri_output

    - name: Output result
      ansible.builtin.debug:
        msg: "{{ uri_output.content }}"
```

Execute the playbook:

```
[student@ansible-1 ~]$ ansible-navigator run check_url.yml -m stdout
```

Snippet of output:

```
TASK [debug] *****
ok: [node1] => {
  "uri_output.content": "<body>\n<h1>This is a development webserver, have fun!</h1>\ndev
wweb</body>\n"
}
ok: [node2] => {
  "uri_output.content": "<body>\n<h1>This is a production webserver, take care!</h1>\nprod
wweb</body>\n"
}
ok: [node3] => {
  "uri_output.content": "<body>\n<h1>This is a development webserver, have fun!</h1>\ndev
wweb</body>\n"
}
```

## Add Survey

- Add a Survey to the template to allow changing the variables `dev_content` and `prod_content`.
- In the Template, click the **Survey** tab and click the **Create survey question** button.
- Fill out the following information:

Parameter	Value
Question	What should the value of dev_content be?
Answer Variable Name	dev_content
Answer Type	Text

- Click **Create survey question**

In the same fashion add a second **Survey Question**

Parameter	Value
Question	What should the value of prod_content be?
Answer Variable Name	prod_content
Answer Type	Text

- Click **Create survey question**

- Click the toggle **Survey disabled** to enable the Survey questions.
- Add permissions to the team `Web Content` so the template **Create Web Content** can be executed by `wweb`.
- Within the **Automation Execution** -> **Templates**, click **Create Web Content** select the **User Access** tab and **Add roles** to add the user `wweb` the ability to execute the template.
  - **Select user(s)** -> select the checkbox `wweb`, click **Next**.
  - **Select roles to apply** -> select the checkbox **JobTemplate Execute** and click **Next**.
  - **Review** -> click **Finish**.
- Run the survey as user `wweb`
  - Logout of the user `admin` of your Ansible automation controller.
  - Login as `wweb` and go to **Automation execution** -> **Templates** and run the **Create Web Content** template.

Check the results again from your automation controller host. We will use the dedicated `uri` module within an Ansible playbook. As arguments it needs the actual URL and a flag to output the body in the results.

```
[student@ansible-1 ~]$ ansible-navigator run check_url.yml -m stdout
```

## Solution

### Warning

No solution this time 😊

You have done all the required configuration steps in the lab already. If unsure, just refer back to the respective chapters.

© Tim Grützmacher 2025