

Variable	Definition (What is it?)	How does it work?	Purpose
[MAIN]			
TasksCount	Number of worker tasks the Vault can run	Creates worker processes to handle multiple jobs at once	Improves performance
DateFormat	Date display format	Formats every displayed date	Keeps dates consistent
TimeFormat	Time display format	Formats every displayed time	Keeps timestamps consistent
ResidentDelay	Background task interval	Background services wake up at this interval	Controls periodic checks
VaultCommunicationProtocol	Communication protocol	Defines how CyberArk components talk to the Vault	Enables communication
BasePort	Network port	Vault listens on this port	Allows client connections
LogRetention	Log retention period	Deletes old logs after set time	Saves disk space
LockTimeout	Object lock timeout	Releases locks after timeout	Prevents conflicts
DaysForAutoClear	Auto cleanup period	Removes old information after set days	Database cleanup
DaysForPicturesDistribution	Picture distribution schedule	Controls user picture distribution	Manages profile pictures
ClockSyncTolerance	Allowed clock difference	Accepts small time differences	Avoids clock sync issues
TraceArchiveMaxSize	Maximum trace log size	Limits debug log archive size	Prevents disk from filling
VaultEventNotifications	Notification events	Sends alerts for selected events	Keeps admins informed
RecoveryPubKey	Recovery public key	Used during recovery encryption	Disaster recovery
ServerKey	Server key	Used to identify/protect the Vault	Security
StagingAreaDirectory	Temporary working folder	Stores temporary files	Processing workspace
EntropyFile	Random data file	Provides randomness for encryption	Stronger encryption
DatabaseConnectionPasswordFile	Database password file	Stores DB password securely	Protects credentials
ServerCertificateFile	Server certificate	Proves Vault identity	Secure communications
ServerPrivateKey	Server private key	Pairs with certificate	Encryption/authentication
AllowedVirusSafeFileTypes	Allowed file types	Permits only listed file extensions	Safer uploads
AutoClearSafeHistory	Auto clear Safe history	Deletes old Safe history	Cleanup
AutoClearUserHistory	Auto clear user history	Deletes old user history	Cleanup
AutoSyncExternalObjects	Sync external users/groups	Synchronizes with LDAP/AD	Keeps identities updated
DebugLevel	Debug logging level	Controls troubleshooting detail	Diagnostics
VaultId	Unique Vault ID	Identifies this Vault	Uniqueness
DefaultTimeout	Default wait time	Stops waiting after timeout	Avoids hanging operations
PooledSocketTimeout	Connection reuse timeout	Keeps sockets open temporarily	Performance
RecoveryPrvKey	Recovery private key	Used with recovery public key	Disaster recovery
EmergencyStationIP	Recovery station IP	Specifies emergency recovery host	Recovery access
EnablePredefinedUsers	Built-in accounts	Enables default users	Initial administration
ExternalAuthenticationMode	External authentication	Uses LDAP/AD login	Centralized authentication
AutomaticallyAddBuiltInGroups	Built-in groups	Creates default groups automatically	Simplifies setup
LicenseUsageAlertLevel	License alert thresholds	Warns at usage percentages	Avoids license exhaustion
MaxTasksAllocation	Task limits per component	Limits worker allocation	Balanced resources
ComponentNotificationThreshold	Component response threshold	Warns if components respond slowly	Monitoring
UserLockoutPeriodInMinutes	Lockout duration	Keeps account locked for set time	Brute-force protection

MaskUserIssuesMessages	Hide detailed errors	Shows generic errors if enabled	Improves security
TerminatedMDBErrorCodes	Fatal DB error codes	Treats listed DB errors as fatal	Error handling
MinSupportedClientVersion	Minimum client version	Rejects older clients	Compatibility/security
MaxConcurrentUsersByClientID	Concurrent user limits	Limits simultaneous client connections	Resource control
[BACKUP]			
BackupKey	Backup encryption key	Encrypts backups	Protects backups
[CRYPTO]			
SymCipherAlg	Symmetric encryption algorithm	Encrypts stored data (AES-256)	Data protection
AsymCipherAlg	Asymmetric encryption algorithm	Uses public/private keys	Secure key exchange
[SYSLOG]			
UseLegacySyslogFormat	Legacy Syslog format	Outputs old Syslog format	Compatibility