Online Ensemble Forecasting of Great Britain Day-Ahead Electricity Prices under a Strict Information Set

Bernstein aggregation of a diverse model pool, quantiles by QRA with adaptive conformal calibration, and a battery-dispatch evaluation

Tim Louis Wilken

Working paper – draft of 12 October 2026

Code and outputs: https://github.com/TimLouisWilken/gb-dayahead-research

Abstract

We forecast the 24 hourly day-ahead prices of the Great Britain (GB) market with a pool of 13 models that are all updated daily, and combine them per delivery hour with Bernstein Online Aggregation (BOA). The decision time is 07:30 UTC on the day before delivery, i.e. before the demand forecast, wind and solar forecast, fuel and weather inputs of the auction morning are final; all inputs are checked for leakage with an automated perturbation test. Over 2024-01-01 to 2026-09-27 (about 1 000 local days) the best combination, built from six members chosen on 2024 only, reaches MAE 8.57 EUR/MWh and rMAE 0.391 against a similar-day naive forecast; the LEAR benchmark with daily recalibration reaches 11.07. Updating the models every day is the largest single gain (random forest −32%, LSTM −21% MAE against the same model trained once). For quantiles we regress the realised price on the 13 point forecasts plus two pinball-loss boosting tail forecasts (QRA) and recalibrate with adaptive conformal inference; the resulting 90 % interval covers 89.6 % of hours. A linear-programme battery backtest (100 MWh / 50 MW) earns 93.1 % (2025) and 93.7 % (2026) of perfect-foresight profit. The paper reports negative results as well: seven feature sets, several combiner variants and an outage-based spike signal did not help. We do not claim superiority over published methods, because no open benchmark exists for GB and our naive benchmark differs from the literature standard.

Keywords: electricity price forecasting, day-ahead market, Great Britain, forecast combination, online learning, quantile regression averaging, conformal prediction, battery storage.

1 Introduction

Day-ahead prices in Great Britain moved through three regimes in five years: the 2021–22 energy crisis, a normalisation in 2023–24, and since 2025 a market with low midday and sharp evening-ramp prices, with gas about 40 % higher in 2026 than in 2025. A model fitted once degrades under this drift. The question of this paper is therefore practical: how much accuracy does a forecaster gain if every model is updated every day, and if the models are combined by an algorithm that also adapts every day?

The electricity price forecasting (EPF) literature gives a clear methodological frame (Lago et al., 2021; Weron, 2014): test over at least a year, recalibrate daily, choose hyper-parameters before the test period, report relative errors and Diebold–Mariano tests, and include a cheap strong benchmark. We follow that frame but add three features that the open benchmark does not cover. First, GB is not one of its five markets. Second, we fix a strict information set at 07:30 UTC on day $D-1$ and audit every input against it, because look-ahead through revised

data, reanalysis weather and post-auction forecasts is the most common silent error in applied EPF. Third, we judge the forecasts not only by statistical scores but also by the profit of a battery that trades on them.

Contributions.

1. A leakage-audited data set and protocol for GB day-ahead prices, including seven concrete leakage patterns found in a student pipeline we started from and in our own first version (Section 2).
2. A 13-member online pool (random forests, boosting, four neural architectures, LEAR, a merit-order regression and a zero-shot foundation model), combined per hour by BOA, with a documented ablation showing that six diverse members beat all thirteen (Section 3).
3. A probabilistic layer, QRA over 15 regressors followed by adaptive conformal inference, whose 50/80/90 % intervals are within about one percentage point of nominal (Section 5).
4. An economic evaluation by battery dispatch and a documented list of negative results (Sections 6, 7).

We positioned the work against 25 papers read in full text; the positioning and its limits are in `docs/LITERATURE.md` of the repository.

2 Data and information set

The target is the hourly GB day-ahead price in EUR/MWh for each local (UK) delivery day D. Daylight-saving days are mapped to 24 hours as in `epftoolbox`: the missing spring hour is interpolated, the doubled autumn hour is averaged. Prices come from Ember (CC-BY-4.0) up to the latest published day and from the Nord Pool N2EX result in the live system.

Information set. The forecast for day D is issued at 07:30 UTC on $D-1$, before the GB gate closures (EPEX 09:20, N2EX 09:50 UK time). Table 1 lists the inputs and the availability rule that was enforced for each.

Input	Availability rule used
Prices	only complete local days $\leq D$–1 (lags 1, 2, 7 and daily statistics)
Wind forecast, transmission (WINDFOR)	latest issue $\leq$ 07:30 UTC on $D-1$
Embedded wind and solar (NESO)	latest issue $\leq$ 07:30 UTC on $D-1$
Temperature forecast (Birmingham)	forecast made 48 h before each valid hour (Open-Meteo previous runs)
National demand forecast (NDF)	latest issue $\leq$ 09:00 UK time on D–1 (the full-day issue appears at 08:45)
Demand outturn	days $\leq D-2$
Gas (SAP)	gas day $D-3$; UK ETS (UKA) futures settlement of $D-2$

Table 1: Inputs and availability rules.

The demand forecast matters: it is three times more accurate than the previous proxy (the outturn one week earlier; MAE 665 vs. 2 031 MW against outturn) and lowers the MAE of the 4-member hybrid by 4.9 %.

Leakage audit. Starting from the data and pipeline of a student group project (UCL BENV0148, April 2026), we found and removed: (i) a rolling price mean containing hours of the forecast day; (ii) gas and carbon lagged by only one day and a demand shift of 24 hours; (iii) weather taken from reanalysis (actual weather) and, in our first version, a previous-day forecast that was issued after the auction; (iv) "day-ahead" wind and solar forecasts that are published at 16:45 UTC on $D-1$, after the auction; (v) UTC days instead of local days, so that in summer an input hour belonged to the auction being forecast; (vi) gap filling with later values; (vii) revised wind outturn published after the cutoff (114 of 97 000 half-hours), found by the issue-time check itself. Two further data errors were fixed: gas SAP is in p/kWh, and the "UK ETS" file of the project was the EU ETS price. The script `src/test_leakage.py` scrambles every value that was unknown at 07:30 UTC (prices from D, demand from $D-1$, gas from $D-2$, and so on), including both daylight-saving switch days, and asserts that the model inputs for D are bit-identical. A positive control scrambles the permitted inputs and must change the result; a third check verifies that no forecast issue time exceeds the cutoff. The cost of removing the leaks was small: on the old evaluation window the hybrid MAE rose from 9.44 to 9.64 and LEAR from 10.56 to 10.64.

3 Models and combination

3.1 Protocol

Models are first fitted on 2021-07-07 to 2023-06-30. From then on each day, every member forecasts day D from information before $D-1$ 07:30 and then learns the realised prices. The second half of 2023 is a burn-in used to warm up combiners and to choose hyper-parameters. All results use **2024-01-01 to 2026-09-27**, which no design choice has seen except where stated (selection on 2024 with a 2025–26 holdout).

3.2 Members

Table 2 lists the pool. Prices are asinh-transformed for stability (Uniejewski et al., 2018); neural members use reversible instance normalisation so that the network learns shapes rather than regime levels (burn-in MAE of the LSTM 16.9 → 13.5).

An important design finding is that the absolute loss is essential for boosting: with squared loss, MAE on the burn-in is 18.3 instead of 13.7, because the model chases the 2022 spikes.

3.3 Combination by BOA

For each delivery hour h and day t, BOA (Wintenberger, 2017) keeps weights $w_{t,k}$ on the K experts and updates them by a second-order exponential-weights rule, so the cumulative loss approaches that of the best expert (and of the best convex combination) at a rate $O(\log K/t)$ up to a $\log\log t$ term. The loss is absolute error. Weights are updated only after the day's prices are known. Following Berrisch and Ziel (2024) we also tested forgetting; a grid search on 2024 confirmed on the 2025–26 holdout (Diebold–Mariano $p = 0.001$) selected *no* forgetting (rate 1.0), which differs from their finding for German data. For serving, the weights of hour h are averaged with those of $h \pm 1$ (selected on 2024, holdout-confirmed, $p < 0.001$, -0.03 MAE); the update itself stays per hour. We found no precedent for this serving-time smoothing in the literature we read.

4 Point-forecast results

Table 3 reports the evaluation window; rMAE is the MAE relative to a similar-day naive forecast (day $D-1$ for Tuesday to Friday, $D-7$ otherwise). The standard in Lago et al. (2021) is $p(d-7)$;

Member	Model	Update scheme
`lstm`, `tcn`, `transformer`, `dnn`	seq2seq LSTM, temporal CNN, encoder–decoder Transformer, MLP; 7-day history to 24 hours	daily fine-tuning with experience replay; cold refit every 91 days
`ddnn`	LSTM with Johnson-SU output (distribution)	as above
`rf_long`, `rf_short`	random forest, 3-year window with recency weights; 84-day window	weekly; daily
`lstm_rf`	LSTM plus random forest fitted to the LSTM's out-of-sample errors	weekly
`gbm`	histogram gradient boosting, *absolute* loss, extra fuel and wind-error features	weekly, time-ordered early stopping
`lear`, `lear4`	LEAR with asinh transform, 182/728-day windows (averaged), and four windows	daily recalibration
`merit`	merit-order regression: residual-load spline × CCGT fuel cost	daily, 182-day window
`chronos`	Chronos-Bolt small, zero-shot, 28-day context	none

Table 2: The 13 members. Two further quantile-loss boosting models (`gbm_q10`, `gbm_q90`) enter only the probabilistic stage.

the two differ and numbers should not be compared across papers.

Findings.

1. **Continual learning is the largest gain.** Online vs. static: random forest 11.58 vs. 17.12 (-32%), LSTM 10.69 vs. 13.50 (-21%), both $p < 0.001$. Static models degrade year by year; online models do not.

2. **The ensemble beats LEAR in every year**, by -23% in MAE over the whole period (8.57 vs. 11.07, $p < 0.001$), and beats every single member, including the best one, the Transformer (9.78).

3. **Adaptive weighting pays once the pool is heterogeneous.** For the four similar core members BOA and equal weights are close (9.63 vs. 9.79). With weak members in the pool (Chronos 14.4, merit 12.2) BOA beats equal weights clearly (8.73 vs. 9.15).

4. **Six diverse members beat all 13.** Greedy backward elimination on 2024 only keeps one member per family (`lstm_rf, gbm, transformer, lear, merit, chronos`); on the untouched 2025–26 holdout it beats the 13-member pool (9.01 vs. 9.18, $p = 0.002$; figures before the serving-time weight smoothing). Redundant siblings dilute the weight of their better twin: the regret bound of BOA protects against bad experts but not against correlated ones. The individually weak merit and Chronos members stay because their errors are the least correlated with the rest. This agrees with the recommendation of small ensembles in Lago et al. (2021).

5. **Error correction helps.** The random forest fitted to LSTM errors improves the LSTM (10.37 vs. 10.69, $p = 0.006$), mostly in RMSE, i.e. at spikes.

Model	MAE	RMSE	rMAE	sMAPE %
Naive (similar day)	21.90	37.22	1.000	32.2
RF, trained once	17.12	26.94	0.782	24.0
LSTM, trained once	13.50	22.03	0.617	20.9
Chronos-Bolt (zero-shot)	14.44	25.89	0.660	21.3
Merit-order regression	12.24	19.97	0.559	19.4
RF long window, online	11.58	19.08	0.529	18.7
LEAR, daily recalibration	11.07	20.11	0.506	17.5
Gradient boosting, online	10.79	18.92	0.493	17.5
LSTM, online	10.69	18.16	0.488	17.6
LSTM + RF error correction	10.37	17.33	0.474	17.1
Transformer, online (best single)	9.78	17.88	0.446	16.6
Equal weights, all 13	9.15	17.29	0.418	15.4
BOA, 4 core members	9.63	16.18	0.440	16.2
BOA, all 13	8.73	16.40	0.399	14.9
BOA, selected 6	**8.57**	**15.72**	**0.391**	**14.7**

Table 3: Out-of-sample accuracy, 2024-01-01 to 2026-09-27, EUR/MWh. Further members are in `outputs/metrics.csv`.

MAE	2024	2025	2026 (to Sep)
Naive	19.14	22.20	25.23
LEAR	9.87	10.42	13.56
Transformer, online	9.13	9.52	10.99
BOA, all 13	7.95	8.63	9.92
BOA, selected 6	7.83	8.32	9.88

Table 4: MAE by calendar year. The absolute rise in 2026 is a market effect; rMAE stays between 0.38 and 0.41.

5 Probabilistic forecasts

5.1 Method

For each hour and each of 19 quantile levels ($5\%, \ldots, 95\%$), QRA (Nowotarski and Weron, 2015) regresses the realised price on the member forecasts over the last 182 days; we use the 13 point forecasts plus the two pinball-loss boosting forecasts (QRA-15), which carry tail information that mean forecasts lack. Raw QRA is overconfident, as the literature reports (Kath and Ziel, 2021). We therefore shift each quantile by the matching quantile of its own past out-of-sample residuals (conformalised quantile regression) and adapt the residual level after every day from the realised hit rate (adaptive conformal inference, Gibbs and Candès, 2021; Zaffran et al., 2022), with the step size $\gamma = 0.005$ fixed from the literature range and not tuned. We found no published use of this two-stage QRA→ACI combination.

5.2 Results

Table 5 reports the average pinball loss over the 19 quantiles (a proper score, about CRPS/2) and empirical coverage of central intervals.

Raw QRA covers only 83–85 % at the nominal 90 %; the conformal step repairs this at almost no cost in pinball loss (3.58 → 3.59). Thirteen members improve on five ($p = 0.009$), and the two tail forecasts improve on the thirteen ($p = 0.016$), mostly in spike hours (spike-hour pinball −3% on the selection year, confirmed on the holdout, $p = 0.038$). The distributions of the neural net




Figure 1: Monthly MAE of selected models (`outputs/figures/monthly_mae.png`).

Method	Pinball	50 %	80 %	90 %	90 % width
Historical simulation (BOA, core)	3.87	49.2	78.6	88.3	41.4
QRA, 5 members (raw)	3.67	45.6	74.4	84.6	36.8
QRA, 13 members (raw)	3.60	44.2	72.6	82.7	35.1
QRA-15 (raw)	3.58	44.1	72.3	82.9	34.5
QRA-13 + adaptive conformal	3.62	49.1	79.3	89.6	45.9
QRA-15 + adaptive conformal	**3.59**	**49.4**	**79.5**	**89.6**	43.4
Distributional LSTM (own output)	3.96	39.3	67.3	79.3	34.5
Chronos-Bolt (own output)	5.61	52.9	81.4	81.4	44.3


Table 5: Quantile forecasts, 2024-01-01 to 2026-09-27, daily recalibration. Coverage in percent of hours.

alone are too narrow (79 % at nominal 90 %) but useful as QRA regressors, in line with Marcjasz et al. (2023). Without LEAR in the pool, QRA gives no gain over historical simulation ($p = 0.40$). The Kupiec test rejects almost every row because about 24 000 autocorrelated hourly hits give it extreme power; we therefore read coverage levels directly. Per-hour Christoffersen tests are not yet reported.

6 Economic value: battery dispatch

Accuracy measured by MAE is only loosely tied to trading value (Maciejowska et al., 2026). We therefore backtest a battery of 100 MWh / 50 MW with 85 % round-trip efficiency. On the morning of $D-1$ a linear programme maximises profit on the *forecast* of day D under state-of-charge limits and a daily cycle ($SoC_{24} = 0$); the schedule is committed as price-taking volume and settled at the *actual* clearing prices. Profit is gross arbitrage revenue without grid charges or degradation.

The ensemble recovers more than 92 % of perfect-foresight profit, LEAR about 90 %, and a naive profile 75 %. The 13-member BOA is slightly *better* for dispatch than the six-member one although its MAE is worse: ranking skill (hit rate for the four most expensive hours 82.8 vs. 82.5 %) matters for arbitrage, level skill for MAE. In the same way the LSTM+RF member has better MAE than the plain LSTM but earns less (90.3 vs. 91.6 % of PF). This reproduces, on GB data, the finding of Maciejowska et al. (2026) that curve shape matters more than MAE. Absolute shares cannot be compared with other papers because strategy and market differ.






Figure 2: Fan chart of the 19 quantiles for an example period (left) and reliability diagram (right). Price data: Ember (CC-BY-4.0).

Strategy	2025 (357 days) EUR/kW/yr	% of PF	2026 to Sep (270 days) EUR/kW/yr	% of PF
Perfect foresight	49.6	100.0	50.4	100.0
BOA, all 13	46.2	93.1	47.2	93.7
BOA, selected 6	45.7	92.1	47.2	93.6
LEAR	44.6	89.9	45.6	90.4
Persistence (profile of $D-1$)	37.0	74.5	38.6	76.5

Table 6: Battery arbitrage profit as a share of perfect foresight (PF).

7 Negative results

We report rejected ideas because each was tested under the same protocol (burn-in first, then a full online A/B on the evaluation window).

- **Neighbour-market prices** (FR, NL, BE, NO, IE, DK, DE) and rolling price statistics: every member slightly worse (hybrid 9.79 → 9.89).
- **Fuel and wind-error features** (TTF, EUA, wind forecast error): better for boosting only (10.85 → 10.79, every year), worse for the LSTM; adopted for `gbm` alone.
- **Four-city temperature** and heating-degree features: better on burn-in, worse in the online A/B ($p = 0.92$).
- **Operating-margin surplus (NESO OC2):** neutral in 2024, $p = 0.31$ in the full A/B.
- **Outage information (REMIT):** falsified at the data level. Planned outages are *anti*-correlated with spikes (20.4 GW unavailable on spike hours vs. 21.8 on normal hours in 2024), because maintenance is scheduled into calm periods; the short-notice variant has no discriminating power.
- **Combiner variants:** forgetting, seasonal BOA states, spike-probability gating, a random-forest correction of the combination (9.13 vs. 8.59), a conditional median shift, QRA-q_{50} as the point forecast (9.08 vs. 8.59), asinh-space BOA, winsorised members, a weighted median.

- **Six-seed Transformer ensemble:** better alone (9.61 vs. 9.78) but neutral inside the combination on the selection year, so not adopted.

The QRA-q_{50} result is consistent with the literature on forecast combination: the median of QRA is an unconstrained least-absolute-deviation combination, and unconstrained weights are reported to perform poorly for point forecasts (Weron, 2014; Nowotarski and Weron, 2016). QRA is the right tool for quantiles, not for the point forecast.

8 Limitations

- **No common GB benchmark.** The `epftoolbox` DNN was not run on our data; our LEAR is a re-implementation. A rank claim against published methods is therefore not possible. We also did not compute rMAE against $p(d-7)$.
- **Selection effects.** The 6-member subset and several hyper-parameters were selected on 2024 and confirmed on 2025–26, but the holdout was reused for more than one decision; p-values from Diebold–Mariano tests on 24 hourly series per day are conditional on this.
- **Data revisions.** Demand outturn and some gas and weather series are final values; a small look-ahead effect remains and is mitigated by lags of at least two days. Re-running the data download revises history, so A/B baselines must be recomputed on the same data state (we learned this the hard way).
- **Probabilistic evaluation.** Per-hour Christoffersen and multivariate Giacomini–White tests are open; the vertical average of QRA, conformal and isotonic regression (Lipiecki et al., 2024) was not tested on QRA-15; $\gamma = 0.005$ is below the values studied by Zaffran et al. (2022).
- **Economic evaluation** uses gross arbitrage on the day-ahead market only, one battery size, no degradation and no imbalance or intraday trading.
- **Regime.** 2026 contains an unusual spike regime (28.5 % of September hours above the trailing 97.5 % quantile); results in other regimes may differ.
- **Sources.** Not all literature could be read in full (see Section 1 of `docs/LITERATURE.md`); one downloaded paper on calibration windows remains unread.

9 Conclusion

On GB day-ahead prices, with a strict 07:30 UTC information set, daily updating of every model and per-hour BOA over a diverse pool cut the MAE of the LEAR benchmark by 23 % (8.57 vs. 11.07 EUR/MWh) over 2.75 years, and the combination was the best forecast in every year and in the battery backtest. Diversity mattered more than size: six models from different families beat thirteen. QRA over point forecasts, with two tail forecasts and adaptive conformal calibration, yields intervals with near-nominal coverage. The same pipeline runs daily in production (a GitHub Actions workflow) and publishes its forecasts and monthly accuracy statistics on a public website. Next steps are the open comparisons named under the limitations: a common GB benchmark with the $p(d-7)$ naive, per-hour calibration tests, and the vertical average of distributional post-processors.

Reproducibility and data statement

Code, predictions of all members, metrics, Diebold–Mariano tables and figures are in the public repository. Raw third-party price data are not redistributed (licences of Nord Pool and others);

Ember data (CC-BY-4.0) can be downloaded with `src/update_data.py`. Full-text PDFs of cited papers are not committed; `literature/download.sh` re-downloads them. Prices: Ember, *European wholesale electricity price data*, CC-BY-4.0.

Acknowledgements

The starting point was the UCL BENV0148 group project on GB electricity price forecasting (April 2026). The literature review and parts of the implementation were carried out with the help of the AI assistant Claude (Anthropic); all numbers in this paper are taken from the repository outputs.

References

Berrisch, J., Ziel, F. (2024/25). Multivariate probabilistic CRPS learning with an application to day-ahead electricity prices. *International Journal of Forecasting*. arXiv:2303.10019.

Gibbs, I., Candès, E. (2021). Adaptive conformal inference under distribution shift. *NeurIPS*. (Not read in full.)

Kath, C., Ziel, F. (2021). Conformal prediction interval estimations with an application to day-ahead and intraday power markets. *International Journal of Forecasting* 37, 777–799.

Lago, J., Marcjasz, G., De Schutter, B., Weron, R. (2021). Forecasting day-ahead electricity prices: a review of state-of-the-art algorithms, best practices and an open-access benchmark. *Applied Energy* 293, 116983.

Lipiecki, A., Uniejewski, B., Weron, R. (2024). Postprocessing of point predictions for probabilistic forecasting of day-ahead electricity prices: the benefits of using isotonic distributional regression. arXiv:2404.02270.

Maciejowska, K., Lipiecki, A., Uniejewski, B. (2026). Statistical and economic evaluation of forecasts in electricity markets: beyond RMSE and MAE. arXiv:2511.13616.

Marcjasz, G., Narajewski, M., Weron, R., Ziel, F. (2023). Distributional neural networks for electricity price forecasting. *Energy Economics* 125, 106843.

Nowotarski, J., Weron, R. (2015). Computing electricity spot price prediction intervals using quantile regression and forecast averaging. *Computational Statistics* 30(3), 791–803.

Nowotarski, J., Weron, R. (2016). To combine or not to combine? Recent trends in electricity price forecasting. HSC Research Report HSC/16/01.

Uniejewski, B., Weron, R., Ziel, F. (2018). Variance stabilizing transformations for electricity spot price forecasting. *IEEE Transactions on Power Systems* 33(2), 2219–2229. (Not read in full.)

Weron, R. (2014). Electricity price forecasting: a review of the state-of-the-art with a look into the future. *International Journal of Forecasting* 30(4), 1030–1081.

Wintenberger, O. (2017). Optimal learning with Bernstein Online Aggregation. *Machine Learning* 106, 119–141.

Zaffran, M., Dieuleveut, A., Féron, O., Goude, Y., Josse, J. (2022). Adaptive conformal predictions for time series. *ICML*.