

 University of Zurich <small>UZH</small>	Test Plan for (Project)	Author: (Besken, Barth, Tornow, Charlé) Doc.No.: GMLG-TEST Date: 2017-11-19 Page of Pages: 1 of 28
--	------------------------------------	--

Contents

1 PUBLIC API OVERVIEW	2
1.1 Public classes to be tested	2
1.2 Public Routines	2
2 TEST SUITE DESCRIPTION	5
2.1 Individual Tests	5
2.1.1 Class: GMLG	5
2.1.1.0 Make a page	5
2.1.1.0.1 Unsupported page name	5
2.1.1.1 Add image	6
2.1.1.2 Add thematic break	7
2.1.1.3 Add anchor link	7
2.1.1.4 Add local link	8
2.1.1.5 Add external link	8
2.1.1.6 Add paragraph	9
2.1.1.7 Add snippet	9
2.1.1.8 Add heading	10
2.1.1.8.0 Add heading with empty text	10
2.1.1.8.1 Add heading with illegal level	11
2.1.1.9 Add table	11
2.1.1.10 Add linebreak	12
2.1.1.11 Add list	13
2.1.1.12 Generate html code	14
2.1.1.13 Generate markdown code	16
2.1.2 Class: GMLG_IMG	19
2.1.2.0 Set width and height	19
2.1.2.0.1 Set width and height with invalid value	19
2.1.3 Class: GMLG_HEADING	20
2.1.3.0 Set italic	20
2.1.4 Class: GMLG_TABLE	20
2.1.4.0 toggle_bordered	20
2.1.4.1 add_element	21
2.1.4.2 Add number	22
2.1.4.3 Add String	22
2.1.5 Class: GMLG_LIST	23
2.1.5.0 Add content	23
2.1.6 Class: GMLG_ANCHOR_LINK	23
2.1.6.0 link to a tag	23
2.1.7 Class: GMLG_LOCAL_LINK	24
2.1.7.0 link to a page	24
2.1.8 Class: GMLG_EXTERNAL_LINK	25
2.1.8.0 Link to a URL	25

3 EXPECTED COVERAGE

27

4 BENCHMARKS

27

4.1. Average output time

27

Revision History

Date	Version	Description	Author(s)
			Clara Maria Barth
4.12.17	1	Final version	Timucin Besken

1 Public API Overview

1.1 Public classes to be tested

1. GMLG
2. GMLG_HEADING
3. GMLG_PARAGRAPH
4. GMLG_TABLE
5. GMLG_SNIPPET
6. GMLG_LIST
7. GMLG_IMG
8. GMLG_EXT_LINK
9. GMLG_LOCAL_LINK
10. GMLG_ANCHOR_LINK

1.2 Public Routines

GMLG

- make(a_title: STRING; a_name: STRING)
- add_img(src: STRING): GMLG_IMG
- add_thbr: GMLG_THEMATIC_BREAK
- add_anchor_link(a_text: STRING): GMLG_ANCHOR_LINK
- add_local_link(a_text: STRING): GMLG_LOCAL_LINK
- add_ext_link(a_text: STRING): GMLG_EXT_LINK
- add_paragraph: GMLG_PARAGRAPH
- add_snippet(code: STRING): GMLG_SNIPPET
- add_heading(text: STRING; level: INTEGER): GMLG_HEADING
- add_table(rows : INTEGER; cols : INTEGER): GMLG_TABLE
- add_linebreak: GMLG_LINEBREAK
- add_list(sort: BOOLEAN): GMLG_LIST
- generate_html_code: STRING
- generate_markdown_code: STRING

GMLG_ANCHOR_LINK

- link_to(tag: GMLG_TAG)

GMLG_EXT_LINK

- link_to(url: STRING)

GMLG_IMG

- set_width (a_width: INTEGER)
- set_height (a_height: INTEGER)

GMLG_LOCAL_LINK

- link_to(page: GMLG)

GMLG_SNIPPET

- toggle_div

GMLG_PARAGRAPH

- add_block(a_string: STRING; a_style: STRING)

GMLG_LIST

- add_content(tag: GMLG_TAG)

GMLG_HEADING

- set_italic

GMLG_TABLE

- add_element(tag: GMLG_TAG; row, column: INTEGER)
- add_number(ele: INTEGER; row, column: INTEGER)
- add_string(ele: STRING; row, column: INTEGER)
- toggle_bordered

2 Test Suite Description

This test suite will test all the functional features of the library in order to see if the expected result is met.

Another thing we'll test are the valid input of the end user and if the library manage to solve those unexpected inputs in the desired way.

2.1 Individual Tests

2.1.1 Class: GMLG

Property	Description
<i>Test ID</i>	FR 2.1.1.0
<i>Title</i>	Make a page
<i>Test</i>	make(a_title: STRING; a_name: STRING)
<i>Description</i>	Create a new page
<i>Set-Up</i>	None
<i>Tear-Down</i>	remove_page(a_page: GMLG) Remove the page created in order to clean test.
<i>Test-Data</i>	<ul style="list-style-type: none">- a_title: "A wonderful title"- name: "name"
<i>Oracle</i>	<ul style="list-style-type: none">- precondition:<ul style="list-style-type: none">- page_name_not_empty: a_name != Void- page_name_less_than_20_chars: a_name.count <= 20 Postcondition: <ul style="list-style-type: none">- Page created with<ul style="list-style-type: none">• title: "A wonderful title"• name: "name"- Empty linked list created (count = 0)

Property	Description
<i>Test ID</i>	FR 2.1.1.0.1
<i>Title</i>	Unsupported page name
<i>Test</i>	make(a_title: STRING; a_name: STRING)
<i>Description</i>	Create a new page with an unsupported name

<i>Set-Up</i>	None
<i>Tear-Down</i>	remove_page(a_page: GMLG) Remove the page created in order to clean test.
<i>Test-Data</i>	<ul style="list-style-type: none"> - a_title: "A wonderful title" - name: "a name"
<i>Oracle</i>	<ul style="list-style-type: none"> - precondition: <ul style="list-style-type: none"> - page_name_not_empty: a_name != Void - page_name_less_than_20_chars: a_name.count <= 20 Postcondition: <ul style="list-style-type: none"> - Page created with <ul style="list-style-type: none"> • title: "A wonderful title" • name: "a name" - Empty linked list created (count = 0) - Error output on the console stating that the name is not supported

Property	Description
<i>Test ID</i>	FR 2.1.1.1
<i>Title</i>	Add image
<i>Test</i>	add_img(src: STRING): GMLG_IMG
<i>Description</i>	Add an image to the page works as expected
<i>Set-Up</i>	<ul style="list-style-type: none"> - Create a new page <ul style="list-style-type: none"> - Title: "Title" - name: "test"
<i>Tear-Down</i>	None
<i>Test-Data</i>	<ul style="list-style-type: none"> - src: "https://zampeamollo.ch/public/images/uploads/gallery-24227.jpg"
<i>Oracle</i>	<ul style="list-style-type: none"> - Tags count of the page increased by 1 - First element of tags list is of type GMLG_IMG - Object created with: <ul style="list-style-type: none"> - src = https://zampeamollo.ch/public/images/uploads/gallery-24227.jpg - width = 50 - height = 50 - class_attr = "image" - id = 0

Property	Description
<i>Test ID</i>	FR 2.1.1.2
<i>Title</i>	Add thematic break
<i>Test</i>	add_thbr: GMLG_THEMATIC_BREAK
<i>Description</i>	Test that adding a thematic break works as expected
<i>Set-Up</i>	<ul style="list-style-type: none"> - Create a new page <ul style="list-style-type: none"> - Title: "Title" - name: "test"
<i>Tear-Down</i>	None
<i>Test-Data</i>	<ul style="list-style-type: none"> - created thematic break call.
<i>Oracle</i>	<ul style="list-style-type: none"> - Tags count of the page increased by 1 - First element of tags list is of type GMLG_THEMATIC_BREAK - Object created with: <ul style="list-style-type: none"> - class_attr = "thematic-break" - id = 0

Property	Description
<i>Test ID</i>	FR 2.1.1.3
<i>Title</i>	Add anchor link
<i>Test</i>	add_anchor_link(a_text: STRING): GMLG_ANCHOR_LINK
<i>Description</i>	Test that adding an anchor link works as expected but not that it can actually be linke to something (this will be tested later)
<i>Set-Up</i>	<ul style="list-style-type: none"> - Create a new page <ul style="list-style-type: none"> - Title: "Title" - name: "test"
<i>Tear-Down</i>	None
<i>Test-Data</i>	<ul style="list-style-type: none"> - a_text: "This is an anchor link"
<i>Oracle</i>	<ul style="list-style-type: none"> - Tags count of the page increased by 1 - First element of tags list is of type GMLG_ANCHOR_LINK - Object created with: <ul style="list-style-type: none"> - class_attr = "anchor-link" - text = This is an external link - id = 0

Property	Description
<i>Test ID</i>	FR 2.1.1.4
<i>Title</i>	Add local link
<i>Test</i>	add_local_link(a_text: STRING): GMLG_LOCAL_LINK
<i>Description</i>	Test that adding a local link works as expected but not that it can actually be linke to something (this will be tested later)
<i>Set-Up</i>	<ul style="list-style-type: none"> - Create a new page <ul style="list-style-type: none"> - Title: "Title" - name: "test"
<i>Tear-Down</i>	None
<i>Test-Data</i>	<ul style="list-style-type: none"> - a_text: "This is a local link"
<i>Oracle</i>	<ul style="list-style-type: none"> - Tags count of the page increased by 1 - First element of tags list is of type GMLG_LOCAL_LINK - Object created with: <ul style="list-style-type: none"> - class_attr = "local-link" - text = This is an external link - id = 0

Property	Description
<i>Test ID</i>	FR 2.1.1.5
<i>Title</i>	Add external link
<i>Test</i>	add_extl_link(a_text: STRING): GMLG_EXT_LINK
<i>Description</i>	Test that adding an external link works as expected but not that it can actually be linke to something (this will be tested later)
<i>Set-Up</i>	<ul style="list-style-type: none"> - Create a new page <ul style="list-style-type: none"> - Title: "Title" - name: "test"
<i>Tear-Down</i>	None
<i>Test-Data</i>	<ul style="list-style-type: none"> - a_text: "This is an external link"
<i>Oracle</i>	<ul style="list-style-type: none"> - Tags count of the page increased by 1 - First element of tags list is of type GMLG_EXT_LINK - Object created with:

	<ul style="list-style-type: none"> - class_attr = "external-link" - text = This is an external link - id = 0
--	---

Property	Description
<i>Test ID</i>	FR 2.1.1.6
<i>Title</i>	Add paragraph
<i>Test</i>	add_paragraph: GMLG_PARAGRAPH
<i>Description</i>	Test that adding a paragraph works as expected
<i>Set-Up</i>	<ul style="list-style-type: none"> - Create a new page <ul style="list-style-type: none"> - Title: "Title" - name: "test"
<i>Tear-Down</i>	None
<i>Test-Data</i>	None
<i>Oracle</i>	<ul style="list-style-type: none"> - Tags count of the page increased by 1 - First element of tags list is of type GMLG_PARAGRAPH - Object created with: <ul style="list-style-type: none"> - class_attr = "paragraph" - id = 0

Property	Description
<i>Test ID</i>	FR 2.1.1.7
<i>Title</i>	Add snippet
<i>Test</i>	add_snippet(code: STRING): GMLG_SNIPPET
<i>Description</i>	Test that adding a code snippet works as expected
<i>Set-Up</i>	<ul style="list-style-type: none"> - Create a new page <ul style="list-style-type: none"> - Title: "Title" - name: "test"
<i>Tear-Down</i>	None
<i>Test-Data</i>	code: "<iframe width="560" height="315" src="https://www.youtube.com/embed/4GFAZBKZVJY?rel=0&showinfo=0" frameborder="0" allowfullscreen></iframe>"

<i>Oracle</i>	<ul style="list-style-type: none"> - Tags count of the page increased by 1 - First element of tags list is of type GMLG_SNIPPET - Object created with: <ul style="list-style-type: none"> - class_attr = "snippet" - code = (the one just passed) - div = False - id = 0
---------------	--

Property	Description
<i>Test ID</i>	FR 2.1.1.8
<i>Title</i>	Add heading
<i>Test</i>	add_heading(text: STRING; level: INTEGER): GMLG_HEADING
<i>Description</i>	Test that adding a heading works as expected
<i>Set-Up</i>	<ul style="list-style-type: none"> - Create a new page <ul style="list-style-type: none"> - Title: "Title" - name: "test"
<i>Tear-Down</i>	None
<i>Test-Data</i>	text: "This is a heading" level: 6
<i>Oracle</i>	<ul style="list-style-type: none"> - Tags count of the page increased by 1 - First element of tags list is of type GMLG_HEADING - Object created with: <ul style="list-style-type: none"> - class_attr = "heading" - text = This is a heading - level = 6 - id = 0 - Pre-condition: 1 <= level <= 6 - Pre-condition: text != ""

Property	Description
<i>Test ID</i>	FR 2.1.1.8.0
<i>Title</i>	Add heading with empty text
<i>Test</i>	add_heading(text: STRING; level: INTEGER): GMLG_HEADING
<i>Description</i>	Test that adding a heading with an empty text will throw a pre-condition violation exception

<i>Set-Up</i>	<ul style="list-style-type: none"> - Create a new page <ul style="list-style-type: none"> - Title: "Title" - name: "test"
<i>Tear-Down</i>	None
<i>Test-Data</i>	text: "" level: 6
<i>Oracle</i>	<ul style="list-style-type: none"> - Pre-condition violated: text_non_empty - Pre-condition: 1 <= level <= 6 - Pre-condition: text != ""

Property	Description
<i>Test ID</i>	FR 2.1.1.8.1
<i>Title</i>	Add heading with illegal level
<i>Test</i>	add_heading(text: STRING; level: INTEGER): GMLG_HEADING
<i>Description</i>	Test that adding a heading with an illegal level value will throw a pre-condition violation exception
<i>Set-Up</i>	<ul style="list-style-type: none"> - Create a new page <ul style="list-style-type: none"> - Title: "Title" - name: "test"
<i>Tear-Down</i>	None
<i>Test-Data</i>	text: "This is a heading" level: 12
<i>Oracle</i>	<ul style="list-style-type: none"> - Pre-condition violated: legal_level - Pre-condition: 1 <= level <= 6 - Pre-condition: text != ""

Property	Description
<i>Test ID</i>	FR 2.1.1.9
<i>Title</i>	Add table
<i>Test</i>	add_table(rows : INTEGER; cols : INTEGER): GMLG_TABLE
<i>Description</i>	Test that adding a table works as expected
<i>Set-Up</i>	<ul style="list-style-type: none"> - Create a new page <ul style="list-style-type: none"> - Title: "Title"

	- name: "test"
<i>Tear-Down</i>	None
<i>Test-Data</i>	rows: 4 cols: 4
<i>Oracle</i>	<ul style="list-style-type: none"> - Tags count of the page increased by 1 - First element of tags list is of type GMLG_TABLE - Object created with: <ul style="list-style-type: none"> - class_attr = "table" - rows: 4 - cols: 4 - bordered: False - generating_page = same as setup page - id = 0

Property	Description
<i>Test ID</i>	FR 2.1.1.10
<i>Title</i>	Add Linebreak
<i>Test</i>	add_linebreak: GMLG_LINEBREAK
<i>Description</i>	Test that adding a linebreak works as expected
<i>Set-Up</i>	<ul style="list-style-type: none"> - Create a new page <ul style="list-style-type: none"> - Title: "Title" - name: "test"
<i>Tear-Down</i>	None
<i>Test-Data</i>	None
<i>Oracle</i>	<ul style="list-style-type: none"> - Tags count of the page increased by 1 - First element of tags list is of type GMLG_LINEBREAK - Object created with: <ul style="list-style-type: none"> - class_attr = "linebreak" - id = 0

Property	Description
<i>Test ID</i>	FR 2.1.1.11
<i>Title</i>	Add List
<i>Test</i>	add_list(order: BOOLEAN): GMLG_LIST
<i>Description</i>	Test that adding a linebreak works as expected
<i>Set-Up</i>	<ul style="list-style-type: none"> - Create a new page <ul style="list-style-type: none"> - Title: "Title" - name: "test"
<i>Tear-Down</i>	None
<i>Test-Data</i>	order: True
<i>Oracle</i>	<ul style="list-style-type: none"> - Tags count of the page increased by 1 - First element of tags list is of type GMLG_LIST - Object created with: <ul style="list-style-type: none"> - class_attr = "list" - id = 0 - ordered: True

Property	Description
<i>Test ID</i>	FR 2.1.1.12
<i>Title</i>	Generate HTML code
<i>Test</i>	generate_html_code: STRING
<i>Description</i>	Generate html code works as expected
<i>Set-Up</i>	None
<i>Tear-Down</i>	None
<i>Test-Data</i>	<ul style="list-style-type: none"> - Create a new page(0) <ul style="list-style-type: none"> - Title: "Title" - name: "test" - add an image to the page (1) <ul style="list-style-type: none"> - src: img.jpg - add a thematic break to the page - add an anchor link to the page <ul style="list-style-type: none"> - text: "anchor link" - link anchor link to the first image (1) - add a local link to the page <ul style="list-style-type: none"> - text: "local link"

	<ul style="list-style-type: none"> - link local link to the page (0) - add an external link to the page <ul style="list-style-type: none"> - text: "external link" - link external link to "https://google.com" - add a paragraph to the page <ul style="list-style-type: none"> - add block <ul style="list-style-type: none"> - text: "no style here" - style: "" - add block <ul style="list-style-type: none"> - text: "this is italic" - style: "italic" - add block <ul style="list-style-type: none"> - text: "and this is bold" - style: "bold" - add block <ul style="list-style-type: none"> - text: "and this underlined" - style: "underlined" - add snippet to the page <ul style="list-style-type: none"> - code: <script>alert("hello");</script> - add heading to the page: <ul style="list-style-type: none"> - text: "This is a heading" - level: 6 - add image (2) <ul style="list-style-type: none"> - src: "test_table.jpg" - add paragraph (3) <ul style="list-style-type: none"> - add block <ul style="list-style-type: none"> - text: "test" - style: "" - add table <ul style="list-style-type: none"> - rows: 3 - cols: 2 - add number <ul style="list-style-type: none"> - 1 <ul style="list-style-type: none"> - row: 1 - col: 1 - add number <ul style="list-style-type: none"> - 2 <ul style="list-style-type: none"> - row: 1 - col: 2 - add string <ul style="list-style-type: none"> - "a" <ul style="list-style-type: none"> - row: 2 - col: 1 - add string <ul style="list-style-type: none"> - "b" <ul style="list-style-type: none"> - row: 2 - col: 2 - add element <ul style="list-style-type: none"> - tag: image (2) - row: 3 - col: 1 - add element
--	--

	<ul style="list-style-type: none"> - tag: paragraph (3) - row:3 - col:2 - add linebreak - add paragraph (4) <ul style="list-style-type: none"> - text: "list example 1" - style: "" - add paragraph (5) <ul style="list-style-type: none"> - text: "list example 2" - style: "" - add list <ul style="list-style-type: none"> - order: true - add content <ul style="list-style-type: none"> - tag: paragraph (4) - add content: <ul style="list-style-type: none"> - tag: paragraph (5)
Oracle	<p>Expected result:</p> <ul style="list-style-type: none"> - The call should return: <pre> <!DOCTYPE html> <html> <head> <meta charset='UTF-8'> <title>Title</title> </head> <body> <hr> anchor link local link external link <p class="paragraph" id="5">no style here <i>this is italic</i> and this is bold <u>and this is underlined</u></p> <script>alert("hello");</script> <h6 id="7">This is a heading</h6> <table id="10" class="table" border="0"> <tr> <td>1</td> <td>2</td> </tr> <tr> <td>a</td> <td>b</td> </tr> <tr> <td></td> <td><p id="table_10_9" class="paragraph">test </p></td> </tr> </table> </pre>

	<pre>
 <ol id="12" class="list"> <p class="paragraph" id="list_12_10">list example 1</p> <p class="paragraph" id="list_12_11">list example 2</p> </body> </html> </pre>
--	---

Property	Description
Test ID	FR 2.1.1.13
Title	Generate MARKDOWN code
Test	generate_markdownl_code: STRING
Description	Generate markdownl code works as expected
Set-Up	<ul style="list-style-type: none"> - add a local link to the page <ul style="list-style-type: none"> - text: "local link" - link local link to the page (0) - add an external link to the page <ul style="list-style-type: none"> - text: "external link" - link external link to "https://google.com" - add a paragraph to the page <ul style="list-style-type: none"> - add block <ul style="list-style-type: none"> - text: "no style here" - style: "" - add block <ul style="list-style-type: none"> - text: "this is italic" - style: "italic" - add block <ul style="list-style-type: none"> - text: "and this is bold" - style: "bold" - add block <ul style="list-style-type: none"> - text: "and this underlined" - style: "underlined" - add snippet to the page <ul style="list-style-type: none"> - code: <script>alert("hello");</script> - add heading to the page: <ul style="list-style-type: none"> - text: "This is a heading" - level: 6 - add image (2) <ul style="list-style-type: none"> - src: "test_table.jpg" - add paragraph (3) <ul style="list-style-type: none"> - add block

	<ul style="list-style-type: none"> - text: "test" - style: "" - add table <ul style="list-style-type: none"> - rows: 3 - cols: 2 - add number <ul style="list-style-type: none"> - 1 - row: 1 - col: 1 - add number <ul style="list-style-type: none"> - 2 - row: 1 - col: 2 - add string <ul style="list-style-type: none"> - "a" - row: 2 - col: 1 - add string <ul style="list-style-type: none"> - "b" - row: 2 - col: 2 - add element <ul style="list-style-type: none"> - tag: image (2) - row: 3 - col: 1 - add element <ul style="list-style-type: none"> - tag: paragraph (3) - row: 3 - col: 2 - add linebreak - add paragraph (4) <ul style="list-style-type: none"> - text: "list example 1" - style: "" - add paragraph (5) <ul style="list-style-type: none"> - text: "list example 2" - style: "" - add list <ul style="list-style-type: none"> - order: true - add content <ul style="list-style-type: none"> - tag: paragraph (4) - add content: <ul style="list-style-type: none"> - tag: paragraph (5)
<i>Tear-Down</i>	None
<i>Test-Data</i>	None (see Set-Up)
<i>Oracle</i>	Expected result: The call should return

	<p>![image]("img.jpg")</p> <p>_____</p> <p>[anchor link](#0)</p> <p>[local link](/test.html)</p> <p>[external link](https://google.com)</p> <p>no style here <u>this is italic</u> **and this is bold** and this is underlined</p> <p><script>alert("hello");</script></p> <p>##### This is a heading</p> <table><tr><td> </td><td>1</td><td> </td><td>2</td><td> </td></tr><tr><td> </td><td>----</td><td> </td><td>----</td><td> </td></tr><tr><td> </td><td>a</td><td> </td><td>b</td><td> </td></tr></table> <p>! image (test_table.jpg) test </p> <ol style="list-style-type: none">1. list example 12. list example 20		1		2			----		----			a		b	
	1		2													
	----		----													
	a		b													

2.1.2 Class: GMLG_IMG

Property	Description
<i>Test ID</i>	FR 2.1.2.0
<i>Title</i>	Set width and height
<i>Test</i>	set_width (a_width: INTEGER) set_height (a_width: INTEGER)
<i>Description</i>	Set a width and a height to an image
<i>Set-Up</i>	<ul style="list-style-type: none"> - Create a new page <ul style="list-style-type: none"> - Title: "Title" - name: "test" - add an image to the page <ul style="list-style-type: none"> - src: img.jpg
<i>Tear-Down</i>	None
<i>Test-Data</i>	width: 100 height: 100
<i>Oracle</i>	image width = 100 image height = 100 Pre-condition: width_size_invalid: a_width >= 5 and a_width <= 1024

Property	Description
<i>Test ID</i>	FR 2.1.2.0.1
<i>Title</i>	Set width and height with invalid values
<i>Test</i>	set_width (a_width: INTEGER) set_height (a_width: INTEGER)
<i>Description</i>	Set a width and a height to an image
<i>Set-Up</i>	<ul style="list-style-type: none"> - Create a new page <ul style="list-style-type: none"> - Title: "Title" - name: "test" - add an image to the page <ul style="list-style-type: none"> - src: img.jpg

<i>Tear-Down</i>	None
<i>Test-Data</i>	width: 2000 height: 1
<i>Oracle</i>	Pre-condition: width_size_invalid: a_width >= 5 and a_width <= 1024 Expected result: precondition violation exception.

2.1.3 Class: GMLG_HEADING

Property	Description
<i>Test ID</i>	FR 2.1.2.3.0
<i>Title</i>	Set italic
<i>Test</i>	set_italic
<i>Description</i>	Set a heading style to italic
<i>Set-Up</i>	<ul style="list-style-type: none"> - Create a new page <ul style="list-style-type: none"> - Title: "Title" - name: "test" - add a heading to the page with: <ul style="list-style-type: none"> - text: "This is a heading" - level: 6
<i>Tear-Down</i>	None
<i>Test-Data</i>	None
<i>Oracle</i>	<ul style="list-style-type: none"> - is_italic = True

2.1.4 Class: GMLG_TABLE

Property	Description
<i>Test ID</i>	FR 2.1.2.4.0
<i>Title</i>	toggle bordered
<i>Test</i>	toggle_bordered
<i>Description</i>	Toggle bordered of a table

<i>Set-Up</i>	<ul style="list-style-type: none"> - Create a new page <ul style="list-style-type: none"> - Title: "Title" - name: "test" - Add a table with: <ul style="list-style-type: none"> - cols: 1 - rows: 1
<i>Tear-Down</i>	None
<i>Test-Data</i>	None
<i>Oracle</i>	<ul style="list-style-type: none"> - Table attributes: <ul style="list-style-type: none"> - bordered: True

Property	Description
<i>Test ID</i>	FR 2.1.2.4.1
<i>Title</i>	Add element
<i>Test</i>	add_element(tag: GMLG_TAG; row, column: INTEGER)
<i>Description</i>	Add an element to a table cell
<i>Set-Up</i>	<ul style="list-style-type: none"> - Create a new page <ul style="list-style-type: none"> - Title: "Title" - name: "test" - Add a table with: <ul style="list-style-type: none"> - cols: 1 - rows: 1 - Add an image with: <ul style="list-style-type: none"> - src: "test.jpg"
<i>Tear-Down</i>	None
<i>Test-Data</i>	image created in Set-Up, col=1, row=1
<i>Oracle</i>	<ul style="list-style-type: none"> - Table element (0,0) is of type GMLG_IMG with feature src = "test.jpg" - Preconditions: <ul style="list-style-type: none"> - row_col_above_zero: row > 0 and column > 0 - legal_row_and_col: row <= Current.get_rows and column <= Current.get_cols - Expected result: <ul style="list-style-type: none"> - image removed from page linked list - page linked list count = 0 - image id = "table_0_1"

Property	Description
----------	-------------

<i>Test ID</i>	FR 2.1.2.4.2
<i>Title</i>	Add number
<i>Test</i>	add_number(ele: INTEGER; row, column: INTEGER)
<i>Description</i>	Add a number to a table cell
<i>Set-Up</i>	<ul style="list-style-type: none"> - Create a new page <ul style="list-style-type: none"> - Title: "Title" - name: "test" - Add a table with: <ul style="list-style-type: none"> - cols: 1 - rows: 1
<i>Tear-Down</i>	None
<i>Test-Data</i>	ele: 10
<i>Oracle</i>	<ul style="list-style-type: none"> - Table element (0,0) is of type GMLG_SNIPPET with feature code = "10" - Preconditions: <ul style="list-style-type: none"> - row_col_above_zero: row > 0 and column > 0 - legal_row_and_col: row <= Current.get_rows and column <= Current.get_cols

Property	Description
<i>Test ID</i>	FR 2.1.2.4.3
<i>Title</i>	Add string
<i>Test</i>	add_string(ele: STRING; row, column: INTEGER)
<i>Description</i>	Add a string to a table cell
<i>Set-Up</i>	<ul style="list-style-type: none"> - Create a new page <ul style="list-style-type: none"> - Title: "Title" - name: "test" - Add a table with: <ul style="list-style-type: none"> - cols: 1 - rows: 1
<i>Tear-Down</i>	None
<i>Test-Data</i>	ele: "this is a test"
<i>Oracle</i>	<ul style="list-style-type: none"> - Table element (0,0) is of type GMLG_SNIPPET with feature code = "this is a test" - Preconditions: <ul style="list-style-type: none"> - row_col_above_zero: row > 0 and column > 0

	<ul style="list-style-type: none"> - legal_row_and_col: row <= Current.get_rows and column <= Current.get_cols
--	---

2.1.5 Class: GMLG_LIST

Property	Description
<i>Test ID</i>	FR 2.1.2.5.0
<i>Title</i>	Add content
<i>Test</i>	add_content(tag: GMLG_TAG)
<i>Description</i>	Add an element to the list
<i>Set-Up</i>	<ul style="list-style-type: none"> - Create a new page <ul style="list-style-type: none"> - Title: "Title" - name: "test" - Add a list with: <ul style="list-style-type: none"> - order: True - Add an img with: <ul style="list-style-type: none"> - src: "img.jpg"
<i>Tear-Down</i>	None
<i>Test-Data</i>	Image in Set-Up
<i>Oracle</i>	<ul style="list-style-type: none"> - Expected result: <ul style="list-style-type: none"> - list elements count + 1 - list elements first element of type GMLG_IMG - list elements first element feature "get_src" = "img.jpg"

2.1.6 Class: GMLG_ANCHOR_LINK

Property	Description
<i>Test ID</i>	FR 2.1.2.6.0
<i>Title</i>	Link to a tag
<i>Test</i>	link_to(tag: GMLG_TAG)
<i>Description</i>	Link the anchor link to a tag
<i>Set-Up</i>	<ul style="list-style-type: none"> - Create a new page

	<ul style="list-style-type: none"> - Title: "Title" - name: "test" - add an anchor to the page: <ul style="list-style-type: none"> - text: "This is linked to a heading" - add a heading to the page with: <ul style="list-style-type: none"> - text: "This is a heading" - level: 6
<i>Tear-Down</i>	None
<i>Test-Data</i>	heading created in Set-up
<i>Oracle</i>	<ul style="list-style-type: none"> - Link attributes: <ul style="list-style-type: none"> - src = "#1" - Pre-condition: tag_id_set: tag.get_id != Void

2.1.7 Class: GMLG_LOCAL_LINK

Property	Description
<i>Test ID</i>	FR 2.1.2.7.0
<i>Title</i>	Link to a page
<i>Test</i>	link_to(page: GMLG)
<i>Description</i>	Link the anchor link to a page
<i>Set-Up</i>	<ul style="list-style-type: none"> - Create a new page <ul style="list-style-type: none"> - Title: "Title" - name: "test" - add a local to the page: <ul style="list-style-type: none"> - text: "This is linked to a page" - Create a new page <ul style="list-style-type: none"> - Title: "New Title" - name: "anothertest"
<i>Tear-Down</i>	None
<i>Test-Data</i>	page created in Set-Up
<i>Oracle</i>	<ul style="list-style-type: none"> - Link attributes: <ul style="list-style-type: none"> - src = "/anothertest.html"

	<ul style="list-style-type: none"> - pre-condition: page_name_set: page.name != Void and page.name != ""
--	---

2.1.8 Class: GMLG_EXTERNAL_LINK

Property	Description
<i>Test ID</i>	FR 2.1.2.7.0
<i>Title</i>	Link to a URL
<i>Test</i>	link_to(url: STRING)
<i>Description</i>	Link the external link to a URL
<i>Set-Up</i>	<ul style="list-style-type: none"> - Create a new page <ul style="list-style-type: none"> - Title: "Title" - name: "test" - add an external to the page: <ul style="list-style-type: none"> - text: "This is linked to a URL"
<i>Tear-Down</i>	None
<i>Test-Data</i>	url: "https://zampeamollo.ch"
<i>Oracle</i>	<ul style="list-style-type: none"> - Link attributes: <ul style="list-style-type: none"> - src = "https://zampeamollo.ch"

Property	Description
<i>Test ID</i>	FR 2.1.2.7.0.1
<i>Title</i>	Link to an invalid URL
<i>Test</i>	link_to(url: STRING)
<i>Description</i>	Link the external link to a URL
<i>Set-Up</i>	<ul style="list-style-type: none"> - Create a new page <ul style="list-style-type: none"> - Title: "Title" - name: "test" - add an external link to the page:

	- text: "This is linked to a URL"
<i>Tear-Down</i>	None
<i>Test-Data</i>	url: "abc"
<i>Oracle</i>	<ul style="list-style-type: none">- Expected result: error log stating that the url is invalid in the console- link feature:<ul style="list-style-type: none">- src = ""

3 Expected Coverage

We expect that those tests cover all features available to the end user with expected input and some special cases with an unexpected input.

We think that since we're covering the creation of all tags and the expected HTML and Markdown output, we can say with a certain degree of certainty that the library is stable enough if it passes all the tests.

Therefore we can estimate a coverage of 90% since all the features are used in a way or another, but we can't be certain that we didn't miss some special cases.

4 Benchmarks

Property	Description
<i>Test ID</i>	FR 4.1
<i>Title</i>	Average output time
<i>Test</i>	generate_html_code
<i>Description</i>	Check that generating html code takes less than 10 seconds in average
<i>Set-Up</i>	None
<i>Tear-Down</i>	None
<i>Test-Data</i>	<ul style="list-style-type: none">- Create a new page<ul style="list-style-type: none">- Title: "Title"- name: "test"- add an external link to the page:<ul style="list-style-type: none">- text: "This is linked to a URL"- link_to "https://google.com"- add image:<ul style="list-style-type: none">- src: "img.jpg"- add table<ul style="list-style-type: none">- cols: 3- rows: 3- add_number(1,1,1)- add_number(2,1,2)- add_number(3,1,3)- add_string("a", 2, 1)- add_string("b",2,2)- add_string("c",2,3)- add_element

	<ul style="list-style-type: none">- image created before- row 3- col 1- add image<ul style="list-style-type: none">- src: "example.jpg"- add linebreak- add paragraph<ul style="list-style-type: none">- add block<ul style="list-style-type: none">- "hi", "italic"
<i>Oracle</i>	<ul style="list-style-type: none">- Expected result: output given in less than 10 seconds