



Blazor State Management

Managing User Data Across Client and Server

Tim Purdum


DevUp Conf

August, 2025






Goals of the Session

- **Identify the major elements and framework features that make up state in Blazor**
 - **Briefly touch on state storage and retrieval**
 - **Learn about how the Blazor rendering modes impact state management**
 - **Identify larger architectural patterns for managing state in a Blazor application**
- 

What is Blazor?

- Modern full-stack web framework
- Built on Asp.NET Core and Modern .NET
- Robust, production-ready solution since .NET Core 3.1 in 2018
- Static and dynamic Server-Side rendering
- Client WebAssembly SPA applications or individual components
- High productivity with a single unifying language and framework
- Hot-reload == rapid development with robust dev tools



dev up **Bl@zing Shipments**

As we look at this web app, consider the following questions:

- Where is the page being rendered?
- How does it know what data to load?
- Is the page comprised of a single component, or many?
- How does the site respond to user interaction?
- If we needed to store data, where would we store it?





What is State Management?

- “State management refers to the management of the state of one or more user interface controls such as text fields, submit buttons, radio buttons, etc. in a graphical user interface.”
 - *from Wikipedia (based on redux.js.org)*





Types of State in Web Development

- **Component State**
- **Application State**
- **User/Session State**





Component State

- Stored in component fields/properties or a model object
- Bound to HTML input and display elements
- Unsaved changes are lost on navigation/refresh

```
<p role="status">Current count: @currentCount</p>
<button class="btn btn-primary"
    @onclick="IncrementCount">Click me</button>
@code {
    private int currentCount = 0;
    private void IncrementCount() => currentCount++;
}
```



Component State

- /

```
<input type="text" @bind="fieldOrProp" />
```

- fires with the event

- Change the event with `@bind:event="oninput"`

- Add a change handler method with `@bind:after="HandlerMethod"`

- C w /

```
<TestComponent @bind-ParameterName="fieldOrProp" />
```


Application State

- State shared across components using
 - **Parameters**
 - **CascadingValues**
 - **EventCallbacks**
 - **Service Classes**



Application State: Parameters

- C# public properties with [Parameter] attribute on a child component

```
MapView.razor
```

```
[Parameter]  
public double? Latitude { get; set; }
```

```
[Parameter]  
public double? Longitude { get; set; }
```

- In consuming (parent) class markup, parameters display like HTML attributes with capital letters

```
<MapView Latitude="@shipment.Latitude" Longitude="@shipment.Longitude">  
  <Map>  
    <Basemap>  
      <BasemapStyle Name="BasemapStyleName.ArcgisStreets"/>  
    </Basemap>  
  </Map>  
</MapView>
```



Application State: Cascading Values

- Wrap child components with markup tags

```
<CascadingValue Value="@User" Name="CurrentUser">  
  <ProfileSelector />  
</CascadingValue>
```

- !

/ t

```
[CascadingParameter(Name="CurrentUser")]  
public ApplicationUser? CurrentUser { get; set; }
```

dev up Application State: EventCallbacks

- A type of Parameter
- Async-supporting Event triggers

```
[Parameter]
public EventCallback<LayerViewCreateEvent> OnLayerViewCreate { get; set; }
```

- Bind to a parent component method instead of field or property

```
<MapView OnLayerViewCreate="OnLayerViewCreate">
  <Map>
    <FeatureLayer OutFields="@(["*"])">
      <PortalItem PortalItemId="234d2e3f6f554e0e84757662469c26d3" />
    </FeatureLayer>
  </Map>
</Extent>
</ MapView>
```

```
private async Task OnLayerViewCreate(LayerViewCreateEvent createEvent)
{
    if (createEvent.Layer is FeatureLayer)
    {
        // query the feature service
    }
}
```



Application State: Service Classes

- Any C# Class can be injected via Property Injection

- In Razor Markup

```
@page "/order"  
@inject StateManagementService StateManagementService
```

- Or in C#

```
@code {  
    [Inject]  
    private StateManagementService? StateManager { get; set; }  
}
```

- ! { a t /
- { /
- Ü b 9Ç 9 l



User/Session State


- Authentication
- Authorization
- Profile
- Records
- Work Progress





User/Session State

- **Browser Persistence**
 - **Query String** <https://blazingshipments.com?id=12345>
 - **Tokens**
 - **Cookies**
 - **localStorage**
 - **sessionStorage**
 - **indexedDb**
- **Server Persistence**
 - **Persistent Cache (e.g., Redis)**
 - **Database**





Application State: Service Classes

- Any C# Class can be injected via Property Injection

- In Razor Markup

```
@page "/order"
@inject StateManagementService StateManagementService
```

- Or in C#

```
@code {
    [Inject]
    private StateManagementService? StateManager { get; set; }
}
```

- ! { a t /
- { /
- Ü b9Ç 9 l



Persistent State: Browser Storage

- **localStorage**
 - persists when tab/browser is closed, across multiple tabs
- **sessionStorage**
 - isolates data between tabs to prevent issues, data also is lost when tab is closed
- **IndexedDb**
 - Object-store structured database
 - Create an object store with a key path (aka ID) or a key generator
 - Also supports indexes
 - Transaction-scoped access: add, put (update), get, delete
- All require JavaScript or NuGet JS wrappers to interact.
- Available in “Interactive Render Modes”



Persistent State: Server Storage

- Too many options to enumerate, but here's a few
 - Redis cache
 - Database
- Only available from “Interactive Server” or via web API calls.




Blazor Render Modes

- { { a
- L { a
- L í ! a
- L ! a




Blazor Render Modes: Static Server






Blazor Render Modes: Interactive Server



- Continuous websocket connection between client and server with SignalR
- Live data-binding, real-time updates, JavaScript interop
- Direct access to server data store
- Fast on first load
- Leaving browser tabs open can cause disconnection issues



Blazor Render Modes: Interactive Server




- **State Challenges**

- Making reconnect a seamless experience
- Large sites with multiples servers require a SignalR service to keep track of which users are connected to each server
- Data size limits and lag can impact usability of some features



Blazor Render Modes: Interactive WebAssembly




- Runs in the client browser
- Live data-binding, real-time updates, JavaScript interop
- HttpClient calls to communicate with server web API

- Single-threaded
- Large/slow first load
- Fast interactions after load
- Closest in approach to most JS SPA frameworks



Blazor Render Modes: Interactive WebAssembly



- **State Challenges**

- Easy for state to get out of sync with server, when tracking changes locally
- Creating new data objects before syncing requires an ID strategy



Blazor Render Modes: Interactive Auto



- On first load, runs from server, creating SignalR connection
- In the background, downloads .NET runtime and client code
- On next load, switches to running from WebAssembly
- “Best of both worlds”
 - Fast start on first load (server)
 - More responsive and robust interactions (client)
- Requires flexible data handling/abstraction to handle both client and server modes



Architectural Patterns for State Management


- {
 - w C w a ëÜ
 - ó! a [C a ëëa
 - ! b9Ç/ a ë/ a ë/
- .



Architectural Patterns for State Management

- **Goals for Blazor State Management**
 - Enable component developers to create flexible components that will work in both Interactive Server and Interactive WebAssembly modes
 - Reduce boilerplate logic like pass-through methods
 - *(e.g., `clientComponent => clientService => webApi => webService => dataRepository`)*
 - Provide a consistent pattern for communication between components
 - Abstract away communication from WebAssembly client to Server
 - Keep pages and components lightweight and easy to read
 - Allow generic implementations for simple use cases

MVSM™



- **Model**
- **View**
- **State Manager**
 - Model and View are tightly coupled, designed to work together with two-way binding.
 - Model actually can live in either the View or the Manager class.
 - State Manager is responsible for all transport and any data transformation that would take place before hitting the data storage.
 - State Manager also provides us a place to add API transport logic.

SERVER

API

SignalR Client

RazorComponentPage
StateComponentBase

Fields & Properties

PageModel
: StateRecord

RedoStack

UndoStack

Methods

Redo

Undo

Delete

Save

Load

Track Changes

ServerStateManager

Load

Delete

Save

Data
Repository

BROWSER

WebAssembly
Client

RazorComponentPage
StateComponentBase

Fields & Properties

PageModel
: StateRecord

RedoStack

UndoStack

Methods

Redo

Undo

Save

Load

Track Changes

Delete


ClientStateManager


Save


Delete

Load

IndexedDb









Review



Core Concepts of State Management

- **Definition:** State management involves tracking the dynamic data of a user interface—across components, sessions, and storage layers.
- **Types of State:**
 - *Component State:* Temporary, lost on refresh or navigation.
 - *Application State:* Shared across components using cascading values, DI services, etc.
 - *User/Session State:* Stored in browser memory (e.g., localStorage, sessionStorage, indexedDb), usually not synced with the server.
 - *Persistent State:* Long-term data stored in a database or API.



Review

Blazor Render Modes & Their State Implications

- **Static Server Mode:**
 - Simple form submission and HTML rendering.
 - Limited interactivity and no real-time state updates.
 - Persistence tools: cookies, tokens, query strings.
- **Interactive Server Mode:**
 - Real-time two-way binding using SignalR.
 - Enables in-memory server-side tracking and real-time updates.
 - Challenges: reconnection handling, distributed server sync.
- **Interactive WebAssembly Mode:**
 - Fully client-side execution.
 - Rich interactivity with flexible state control
 - .Risks of state desynchronization and ID conflicts for new data.
- **Interactive Auto Mode:**
 - Hybrid approach: server-rendered first load, client-side on reload.
 - Balances fast startup with responsive interactivity.



Review

✦ Patterns for Binding & Application State Sharing

- *Binding:*
 - @bind, @bind:event, @bind:get/set, and @bind:after allow seamless two-way data binding in Razor.
- *Component Communication:*
 - Parameters, CascadingValues, EventCallbacks, and DI Services are used to maintain shared state and coordination.

📁 Browser Storage Techniques

- *localStorage and sessionStorage:*
 - Simple key-value stores for persistence.
- *IndexedDb:*
 - Structured object store with indexing and transaction support. Can be wrapped with JS + C# logic or NuGet packages.



Review

🧠 Architectural Patterns for Blazor

- **MVU:** Immutable, Redux-style, but not ideal for Blazor's reactive capabilities.
- **MVVM:** Familiar in .NET but verbose; Blazor doesn't require `INotifyPropertyChanged`.
- **MVC:** Suited for non-interactive, server-rendered apps—less effective in Blazor.

🧩 MVSM™ – A Blazor-Centric Pattern

- **Model-View-State Manager:**
 - Two-way binding between View and Model
 - .State Manager handles all data transport, persistence, and API abstraction.
 - Designed for extensibility using generics, reflection, and browser storage.

<https://nation-finder.geoblazor.com>

Find the country based on its outline



Thank you to our Sponsors!



Thank You!



dymaptic

Notes & Links @
<https://timpurdum.dev>

