Formalizing reachability, viability and avoidability in the context of sequential decision problems

Nicola Botta

Outline

- Why formalizing what?
- ► Minimal goals
- Sequential decision problems
- Reachability, viability and avoidability
- Decision procedures

- ▶ International emissions trading: Good or bad?, Holtsmark & Sommervoll, 2012: "[...] we find that an agreement with international emissions trading leads to increased emissions and reduced efficiency."
- ► The case for international emission trade in the absence of cooperative climate policy, Carbone et al., 2009: "[...] we find that emission trade agreements can be effective [...]"

- ▶ International emissions trading: Good or bad?, Holtsmark & Sommervoll, 2012: "[...] we find that an agreement with international emissions trading leads to increased emissions and reduced efficiency."
- ► The case for international emission trade in the absence of cooperative climate policy, Carbone et al., 2009: "[...] we find that emission trade agreements can be effective [...]"

- ▶ International emissions trading: Good or bad?, Holtsmark & Sommervoll, 2012: "[...] we find that an agreement with international emissions trading leads to increased emissions and reduced efficiency."
- ► The case for international emission trade in the absence of cooperative climate policy, Carbone et al., 2009: "[...] we find that emission trade agreements can be effective [...]"

- ▶ International emissions trading: Good or bad?, Holtsmark & Sommervoll, 2012: "[...] we find that an agreement with international emissions trading leads to increased emissions and reduced efficiency."
- ▶ The case for international emission trade in the absence of cooperative climate policy, Carbone et al., 2009: "[...] we find that emission trade agreements can be effective [...]"
- Confronting Climate Change: Avoiding the Unmanageable and Managing the Unavoidable, P. Raven, R. Bierbaum, J. Holdren, UN-Sigma Xi Climate Change Report, 2007.

Some notion of avoidability is implicit in the WG3_IPCC_AR5_2014 definitions of

mitigation: "A human intervention to reduce the sources or enhance the sinks of greenhouse gases"

Some notion of avoidability is implicit in the WG3_IPCC_AR5_2014 definitions of

► mitigation: "A human intervention to reduce the sources or enhance the sinks of greenhouse gases" ⇒ avoid high atmospheric GHG concentrations

Some notion of avoidability is implicit in the WG3_IPCC_AR5_2014 definitions of

- ► mitigation: "A human intervention to reduce the sources or enhance the sinks of greenhouse gases" ⇒ avoid high atmospheric GHG concentrations
- ► adaptation: "The process of adjustment to actual or expected climate and its effects . . . to moderate harm or exploit beneficial opportunities"

Some notion of avoidability is implicit in the WG3_IPCC_AR5_2014 definitions of

- ► mitigation: "A human intervention to reduce the sources or enhance the sinks of greenhouse gases" ⇒ avoid high atmospheric GHG concentrations
- adaptation: "The process of adjustment to actual or expected climate and its effects ... to moderate harm or exploit beneficial opportunities" ⇒ avoid too much harm, realize beneficial opportunities

Some notion of avoidability is implicit in the WG3_IPCC_AR5_2014 definitions of

- ► mitigation: "A human intervention to reduce the sources or enhance the sinks of greenhouse gases" ⇒ avoid high atmospheric GHG concentrations
- adaptation: "The process of adjustment to actual or expected climate and its effects ... to moderate harm or exploit beneficial opportunities" ⇒ avoid too much harm, realize beneficial opportunities

But what does it mean (for atmospheric GHG concentrations) to be avoidable?



"Die Rolle der Klimaforschung bleibt weiterhin, die Problemfakten auf den Tisch zu knallen und Optionen für geeignete Lösungswege zu identifizieren."

H.-J. Schellnhuber in Frankfurter Allgemeine from 2012-06-19

But how can we produce "hard facts" if the notions used to phrase specific, concrete problems are ambiguous, devoid of precise, well established, meanings?

Explain what it means for future (possibly harmful) states to be avoidable [reachable, viable, ...]

- ► Explain what it means for future (possibly harmful) states to be avoidable [reachable, viable, ...]
- ► Explain under which conditions is it *decidable* whether future states are avoidable [reachable, viable, . . .] or not

- Explain what it means for future (possibly harmful) states to be avoidable [reachable, viable, ...]
- Explain under which conditions is it decidable whether future states are avoidable [reachable, viable, ...] or not

Further questions, goals

- Explain what it means for future (possibly harmful) states to be avoidable [reachable, viable, ...]
- ► Explain under which conditions is it *decidable* whether future states are avoidable [reachable, viable, ...] or not

Further questions, goals

Can one exploit decidability to derive useful avoidability (levity?) measures?

- Explain what it means for future (possibly harmful) states to be avoidable [reachable, viable, ...]
- ► Explain under which conditions is it *decidable* whether future states are avoidable [reachable, viable, ...] or not

Further questions, goals

- Can one exploit decidability to derive useful avoidability (levity?) measures?
- Can one refine decidable notions of viability, avoidability to derive operational notions (measures?) of sustainability, adaptability, resilience?

Sequential decision problems (intuition)


Sequential decision problems (intuition)




You are here...




These are your options. . .




Pick one!



Advance one step. . .



... collect rewards ...




...and go!



n steps left

General sequential decision problems (intuition)


General sequential decision problems (intuition)



Sequential decision problems (notation)

Idris	Logic
A : Type	A is a set
a : A	$a \in A$
P : Type	P is a predicate
p : P	p is a proof of P
FALSE (empty type)	False
non-empty type	True
$P \rightarrow Q$	P implies Q
(a : A ** P a)	there exists an $a \in A$ such that P a holds
$(a:A) \rightarrow P a$	forall $a \in A$, P a holds

Figure: Curry-Howard correspondence relating Idris and logic.



At each decision step, a set of possible states:

$$X:(t:\mathbb{N}) o extit{Type}$$

At each decision step, a set of possible states:

$$X:(t:\mathbb{N})\to \mathit{Type}$$

At each decision step and for each state, a set of options

$$Y:(t:\mathbb{N}) o (x:X\;t) o \mathit{Type}$$

At each decision step, a set of possible states:

$$X:(t:\mathbb{N})\to \mathit{Type}$$

At each decision step and for each state, a set of options

$$Y:(t:\mathbb{N})\to(x:X\;t)\to \mathit{Type}$$

A transition function

$$step: (t: \mathbb{N}) \rightarrow (x: X t) \rightarrow (y: Y t x) \rightarrow M(X(S t))$$

At each decision step, a set of possible states:

$$X:(t:\mathbb{N})\to \mathit{Type}$$

At each decision step and for each state, a set of options

$$Y:(t:\mathbb{N})\to (x:X\;t)\to \mathit{Type}$$

A transition function

$$step: (t: \mathbb{N}) \rightarrow (x: X t) \rightarrow (y: Y t x) \rightarrow M(X(S t))$$

What about rewards? What are M and S?

Sequential decision problems (uncertainties)

S t is just the successor of *t*:

data \mathbb{N} : Type where

 $Z:\mathbb{N}$

 $S: \mathbb{N} \to \mathbb{N}$

Sequential decision problems (uncertainties)

S t is just the successor of *t*:

data \mathbb{N} : Type where

 $Z:\mathbb{N}$

 $S: \mathbb{N} \to \mathbb{N}$

 $M: Type \rightarrow Type$ represents the uncertainties of the problem:

- ▶ deterministic problems: M = Id
- ▶ non-deterministic problems: M = List
- ▶ stochastic problems: *M* = *Prob*

Sequential decision problems (uncertainties)

S t is just the successor of *t*:

data \mathbb{N} : Type where

 $Z: \mathbb{N}$

 $S: \mathbb{N} \to \mathbb{N}$

 $M: Type \rightarrow Type$ represents the uncertainties of the problem:

- deterministic problems: M = Id
- ▶ non-deterministic problems: M = List
- ▶ stochastic problems: M = Prob

```
data Prob : Type \rightarrow Type where mkProb : (as : Vect \ n \ a) \rightarrow (ps : Vect \ n \ Float) \rightarrow sum \ ps = 1.0 \rightarrow Prob \ a
```

Sequential decision problems (container monad)

Formally, M is a container monad, that is M is a monad:

```
fmap: (a \rightarrow b) \rightarrow Ma \rightarrow Mb
    ret : a \rightarrow M a
    bind : Ma \rightarrow (a \rightarrow Mb) \rightarrow Mb
ioin : M(Ma) \rightarrow Ma
      functorSpec1 : fmap \circ id = id
      functorSpec2: fmap (f \circ g) = (fmap \ f) \circ (fmap \ g)
    monadSpec1 : (fmap f) \circ ret = ret \circ f
    monadSpec2: bind (ret a) f = f a
      monadSpec3: bind ma ret = ma
    monadSpec4: \{f: a \rightarrow Mb\} \rightarrow \{g: b \rightarrow Mc\} \rightarrow \{g
                                                                                                                                                                                                     bind (bind ma f) g = bind ma (\lambda x \Rightarrow bind (f x) g)
    monadSpec5: join mma = bind mma id
```

Sequential decision problems (container monad)

and M is a container:

```
Elem: a \rightarrow M \ a \rightarrow Type

All: (a \rightarrow Type) \rightarrow M \ a \rightarrow Type
```

```
containerSpec1: a 'Elem' (ret a) containerSpec2: a 'Elem' ma \rightarrow ma 'Elem' mma \rightarrow a 'Elem' (join mma) containerSpec3: All p ma \rightarrow a 'Elem' ma \rightarrow p a
```

Sequential decision problems (basic ideas)

Thus, a concrete sequential decision problem is defined (up to the rewards) in terms of 4 entities: X, Y, M and step

$$X:(t:\mathbb{N}) o \mathit{Type}$$

$$Y:(t:\mathbb{N}) o (x:X\;t) o \mathit{Type}$$

$$step: (t: \mathbb{N}) \rightarrow (x: X t) \rightarrow (y: Y t x) \rightarrow M(X(S t))$$

Sequential decision problems (basic ideas)

Thus, a concrete sequential decision problem is defined (up to the rewards) in terms of 4 entities: X, Y, M and step

$$X:(t:\mathbb{N})\to \mathit{Type}$$

$$Y:(t:\mathbb{N})\to (x:X\;t)\to \mathit{Type}$$

$$step: (t:\mathbb{N}) \rightarrow (x:X\;t) \rightarrow (y:Y\;t\;x) \rightarrow M(X\;(S\;t))$$

We formalize reachability, viability and avoidability in terms of these notions

Reachability and viability (intuition)




Figure: Possible evolution starting from *b* (left), states with limited viability (middle) and unreachable states (right).

Predecessor relation, reachability and viability

The (possible) predecessor relation:

```
\begin{array}{ll} \textit{Pred} \; : \; X \; t \; \rightarrow \; X \; (S \; t) \; \rightarrow \; \textit{Type} \\ \textit{Pred} \; \{ \; t \; \} \; x \; x' \; = \; (y \; : \; Y \; t \; x \; ** \; x' \; `Elem` \; (step \; t \; x \; y)) \end{array}
```

Predecessor relation, reachability and viability

The (possible) predecessor relation:

```
Pred : X t \rightarrow X (S t) \rightarrow Type
Pred \{t\} \times x' = (y : Y t \times ** x' `Elem` (step t \times y))
```

reachability

```
Reachable : X \ t' \rightarrow Type
Reachable \{t' = Z\} \ x' = Unit
Reachable \{t' = S \ t\} \ x' = (x : X \ t ** (Reachable \ x, x `Pred` \ x'))
```

Predecessor relation, reachability and viability

The (possible) predecessor relation:

```
Pred: X t \rightarrow X (S t) \rightarrow Type

Pred \{t\} \times x' = (y : Y t \times ** x' `Elem` (step t \times y))
```

reachability

```
Reachable: X \ t' \rightarrow Type
Reachable \{ t' = Z \} \ x' = Unit
Reachable \{ t' = S \ t \} \ x' = (x : X \ t ** (Reachable \ x, x `Pred` \ x'))
```

and viability

```
Viable : (n : \mathbb{N}) \to X \ t \to Type
Viable \{t\} \ Z \ x = Unit
Viable \{t\} \ (S \ m) \ x = (y : Y \ t \ x ** All \ (Viable \ m) \ (step \ t \ x \ y))
```

► The notion of avoidability is necessarily a relative one: whether a future state is avoidable or not, depends in general on an (actual or hypothetical) current state.

- ► The notion of avoidability is necessarily a relative one: whether a future state is avoidable or not, depends in general on an (actual or hypothetical) current state.
- Thus, avoidability is a relation between states. More precisely, it is a relation between states at a given time and states at some later times.

- ► The notion of avoidability is necessarily a relative one: whether a future state is avoidable or not, depends in general on an (actual or hypothetical) current state.
- Thus, avoidability is a relation between states. More precisely, it is a relation between states at a given time and states at some later times.
- ▶ We are interested in the avoidability of "possible" future states. Specifically, we are interested in the avoidability of states which are reachable from some given state.

- ► The notion of avoidability is necessarily a relative one: whether a future state is avoidable or not, depends in general on an (actual or hypothetical) current state.
- Thus, avoidability is a relation between states. More precisely, it is a relation between states at a given time and states at some later times.
- ▶ We are interested in the avoidability of "possible" future states. Specifically, we are interested in the avoidability of states which are reachable from some given state.
- ▶ The notion of avoidability entails the notion of an alternative.

We are interested in the avoidability of states which are reachable from some given state:

```
ReachableFrom : X \ t'' \rightarrow X \ t \rightarrow Type
ReachableFrom \{t'' = Z\} \{t\} \ x'' \ x = (t = Z, x = x'')
ReachableFrom \{t'' = S \ t'\} \{t\} \ x'' \ x =
Either (t = S \ t', x = x'')
(x' : X \ t' ** (x' `ReachableFrom` x, x' `Pred` x''))
```

where

data Either a
$$b = Left \ a \mid Right \ b$$

We are interested in the avoidability of states which are reachable from some given state:

```
ReachableFrom : X \ t'' \rightarrow X \ t \rightarrow Type
ReachableFrom \{t'' = Z\} \{t\} \ x'' \ x = (t = Z, x = x'')
ReachableFrom \{t'' = S \ t'\} \{t\} \ x'' \ x =
Either (t = S \ t', x = x'')
(x' : X \ t' ** (x' `ReachableFrom` x, x' `Pred` x''))
```

where

data Either a
$$b = Left \ a \mid Right \ b$$

Proof of concept: show that

reachableFromLemma :
$$(x'':X\ t'') \rightarrow (x:X\ t) \rightarrow x''$$
 'ReachableFrom' $x \rightarrow t''$ 'GTE' t

The notion of avoidability entails the notion of an alternative state x''. This has to fulfill three conditions:

```
 \begin{array}{l} \textit{AvoidableFrom}: (x':X\ t') \rightarrow (x:X\ t) \rightarrow \\ \qquad \qquad x' \, \textit{`ReachableFrom'}\ x \rightarrow (m:\mathbb{N}) \rightarrow \textit{Type} \\ \textit{AvoidableFrom}\ \{\,t'\,\}\ x'\ x\ r\ m = \\ \qquad (x'':X\ t'\ **(x''\ \textit{`ReachableFrom'}\ x,(\textit{Viable}\ m\ x'',\textit{Not}\ (x''=x')))) \end{array}
```

The notion of avoidability entails the notion of an alternative state x''. This has to fulfill three conditions:

```
 \begin{array}{lll} \textit{AvoidableFrom} : (x':X\ t') \rightarrow (x:X\ t) \rightarrow & \\ & x' \text{``ReachableFrom'}\ x \rightarrow (m:\mathbb{N}) \rightarrow & \textit{Type} \\ \textit{AvoidableFrom}\ \{t'\}\ x'\ x\ r\ m = & \\ & (x'':X\ t'\ **\ (x'' \text{``ReachableFrom'}\ x, (\textit{Viable}\ m\ x'', \textit{Not}\ (x'' = x')))) \end{array}
```

Back to the minimal goals: under which conditions are reachability, viability and avoidability decidable?

For every type (predicate) P: Type, Not P is just a synonym for $P \rightarrow Void$:

```
Not: Type \rightarrow Type
Not P = P \rightarrow Void
```

For every type (predicate) P: Type, Not P is just a synonym for $P \rightarrow Void$:

```
Not: Type \rightarrow Type
Not P = P \rightarrow Void
```

A predicate P: Type is decidable if one can compute either a value p: P or a value of type Not P:

```
Decidable : Type \rightarrow Type
Decidable P = Either P (Not P)
```

Thus, the question is under which conditions one can implement

```
decReachable: (x:Xt) \rightarrow Decidable (Reachable x) decViable: (n:\mathbb{N}) \rightarrow (x:Xt) \rightarrow Decidable (Viable n x) decAvoidableFrom: \{t':\mathbb{N}\} \rightarrow \{t:\mathbb{N}\} \rightarrow (x':Xt') \rightarrow (x:Xt) \rightarrow (r:x' `ReachableFrom` x) \rightarrow (n:\mathbb{N}) \rightarrow Decidable (AvoidableFrom \{t'\} \{t\} x' x r n)
```

As one would expect, the conditions

$$fX: (t: \mathbb{N}) \to \textit{Finite}(X t)$$
 $fY: (t: \mathbb{N}) \to (x: X t) \to \textit{Finite}(Y t x)$
 $decElem: \{t: \mathbb{N}\} \to (x: X t) \to (mx: M(X t)) \to Decidable(x 'Elem' mx)$

$$decAll: \{t: \mathbb{N}\} \rightarrow (P: X t \rightarrow Type) \rightarrow ((x: X t) \rightarrow Decidable (P x)) \rightarrow (mx: M (X t)) \rightarrow Decidable (All P mx)$$

are sufficient for decidability.

The key lemma for implementing decision procedures for Reachable, Viable and AvoidableFrom is intuitively obvious

```
\begin{array}{c} \textit{finiteDecidableLemma} : \{\textit{A} : \textit{Type}\} \rightarrow \{\textit{P} : \textit{A} \rightarrow \textit{Type}\} \rightarrow \\ \textit{Finite} \; \textit{A} \rightarrow ((\textit{a} : \textit{A}) \rightarrow \textit{Decidable} (\textit{P} \; \textit{a})) \rightarrow \\ \textit{Decidable} \; (\textit{a} : \textit{A} * * \textit{P} \; \textit{a}) \end{array}
```

The key lemma for implementing decision procedures for Reachable, Viable and AvoidableFrom is intuitively obvious

```
\begin{array}{c} \textit{finiteDecidableLemma} : \{\textit{A} : \textit{Type}\} \rightarrow \{\textit{P} : \textit{A} \rightarrow \textit{Type}\} \rightarrow \\ \textit{Finite} \; \textit{A} \rightarrow ((\textit{a} : \textit{A}) \rightarrow \textit{Decidable} (\textit{P} \; \textit{a})) \rightarrow \\ \textit{Decidable} \; (\textit{a} : \textit{A} * * \textit{P} \; \textit{a}) \end{array}
```

but implementing finiteDecidableLemma is not trivial!

With *finiteDecidableLemma*, *fY* and decidability of *Elem* one immediately has decidability of *Pred*

```
decPred: \{t: \mathbb{N}\} \rightarrow (x: X t) \rightarrow (x': X (S t)) \rightarrow Decidable (x 'Pred' x')

decPred \{t\} \times x' = finiteDecidableLemma (fY t x) prf where

prf: (y: Y t x) \rightarrow Decidable (x' 'Elem' (step t x y))

prf y = decElem x' (step t x y)
```

```
and, with
   decPair : Decidable p \rightarrow Decidable q \rightarrow Decidable (p, q)
decidability of Reachable:
   decReachable: \{t': \mathbb{N}\} \rightarrow (x': X \ t') \rightarrow Decidable (Reachable x')
   decReachable \{t' = Z\} x' = Left()
   decReachable { t' = S t } x' = s1 where
     s1 : Decidable (x : X t ** (Reachable x, x 'Pred' x'))
     s1 = finiteDecidableI emma
           (fX t)
           (\lambda x \Rightarrow decPair (decReachable x) (decPred x x'))
```

Similarly, one implement (prove) decidability of *Viable*:

```
decViable : \{t : \mathbb{N}\} \rightarrow (n : \mathbb{N}) \rightarrow (x : X t) \rightarrow Decidable (Viable n x)

decViable \{t\} \ Z \ x = Left \ ()

decViable \{t\} \ (S \ m) \ x = s3 \ \text{where}

s1 : (y : Y t \ x) \rightarrow Decidable \ (All \ (Viable \ m) \ (step t \ x \ y))

s1 \ y = decAll \ (Viable \ m) \ (decViable \ m) \ (step t \ x \ y)

s2 : Decidable \ (y : Y t \ x ** All \ (Viable \ m) \ (step t \ x \ y))

s2 = finiteDecidableLemma \ (fY t \ x) \ s1

s3 : Decidable \ (Viable \ (S \ m) \ x)

s3 = s2
```

Similarly, one implement (prove) decidability of *Viable*:

```
decViable : \{t : \mathbb{N}\} \rightarrow (n : \mathbb{N}) \rightarrow (x : X t) \rightarrow Decidable (Viable n x)

decViable \{t\} \ Z \ x = Left \ ()

decViable \{t\} \ (S \ m) \ x = s3 \ \text{where}

s1 : (y : Y t \ x) \rightarrow Decidable \ (All \ (Viable \ m) \ (step t \ x \ y))

s1 \ y = decAll \ (Viable \ m) \ (decViable \ m) \ (step t \ x \ y)

s2 : Decidable \ (y : Y t \ x ** All \ (Viable \ m) \ (step t \ x \ y))

s2 = finiteDecidableLemma \ (fY t \ x) \ s1

s3 : Decidable \ (Viable \ (S \ m) \ x)

s3 = s2
```

Implementing a decidion procedure for *AvoidableFrom* is a bit more complicated but conceptually equivalent.

Acknowledgments

Contributors:

Patrik Jansson (Chalmers Univ. of Technology), Cezar Ionescu (Chalmers Univ. of Technology), David Christiansen (IT University of Copenhagen), Edwin Brady (University of St. Andrews), Matteo Acerbi, members of the Cartesian Seminar at the Univ. of Potsdam

Acknowledgments

Contributors:

Patrik Jansson (Chalmers Univ. of Technology), Cezar Ionescu (Chalmers Univ. of Technology), David Christiansen (IT University of Copenhagen), Edwin Brady (University of St. Andrews), Matteo Acerbi, members of the Cartesian Seminar at the Univ. of Potsdam These slides:

Acknowledgments

Contributors:

Patrik Jansson (Chalmers Univ. of Technology), Cezar Ionescu (Chalmers Univ. of Technology), David Christiansen (IT University of Copenhagen), Edwin Brady (University of St. Andrews), Matteo Acerbi, members of the Cartesian Seminar at the Univ. of Potsdam These slides:

The code shown: