

UPXV.Api (1.0)

Download OpenAPI specification: [Download](#)

Consumable

/Consumable

QUERY PARAMETERS

page	integer <int32> Default: <input type="text" value="0"/>
size	integer <int32> Default: <input type="text" value="5"/>

Responses

— 200 OK

GET /Consumable

/Consumable

REQUEST BODY SCHEMA: application/json ▼

tid required	string or null
unitNid required	integer <int32>
quantity	number <double>
description	string or null
tagNids	Array of integers or null <int32> [items <int32 >]

Responses

— 200 OK

POST /Consumable

Request samples

Payload

Content type

application/json

Copy Expand all Collapse all

```
{
  "tid": "string",
  "unitNid": 0,
  "quantity": 0.1,
  "description": "string",
  - "tagNids": [
    0
  ]
}
```

/Consumable

nid required	integer <int32>
tid	string or null
description	string or null
tagNids	Array of integers or null <int32> [items <int32 >]
quantity	number or null <double>
unitNid	integer or null <int32>

Responses

— 200 OK

PUT /Consumable

Request samples

Payload

Content type
application/json

```
{
  "nid": 0,
  "tid": "string",
  "description": "string",
  - "tagNids": [
    0
  ],
  "quantity": 0.1,
  "unitNid": 0
}
```

/Consumable/{nid}

PATH PARAMETERS

nid	integer <int32>
required	

Responses

— 200 OK

GET /Consumable/{nid}

/Consumable/{nid}

PATH PARAMETERS

nid	integer <int32>
required	

Responses

— 200 OK

DELETE /Consumable/{nid}

Item

/Item

QUERY PARAMETERS

page	integer <int32> Default: <input type="text" value="0"/>
------	--

size	integer <int32> Default: <input type="text" value="5"/>
------	--

Responses

— 200 OK

GET /Item

Patrimony

/Patrimony

QUERY PARAMETERS

page	integer <int32> Default: <input type="text" value="0"/>
size	integer <int32> Default: <input type="text" value="5"/>

Responses

— 200 OK

GET /Patrimony

/Patrimony

REQUEST BODY SCHEMA: application/json ▼

tid <small>required</small>	string or null
description	string or null
tagNids	Array of integers or null <int32> [items <int32 >]
registeredBy	string or null

statusNid

integer <int32>

Responses

— 200 OK

POST /Patrimony

Request samples

Payload

Content type
application/json

Copy Expand all Collapse all

```
{
  "tid": "string",
  "description": "string",
  - "tagNids": [
    0
  ],
  "registeredBy": "string",
  "statusNid": 0
}
```

/Patrimony

REQUEST BODY SCHEMA: application/json ▼

nid required	integer <int32>
tid	string or null
description	string or null

tagNids	Array of integers or null <int32> [items <int32 >]
statusNid	integer or null <int32>

Responses

— 200 OK

PUT /Patrimony

Request samples

Payload

Content type
application/json

Copy Expand all Collapse all

```
{
  "nid": 0,
  "tid": "string",
  "description": "string",
  - "tagNids": [
    0
  ],
  "statusNid": 0
}
```

/Patrimony/{nid}

PATH PARAMETERS

nid required	integer <int32>
-----------------	-----------------

Responses

— 200 OK

GET /Patrimony/{nid}

/Patrimony/{nid}

PATH PARAMETERS

nid	integer <int32>
required	

Responses

— 200 OK

DELETE /Patrimony/{nid}

Status

/Status

QUERY PARAMETERS

page integer <int32>
Default:

size integer <int32>
Default:

Responses

— 200 OK

GET /Status

/Status

REQUEST BODY SCHEMA: application/json ▼

tid
required string or null

description string or null

Responses

— 200 OK

POST /Status

Request samples

Payload

Content type
application/json

Copy

```
{
  "tid": "string",
  "description": "string"
}
```

/Status

REQUEST BODY SCHEMA: application/json ▾

nid	integer <int32>
required	
tid	string or null
description	string or null

Responses

— 200 OK

PUT /Status

Request samples

Payload

Content type
application/json

Copy

```
{
  "nid": 0,
```

```
    "tid": "string",  
    "description": "string"  
  }  
}
```

/Status/{nid}

PATH PARAMETERS

nid	integer <int32>
required	

Responses

— 200 OK

GET /Status/{nid}

/Status/{nid}

PATH PARAMETERS

nid	integer <int32>
required	

Responses

— 200 OK

DELETE /Status/{nid}

Tag

/Tag

QUERY PARAMETERS

page	integer <int32> Default: <input type="text" value="0"/>
------	--

size	integer <int32> Default: <input type="text" value="5"/>
------	--

Responses

— 200 OK

GET /Tag

/Tag

REQUEST BODY SCHEMA: application/json ▼

tid required	string or null
-----------------	----------------

description

string or null

Responses

— 200 OK

POST /Tag

Request samples

Payload

Content type
application/json

Copy

```
{
  "tid": "string",
  "description": "string"
}
```

/Tag

REQUEST BODY SCHEMA: application/json ▼

nid

required

integer <int32>

tid

string or null

description

string or null

Responses

— 200 OK

PUT /Tag

Request samples

Payload

Content type
application/json

Copy

```
{
  "nid": 0,
  "tid": "string",
  "description": "string"
}
```

/Tag/{nid}

PATH PARAMETERS

nid	integer <int32>
required	

Responses

— 200 OK

GET /Tag/{nid}

/Tag/{nid}

PATH PARAMETERS

nid required	integer <int32>
-----------------	-----------------

Responses

— 200 OK

DELETE /Tag/{nid}

Unit

/Unit

QUERY PARAMETERS

page	integer <int32> Default: <input type="text" value="0"/>
------	--

size	integer <int32> Default: <input type="text" value="5"/>
------	--

Responses

— 200 OK

GET /Unit

/Unit

REQUEST BODY SCHEMA: application/json ▾

tid required	string or null
-----------------	----------------

abbreviation required	string or null
--------------------------	----------------

Responses

— 200 OK

POST /Unit

Request samples

Payload

Content type
application/json

Copy

```
{
  "tid": "string",
  "abbreviation": "string"
}
```

/Unit

REQUEST BODY SCHEMA: application/json ▼

nid	integer <int32>
tid	string or null
abbreviation	string or null

Responses

— 200 OK

PUT /Unit

Request samples

Payload

Content type
application/json

Copy

```
{
  "nid": 0,
  "tid": "string",
  "abbreviation": "string"
}
```

/Unit/{nid}

PATH PARAMETERS

nid	integer <int32>
required	

Responses

— 200 OK

GET /Unit/{nid}

/Unit/{nid}

PATH PARAMETERS

nid	integer <int32>
required	

Responses

— 200 OK

DELETE /Unit/{nid}

