Electricity and Magnetism

- Physics 259 – L02
- Lecture 43

Chapter 29: Magnetic field due to current

Last time:

- Biot-Savart Law (like Coulomb's Law for magnetism)
- B-field of a line of current
- Magnetic force between parallel current-carrying wires
- Ampere's law

Today:

- Applications of Ampere's law



For a single charge $\rightarrow$ $$\boxed{\vec{F}_B = q\vec{v}_d \times \vec{B}}$$

For N charges moving through the wire (current carrying wire) $\rightarrow$ $$\boxed{\vec{F}_B = i\vec{\ell} \times \vec{B}}$$

The Biot-Savart Law $\rightarrow$ $$\boxed{\vec{B}_{\text{point charge}} = \frac{\mu_0}{4\pi}\frac{q\vec{v} \times \hat{r}}{r^2}}$$

For an electric current $\rightarrow$ $$\boxed{\vec{B}_{\text{current segment}} = \frac{\mu_0}{4\pi}\frac{I\,\Delta\vec{s} \times \hat{r}}{r^2}}$$

Magnetic field due to current in long straight wire



$$B_z = \frac{\mu_0}{2\pi}\frac{I}{d}$$

Non-infinite straight wire→ Appendix 1-chapter 22



$$B = \frac{\mu_0 i \phi}{4\pi R}$$



$$\vec{B} = \frac{\mu_0}{2}\frac{IR^2}{\left(z^2 + R^2\right)^{3/2}}\hat{k}$$

if $\quad z = 0 \quad \vec{B}_{center} = \frac{\mu_0}{2}\frac{I}{R}\hat{k}$

Force between two antiparallel currents



Ampère’s law

$$\boxed{\text{i.e.} \oint \vec{B} \cdot d\vec{l} = \mu_0 I_{encl}}$$





$$\oint \vec{E}.d\vec{A} = \frac{Q_{in}}{\varepsilon_0}$$

For a closed surface enclosing total Charge Q

$$\oint \vec{B}.d\vec{l} = \mu_0 I_{enclosing}$$

Current I passes through an area bounded by a closed curve

A coaxial cable consists of a wire (radius R_1) surrounded by an insulating sleeve and another cylindrical conducting shell (inner radius R_2) and finally another insulating sleeve. **The wire and the shell carry the same current I but in opposite directions**.

Which diagram best represents the **magnetic field** as a function of radial distance from the cable's axis?







Ampère's law: application (3)

(a) Using Ampère's law, calculate the magnetic field above the current carrying slab

b) Calculate the magnetic field inside the current carrying slab



$\vec{B}$ above or below the slab $\Rightarrow$

$\oint \vec{B} \cdot d\vec{l} = \mu_0 I_{enc}$



$\oint \vec{B} \cdot d\vec{l} \Rightarrow$

$\rightarrow \int_1 \vec{B} \cdot d\vec{l} + \int_2 \vec{B} \cdot d\vec{l} + \int_3 \vec{B} \cdot d\vec{l} + \int_4 \vec{B} \cdot dl$

$\rightarrow 2B \int dl = \mu_0 I_{enc} = \mu_0 J A = \mu_0 J L d$

$\rightarrow B = \dfrac{\mu_0 J d}{2}$

$\vec{B}$ inside the slab $\Rightarrow$

$$\oint \vec{B}\cdot\vec{dl} = \mu_0 I_{enc}$$

$$\rightarrow \int_1 \vec{B}\cdot\vec{dl} + \int_2 \vec{B}\cdot\vec{dl} + \int_3 + \int_4$$



$$\rightarrow 2Bl = \mu_0 I_{enc} = \mu_0 J A_{in} = \mu_0 J\, 2zl$$

$$\rightarrow B = \mu_0 J z$$ & if $z = \frac{d}{2} \rightarrow B = \frac{\mu_0 J d}{2}$

Ampère’s law: application(2)

29.3: Solenoids and Toroids









$$\oint \vec{B}.d\vec{s} = \mu_0 i_{enc}$$



$\mathbf{n} = \dfrac{\mathbf{N}}{\mathbf{L}}$ **number of turns per unit length**

$i_{enc} = nih$

$$B_{Solenoid} = \mu_0 ni$$



$$B_{Solenoid} = \mu_0 n i$$

magnetic field inside toroid

$$\oint \vec{B} \cdot d\vec{l} = \mu_0 \, i_{enc}$$

$$\rightarrow BL = \mu_0 \, i_{enc} \quad \& \quad i_{enc} = Ni$$



Amperian loop

$$\rightarrow B = \frac{\mu_0 i N}{2\pi} \frac{1}{r}$$

This section we talked about:

Chapter 29

See you on Friday