MiniCommerce API Reference

Complete reference for the HTTP API exposed by the backend. The local development server listens on `http://localhost:3001`; all endpoints use the `/api` prefix and use JSON request or response bodies where applicable.

Authentication

Login returns a signed JWT valid for 8 hours. Send it on protected requests as `Authorization: Bearer <token>`. Product creation, updates, deletion, and `GET /api/auth/me` require an admin token. There are no API endpoints to register users or manage categories.

Health

`GET /api/health`

Public service health check.

200 response

```
{ "status": "ok" }
```

Authentication endpoints

`POST /api/auth/login`

Authenticate with an email and password.

Request body

```
{ "email": "admin@minicommerce.dev", "password": "admin123" }
```

200 response

```
{
  "token": "<jwt>",
  "user": { "id": 1, "email": "admin@minicommerce.dev", "name": "Admin", "isAdmin": true }
}
```

Returns `400` if email or password is missing or not a string, and `401` when credentials are invalid.

`GET /api/auth/me`

Admin-only. Returns the authenticated user's JWT payload.

200 response

```
{ "user": { "userId": 1, "email": "admin@minicommerce.dev", "isAdmin": true } }
```

Category endpoints

`GET /api/categories`

Public. Lists categories alphabetically. Each object contains `id`, `name`, `description`, `createdAt`, and `productCount`.

`GET /api/categories/:id`

Public. Returns one category with the same fields as the list endpoint. Returns `400` for an invalid ID and `404` if the category does not exist.

`GET /api/categories/:id/products`

Public. Lists a category's products alphabetically. Each product includes its category name. Returns `400` for an invalid ID and `404` if the category does not exist.

Article (product) endpoints

Product objects returned by the list and detail routes include `id`, `name`, `description`, `categoryId`, `category` (category name), `brand`, `price`, `stock`, `imageUrl`, and `createdAt`.

`GET /api/products`

Public. Lists products. All query parameters are optional and can be combined:

Parameter	Description
`search`	Substring match across name, description, and brand.
`category`	Exact category name.
`categoryId`	Category ID; takes precedence over `category` when valid.
`brand`	Exact brand match.
`minPrice`, `maxPrice`	Inclusive numeric price bounds.
`sort`	Sort field: `name`, `price`, `stock`, `category`, or `createdAt`; defaults to `name`.
`order`	`asc` or `desc`; defaults to `asc`.

Example: `GET /api/products?search=mouse&minPrice=10&sort=price&order=desc`

`GET /api/products/categories`

Public. Returns an alphabetically sorted array of category names, for example `["Accessori", "Monitor"]`.

`GET /api/products/:id`

Public. Returns a single product. Returns `400` for an invalid ID and `404` if no product exists.

`POST /api/products`

Admin-only. Creates a product and returns the created product with status `201`.

`PUT /api/products/:id`

Admin-only. Replaces the product fields with the submitted values and returns the updated product. Returns `400` for an invalid ID or body and `404` if no product exists.

Create/update request body

```
{
  "name": "Wireless Mouse",
  "description": "Bluetooth ergonomic mouse",
  "categoryId": 3,
  "brand": "Example",
  "price": 29.99,
  "stock": 12,
  "imageUrl": "https://example.com/mouse.jpg"
}
```

Use `categoryId` (preferred) or an existing category name in `category`. The name is accepted for compatibility; categories are not created automatically. `name` must be non-empty, `price` must be numeric and at least zero, and `stock` must be a non-negative integer (omitted or empty stock defaults to zero). `description` and `brand` default to empty strings; `imageUrl` defaults to `null`.

`DELETE /api/products/:id`

Admin-only. Deletes a product and returns `204 No Content`. Returns `400` for an invalid ID and `404` if no product exists.

Common errors

Validation and invalid-ID errors generally return `400` with `{ "error": "..." }`. Missing records return `404`. Invalid or missing authentication returns `401`; authenticated non-admin users are forbidden from admin-only routes (`403`). Unexpected server errors return `500` with an `error` field; development responses may also include `detail`.