



2019-04-11-extra questions

Real-time Systems (Technische Universiteit Delft)

IN4343 – Real Time Systems

April 11th 2019, from 09:00 to 12:00

Mitra Nasri

Question:	1	2	3	4	Total
Points:	6	15	5	2	28
Score:					

- This is a closed book exam
 - You may use a **simple** calculator only (i.e. graphical calculators are not permitted)
 - Write your answers with a black or blue pen, not with a pencil
 - **Always justify your answers, unless stated otherwise**
 - Question 8 is an **optional question (bonus)**.
-
- The exam covers the following material:
 - (a) chapters 1-9 of the book “Hard Real-Time Computing Systems (3rd ed)” by G. Buttazzo
 - (b) the paper “The Worst-Case Execution-Time Problem” by Wilhelm et al. (except Section 6)
 - (c) the paper “Non-Work-Conserving Non-preemptive Scheduling: Motivations, Challenges, and Potential Solutions” by Mitra Nasri and Gerhard Fohler
 - (d) the paper “An Exact and Sustainable Analysis of Non-Preemptive Scheduling” by Mitra Nasri and Björn B. Brandenburg
 - (e) the paper “Best-case response times and jitter analysis of real-time tasks” by R.J. Bril, E.F.M. Steffens, and W.F.J. Verhaegh

Liu and Layland (LL) bound	$U_{lub}^{RM} = n(2^{1/n} - 1)$
Hyperbolic (HB) bound	$\prod_{i=1}^n (U_i + 1) \leq 2$
Response Time Analysis	$WR_i = C_i + \sum_{k=1}^{i-1} \left\lceil \frac{WR_i + AJ_k}{T_k} \right\rceil C_k$ $BR_i = C_i + \sum_{k=1}^{i-1} \left(\left\lceil \frac{BR_i - AJ_k}{T_k} \right\rceil - 1 \right)^+ C_k$ $w^+ = \max(w, 0)$
Processor Demand schedulability	$g(t_1, t_2) = \sum_{r_i \geq t_1}^{d_i \leq t_2} C_i \quad g(0, L) = \sum_{i=1}^n \left\lfloor \frac{L + T_i - D_i}{T_i} \right\rfloor C_i$ $\forall L \in D, \quad g(0, L) \leq L$ $D = \{d_k d_k \leq \min(H, \max(D_{max}, L^*))\}$ $H = lcm(T_1, \dots, T_n)$ $L^* = \frac{\sum_{i=1}^n (T_i - D_i) \cdot U_i}{1 - U}$
CBS Server arrival of a job J_k budget exhaustion	<p>if $(\exists \text{ a pending aperiodic job})$ then enqueue J_k;</p> <p>else if $(q_s \geq (d_s - a_k) \cdot U_s)$ then</p> <p style="padding-left: 40px;">$\{ q_s \leftarrow Q_s; \quad d_s \leftarrow d_s + T_s; \}$</p> <p>$q_s \leftarrow Q_s$</p> <p>$d_s \leftarrow d_s + T_s$</p>
NP scheduling response time NP-FP response time NP-EDF	<p>pre-requisites: $D \leq T$ and preemptive-schedulable</p> $WO_i^{(n)} = B_i + \sum_{k=1}^{i-1} \left(\left\lfloor \frac{WO_i^{(n-1)}}{T_k} \right\rfloor + 1 \right) \cdot C_k$ $B_i = \max\{C_j \mid \forall \tau_j, P_i < P_j\}$ $R_i = C_i + WO_i$ $WO_i^{(0)} = B_i + \sum_{k=1}^{i-1} C_k$ <p>$\forall \tau_i, 1 < i \leq n, \forall L, T_1 < L < T_i$:</p> $L \geq C_i + \sum_{k=1}^{i-1} \left\lfloor \frac{L - 1}{T_k} \right\rfloor \cdot C_k$

Question 1

[6 points]

Consider the following code in the context of dynamic techniques to estimate the worst-case execution time of a task on a given platform.

```
int foo (int x, int y) {  
    int z = 0;  
    if (x > 7 && y < 5) {  
        z = x;  
    }  
    else {  
        if (x > 4 && y > 0){  
            z = 2 * x + y;  
        }  
    }  
    return z;  
}
```

- (a) 3 points Generate the minimum number of test cases (i.e., calls to the foo function with different inputs) such that the statement coverage is satisfied.
- (b) 3 points Generate the minimum number of test cases such that the branch coverage is satisfied.

Question 2

[15 points]

A rate-monotonic scheduler is used to run the following task set ¹.

	C_i	T_i	D_i
τ_1	3	6	6
τ_2	7	18	18
τ_3	8	24	24

- (a) 10 points Compute the WCRT (worst-case response time) of each task.
- (b) 5 points Determine the worst-case response times of the three tasks. *Hint: draw a time line.*

Question 3

[5 points]

Park's test may be used with fixed-priority schedules to verify that the workload to be completed before a task's deadline is smaller than the deadline of the task itself. The test condition is formalized as²

$$C_i + \sum_{k=1}^{i-1} \left\lceil \frac{D_i}{T_k} \right\rceil \cdot C_k \leq D_i$$

¹Thanks to Charles Randolph for preparing this numerical example.

²Thanks to Charles Randolph for his suggestion.

- (a) 5 points Is Park's test a *sufficient*, *necessary*, or *exact* test? Justify your answer.

Question 4

[2 points]

- (a) 1 point **Claim:** In general, preemptive fixed-priority scheduling with rate-monotonic priorities has a larger number of preemptions than EDF.
Cause: because each time a high-priority task is released, it will certainly preempt a low-priority task.
(a) claim is true, cause is true (b) claim is true, cause is false (c) claim is false
- (b) 1 point Which resource access policy may result in deadlock?
- (a) Priority Ceiling Protocol (PCP) (b) Highest-Locker Priority (HLP)
(c) Priority Inheritance Protocol (PIP) (d) Non-Preemptive Protocol (NPP)