

Clustering Analysis of Mobility Data

Miriam Wagner, Martin Breuer, Moritz Werthebach, Timo Bergerbusch, and
Walter Schikowski

RWTH Aachen, Templergraben 55, 52062 Aachen, Germany

Abstract. The abstract should briefly summarize the contents of the paper in 150–250 words.

Keywords: Clustering · Rapidminer · Cluster · Data Mining

1 Introduction

2 Preprocessing

- max equal of 2038 for a strata
- max equal of 595 per persona in strata
- vector calc.

2.1 Vector

Instead of simple IDs for every person we expand the parsing by using a data encapsulating in a class called `Person`. This class stores the ID, the parameters defining a person, and all movements from that person.

Then we are able to compute the following vector, with 848 entries, for further usage, that combines all movements of the person:

$$\underbrace{\#o_1, \dots, \#o_{413}, \#d_1, \dots, \#d_{413}}_{2 \cdot 413} \underbrace{AM, MD, PM, MN}_4 \underbrace{\#r_1, \dots, \#r_7}_7, \\ \underbrace{\#MoT_1, \dots, \#MoT_7}_7 \underbrace{SDest, SDist, G, A, strata, strataGrouped}_6$$

with the following abbreviations ($1 \leq i \leq 413$, $1 \leq j \leq 7$):

o_i : the i -th origin data point	MoT_j : the j -th mean of transportation
d_i : the i -th destination data point	$SDest$: sum of all durations
AM : movements at time stamp AM	$SDist$: sum of all distances
MD : movements at time stamp MD	G : the gender
PM : movements at time stamp PM	A : the age
MN : movements at time stamp MN	$strata$: the strata (used for comparison)
r_j : the j -th reason	$strataGrouped$: the aggregated stratas

3 Predicting

3.1 Classification

3.2 Neural Net

Also we have a max. of 595 persons for strata 6 to have an equally distributed test set.

All using the vector data

We consider 3 neural nets $\mathcal{N}_1, \mathcal{N}_2$ and \mathcal{N}_3 , all having 4 hidden layers, 50 epochs and 10 iterations. As an example of other strata aggregation we combine the stratas 1–2, 3–4 and 5–6 together and call them \mathcal{N}_i^* , for $i \in \{5, 10, 20\}$. For that we take an equal distribution of all original stratas and map them correspondingly to the new stratas.

Name	# Neurons	AG	Set size		
			100	200	595
\mathcal{N}_5	5	✗	60.03	59.92	60.18
\mathcal{N}_5^*	5	✓	87.6	89.7	71.05
\mathcal{N}_{10}	10	✗	75.83	73.54	69.56
\mathcal{N}_{10}^*	10	✓	92.93	93.48	74.58
\mathcal{N}_{20}	20	✗	75.45	71.14	61.87
\mathcal{N}_{20}^*	20	✓	92.87	94.4	78.32

Fig. 1: The accuracy values of the neural nets. (See excel-spreadsheet)

If we take 50 neurons per layer we have $14 \cdot 50^4 \cdot 6 \cong 525.000.000$ synapses for which the input data set would be too small to have sufficient training.

The greater the population, the more the borders between the stratas blur.