A test of citation reading

Ada Lovelace[1], Alan Turing[2]

Introduction

Rare disease diagnosis still fails for most patients[1].

Population databases shape how variants are read[2].

Genome sequencing in a national health system raised the yield[3].

Deep learning has changed many fields[4].

Protein structure can now be predicted[5].

Short reads are aligned with fast index methods[6].

Gapped alignment scales to large genomes[7].

Count data need their own statistical models[8].

Visual inspection of alignments remains useful[9].

We grew 10^5 cells on 3 m^2 plates (n = 12), as in Fig. 2.

Reads on chr11 and exon2 were counted at day3.

This agrees with earlier work[2].

(1) prepare the samples.

(2) sequence them.

References

1.Rentzsch, P., Witten, D., Cooper, G. M., Shendure, J. & Kircher, M. CADD: predicting the deleteriousness of variants throughout the human genome. Nucleic Acids Research vol. 47 D886–D894 (2018).

2.Gudmundsson, S. et al. Variant interpretation using population databases: Lessons from gnomAD. Human Mutation vol. 43 1012–1030 (2021).

3.Turro, E. et al. Whole-genome sequencing of patients with rare diseases in a national health system. Nature vol. 583 96–102 (2020).

4.LeCun, Y., Bengio, Y. & Hinton, G. Deep learning. Nature vol. 521 436–444 (2015).

6.Li, H. & Durbin, R. Fast and accurate short read alignment with Burrows–Wheeler transform. Bioinformatics vol. 25 1754–1760 (2009).

7.Langmead, B. & Salzberg, S. L. Fast gapped-read alignment with Bowtie 2. Nature Methods vol. 9 357–359 (2012).

8.Love, M. I., Huber, W. & Anders, S. Moderated estimation of fold change and dispersion for RNA-seq data with DESeq2. Genome Biology vol. 15 (2014).

9.Robinson, J. T. et al. Integrative genomics viewer. Nature Biotechnology vol. 29 24–26 (2011).

10.McKenna, A. et al. The Genome Analysis Toolkit: A MapReduce framework for analyzing next-generation DNA sequencing data. Genome Research vol. 20 1297–1303 (2010).