

CSCI 331 PROJECT 1 – INDIVIDUAL PDF

PROFESSOR: PETER HELLER

SECTION: 9:15-10:30 AM

GROUP: G9-5

PDF OF: SHIVANIE KEMRAJ

THIS PDF CONTAINS THE 3 TOP, 3 WORST, AND WORST CORRECTED QUERIES

CONTENTS

Top #1: A Simple Query	4
Problem Statement.....	4
Reason it is a top.....	4
Key and Standard View of Tables Used	4
Table showing columns projected in the end	5
Table showing how projection sorted (if applicable)	5
Query	5
Relational and Json Output (231412 Rows Affected)	6
Top #2: A Simple Query	7
Problem Statement.....	7
Reason it is a top.....	7
Key and Standard View of Tables Used	7
Table showing columns projected in the end	8
Table showing how projection sorted (if applicable)	8
Query	8
Relational and Json Output (831 Rows Affected)	9
Top #3: A Complex Query	10
Problem Statement.....	10
Reason it is a top.....	10
Key and Standard View of Tables Used	10
Table showing columns projected in the end	11
Table showing how projection sorted (if applicable)	11
Query	12
Relational and Json Output (830 Rows Affected)	13
Worst #1: A Simple Query	14
Problem Statement.....	14
Reason it is a Worst	14
Key and Standard View of Tables Used	14
Table showing columns projected in the end	15
Table showing how projection sorted (if applicable)	15
Query Of Worst.....	15
Query of Worst Corrected	15

How it was Corrected:.....	15
Relational and Json Output (296 Rows Affected)	16
Worst #2: A Medium Query.....	17
Problem Statement.....	17
Reason it is a Worst	17
Key and Standard View of Tables Used	17
Table showing columns projected in the end	18
Table showing how projection sorted (if applicable)	18
Query Of Worst.....	18
Query of Worst Corrected	19
How it was Corrected:.....	19
Relational and Json Output (1267 Rows Affected)	20
Worst #3: A Complex Query	21
Problem Statement.....	21
Reason it is a Worst	21
Key and Standard View of Tables Used	21
Table showing columns projected in the end	22
Table showing how projection sorted (if applicable)	22
Query Of Worst.....	23
Query of Worst Corrected	24
How it was Corrected:.....	24
Relational and Json Output (830 Rows Affected)	25

TOP #1: A SIMPLE QUERY



PROBLEM STATEMENT

Return order key with unit price using WideWorldImportersDW

REASON IT IS A TOP

Sorted by order key

KEY AND STANDARD VIEW OF TABLES USED

Order (Fact)	
	[Order Key]
	[City Key]
	[Customer Key]
	[Stock Item Key]
	[Order Date Key]
	[Picked Date Key]
	[Salesperson Key]
	[Picker Key]



Order (Fact)			
	Column Name	Data Type	Allow Nulls
	[Order Key]	bigint	<input type="checkbox"/>
	[City Key]	int	<input type="checkbox"/>
	[Customer Key]	int	<input type="checkbox"/>
	[Stock Item Key]	int	<input type="checkbox"/>
	[Order Date Key]	date	<input type="checkbox"/>
	[Picked Date Key]	date	<input checked="" type="checkbox"/>
	[Salesperson Key]	int	<input type="checkbox"/>
	[Picker Key]	int	<input checked="" type="checkbox"/>
	[WWI Order ID]	int	<input type="checkbox"/>
	[WWI Backorder ID]	int	<input checked="" type="checkbox"/>
	Description	nvarchar(100)	<input type="checkbox"/>
	Package	nvarchar(50)	<input type="checkbox"/>
	Quantity	int	<input type="checkbox"/>
	[Unit Price]	decimal(18, 2)	<input type="checkbox"/>
	[Tax Rate]	decimal(18, 3)	<input type="checkbox"/>
	[Total Excluding Tax]	decimal(18, 2)	<input type="checkbox"/>
	[Tax Amount]	decimal(18, 2)	<input type="checkbox"/>
	[Total Including Tax]	decimal(18, 2)	<input type="checkbox"/>
	[Lineage Key]	int	<input type="checkbox"/>
			<input type="checkbox"/>

TABLE SHOWING COLUMNS PROJECTED IN THE END

Table Name	Column Name
Fact.Order	Order Key Unit Price

TABLE SHOWING HOW PROJECTION SORTED (IF APPLICABLE)

Table Name	Column Name	Sort Order
Fact.Order	Order Key	ASC

QUERY

```
USE WideWorldImportersDW;
```

```
SELECT [Order Key],  
       [Unit Price]  
FROM Fact.[Order]  
ORDER BY [Order Key];
```

RELATIONAL AND JSON OUTPUT (231412 ROWS AFFECTED)

	Order Key ▾	Unit Price ▾
1	1	230.00
2	2	13.00
3	3	32.00
4	4	30.00
5	5	2.70
6	6	32.00
7	7	13.00
8	8	32.00

```
{
  "Order Key": 1,
  "Unit Price": 230.00
},
{
  "Order Key": 2,
  "Unit Price": 13.00
},
{
  "Order Key": 3,
  "Unit Price": 32.00
},
{
  "Order Key": 4,
  "Unit Price": 30.00
},
{
  "Order Key": 5,
  "Unit Price": 2.70
},
{
  "Order Key": 6,
  "Unit Price": 32.00
},
{
  "Order Key": 7,
  "Unit Price": 13.00
},
{
  "Order Key": 8,
  "Unit Price": 32.00
},
}
```

TOP #2: A SIMPLE QUERY


PROBLEM STATEMENT

Returns concated employee's name with order id using Northwinds2022TSQLV7

REASON IT IS A TOP

Uses an inner join rather than cross join

KEY AND STANDARD VIEW OF TABLES USED



Column Name	Data Type	Allow Nulls
Orderid	Udt.SurrogateKeyInt: int	<input type="checkbox"/>
Customerid	Udt.SurrogateKeyInt: int	<input checked="" type="checkbox"/>
Employeeid	Udt.SurrogateKeyInt: int	<input type="checkbox"/>
Shipperid	Udt.SurrogateKeyInt: int	<input type="checkbox"/>
OrderDate	Udt.DateYYYYMMDD: d...	<input type="checkbox"/>
RequiredDate	Udt.DateYYYYMMDD: d...	<input type="checkbox"/>
ShipToDate	Udt.DateYYYYMMDD: d...	<input checked="" type="checkbox"/>
Freight	Udt.Currency: money	<input type="checkbox"/>
ShipToName	Udt.ContactName: nvarc...	<input type="checkbox"/>
ShipToAddress	Udt.Address: nvarchar(6...	<input type="checkbox"/>
ShipToCity	Udt.City: nvarchar(15)	<input type="checkbox"/>
ShipToRegion	Udt.Region: nvarchar(15)	<input checked="" type="checkbox"/>
ShipToPostalCode	Udt.PostalCode: nvarch...	<input checked="" type="checkbox"/>
ShipToCountry	Udt.Country: nvarchar(15)	<input type="checkbox"/>
UserAuthenticationId	int	<input checked="" type="checkbox"/>
DateAdded	datetime2(7)	<input checked="" type="checkbox"/>
DateOfLastUpdate	datetime2(7)	<input checked="" type="checkbox"/>

Column Name	Data Type	Allow Nulls
Employeeid	Udt.SurrogateKeyInt: int	<input type="checkbox"/>
EmployeeLastName	Udt.LastName: nvarchar...	<input type="checkbox"/>
EmployeeFirstName	Udt.FirstName: nvarchar...	<input type="checkbox"/>
EmployeeTitle	Udt.Title: nvarchar(30)	<input type="checkbox"/>
EmployeeTitleOfCourtesy	Udt.TitleOfCourtesy: nva...	<input type="checkbox"/>
BirthDate	Udt.DateYYYYMMDD: d...	<input type="checkbox"/>
HireDate	Udt.DateYYYYMMDD: d...	<input type="checkbox"/>
EmployeeAddress	Udt.Address: nvarchar(6...	<input type="checkbox"/>
EmployeeCity	Udt.City: nvarchar(15)	<input checked="" type="checkbox"/>
EmployeeRegion	Udt.Region: nvarchar(15)	<input checked="" type="checkbox"/>
EmployeePostalCode	Udt.PostalCode: nvarch...	<input checked="" type="checkbox"/>
EmployeeCountry	Udt.Country: nvarchar(15)	<input type="checkbox"/>
EmployeePhoneNumber	Udt.TelephoneNumber: n...	<input type="checkbox"/>
EmployeeManagerid	Udt.SurrogateKeyInt: int	<input checked="" type="checkbox"/>

TABLE SHOWING COLUMNS PROJECTED IN THE END

Table Name	Column Name
HumanResources.Employee	FullName (using EmployeeFirstName , EmployeeLastName)
Sales.Order	OrderID

TABLE SHOWING HOW PROJECTION SORTED (IF APPLICABLE)

Not applicable

QUERY

```
USE Northwinds2022TSQLV7;

SELECT CONCAT(E.EmployeeFirstName, ' ', E.EmployeeLastName) AS FullName,
       O.OrderId
FROM HumanResources.Employee AS E
     INNER JOIN Sales.[Order] AS O
       ON E.EmployeeId =
       (
         SELECT O.EmployeeId
       )
GROUP BY O.OrderId,
         E.EmployeeFirstName,
         E.EmployeeLastName
```


RELATIONAL AND JSON OUTPUT (831 ROWS AFFECTED)

	FullName ▼	OrderID ▼
1	Sven Mortensen	10248
2	Paul Suurs	10249
3	Yael Peled	10250
4	Judy Lew	10251
5	Yael Peled	10252
6	Judy Lew	10253
7	Sven Mortensen	10254
8	Patricia Doyle	10255
9	Judy Lew	10256
10	Yael Peled	10257

```
{
  "FullName": "Sven Mortensen",
  "OrderID": 10248
},
{
  "FullName": "Paul Suurs",
  "OrderID": 10249
},
{
  "FullName": "Yael Peled",
  "OrderID": 10250
},
{
  "FullName": "Judy Lew",
  "OrderID": 10251
},
{
  "FullName": "Yael Peled",
  "OrderID": 10252
},
{
  "FullName": "Judy Lew",
  "OrderID": 10253
},
{
  "FullName": "Sven Mortensen",
  "OrderID": 10254
},
{
  "FullName": "Patricia Doyle",
  "OrderID": 10255
},
{
  "FullName": "Judy Lew",
  "OrderID": 10256
},
{
  "FullName": "Yael Peled",
  "OrderID": 10257
}
```

TOP #3: A COMPLEX QUERY


PROBLEM STATEMENT

Return custid, employed, ordered, and the season of the orders using Northwinds2022TSQLV7

REASON IT IS A TOP

Only scalar function that does something a built-in function could not

KEY AND STANDARD VIEW OF TABLES USED



Column Name	Data Type	Allow Nulls
Orderid	Udt.SurrogateKey/Int/Int	<input checked="" type="checkbox"/>
Customerid	Udt.SurrogateKey/Int/Int	<input checked="" type="checkbox"/>
Employeeid	Udt.SurrogateKey/Int/Int	<input checked="" type="checkbox"/>
Shipperid	Udt.SurrogateKey/Int/Int	<input checked="" type="checkbox"/>
OrderDate	Udt.Date/YYYYMMDD/date	<input checked="" type="checkbox"/>
RequiredDate	Udt.Date/YYYYMMDD/date	<input checked="" type="checkbox"/>
ShipToDate	Udt.Date/YYYYMMDD/date	<input checked="" type="checkbox"/>
Freight	Udt.Currency/money	<input checked="" type="checkbox"/>
ShipToName	Udt.ContactName/nvarchar(100)	<input checked="" type="checkbox"/>
ShipToAddress	Udt.Address/nvarchar(60)	<input checked="" type="checkbox"/>
ShipToCity	Udt.City/nvarchar(15)	<input checked="" type="checkbox"/>
ShipToRegion	Udt.Region/nvarchar(15)	<input checked="" type="checkbox"/>
ShipToPostalCode	Udt.PostalCode/nvarchar(10)	<input checked="" type="checkbox"/>
ShipToCountry	Udt.Country/nvarchar(15)	<input checked="" type="checkbox"/>
UserAuthenticationId	int	<input checked="" type="checkbox"/>
DateAdded	datetime2(7)	<input checked="" type="checkbox"/>
DateOfLastUpdate	datetime2(7)	<input checked="" type="checkbox"/>

Column Name	Data Type	Allow Nulls
Employeeid	Udt.SurrogateKey/Int/Int	<input checked="" type="checkbox"/>
EmployeeLastName	Udt.LastName/nvarchar(25)	<input checked="" type="checkbox"/>
EmployeeFirstName	Udt.FirstName/nvarchar(25)	<input checked="" type="checkbox"/>
EmployeeTitle	Udt.Title/nvarchar(30)	<input checked="" type="checkbox"/>
EmployeeTitleOfCourtesy	Udt.TitleOfCourtesy/nvarchar(30)	<input checked="" type="checkbox"/>
BirthDate	Udt.Date/YYYYMMDD/date	<input checked="" type="checkbox"/>
HireDate	Udt.Date/YYYYMMDD/date	<input checked="" type="checkbox"/>
EmployeeAddress	Udt.Address/nvarchar(60)	<input checked="" type="checkbox"/>
EmployeeCity	Udt.City/nvarchar(15)	<input checked="" type="checkbox"/>
EmployeeRegion	Udt.Region/nvarchar(15)	<input checked="" type="checkbox"/>
EmployeePostalCode	Udt.PostalCode/nvarchar(10)	<input checked="" type="checkbox"/>
EmployeeCountry	Udt.Country/nvarchar(15)	<input checked="" type="checkbox"/>
EmployeePhoneNumber	Udt.TelephoneNumber/nvarchar(20)	<input checked="" type="checkbox"/>
EmployeeManagerid	Udt.SurrogateKey/Int/Int	<input checked="" type="checkbox"/>

Column Name	Data Type	Allow Nulls
Customerid	Udt.SurrogateKey/Int/Int	<input checked="" type="checkbox"/>
CustomerCompanyName	Udt.CompanyName/nvarchar(100)	<input checked="" type="checkbox"/>
CustomerContactName	Udt.ContactName/nvarchar(100)	<input checked="" type="checkbox"/>
CustomerContactTitle	Udt.Title/nvarchar(30)	<input checked="" type="checkbox"/>
CustomerAddress	Udt.Address/nvarchar(60)	<input checked="" type="checkbox"/>
CustomerCity	Udt.City/nvarchar(15)	<input checked="" type="checkbox"/>
CustomerRegion	Udt.Region/nvarchar(15)	<input checked="" type="checkbox"/>
CustomerPostalCode	Udt.PostalCode/nvarchar(10)	<input checked="" type="checkbox"/>
CustomerCountry	Udt.Country/nvarchar(15)	<input checked="" type="checkbox"/>
CustomerPhoneNumber	Udt.TelephoneNumber/nvarchar(20)	<input checked="" type="checkbox"/>
CustomerFaxNumber	Udt.TelephoneNumber/nvarchar(20)	<input checked="" type="checkbox"/>

TABLE SHOWING COLUMNS PROJECTED IN THE END

Table Name	Column Name
Sales.Customer	CustomerId
HumanResources.Employee	EmployeeId
Sales.Order	OrderId Order Season (using OrderDate)

TABLE SHOWING HOW PROJECTION SORTED (IF APPLICABLE)

Not applicable

QUERY

```
USE Northwinds2022TSQLV7;

DROP FUNCTION IF EXISTS Sales.Season;
GO
CREATE FUNCTION Sales.Season
(
    @date DATE
)
RETURNS NVARCHAR(20)
AS
BEGIN
    DECLARE @Result NVARCHAR(20);
    DECLARE @Month INT = MONTH(@date);

    SELECT @Result = CASE
        WHEN @Month IN ( 12, 1, 2 ) THEN
            'Winter'
        WHEN @Month
            BETWEEN 3 AND 5 THEN
            'Spring'
        WHEN @Month
            BETWEEN 6 AND 8 THEN
            'Summer'
        WHEN @Month
            BETWEEN 9 AND 11 THEN
            'Autumn'
        ELSE
            'ERROR - CANNOT CALCULATE Season'
    END;

    RETURN @Result;
END;
GO
SELECT C.CustomerId,
       E.EmployeeId,
       O.OrderId,
       Sales.Season(O.OrderDate) AS [Order Season]
FROM Sales.Customer AS C
CROSS JOIN HumanResources.Employee AS E
CROSS JOIN Sales.[Order] AS O
WHERE C.CustomerId =
(
    SELECT O.CustomerId WHERE E.EmployeeId = O.EmployeeId
)
GROUP BY C.CustomerId,
         E.EmployeeId,
         O.OrderId,
         Sales.Season(O.OrderDate);
```

RELATIONAL AND JSON OUTPUT (830 ROWS AFFECTED)

	customerid ▾	employeeid ▾	OrderId ▾	Order Season ▾
1	85	5	10248	Summer
2	79	6	10249	Summer
3	34	4	10250	Summer
4	84	3	10251	Summer
5	76	4	10252	Summer
6	34	3	10253	Summer
7	14	5	10254	Summer
8	68	9	10255	Summer
9	88	3	10256	Summer
10	35	4	10257	Summer

```

{
  "customerid": 85,
  "employeeid": 5,
  "OrderId": 10248,
  "Order Season": "Summer"
},
{
  "customerid": 79,
  "employeeid": 6,
  "OrderId": 10249,
  "Order Season": "Summer"
},
{
  "customerid": 34,
  "employeeid": 4,
  "OrderId": 10250,
  "Order Season": "Summer"
},
{
  "customerid": 84,
  "employeeid": 3,
  "OrderId": 10251,
  "Order Season": "Summer"
},
{
  "customerid": 76,
  "employeeid": 4,
  "OrderId": 10252,
  "Order Season": "Summer"
},

```

WORST #1: A SIMPLE QUERY

PROBLEM STATEMENT

Return employee's full name with their birthday using AdventureWorksDW2017

REASON IT IS A WORST

Can utilize concat function

KEY AND STANDARD VIEW OF TABLES USED




Diagram illustrating a self-referencing relationship on the **DimEmployee** table. The relationship is labeled **FK_DimEmployee_DimEmployee**.

Column Name	Data Type	Allow Nulls
EmployeeKey	int	<input type="checkbox"/>
ParentEmployeeKey	int	<input checked="" type="checkbox"/>
EmployeeNationalIDAlternateKey	nvarchar(15)	<input checked="" type="checkbox"/>
ParentEmployeeNationalIDAlternate...	nvarchar(15)	<input checked="" type="checkbox"/>
SalesTerritoryKey	int	<input checked="" type="checkbox"/>
FirstName	nvarchar(50)	<input type="checkbox"/>
LastName	nvarchar(50)	<input type="checkbox"/>
MiddleName	nvarchar(50)	<input checked="" type="checkbox"/>
NameStyle	bit	<input type="checkbox"/>
Title	nvarchar(50)	<input checked="" type="checkbox"/>
HireDate	date	<input checked="" type="checkbox"/>
BirthDate	date	<input checked="" type="checkbox"/>
LoginID	nvarchar(256)	<input checked="" type="checkbox"/>
EmailAddress	nvarchar(50)	<input checked="" type="checkbox"/>
Phone	nvarchar(25)	<input checked="" type="checkbox"/>
MaritalStatus	nchar(1)	<input checked="" type="checkbox"/>
EmergencyContactName	nvarchar(50)	<input checked="" type="checkbox"/>
EmergencyContactPhone	nvarchar(25)	<input checked="" type="checkbox"/>
SalariedFlag	bit	<input checked="" type="checkbox"/>
Gender	nchar(1)	<input checked="" type="checkbox"/>
PayFrequency	tinyint	<input checked="" type="checkbox"/>
BaseRate	money	<input checked="" type="checkbox"/>
VacationHours	smallint	<input checked="" type="checkbox"/>
SickLeaveHours	smallint	<input checked="" type="checkbox"/>
CurrentFlag	bit	<input type="checkbox"/>
SalesPersonFlag	bit	<input type="checkbox"/>
DepartmentName	nvarchar(50)	<input checked="" type="checkbox"/>
StartDate	date	<input checked="" type="checkbox"/>
EndDate	date	<input checked="" type="checkbox"/>
Status	nvarchar(50)	<input checked="" type="checkbox"/>
EmployeePhoto	varbinary(MAX)	<input checked="" type="checkbox"/>

TABLE SHOWING COLUMNS PROJECTED IN THE END

Table Name	Column Name
dbo.DimEmployee	FullName (using FirstName, LastName) BirthDate

TABLE SHOWING HOW PROJECTION SORTED (IF APPLICABLE)

Not applicable

QUERY OF WORST

```
USE AdventureWorksDW2017;
```

```
SELECT FirstName + ' ' + LastName AS FullName,  
       BirthDate  
FROM dbo.DimEmployee;
```

QUERY OF WORST CORRECTED

```
USE AdventureWorksDW2017;
```

```
SELECT CONCAT(FirstName, ' ', LastName) AS FullName,  
       BirthDate  
FROM dbo.DimEmployee;
```

HOW IT WAS CORRECTED:

Used a concat function for better readability

RELATIONAL AND JSON OUTPUT (296 ROWS AFFECTED)

	FullName ▾	BirthDate ▾
1	Guy Gilbert	1981-11-12
2	Kevin Brown	1986-12-01
3	Roberto Ta...	1974-06-12
4	Rob Walters	1974-07-23
5	Rob Walters	1974-07-23
6	Thierry D'...	1959-02-26
7	David Brad...	1974-10-17
8	David Brad...	1974-10-17
9	JoLynn Dob...	1955-08-16
10	Ruth Eller...	1956-01-03

```
{
  "FullName": "Guy Gilbert",
  "BirthDate": "1981-11-12"
},
{
  "FullName": "Kevin Brown",
  "BirthDate": "1986-12-01"
},
{
  "FullName": "Roberto Tamburello",
  "BirthDate": "1974-06-12"
},
{
  "FullName": "Rob Walters",
  "BirthDate": "1974-07-23"
},
{
  "FullName": "Rob Walters",
  "BirthDate": "1974-07-23"
},
```


WORST #2: A MEDIUM QUERY

PROBLEM STATEMENT

Return custid, emplid, and order year using Northwinds2022TSQLV7

REASON IT IS A WORST

Can use built-in function for full name, also can use inner joins to replace the cross join and subquery

KEY AND STANDARD VIEW OF TABLES USED




TABLE SHOWING COLUMNS PROJECTED IN THE END

Table Name	Column Name
Sales.Order	EmployeeID
Sales.uvw_CustomerOrder	CustomerID Year (using OrderMonth)

TABLE SHOWING HOW PROJECTION SORTED (IF APPLICABLE)

Table Name	Column Name	Sort Order
Sales.uvw_CustomerOrder	CustomerID	ASC
Sales.Order	Employeeid	ASC

QUERY OF WORST

```
USE Northwinds2022TSQLV7;
```

```
SELECT CO.CustomerId,
       O.EmployeeId,
       YEAR(CO.OrderMonth) AS [Year]
FROM Sales.[Order] AS O
     CROSS JOIN Sales.uvw_CustomerOrder AS CO
WHERE CO.CustomerId =
(
    SELECT O.CustomerId
)
GROUP BY CO.CustomerId,
         O.EmployeeId,
         YEAR(CO.OrderMonth)
ORDER BY CO.CustomerId,
         O.EmployeeId;
```

QUERY OF WORST CORRECTED

```
USE Northwinds2022TSQLV7;

SELECT CO.CustomerId,
       O.EmployeeId,
       YEAR(CO.OrderMonth) AS [Year]
FROM Sales.[Order] AS O
     INNER JOIN Sales.uvw_CustomerOrder AS CO
       ON CO.CustomerId = O.CustomerId
GROUP BY CO.CustomerId,
         O.EmployeeId,
         YEAR(CO.OrderMonth)
ORDER BY CO.CustomerId,
         O.EmployeeId;
```

HOW IT WAS CORRECTED:

Used an inner join to replace cross join which now does not need a subquery

RELATIONAL AND JSON OUTPUT (1267 ROWS AFFECTED)

	CustomerID ▾	EmployeeId ▾	Year ▾
1	1	1	2015
2	1	1	2016
3	1	3	2016
4	1	3	2015
5	1	4	2015
6	1	4	2016
7	1	6	2016
8	1	6	2015

```
{
  "CustomerID": 1,
  "EmployeeId": 1,
  "Year": 2015
},
{
  "CustomerID": 1,
  "EmployeeId": 1,
  "Year": 2016
},
{
  "CustomerID": 1,
  "EmployeeId": 3,
  "Year": 2016
},
{
  "CustomerID": 1,
  "EmployeeId": 3,
  "Year": 2015
},
{
  "CustomerID": 1,
  "EmployeeId": 4,
  "Year": 2015
},
}
```

WORST #3: A COMPLEX QUERY

PROBLEM STATEMENT

Concats the employee's first and last name to make full name; returns the ordered, custid, emplid, and name using Northwinds2022TSQLV7

REASON IT IS A WORST

Can use a built-in function for full name, also can use inner joins to replace the cross join and subquery

KEY AND STANDARD VIEW OF TABLES USED




TABLE SHOWING COLUMNS PROJECTED IN THE END

Table Name	Column Name
Sales.Customer	CustomerId
HumanResources.Employee	EmployeeId Name (using EmployeeFirstName, EmployeeLastName)
Sales.Order	OrderId

TABLE SHOWING HOW PROJECTION SORTED (IF APPLICABLE)

Not applicable

QUERY OF WORST

```
USE Northwinds2022TSQLV7;

DROP FUNCTION IF EXISTS HumanResources.findFullName;
GO
CREATE FUNCTION HumanResources.findFullName
(
    @firstName VARCHAR(30),
    @lastName VARCHAR(30)
)
RETURNS VARCHAR(65)
AS
BEGIN
    DECLARE @Result VARCHAR(65);

    SELECT @Result = CONCAT(@firstName, ' ', @lastName);

    RETURN @Result;
END;
GO
SELECT O.OrderId,
       C.CustomerId,
       E.EmployeeId,
       HumanResources.findFullName(E.EmployeeFirstName, E.EmployeeLastName) AS [NAME]
FROM Sales.Customer AS C
     CROSS JOIN HumanResources.Employee AS E
     CROSS JOIN Sales.[Order] AS O
WHERE C.CustomerId =
(
    SELECT O.CustomerId WHERE E.EmployeeId = O.EmployeeId
)
GROUP BY O.OrderId,
         C.CustomerId,
         E.EmployeeId,
         HumanResources.findFullName(E.EmployeeFirstName, E.EmployeeLastName);
```

QUERY OF WORST CORRECTED

```
USE Northwinds2022TSQLV7;

SELECT O.OrderId,
       C.CustomerId,
       E.EmployeeId,
       CONCAT(E.EmployeeFirstName, ' ', E.EmployeeLastName) AS [NAME]
FROM Sales.Customer AS C
     INNER JOIN Sales.[Order] AS O
       ON C.CustomerId = O.CustomerId
     INNER JOIN HumanResources.Employee AS E
       ON E.EmployeeId = O.EmployeeId
GROUP BY O.OrderId,
         C.CustomerId,
         E.EmployeeId,
         CONCAT(E.EmployeeFirstName, ' ', E.EmployeeLastName);
```

HOW IT WAS CORRECTED:

Used built-in concat function, also used an inner join to replace cross join which now does not need a subquery

RELATIONAL AND JSON OUTPUT (830 ROWS AFFECTED)

	OrderId	CustomerId	EmployeeId	NAME
1	10248	85	5	Sven Mortensen
2	10249	79	6	Paul Suurs
3	10250	34	4	Yael Peled
4	10251	84	3	Judy Lew
5	10252	76	4	Yael Peled
6	10253	34	3	Judy Lew
7	10254	14	5	Sven Mortensen
8	10255	68	9	Patricia Doyle
9	10256	88	3	Judy Lew
10	10257	35	4	Yael Peled

```

{
  "OrderId": 10248,
  "CustomerId": 85,
  "EmployeeId": 5,
  "NAME": "Sven Mortensen"
},
{
  "OrderId": 10249,
  "CustomerId": 79,
  "EmployeeId": 6,
  "NAME": "Paul Suurs"
},
{
  "OrderId": 10250,
  "CustomerId": 34,
  "EmployeeId": 4,
  "NAME": "Yael Peled"
},
{
  "OrderId": 10251,
  "CustomerId": 84,
  "EmployeeId": 3,
  "NAME": "Judy Lew"
},

```