

CSCI 331 PROJECT 1 – INDIVIDUAL PDF

PROFESSOR: PETER HELLER

SECTION: 9:15-10:30 AM

GROUP: G9-5

PDF OF: KONRAD RAKOWSKI

THIS PDF CONTAINS THE 3 TOP, 3 WORST, AND WORST CORRECTED QUERIES

## CONTENTS

Top #1: A Simple Query .....	4
Problem Statement.....	4
Reason it is a top.....	4
Key and Standard View of Tables Used .....	4
Table showing columns projected in the end .....	5
Table showing how projection sorted (if applicable) .....	5
Query .....	5
Relational and Json Output (827 Rows Affected) .....	6
Top #2: A Medium Query .....	7
Problem Statement.....	7
Reason it is a top.....	7
Key and Standard View of Tables Used .....	7
Table showing columns projected in the end .....	8
Table showing how projection sorted (if applicable) .....	8
Query .....	8
Relational and Json Output (28 Rows Affected) .....	9
Top #3: A Complex Query .....	10
Problem Statement.....	10
Reason it is a top.....	10
Key and Standard View of Tables Used .....	10
Table showing columns projected in the end .....	11
Table showing how projection sorted (if applicable) .....	11
Query .....	12
Relational and Json Output (228 Rows Affected) .....	13
Worst #1: A Simple Query .....	14
Problem Statement.....	14
Reason it is a Worst .....	14
Key and Standard View of Tables Used .....	14
Table showing columns projected in the end .....	15
Table showing how projection sorted (if applicable) .....	15
Query Of Worst.....	15
Query of Worst Corrected .....	15

How it was Corrected:.....	15
Relational and Json Output (31406 Rows Affected) .....	16
Corrected Relational and Json Output (1 Row Affected).....	17
Worst #2: A Medium Query.....	18
Problem Statement.....	18
Reason it is a Worst .....	18
Key and Standard View of Tables Used .....	18
Table showing columns projected in the end .....	19
Table showing how projection sorted (if applicable) .....	19
Query Of Worst.....	19
Query of Worst Corrected .....	20
How it was Corrected:.....	20
Relational and Json Output (1 Row Affected).....	21
Worst #3: A Complex Query .....	22
Problem Statement.....	22
Reason it is a Worst .....	22
Key and Standard View of Tables Used .....	22
Table showing columns projected in the end .....	23
Table showing how projection sorted (if applicable) .....	23
Query Of Worst.....	24
Query of Worst Corrected .....	25
How it was Corrected:.....	25
Relational and Json Output (23578 Rows Affected) .....	26

## TOP #1: A SIMPLE QUERY



### PROBLEM STATEMENT



Using Northwinds2022TSQLV, display orders with a total value less than 15000

### REASON IT IS A TOP

Efficient and relatively easy to read

### KEY AND STANDARD VIEW OF TABLES USED

OrderDetail (Sales)	
	OrderId
	ProductId

OrderDetail (Sales)			
	Column Name	Data Type	Allow Nulls
	OrderId	Udt.SurrogateKeyIn...	<input type="checkbox"/>
	ProductId	Udt.SurrogateKeyIn...	<input type="checkbox"/>
	UnitPrice	Udt.Currency:money	<input type="checkbox"/>
	Quantity	Udt.QuantitySmall:...	<input type="checkbox"/>
	DiscountPercentage	Udt.Percentage:nu...	<input type="checkbox"/>
			<input type="checkbox"/>

#### TABLE SHOWING COLUMNS PROJECTED IN THE END

Table Name	Column Name
[Sales].[OrderDetail]	OrderId
Derived	Total

#### TABLE SHOWING HOW PROJECTION SORTED (IF APPLICABLE)

Not applicable

#### QUERY

```
USE Northwinds2022TSQLV7;
SELECT D.OrderId,
       SUM(D.Quantity * D.UnitPrice) AS Total
FROM [Sales].[OrderDetail] AS D
GROUP BY D.OrderId
HAVING SUM(D.Quantity * D.UnitPrice) < 15000
ORDER BY Total DESC;
GO
```

# RELATIONAL AND JSON OUTPUT (827 ROWS AFFECTED)

Results		Messages	
	OrderId	Total	
1	10372	12281.2000	
2	10424	11493.2000	
3	10817	11490.7000	
4	10889	11380.0000	
5	10417	11283.2000	
6	10897	10835.2400	
7	10353	10741.6000	
8	10515	10588.5000	
9	10479	10495.6000	
1...	10540	10191.7000	
1...	10691	10164.8000	
1...	11032	8902.5000	
1...	10816	8891.0000	
1...	10514	8623.4500	

```

"Total Value less than 15000": [{
  "OrderId": 10372,
  "Total": 12281.2000
}, {
  "OrderId": 10424,
  "Total": 11493.2000
}, {
  "OrderId": 10817,
  "Total": 11490.7000
}, {
  "OrderId": 10889,
  "Total": 11380.0000
}, {
  "OrderId": 10417,
  "Total": 11283.2000
}, {
  "OrderId": 10897,
  "Total": 10835.2400
}, {
  "OrderId": 10353,
  "Total": 10741.6000
}, {
  "OrderId": 10515,
  "Total": 10588.5000
}, {
  "OrderId": 10479,
  "Total": 10495.6000
}, {
  "OrderId": 10540,
  "Total": 10191.7000
}, {
  "OrderId": 10691,
  "Total": 10164.8000
}, {
  "OrderId": 11032,
  "Total": 8902.5000
}, {
  "OrderId": 10816,
  "Total": 8891.0000
}, {
  "OrderId": 10514,
  "Total": 8623.4500
}]

```

## TOP #2: A MEDIUM QUERY


### PROBLEM STATEMENT

Using AdventureWorksDW2017, display every employee (oldest to youngest) who's birthday is in July

### REASON IT IS A TOP

Interesting concept and relatively easy to read as well

### KEY AND STANDARD VIEW OF TABLES USED



Column Name	Data Type	Allow Null
DateKey	int	<input type="checkbox"/>
FullDateAlternateKey	date	<input type="checkbox"/>
DayNumberOfWeek	tinyint	<input type="checkbox"/>
EnglishDayNameOfWeek	nvarchar(10)	<input type="checkbox"/>
SpanishDayNameOfWeek	nvarchar(10)	<input type="checkbox"/>
FrenchDayNameOfWeek	nvarchar(10)	<input type="checkbox"/>
DayNumberOfMonth	tinyint	<input type="checkbox"/>
DayNumberOfYear	smallint	<input type="checkbox"/>
WeekNumberOfYear	tinyint	<input type="checkbox"/>
EnglishMonthName	nvarchar(10)	<input type="checkbox"/>
SpanishMonthName	nvarchar(10)	<input type="checkbox"/>
FrenchMonthName	nvarchar(10)	<input type="checkbox"/>
MonthNumberOfYear	tinyint	<input type="checkbox"/>
CalendarQuarter	tinyint	<input type="checkbox"/>
CalendarYear	smallint	<input type="checkbox"/>
CalendarSemester	tinyint	<input type="checkbox"/>
FiscalQuarter	tinyint	<input type="checkbox"/>
FiscalYear	smallint	<input type="checkbox"/>
FiscalSemester	tinyint	<input type="checkbox"/>

FK\_DimEmployee\_DimEmployee

Column Name	Data Type	Allow Null
EmployeeKey	int	<input type="checkbox"/>
ParentEmployeeKey	int	<input checked="" type="checkbox"/>
EmployeeNationalIDAltern...	nvarchar(15)	<input checked="" type="checkbox"/>
ParentEmployeeNational...	nvarchar(15)	<input checked="" type="checkbox"/>
SalesTerritoryKey	int	<input checked="" type="checkbox"/>
FirstName	nvarchar(50)	<input type="checkbox"/>
LastName	nvarchar(50)	<input type="checkbox"/>
MiddleName	nvarchar(50)	<input checked="" type="checkbox"/>
NameStyle	bit	<input checked="" type="checkbox"/>
Title	nvarchar(50)	<input checked="" type="checkbox"/>
HireDate	date	<input checked="" type="checkbox"/>
BirthDate	date	<input checked="" type="checkbox"/>
LoginID	nvarchar(256)	<input checked="" type="checkbox"/>
EmailAddress	nvarchar(50)	<input checked="" type="checkbox"/>
Phone	nvarchar(25)	<input checked="" type="checkbox"/>
MaritalStatus	nchar(1)	<input checked="" type="checkbox"/>
EmergencyContactName	nvarchar(50)	<input checked="" type="checkbox"/>
EmergencyContactPhone	nvarchar(25)	<input checked="" type="checkbox"/>
SalaryFlag	bit	<input checked="" type="checkbox"/>
Gender	nchar(1)	<input checked="" type="checkbox"/>
PayFrequency	tinyint	<input checked="" type="checkbox"/>
BaseRate	money	<input checked="" type="checkbox"/>
VacationHours	smallint	<input checked="" type="checkbox"/>
SickLeaveHours	smallint	<input checked="" type="checkbox"/>
CurrentFlag	bit	<input type="checkbox"/>
SalesPersonFlag	bit	<input type="checkbox"/>
DepartmentName	nvarchar(50)	<input checked="" type="checkbox"/>
StartDate	date	<input checked="" type="checkbox"/>
EndDate	date	<input checked="" type="checkbox"/>
Status	nvarchar(50)	<input checked="" type="checkbox"/>
EmployeePhoto	varbinary(MAX)	<input type="checkbox"/>

#### TABLE SHOWING COLUMNS PROJECTED IN THE END

Table Name	Column Name
[dbo].[DimDate]	EnglishMonthName
[dbo].[DimEmployee]	LastName FirstName
Derived	Day Year

#### TABLE SHOWING HOW PROJECTION SORTED (IF APPLICABLE)

Table Name	Column Name	Sort Order
Derived	Year	ASC
	Day	ASC

#### QUERY

```

USE AdventureWorksDW2017;
WITH MonthName
AS (SELECT D.EnglishMonthName AS Month,
          D.MonthNumberOfYear AS MonthNum
     FROM [dbo].[DimDate] AS D
     GROUP BY D.EnglishMonthName,
              D.MonthNumberOfYear)
SELECT DISTINCT
    E.LastName,
    E.FirstName,
    D.Month,
    DAY(E.BirthDate) AS Day,
    YEAR(E.BirthDate) AS Year
FROM [dbo].[DimEmployee] AS E
     JOIN MonthName AS D
       ON MONTH(E.BirthDate) = D.MonthNum
WHERE MONTH(E.BirthDate) = 7
ORDER BY Year,
         Day;
GO

```



# RELATIONAL AND JSON OUTPUT (28 ROWS AFFECTED)

Results		Messages			
	LastName	FirstName	Month	Day	Year
1	Saraiva	José	July	11	1939
2	Charncherngkha	Sootha	July	5	1942
3	Brown	Eric	July	8	1942
4	Abercrombie	Kim	July	14	1942
5	Stadick	Betsy	July	17	1942
6	Blythe	Michael	July	25	1968
7	Coleman	Pat	July	3	1970
8	Kaliyath	Sandeep	July	3	1970
9	Goldstein	Brian	July	23	1970
1...	Macrae	Stuart	July	17	1971
1...	Cook	Patrick	July	23	1973
1...	Ansman-Wolfe	Pamela	July	6	1974
1...	Walters	Rob	July	23	1974
1...	Trenary	Jean	July	13	1975
1...	Hesse	Stefen	July	21	1975

```

] {
  "Birthday Output": [ {
    "LastName": "Saraiva",
    "FirstName": "José",
    "Month": "July",
    "Day": 11,
    "Year": 1939
  }, {
    "LastName": "Charncherngkha",
    "FirstName": "Sootha",
    "Month": "July",
    "Day": 5,
    "Year": 1942
  }, {
    "LastName": "Brown",
    "FirstName": "Eric",
    "Month": "July",
    "Day": 8,
    "Year": 1942
  }, {
    "LastName": "Abercrombie",
    "FirstName": "Kim",
    "Month": "July",
    "Day": 14,
    "Year": 1942
  }, {
    "LastName": "Stadick",
    "FirstName": "Betsy",
    "Month": "July",
    "Day": 17,
    "Year": 1942
  }, {
    "LastName": "Blythe",
    "FirstName": "Michael",
    "Month": "July",
    "Day": 25,
    "Year": 1968
  }, {

```

## TOP #3: A COMPLEX QUERY

### PROBLEM STATEMENT

Using Northwinds2022TSQLV7, display the information of customers who purchased discontinued items

### REASON IT IS A TOP

Separates the main code from the function cleanly, allowing for better readability

### KEY AND STANDARD VIEW OF TABLES USED




TABLE SHOWING COLUMNS PROJECTED IN THE END

Table Name	Column Name
[Production].[Product]	ProductId
[Sales].[Order]	OrderId, OrderDate
[Sales].[Customer]	CustomerCompanyName
Derived	Paid

TABLE SHOWING HOW PROJECTION SORTED (IF APPLICABLE)

Not applicable

## QUERY

```

USE Northwinds2022TSQLV7;

DROP FUNCTION IF EXISTS getDiscontinued;
GO
CREATE FUNCTION getDiscontinued
(
    @disc AS INT
)
RETURNS TABLE
AS
RETURN SELECT ProductId,
               ProductName,
               SupplierId,
               CategoryId,
               UnitPrice,
               Discontinued
FROM [Production].[Product]
WHERE Discontinued = @disc;
GO
WITH Ord
AS (SELECT O.OrderId,
           O.OrderDate AS DATE,
           O.CustomerId
FROM [Sales].[Order] AS O
GROUP BY O.OrderId,
         O.OrderDate,
         O.CustomerId),
    Ord2
AS (SELECT C.CustomerCompanyName AS CompanyName,
           C.CustomerId
FROM [Sales].[Customer] AS C
GROUP BY C.CustomerCompanyName,
         C.CustomerId)
SELECT C.CompanyName,
       P.ProductId,
       O.OrderId,
       O.DATE,
       SUM(D.UnitPrice * D.Quantity) AS Paid
FROM Ord2 AS C
JOIN Ord AS O
    ON C.CustomerId = O.CustomerId
JOIN [Sales].[OrderDetail] AS D
    ON O.OrderId = D.OrderId
JOIN getDiscontinued(1) AS P
    ON D.ProductId = P.ProductId
GROUP BY C.CompanyName,
         P.ProductId,
         O.OrderId,
         O.DATE;

```

# RELATIONAL AND JSON OUTPUT (228 ROWS AFFECTED)

Results		Messages			
	CompanyName	ProductId	OrderId	DATE	Paid
1	Customer ENQZT	42	10248	2014-07-04	98.0000
2	Customer WNMAF	24	10254	2014-07-11	54.0000
3	Customer SRQVM	53	10256	2014-07-15	393.0000
4	Customer THHDP	5	10258	2014-07-17	1105.0000
5	Customer NYUHS	5	10262	2014-07-22	204.0000
6	Customer THHDP	24	10263	2014-07-23	100.8000
7	Customer QXVLA	17	10265	2014-07-25	936.0000
8	Customer FVXPQ	29	10268	2014-07-30	990.0000
9	Customer CQRAA	24	10275	2014-08-07	43.2000
1..	Customer PZNLA	28	10277	2014-08-09	728.0000
1..	Customer OXFRU	17	10279	2014-08-13	468.0000
1..	Customer HGV LZ	24	10280	2014-08-14	43.2000
1..	Customer SIUIH	24	10281	2014-08-14	21.6000
1..	Customer IRRVL	53	10285	2014-08-20	943.2000

```
{
  "Discontinued Output": [{
    "CompanyName": "Customer ENQZT",
    "ProductId": 42,
    "OrderId": 10248,
    "Date": "2014-07-04",
    "Paid": 98.0000
  }, {
    "CompanyName": "Customer WNMAF",
    "ProductId": 24,
    "OrderId": 10254,
    "Date": "2014-07-11",
    "Paid": 54.0000
  }, {
    "CompanyName": "Customer SRQVM",
    "ProductId": 53,
    "OrderId": 10256,
    "Date": "2014-07-15",
    "Paid": 393.0000
  }, {
    "CompanyName": "Customer THHDP",
    "ProductId": 5,
    "OrderId": 10258,
    "Date": "2014-07-17",
    "Paid": 1105.0000
  }, {
    "CompanyName": "Customer NYUHS",
    "ProductId": 5,
    "OrderId": 10262,
    "Date": "2014-07-22",
    "Paid": 204.0000
  }, {
    "CompanyName": "Customer THHDP",
    "ProductId": 24,
    "OrderId": 10263,
    "Date": "2014-07-23",
    "Paid": 100.8000
  }, {
    "CompanyName": "Customer QXVLA",
    "ProductId": 17,
    "OrderId": 10265,
    "Date": "2014-07-25"
```

## WORST #1: A SIMPLE QUERY


### PROBLEM STATEMENT


Using AdventureWorks2017, display the order from the highest orderid

### REASON IT IS A WORST

Can be written much easier and have a simpler output

### KEY AND STANDARD VIEW OF TABLES USED

 SalesOrderID
SalesOrderNumber
CustomerID
SalesPersonID
TerritoryID
BillToAddressID
ShipToAddressID
ShipMethodID
CreditCardID
CurrencyRateID
rowguid

Column Name	Data Type	Allow Nulls
 SalesOrderID	int	<input type="checkbox"/>
RevisionNumber	tinyint	<input type="checkbox"/>
OrderDate	datetime	<input type="checkbox"/>
DueDate	datetime	<input type="checkbox"/>
ShipDate	datetime	<input checked="" type="checkbox"/>
Status	tinyint	<input type="checkbox"/>
OnlineOrderFlag	Flag:bit	<input type="checkbox"/>
SalesOrderNumber		<input type="checkbox"/>
PurchaseOrderNumber	OrderNumber:nvar...	<input checked="" type="checkbox"/>
AccountNumber	AccountNumber:n...	<input checked="" type="checkbox"/>
CustomerID	int	<input type="checkbox"/>
SalesPersonID	int	<input checked="" type="checkbox"/>
TerritoryID	int	<input checked="" type="checkbox"/>
BillToAddressID	int	<input type="checkbox"/>
ShipToAddressID	int	<input type="checkbox"/>
ShipMethodID	int	<input type="checkbox"/>
CreditCardID	int	<input checked="" type="checkbox"/>
CreditCardApprovalCode	varchar(15)	<input checked="" type="checkbox"/>
CurrencyRateID	int	<input checked="" type="checkbox"/>
SubTotal	money	<input type="checkbox"/>
TaxAmt	money	<input type="checkbox"/>
Freight	money	<input type="checkbox"/>
TotalDue		<input type="checkbox"/>
Comment	nvarchar(128)	<input checked="" type="checkbox"/>
rowguid	uniqueidentifier	<input type="checkbox"/>
ModifiedDate	datetime	<input type="checkbox"/>

#### TABLE SHOWING COLUMNS PROJECTED IN THE END

Table Name	Column Name
[Sales].[SalesOrderHeader]	OrderDate, CustomerId
Derived	MAX(SalesOrderId)

#### TABLE SHOWING HOW PROJECTION SORTED (IF APPLICABLE)

Table Name	Column Name	Sort Order
Derived	MAX(SalesOrderId)	DESC

#### QUERY OF WORST

```
USE AdventureWorks2017;

SELECT MAX(H.SalesOrderID),
       H.OrderDate,
       H.CustomerID
FROM [Sales].[SalesOrderHeader] AS H
GROUP BY H.OrderDate,
         H.CustomerID
ORDER BY MAX(H.SalesOrderID) DESC;
```

#### QUERY OF WORST CORRECTED

```
USE AdventureWorks2017;
SELECT H.SalesOrderID,
       H.OrderDate,
       H.CustomerID
FROM [Sales].[SalesOrderHeader] AS H
WHERE H.SalesOrderID =
(
    SELECT MAX(H2.SalesOrderID) FROM [Sales].[SalesOrderHeader] AS H2
);
GO
```

---

#### HOW IT WAS CORRECTED:

Used a subquery to allow the maximum ordered to only be outputted

# RELATIONAL AND JSON OUTPUT (31406 ROWS AFFECTED)

	(No column name) ▾	OrderDate ▾	CustomerId ▾
1	75123	2014-06-30 00:00:00.000	18759
2	75122	2014-06-30 00:00:00.000	15868
3	75121	2014-06-30 00:00:00.000	15251
4	75120	2014-06-30 00:00:00.000	18749
5	75119	2014-06-30 00:00:00.000	11981
6	75118	2014-06-30 00:00:00.000	13671
7	75117	2014-06-30 00:00:00.000	18178
8	75116	2014-06-30 00:00:00.000	16402
9	75115	2014-06-30 00:00:00.000	26832
1...	75114	2014-06-30 00:00:00.000	24704
1...	75113	2014-06-30 00:00:00.000	21524
1...	75112	2014-06-30 00:00:00.000	21523

```
{
  "Highest OrderId": [
    {
      "Highest": 75123,
      "OrderDate": "2014-06-30T00:00:00",
      "CustomerId": 18759
    },
    {
      "Highest": 75122,
      "OrderDate": "2014-06-30T00:00:00",
      "CustomerId": 15868
    },
    {
      "Highest": 75121,
      "OrderDate": "2014-06-30T00:00:00",
      "CustomerId": 15251
    },
    {
      "Highest": 75120,
      "OrderDate": "2014-06-30T00:00:00",
      "CustomerId": 18749
    },
    {
      "Highest": 75119,
      "OrderDate": "2014-06-30T00:00:00",
      "CustomerId": 11981
    },
    {
      "Highest": 75118,
      "OrderDate": "2014-06-30T00:00:00",
      "CustomerId": 13671
    },
    {
      "Highest": 75117,
      "OrderDate": "2014-06-30T00:00:00",
      "CustomerId": 18178
    },
    {
      "Highest": 75116,
      "OrderDate": "2014-06-30T00:00:00",
      "CustomerId": 16402
    },
    {
      "Highest": 75115,
      "OrderDate": "2014-06-30T00:00:00",
      "CustomerId": 26832
    },
    {
      "Highest": 75114,
      "OrderDate": "2014-06-30T00:00:00",
      "CustomerId": 24704
    },
    {
      "Highest": 75113,
      "OrderDate": "2014-06-30T00:00:00",
      "CustomerId": 21524
    },
    {
      "Highest": 75112,
      "OrderDate": "2014-06-30T00:00:00",
      "CustomerId": 21523
    }
  ]
}
```



CORRECTED RELATIONAL AND JSON OUTPUT (1 ROW AFFECTED)

Results		Messages	
	SalesOrderID ▾	OrderDate ▾	CustomerId ▾
1	75123	2014-06-30 00:00:00.000	18759

```
[{
  "Highest OrderId": [{
    "SalesOrderID": 75123,
    "OrderDate": "2014-06-30T00:00:00",
    "CustomerId": 18759
  }]
}]
```

## WORST #2: A MEDIUM QUERY


### PROBLEM STATEMENT

Using AdventureWorks2017, display how many 'silver' products have been sold to an address that is in 'New York' (city)

### REASON IT IS A WORST

Can create an extension CTE to make the main a little cleaner

### KEY AND STANDARD VIEW OF TABLES USED



#### TABLE SHOWING COLUMNS PROJECTED IN THE END

Table Name	Column Name
Derived	SilverTotal

#### TABLE SHOWING HOW PROJECTION SORTED (IF APPLICABLE)

Not applicable

#### QUERY OF WORST

```
USE AdventureWorks2017;
WITH Product
AS (SELECT P.ProductID,
           P.Color
     FROM [Production].[Product] AS P
     WHERE P.Color = 'silver')
SELECT SUM(D.OrderQty) AS SilverTotal
FROM Product AS P
JOIN [Sales].[SalesOrderDetail] AS D
  ON P.ProductID = D.ProductID
JOIN [Sales].[SalesOrderHeader] AS H
  ON D.SalesOrderID = H.SalesOrderID
JOIN [Person].[Address] AS A
  ON H.ShipToAddressID = A.AddressID
WHERE A.City = 'New York';
GO
```

#### QUERY OF WORST CORRECTED

```
USE AdventureWorks2017;
WITH Product
AS (SELECT P.ProductID,
          P.Color
     FROM [Production].[Product] AS P
     WHERE P.Color = 'silver'),
     City
AS (SELECT A.AddressID,
          A.City
     FROM [Person].[Address] AS A
     WHERE A.City = 'New York')
SELECT SUM(D.OrderQty) AS SilverTotal
FROM Product AS P
     JOIN [Sales].[SalesOrderDetail] AS D
       ON P.ProductID = D.ProductID
     JOIN [Sales].[SalesOrderHeader] AS H
       ON D.SalesOrderID = H.SalesOrderID
     JOIN City AS A
       ON H.ShipToAddressID = A.AddressID;
GO
```

---

#### HOW IT WAS CORRECTED:

Created an extension to the CTE to clear up the main code

## RELATIONAL AND JSON OUTPUT (1 ROW AFFECTED)

Results		Messages	
	SilverTotal		
1	9		

```
{
  "Silver Output": [
    {
      "SilverTotal": 9
    }
  ]
}
```

## WORST #3: A COMPLEX QUERY

### PROBLEM STATEMENT

Using WideWorldImporters, display the transaction id of every customer who ordered where the payment was received at the end of every month in 2015

### REASON IT IS A WORST

Too much unnecessary information in the custom function

### KEY AND STANDARD VIEW OF TABLES USED





TABLE SHOWING COLUMNS PROJECTED IN THE END

Table Name	Column Name
[Sales].[CustomerTransactions]	CustomerTransactionId
[Sales].[Orders]	OrderDate
[Application].[TransactionTypes]	TransactionTypeName

TABLE SHOWING HOW PROJECTION SORTED (IF APPLICABLE)

Not applicable

## QUERY OF WORST

```
DROP FUNCTION IF EXISTS getDte;
GO
CREATE FUNCTION getDte
(
    @date AS INT
)
RETURNS TABLE
AS
RETURN SELECT OrderID,
               CustomerID,
               SalespersonPersonID,
               PickedByPersonID,
               ContactPersonID,
               BackorderOrderID,
               OrderDate,
               ExpectedDeliveryDate,
               CustomerPurchaseOrderNumber,
               IsUndersupplyBackordered,
               Comments,
               DeliveryInstructions,
               InternalComments,
               PickingCompletedWhen,
               LastEditedBy,
               LastEditedWhen
           FROM [Sales].[Orders]
           WHERE EOMONTH(OrderDate) = OrderDate
              AND YEAR(OrderDate) = @date;
GO
WITH TransactionName
AS (SELECT TT.TransactionTypeName AS Condition,
          TT.TransactionTypeID AS ID
     FROM [Application].[TransactionTypes] AS TT
     WHERE TT.TransactionTypeID = 3)
SELECT T.CustomerTransactionID,
       O.OrderDate,
       TT.Condition
FROM [Sales].[CustomerTransactions] AS T
JOIN getDte(2015) AS O
  ON T.CustomerID = O.CustomerID
JOIN TransactionName AS TT
  ON T.TransactionTypeID = TT.ID
GROUP BY T.CustomerTransactionID,
         O.OrderDate,
         TT.Condition
ORDER BY O.OrderDate;
```



#### QUERY OF WORST CORRECTED

```
USE WideWorldImporters;
DROP FUNCTION IF EXISTS getDte;
GO
CREATE FUNCTION getDte
(
    @date AS INT
)
RETURNS TABLE
AS
RETURN SELECT CustomerID,
              OrderDate
          FROM [Sales].[Orders]
          WHERE EOMONTH(OrderDate) = OrderDate
              AND YEAR(OrderDate) = @date;
GO
WITH TransactionName
AS (SELECT TT.TransactionTypeName AS Condition,
          TT.TransactionTypeID AS ID
     FROM [Application].[TransactionTypes] AS TT
     WHERE TT.TransactionTypeID = 3)
SELECT T.CustomerTransactionID,
       O.OrderDate,
       TT.Condition
FROM [Sales].[CustomerTransactions] AS T
JOIN getDte(2015) AS O
  ON T.CustomerID = O.CustomerID
JOIN TransactionName AS TT
  ON T.TransactionTypeID = TT.ID
GROUP BY T.CustomerTransactionID,
         O.OrderDate,
         TT.Condition
ORDER BY O.OrderDate;
```

---

#### HOW IT WAS CORRECTED:

Shrank number of rows selected in the Custom Function

# RELATIONAL AND JSON OUTPUT (23578 ROWS AFFECTED)

Results		Messages	
	CustomerTransactionID	OrderDate	Condition
1	247	2015-01-31	Customer Payment Received
2	607	2015-01-31	Customer Payment Received
3	622	2015-01-31	Customer Payment Received
4	621	2015-01-31	Customer Payment Received
5	624	2015-01-31	Customer Payment Received
6	1917	2015-01-31	Customer Payment Received
7	1202	2015-01-31	Customer Payment Received
8	251	2015-01-31	Customer Payment Received
9	1383	2015-01-31	Customer Payment Received
1..	1898	2015-01-31	Customer Payment Received
1..	2375	2015-01-31	Customer Payment Received
1..	1381	2015-01-31	Customer Payment Received
1..	2091	2015-01-31	Customer Payment Received
1..	7137	2015-01-31	Customer Payment Received
1..	2728	2015-01-31	Customer Payment Received
1..	620	2015-01-31	Customer Payment Received

```
{
  "Date Output": [
    {
      "CustomerTransactionID": 247,
      "OrderDate": "2015-01-31",
      "Condition": "Customer Payment Received"
    },
    {
      "CustomerTransactionID": 607,
      "OrderDate": "2015-01-31",
      "Condition": "Customer Payment Received"
    },
    {
      "CustomerTransactionID": 622,
      "OrderDate": "2015-01-31",
      "Condition": "Customer Payment Received"
    },
    {
      "CustomerTransactionID": 621,
      "OrderDate": "2015-01-31",
      "Condition": "Customer Payment Received"
    },
    {
      "CustomerTransactionID": 624,
      "OrderDate": "2015-01-31",
      "Condition": "Customer Payment Received"
    },
    {
      "CustomerTransactionID": 1917,
      "OrderDate": "2015-01-31",
      "Condition": "Customer Payment Received"
    },
    {
      "CustomerTransactionID": 1202,
      "OrderDate": "2015-01-31",
      "Condition": "Customer Payment Received"
    },
    {
      "CustomerTransactionID": 251,
      "OrderDate": "2015-01-31",
      "Condition": "Customer Payment Received"
    },
    {
      "CustomerTransactionID": 1383,
      "OrderDate": "2015-01-31",
      "Condition": "Customer Payment Received"
    },
    {
      "CustomerTransactionID": 1898,
      "OrderDate": "2015-01-31",
      "Condition": "Customer Payment Received"
    },
    {
      "CustomerTransactionID": 2375,
      "OrderDate": "2015-01-31",
      "Condition": "Customer Payment Received"
    },
    {
      "CustomerTransactionID": 1381,
      "OrderDate": "2015-01-31",
      "Condition": "Customer Payment Received"
    },
    {
      "CustomerTransactionID": 2091,
      "OrderDate": "2015-01-31",
      "Condition": "Customer Payment Received"
    },
    {
      "CustomerTransactionID": 7137,
      "OrderDate": "2015-01-31",
      "Condition": "Customer Payment Received"
    },
    {
      "CustomerTransactionID": 2728,
      "OrderDate": "2015-01-31",
      "Condition": "Customer Payment Received"
    },
    {
      "CustomerTransactionID": 620,
      "OrderDate": "2015-01-31",
      "Condition": "Customer Payment Received"
    }
  ]
}
```