

# Extending CAS with Algebraic Reductions

Author: Zongzhe Yuan

**Supervised by: Timothy G. Griffin**



UNIVERSITY OF  
CAMBRIDGE


# Outline

- Introduction to Reduction
- Introduction to Routing Problem
- Main Contributions
  - Full Reduction Representation
  - Generalized Reduction
  - Predicate Reduction
  - Example Applications
  - Coq Implementation



# Reduction (Classical)

By Wongseelashote in 1979



- Function **r** on the problem set **S**
- Congruence  $\forall a, b \in S, a =_S b \rightarrow r(a) =_S r(b)$
- Idempotent  $\forall a \in S, r(a) =_S r(r(a))$
- Left Invariant  $\forall a, b \in S, r(a) \oplus b =_S a \oplus b$
- Right Invariant  $\forall a, b \in S, a \oplus r(b) =_S a \oplus b$



# Traditional Representation

- Representation  $\{x \in S \mid r(x) =_S x\}$   
 $\forall a, b \in S, a \oplus_r b =_S r(a \oplus b)$
- Example  $\min_{\leq} \equiv \{x \in S \mid \forall y \in S, \neg y \leq x\}$
- Hard to be implemented

$$r_2(r_1(S)) \equiv \{y \in \{x \in S \mid r_1(x) = x\} \mid r_2(y) = y\}$$

- Motivate us to create the full reduction representation



# Full Reduction Representation

- Traditional Representation on Semiring

$$(S, =_S, \oplus) \longrightarrow (\{x \in S \mid r(x) =_S x\}, =_S, \oplus_r)$$

- Full Reduction Representation on Semiring

$$(S, =_S, \oplus) \longrightarrow (S, =_S^r, \oplus^r)$$

- Full Reduction Representation

$$\forall a, b \in S, a =_S^r b \equiv r(a) =_S r(b)$$

- $\forall a, b \in S, a \oplus^r b \equiv r(r(a) \oplus r(b))$



# Isomorphism

- Isomorphic on the equality for reflexive, symmetric, congruence and transitive properties
- Isomorphic on the binary operator for associative, commutative, selective, congruence and distributive.
- Proofs only need the idempotent and congruence properties for the reduction — Detail proof can be found in Coq file
- Conclusion: two representations represent the same problem



# Internet Routing Problem

- Problem for RIP like algorithm: can't start from arbitrary states
- Use BGP like algorithm, Adding Explicit Path to Shortest Path
$$spwp \equiv AddZero(\infty, (\mathbb{N}, min, +) \xrightarrow{\quad} path(E))$$
- Adding reduction to eliminate problems
$$spwp \equiv red_{r_2}(AddZero(\infty, (\mathbb{N}, min, +) \xrightarrow{\quad} epath(E)))$$



# Classical Reduction

- Reduction with the properties of Congruence, Idempotent, Left/right invariant.
- Elementary Path reduction on **min** operator is not classical, no left/right invariant properties.

$$p_1 = \{a, a\}, p_2 = \{a, b, c\}$$

$$\min(p_1, p_2) = p_1, \min(r(p_1), p_2) = p_2$$

- Motivate us to generalize the definition of reduction.





# Generalized Reduction

- Get rid of left/right invariant properties
- Only have influence on associative and distributive properties — but only a sufficient condition
- Derive pseudo-associative and pseudo-distributive properties — isomorphic to associative and distributive

$$\forall a, b, c \in S, r(r(r(a) \oplus r(b)) \oplus r(c)) = r(r(a) \oplus r(r(b) \oplus r(c)))$$

$$\forall a, b, c \in S, r(r(r(a) \oplus r(r(r(b) \oplus r(c)))))) = r(r(r(r(r(a) \oplus r(b)))) \oplus r(c)))$$



# Predicate Reduction

- A kind of Generalized Reduction
- The reduction is defined on a predicate

$$r_p(a) \equiv \begin{cases} c & P(a) \\ a & \text{otherwise} \end{cases}$$

- Decompositional — Associative and Distributive

$$\forall a, b \in S, P(a \oplus b) \rightarrow P(a) \bigvee P(b)$$

- Compositional — Classical

$$\forall a, b \in S, P(a) \bigvee P(b) \rightarrow P(a \oplus b)$$

- Preserve Order — Classical on Identity

$$\forall a, b \in S, a \leq b \wedge P(a) \rightarrow P(b)$$



# Example Applications

- Min Plus With Ceiling  $\forall n \in \mathbb{N}, P(n) \equiv n \geq \textit{ceiling}$

- Elementary Path  $\forall p \in \textit{Path}, P(p) \equiv \textit{dup}(p)$

- Reduce Annihilator

$$\forall (n, p) \in \mathbb{N} \times (c + \textit{Path}), P((n, p)) \equiv n = \textit{ceiling} \vee p = \textit{inl}(c)$$

- Final Path Problem Construction

$$(\mathbb{N} \times (c + \textit{Path}), (\textit{min}^r \bar{\times} \textit{min}_d^r)_a, (+^r \times \textit{concat}_d^r)_a, (\textit{ceiling}, \textit{inl}(c)), (0, \textit{inr}([])))$$



# Coq Implementation

- Reason the Properties of Classical Reduction
- Prove the Isomorphism Between Full Reduction and Traditional Representation
- Prove the Properties of Generalized Reduction
- Prove the Properties of Predicate Reduction
- Construct Reduction Instance and Construct Path Problem Semiring



# Coq Code Examples

```
Definition min_app_non_distributive_diod : selective_biod M
:= {|
    sbiod_eq          := brel_eq_M
  ; sbiod_add         := bop_rap_add
  ; sbiod_mul         := bop_rap_mul
  ; sbiod_zero        := zero
  ; sbiod_one         := one
  ; sbiod_eqv         := eqv_proofs_eq_T
  ; sbiod_add_pfs     := min_proofs
  ; sbiod_mul_pfs     := app_proofs
  ; sbiod_pfs         := min_app_non_distributive_diod_proofs
|}.

```



# Summary

## Questions?



UNIVERSITY OF  
CAMBRIDGE