Design System Drift Audit: shadcn-ui/taxonomy (DRAFT)

DRAFT for review. Not for the client until it has been reviewed and edited. Every class below is proposed by rule and confirmed by hand before the report leaves.

Run: shadcn-ui/taxonomy at 298a885, against @/components/ui@0.0.0. 117 files checked in 0.4 seconds by @zenginui/cli@0.9.0, 2026-10-15.

Summary

- This run reported 35 findings in 31 groups. A group is one rule and one found value with one proposed class: one decision.
- 35 findings in 31 groups are queued for hand review, up to the cap of 150, taken in rank order (severity times the number of files). 0 findings past the cap are summarised. 35 + 0 = 35.
- Confirmed by hand so far: 0 of 35. Until a reviewer confirms a finding, its class is a proposal made by rule.
- False positives proposed in the queue: 0 of 35. The rate is stated once each one has been confirmed by hand.
- Every number here comes from this run and is reconciled above. No figure from another run is quoted.

```
Proposed class | Findings | Groups
True drift | 31 | 27
Needs a decision | 4 | 4
Intentional exception | 0 | 0
False positive | 0 | 0
Queued for hand review | 35 | 31
```

Top issues

G01: token-reference hover:text-brand (True drift)

- What: No token matches "hover:text-brand".
- Spread: 3 findings in 2 files, at error. Involves hover:text-brand.
- Why this class: token-reference at error, with a fix to be written by hand.
- Fix: No fix the engine can write; decided by hand.
- Examples: F001 app/(auth)/login/page.tsx:43, F002 app/(auth)/register/page.tsx:42, F003 app/(auth)/register/page.tsx:49.
- Findings: F001, F002, F003.

G02: color-literal text-red-600 (True drift)

- What: text-red-600 references the Tailwind default palette (--color-red-600), not a system token.
- Spread: 2 findings in 2 files, at error. Involves color.destructive.
- Why this class: color-literal at error, with a nearest fix.
- Fix: text-destructive (nearest). destructive is the system's token for this role. Chosen by role, not by value; verify it reads correctly here.
- Examples: F004 components/user-auth-form.tsx:78, F005 components/user-name-form.tsx:102.
- Findings: F004, F005.

G03: spacing-literal p-[1px] (True drift)

- What: Arbitrary spacing value. 1px is not on the spacing scale.
- Spread: 2 findings in 1 file, at error. Involves p-[1px].
- Why this class: spacing-literal at error, with an exact fix.
- Fix: p-px (exact)
- Examples: F006 components/ui/scroll-area.tsx:36, F007 components/ui/scroll-area.tsx:38.
- Findings: F006, F007.

G04: color-literal bg-black (True drift)

- What: bg-black references the Tailwind default palette (--color-black), not a system token.
- Spread: 1 finding in 1 file, at error. Involves color.primary.foreground.
- Why this class: color-literal at error, with a nearest fix.
- Fix: bg-primary-foreground (nearest). Nearest by value: color.primary.foreground = #020205 in the dark theme. Verify the semantic role before applying.
- Examples: F008 components/mdx-components.tsx:135.
- Findings: F008.

G05: color-literal bg-gray-800 (True drift)

- What: bg-gray-800 references the Tailwind default palette (--color-gray-800), not a system token.
- Spread: 1 finding in 1 file, at error. Involves color.border.
- Why this class: color-literal at error, with a nearest fix.
- Fix: bg-border (nearest). Nearest by value: color.border = #1d283a in the dark theme. Verify the semantic role before applying.
- Examples: F009 components/tailwind-indicator.tsx:5.
- Findings: F009.

G06: color-literal bg-red-50 (True drift)

- What: bg-red-50 references the Tailwind default palette (--color-red-50), not a system token.
- Spread: 1 finding in 1 file, at error. Involves color.destructive.
- Why this class: color-literal at error, with a nearest fix.
- Fix: bg-destructive (nearest). destructive is the system's token for this role. Chosen by role, not by value; verify it reads correctly here.
- Examples: F010 components/callout.tsx:18.
- Findings: F010.

G07: color-literal bg-red-600 (True drift)

- What: bg-red-600 references the Tailwind default palette (--color-red-600), not a system token.
- Spread: 1 finding in 1 file, at error. Involves color.destructive.
- Why this class: color-literal at error, with a nearest fix.
- Fix: bg-destructive (nearest). destructive is the system's token for this role. Chosen by role, not by value; verify it reads correctly here.
- Examples: F011 components/post-operations.tsx:100.
- Findings: F011.

G08: color-literal bg-slate-50 (True drift)

- What: bg-slate-50 references the Tailwind default palette (--color-slate-50), not a system token.
- Spread: 1 finding in 1 file, at error. Involves color.primary.foreground.
- Why this class: color-literal at error, with a nearest fix.
- Fix: bg-primary-foreground (nearest). Several tokens share this value. Pick by role: color.primary.foreground, color.destructive.foreground.
- Examples: F012 app/(marketing)/page.tsx:73.
- Findings: F012.

G09: color-literal bg-white (True drift)

- What: bg-white references the Tailwind default palette (--color-white), not a system token.
- Spread: 1 finding in 1 file, at error. Involves color.background.
- Why this class: color-literal at error, with a nearest fix.
- Fix: bg-background (nearest). Several tokens share this value. Pick by role: color.background, color.popover, color.card.
- Examples: F013 app/(marketing)/blog/[...slug]/page.tsx:135.
- Findings: F013.

G10: color-literal bg-yellow-50 (True drift)

- What: bg-yellow-50 references the Tailwind default palette (--color-yellow-50), not a system token.
- Spread: 1 finding in 1 file, at error. Involves color.primary.foreground.
- Why this class: color-literal at error, with a nearest fix.
- Fix: bg-primary-foreground (nearest). Nearest by value: color.primary.foreground = #f8fafc. Verify the semantic role before applying.
- Examples: F014 components/callout.tsx:19.
- Findings: F014.

Fix path by class

True drift

Fix in code, in group order. Apply exact fixes first; check each nearest fix by eye, since a neighbouring step can be a different design.

```
Group | Rule | Found | Findings | Files
G01 | token-reference | hover:text-brand | F001, F002, F003 | 2
G02 | color-literal | text-red-600 | F004, F005 | 2
G03 | spacing-literal | p-[1px] | F006, F007 | 1
G04 | color-literal | bg-black | F008 | 1
G05 | color-literal | bg-gray-800 | F009 | 1
G06 | color-literal | bg-red-50 | F010 | 1
G07 | color-literal | bg-red-600 | F011 | 1
G08 | color-literal | bg-slate-50 | F012 | 1
G09 | color-literal | bg-white | F013 | 1
G10 | color-literal | bg-yellow-50 | F014 | 1
G11 | color-literal | border-red-900 | F015 | 1
```

```
G12 | color-literal | border-yellow-900 | F016 | 1
G13 | color-literal | group-[.destructive]:hover:text-red-50 | F017 | 1
G14 | color-literal | group-[.destructive]:text-red-300 | F018 | 1
G15 | color-literal | text-gray-500 | F019 | 1
G16 | color-literal | text-white | F020 | 1
G17 | component-substitution | <button type="submit" className={cn(buttonVariants(), className)}
disabled={isSa | F021 | 1
G18 | component-substitution | <button type="submit" className={cn(buttonVariants())}
disabled={isLoading} > | F022 | 1
G19 | component-substitution | <button type="button" className={cn(buttonVariants({ variant: "outline"
}))} onC | F023 | 1
G20 | component-substitution | <button onClick={onClick} className={cn( buttonVariants({ variant }), {
"cursor- | F024 | 1
G21 | component-substitution | <button className={cn(buttonVariants())} disabled={isLoading}> | F025 | 1
G22 | component-substitution | <button type="submit" className={cn(buttonVariants())}> | F026 | 1
G24 | spacing-literal | px-[0.3rem] | F028 | 1
G25 | spacing-literal | py-[0.2rem] | F029 | 1
G26 | token-reference | divide-border-200 | F030 | 1
G27 | token-reference | placeholder:text-foreground-muted | F031 | 1
G28 | token-reference | text-on-popover | F032 | 1
```

Needs a decision

A decision for the team before any code changes: add the missing token, name the file as a foundation, or widen the component's className.allow. Each decision closes a whole group.

```
Group | Rule | Found | Findings | Files
G23 | spacing-literal | marginLeft: "-3px" | F027 | 1
G29 | classname-policy | !pl-14 | F033 | 1
G30 | classname-policy | px-0 | F034 | 1
G31 | classname-policy | sm:pr-12 | F035 | 1
```

Intentional exception

Keep it and write the reason after the zengin-allow comment's colon, so the engine honours it and the next reader knows why; or remove the exception.

No group in the hand-review queue.

False positive

Not a code change. Tune the definitions (a passthrough type, a foundation file) so the engine stops reporting it, and count it in the report's false-positive rate.

No group in the hand-review queue.

Beyond the hand-review cap

Every finding is queued for hand review; the cap of 150 was not reached.

What the scan cannot see

- Drift outside the engine's seven rule kinds (color-literal, spacing-literal, token-reference, unknown-prop, unknown-prop-value, classname-policy, component-substitution): behavioural, architectural and most accessibility drift.
- What renders at runtime: class names built from runtime values, styles set from JavaScript, and

the visual result of an override.

- Files outside the configured scope, and any system the definitions do not describe.
- Whether a finding matters to a user. That judgement is the hand review.

Evidence

Every finding id above resolves in findings.json, with its file:line, rule, found value, the token or component involved, its proposed class and the reason for it. run.json records the run.