

# class14

Tin Nguyen

```
library(DESeq2)
library(AnnotationDbi)
library(org.Hs.eg.db)
library(pathview)
library(gage)
library(gageData)
```

## Data import

```
colData <- read.csv("GSE37704_metadata.csv",row.names = 1)
countData <- read.csv("GSE37704_featurecounts.csv",row.names = 1)
```

```
head(countData)
```

	length	SRR493366	SRR493367	SRR493368	SRR493369	SRR493370
ENSG00000186092	918	0	0	0	0	0
ENSG00000279928	718	0	0	0	0	0
ENSG00000279457	1982	23	28	29	29	28
ENSG00000278566	939	0	0	0	0	0
ENSG00000273547	939	0	0	0	0	0
ENSG00000187634	3214	124	123	205	207	212
	SRR493371					
ENSG00000186092	0					
ENSG00000279928	0					
ENSG00000279457	46					
ENSG00000278566	0					
ENSG00000273547	0					
ENSG00000187634	258					

check the correspondance of colData rows and countData columns

```
rownames(colData)
```

```
[1] "SRR493366" "SRR493367" "SRR493368" "SRR493369" "SRR493370" "SRR493371"
```

Remove the troublesome first column so we can match the matadata

```
counts <- countData[,-1]
```

```
all(rownames(colData) == colnames(counts))
```

```
[1] TRUE
```

We will have rows in 'counts' for genes that we can not say anything about because they have zero expression in the particular tissue we are looking at.

```
head(counts)
```

	SRR493366	SRR493367	SRR493368	SRR493369	SRR493370	SRR493371
ENSG00000186092	0	0	0	0	0	0
ENSG00000279928	0	0	0	0	0	0
ENSG00000279457	23	28	29	29	28	46
ENSG00000278566	0	0	0	0	0	0
ENSG00000273547	0	0	0	0	0	0
ENSG00000187634	124	123	205	207	212	258

## Remove zero count genes

If the `rowSums()` is zero then a give gene (i.e. row) has no count data and we should exclode these genes from further consideration.

```
#rowSums(counts) == 0
```

```
to.keep <- rowSums(counts) != 0  
cleancounts <- counts[to.keep, ]
```

Q. How many genes do we have left ?

```
nrow(cleancounts)
```

```
[1] 15975
```

## SEtup DESeq object for analysis

```
dds <- DESeqDataSetFromMatrix(countData = cleancounts,  
                              colData = colData,  
                              design = ~condition)
```

Warning in DESeqDataSet(se, design = design, ignoreRank): some variables in design formula are characters, converting to factors

```
#Run DESeq analysis
```

```
dds <- DESeq(dds)
```

```
estimating size factors
```

```
estimating dispersions
```

```
gene-wise dispersion estimates
```

```
mean-dispersion relationship
```

```
final dispersion estimates
```

```
fitting model and testing
```

```
#Extract the results
```

```
res <- results(dds)
```

```
head(res)
```

log2 fold change (MLE): condition hoxa1 kd vs control sirna

Wald test p-value: condition hoxa1 kd vs control sirna


DataFrame with 6 rows and 6 columns

	baseMean	log2FoldChange	lfcSE	stat	pvalue
	<numeric>	<numeric>	<numeric>	<numeric>	<numeric>
ENSG00000279457	29.9136	0.1792571	0.3248216	0.551863	5.81042e-01
ENSG00000187634	183.2296	0.4264571	0.1402658	3.040350	2.36304e-03
ENSG00000188976	1651.1881	-0.6927205	0.0548465	-12.630158	1.43989e-36
ENSG00000187961	209.6379	0.7297556	0.1318599	5.534326	3.12428e-08
ENSG00000187583	47.2551	0.0405765	0.2718928	0.149237	8.81366e-01
ENSG00000187642	11.9798	0.5428105	0.5215599	1.040744	2.97994e-01
	padj				
	<numeric>				
ENSG00000279457	6.86555e-01				
ENSG00000187634	5.15718e-03				
ENSG00000188976	1.76549e-35				
ENSG00000187961	1.13413e-07				
ENSG00000187583	9.19031e-01				
ENSG00000187642	4.03379e-01				

```
mycols <- rep("gray", nrow(res))
mycols[ res$log2FoldChange <= -2 ] <- "blue"
mycols[ res$log2FoldChange >= +2 ] <- "red"
mycols[res$padj >= 0.005] <- "gray"

plot(res$log2FoldChange, -log(res$padj), col = mycols)

abline( v = -2, col = "red" )
abline( v = +2, col = "red" )
abline( h = -log(0.05), col = "red" )
```



#Add Gene annotation

```
library("AnnotationDbi")
library("org.Hs.eg.db")

columns(org.Hs.eg.db)
```

[1]	"ACCNUM"	"ALIAS"	"ENSEMBL"	"ENSEMBLPROT"	"ENSEMBLTRANS"
[6]	"ENTREZID"	"ENZYME"	"EVIDENCE"	"EVIDENCEALL"	"GENENAME"
[11]	"GENETYPE"	"GO"	"GOALL"	"IPI"	"MAP"
[16]	"OMIM"	"ONTOLOGY"	"ONTOLOGYALL"	"PATH"	"PFAM"
[21]	"PMID"	"PROSITE"	"REFSEQ"	"SYMBOL"	"UCSCKG"
[26]	"UNIPROT"				

```
#row.names(res)
```

```
res$symbol <- mapIds(org.Hs.eg.db,
                     keys=row.names(res), # Our genenames
                     keytype="ENSEMBL",   # The format of our genenames
                     column="SYMBOL",     # The new format we want to add
                     multiVals="first")
```

'select()' returned 1:many mapping between keys and columns

```
head(res)
```

log2 fold change (MLE): condition hoxa1 kd vs control sirna

Wald test p-value: condition hoxa1 kd vs control sirna

DataFrame with 6 rows and 7 columns

	baseMean	log2FoldChange	lfcSE	stat	pvalue
	<numeric>	<numeric>	<numeric>	<numeric>	<numeric>
ENSG00000279457	29.9136	0.1792571	0.3248216	0.551863	5.81042e-01
ENSG00000187634	183.2296	0.4264571	0.1402658	3.040350	2.36304e-03
ENSG00000188976	1651.1881	-0.6927205	0.0548465	-12.630158	1.43989e-36
ENSG00000187961	209.6379	0.7297556	0.1318599	5.534326	3.12428e-08
ENSG00000187583	47.2551	0.0405765	0.2718928	0.149237	8.81366e-01
ENSG00000187642	11.9798	0.5428105	0.5215599	1.040744	2.97994e-01
	padj	symbol			
	<numeric>	<character>			
ENSG00000279457	6.86555e-01	NA			
ENSG00000187634	5.15718e-03	SAMD11			
ENSG00000188976	1.76549e-35	NOC2L			
ENSG00000187961	1.13413e-07	KLHL17			
ENSG00000187583	9.19031e-01	PLEKHN1			
ENSG00000187642	4.03379e-01	PERM1			

#Save my results to a CSV file


```
write.csv(res, file = "results.csv")
```

#Result visualization

```
library(ggplot2)

ggplot(as.data.frame(res))+
  aes(log2FoldChange, -log(padj), label=res$symbol) +
  geom_point( color = mycols) +
  geom_vline(xintercept = -2, color = "red") +
  geom_vline(xintercept = 2, color = "red") +
  geom_hline(yintercept = -log(0.05), color = "red") +
  labs(title = "Title", x= "xaxis" ,y ="yaxis") +
  theme_bw() +
  labs( x = "Log2 Fold-Change", y = "-log(Adjusted P-value)")
```

Warning: Removed 1237 rows containing missing values or values outside the scale range (`geom\_point()`).



```
res$name <- mapIds( x = org.Hs.eg.db,
  keys = rownames(res),
  keytype = "ENSEMBL",
  column = "GENENAME")
```

'select()' returned 1:many mapping between keys and columns

```
res$entrez <- mapIds( x = org.Hs.eg.db,
  keys = rownames(res),
  keytype = "ENSEMBL",
  column = "ENTREZID")
```

'select()' returned 1:many mapping between keys and columns

```
head(res)
```

log2 fold change (MLE): condition hoxa1 kd vs control sirna

Wald test p-value: condition hoxa1 kd vs control sirna

DataFrame with 6 rows and 9 columns

	baseMean	log2FoldChange	lfcSE	stat	pvalue
	<numeric>	<numeric>	<numeric>	<numeric>	<numeric>

ENSG00000279457	29.9136	0.1792571	0.3248216	0.551863	5.81042e-01
ENSG00000187634	183.2296	0.4264571	0.1402658	3.040350	2.36304e-03
ENSG00000188976	1651.1881	-0.6927205	0.0548465	-12.630158	1.43989e-36
ENSG00000187961	209.6379	0.7297556	0.1318599	5.534326	3.12428e-08
ENSG00000187583	47.2551	0.0405765	0.2718928	0.149237	8.81366e-01
ENSG00000187642	11.9798	0.5428105	0.5215599	1.040744	2.97994e-01
	padj	symbol		name	entrez
	<numeric>	<character>		<character>	<character>
ENSG00000279457	6.86555e-01	NA		NA	NA
ENSG00000187634	5.15718e-03	SAMD11	sterile alpha motif ..		148398
ENSG00000188976	1.76549e-35	NOC2L	NOC2 like nucleolar ..		26155
ENSG00000187961	1.13413e-07	KLHL17	kelch like family me..		339451
ENSG00000187583	9.19031e-01	PLEKHN1	pleckstrin homology ..		84069
ENSG00000187642	4.03379e-01	PERM1	PPARGC1 and ESRR ind..		84808

```
library(gage)
library(gageData)
library(pathview)
```

```
data(kegg.sets.hs)
```

```
# Examine the first 2 pathways in this kegg set for humans
head(kegg.sets.hs, 2)
```

```
$`hsa00232 Caffeine metabolism`
```

```
[1] "10" "1544" "1548" "1549" "1553" "7498" "9"
```

```
$`hsa00983 Drug metabolism - other enzymes`
```

```
[1] "10" "1066" "10720" "10941" "151531" "1548" "1549" "1551"
[9] "1553" "1576" "1577" "1806" "1807" "1890" "221223" "2990"
[17] "3251" "3614" "3615" "3704" "51733" "54490" "54575" "54576"
[25] "54577" "54578" "54579" "54600" "54657" "54658" "54659" "54963"
[33] "574537" "64816" "7083" "7084" "7172" "7363" "7364" "7365"
[41] "7366" "7367" "7371" "7372" "7378" "7498" "79799" "83549"
[49] "8824" "8833" "9" "978"
```

```
foldchanges = res$log2FoldChange
names(foldchanges) = res$entrez
head(foldchanges)
```

<NA>	148398	26155	339451	84069	84808
0.17925708	0.42645712	-0.69272046	0.72975561	0.04057653	0.54281049



```
library(pathview)
```

```
library(gage)
```

```
library(gageData)
```

```
data(kegg.sets.hs)
```

```
data(sigmet.idx.hs)
```

```
# Focus on signaling and metabolic pathways only
```

```
kegg.sets.hs = kegg.sets.hs[sigmet.idx.hs]
```

```
# Examine the first 3 pathways
```

```
head(kegg.sets.hs, 3)
```

```
$`hsa00232 Caffeine metabolism`
```

```
[1] "10" "1544" "1548" "1549" "1553" "7498" "9"
```

```
$`hsa00983 Drug metabolism - other enzymes`
```

```
[1] "10" "1066" "10720" "10941" "151531" "1548" "1549" "1551"  
[9] "1553" "1576" "1577" "1806" "1807" "1890" "221223" "2990"  
[17] "3251" "3614" "3615" "3704" "51733" "54490" "54575" "54576"  
[25] "54577" "54578" "54579" "54600" "54657" "54658" "54659" "54963"  
[33] "574537" "64816" "7083" "7084" "7172" "7363" "7364" "7365"  
[41] "7366" "7367" "7371" "7372" "7378" "7498" "79799" "83549"  
[49] "8824" "8833" "9" "978"
```

```
$`hsa00230 Purine metabolism`
```

```
[1] "100" "10201" "10606" "10621" "10622" "10623" "107" "10714"  
[9] "108" "10846" "109" "111" "11128" "11164" "112" "113"  
[17] "114" "115" "122481" "122622" "124583" "132" "158" "159"  
[25] "1633" "171568" "1716" "196883" "203" "204" "205" "221823"  
[33] "2272" "22978" "23649" "246721" "25885" "2618" "26289" "270"  
[41] "271" "27115" "272" "2766" "2977" "2982" "2983" "2984"  
[49] "2986" "2987" "29922" "3000" "30833" "30834" "318" "3251"  
[57] "353" "3614" "3615" "3704" "377841" "471" "4830" "4831"  
[65] "4832" "4833" "4860" "4881" "4882" "4907" "50484" "50940"  
[73] "51082" "51251" "51292" "5136" "5137" "5138" "5139" "5140"  
[81] "5141" "5142" "5143" "5144" "5145" "5146" "5147" "5148"  
[89] "5149" "5150" "5151" "5152" "5153" "5158" "5167" "5169"  
[97] "51728" "5198" "5236" "5313" "5315" "53343" "54107" "5422"  
[105] "5424" "5425" "5426" "5427" "5430" "5431" "5432" "5433"
```

```
[113] "5434"    "5435"    "5436"    "5437"    "5438"    "5439"    "5440"    "5441"
[121] "5471"    "548644"  "55276"   "5557"    "5558"    "55703"   "55811"   "55821"
[129] "5631"    "5634"    "56655"   "56953"   "56985"   "57804"   "58497"   "6240"
[137] "6241"    "64425"   "646625"  "654364"  "661"     "7498"    "8382"    "84172"
[145] "84265"   "84284"   "84618"   "8622"    "8654"    "87178"   "8833"    "9060"
[153] "9061"    "93034"   "953"     "9533"    "954"     "955"     "956"     "957"
[161] "9583"    "9615"
```

```
foldchanges = res$log2FoldChange
names(foldchanges) = res$entrez
head(foldchanges)
```

```
      <NA>      148398      26155      339451      84069      84808
0.17925708 0.42645712 -0.69272046 0.72975561 0.04057653 0.54281049
```

```
# Get the results
keggres = gage(foldchanges, gsets=kegg.sets.hs)
```

```
attributes(keggres)
```

```
$names
[1] "greater" "less"    "stats"
```

```
head(keggres$less)
```

		p.geomean	stat.mean	p.val
hsa04110	Cell cycle	8.995727e-06	-4.378644	8.995727e-06
hsa03030	DNA replication	9.424076e-05	-3.951803	9.424076e-05
hsa03013	RNA transport	1.246882e-03	-3.059466	1.246882e-03
hsa03440	Homologous recombination	3.066756e-03	-2.852899	3.066756e-03
hsa04114	Oocyte meiosis	3.784520e-03	-2.698128	3.784520e-03
hsa00010	Glycolysis / Gluconeogenesis	8.961413e-03	-2.405398	8.961413e-03

		q.val	set.size	exp1
hsa04110	Cell cycle	0.001448312	121	8.995727e-06
hsa03030	DNA replication	0.007586381	36	9.424076e-05
hsa03013	RNA transport	0.066915974	144	1.246882e-03
hsa03440	Homologous recombination	0.121861535	28	3.066756e-03
hsa04114	Oocyte meiosis	0.121861535	102	3.784520e-03
hsa00010	Glycolysis / Gluconeogenesis	0.212222694	53	8.961413e-03

```
pathview(gene.data=foldchanges, pathway.id="hsa04110")
```

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory /Users/tinnguyen/Downloads/BIMM143/class14

Info: Writing image file hsa04110.pathview.png




Figure 1: hsa04110

# A different PDF based output of the same data

```
pathview(gene.data=foldchanges, pathway.id="hsa04110", kegg.native=FALSE)
```

'select()' returned 1:1 mapping between keys and columns

Warning: reconcile groups sharing member nodes!

```
      [,1] [,2]  
[1,] "9"  "300"  
[2,] "9"  "306"
```

Info: Working in directory /Users/tinnguyen/Downloads/BIMM143/class14

Info: Writing image file hsa04110.pathview.pdf

## Reactome analysis online

we need to make a little file of our significant genes that we can upload to the reactome webpage:

```
## Focus on top 5 upregulated pathways here for demo purposes only  
keggrespathways <- rownames(keggres$greater)[1:5]  
  
# Extract the 8 character long IDs part of each string  
keggresids = substr(keggrespathways, start=1, stop=8)  
keggresids
```

```
[1] "hsa04640" "hsa04630" "hsa00140" "hsa04142" "hsa04330"
```

```
pathview(gene.data=foldchanges, pathway.id=keggresids, species="hsa")
```

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory /Users/tinnguyen/Downloads/BIMM143/class14

Info: Writing image file hsa04640.pathview.png

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory /Users/tinnguyen/Downloads/BIMM143/class14

Info: Writing image file hsa04630.pathview.png

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory /Users/tinnguyen/Downloads/BIMM143/class14

Info: Writing image file hsa00140.pathview.png

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory /Users/tinnguyen/Downloads/BIMM143/class14

Info: Writing image file hsa04142.pathview.png

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory /Users/tinnguyen/Downloads/BIMM143/class14

Info: Writing image file hsa04330.pathview.png

```
sig_genes <- res[res$padj <= 0.05 & !is.na(res$padj), "symbol"]  
print(paste("Total number of significant genes:", length(sig_genes)))
```

```
[1] "Total number of significant genes: 8147"
```

```
sig_genes[6]
```

```
ENSG00000188157  
  "AGRN"
```

```
write.table(sig_genes, file="significant_genes.txt", row.names=FALSE, col.names=FALSE, quote=
```